



FIRE FIGHTING ROBOT

STEM PROJECT REPORT

Submitted by

GOPIKA J **710723106033**

MADHU PRIYA P **710723106055**

METHUN VIJAY S **710723106059**

MIDHUNESH R **710723106060**

**BACHELOR OF ENGINEERING
IN
ELECTRONICS AND COMMUNICATION ENGINEERING**

**Dr. N.G.P. INSTITUTE OF TECHNOLOGY, COIMBATORE
(An Autonomous Institution)**

ANNA UNIVERSITY ::CHENNAI-600025

June 2024

BONAFIDE CERTIFICATE

Certified that this project report “**FIRE FIGHTING ROBOT**” is the bonafide work of “GOPIKAJ(710723106033), MADHU PRIYA P(710723106055),METHUN VIJAY S(710723106059), MIDHUNESH R (710723106060), ”who carried out the project work under my supervision.

SIGNATURE

HEAD OF THE DEPARTMENT

Dr.P.Sampath M.E., Ph.D.,
Professor and Head,
Department of Electronics and
Communication Engineering,
Dr. N.G.P.Institute of Technology
Coimbatore-641048

SIGNATURE

SUPERVISOR

Dr.P.Sampath M.E., Ph.D.,
Professor and Head,
Department of Electronics and
Communication Engineering,
Dr. N.G.P.Institute of Technology
Coimbatore-641048

Submitted for the Project and Viva voce held on.....

INTERNAL EXAMINER

EXTERNAL EXAMINER

ACKNOWLEDGEMENT

ACKNOWLEDGEMENT

We would like to express our gratitude to the divine power who has been with us throughout our project journey. We are truly thankful for his guidance and support.

We are highly thankful to our beloved Chairman **Dr. Nalla G. Palaniswami M.D., A.B. (USA)**, Kovai Medical Centre and Hospital, Coimbatore, and our respected Secretary, **Dr. Thavamani D. Palaniswami M.D., A.B. (USA), FAAP** who encouraged us throughout our career giving support and advice for shaping us to this level.

We greatly thank our Principal, **Dr. S. U. Prabha M.E., Ph.D.**, for helping us to do our project successfully.

We heartily thank **Dr.P.Sampath M.E., Ph.D.**, Professor & Head of the Department of Electronics and Communication Engineering, for his invaluable support for doing this project.

We express our sincere thanks to our project coordinator and faculty, **Dr.P.Sampath M.E., Ph.D.**, for her invaluable contribution to the successful completion of our project.

We express our sincere gratitude to our project guide and faculty to our guide **Dr.P.Sampath M.E., Ph.D.**, Department of Electronics and Communication Engineering for her advice and encouragement in the implementation of the project.

The successful completion of any project requires the support and guidance of a team of people. In this regard, we would like to extend our heartfelt gratitude to all the teaching and non-teaching staff members of the Department of Electronics and Communication. We appreciate their efforts and contribution towards the successful completion of this project.

ABSTRACT

ABSTRACT

This project presents the development of a fire-fighting robot using Arduino microcontrollers and a comprehensive array of sensors, motors, and actuators. The robot is designed to autonomously detect and extinguishes fire in indoor environments. The sensor array includes infrared sensors for heat detection and flame sensors for precise fire localization. These sensors provide real-time data to the Arduino microcontroller, enabling the robot to analyze its surroundings and make intelligent decisions. The robot's mobility is facilitated by a combination of DC motors and motor drivers, allowing it to maneuver swiftly and effectively. To enhance its operational capabilities, the robot integrates obstacle avoidance mechanisms based on ultrasonic sensors, ensuring safe navigation through cluttered environments. The extinguishing mechanism employs a water spraying system, controlled by solenoid valves, triggered upon fire detection. The software architecture uses Arduino programming and algorithms for sensor fusion, navigation, and fire suppression strategies.

TABLE OF CONTENTS

TABLE OF CONTENTS

CHAPTER NO	TITLE	PAGE NO.
	ABSTRACT	
	LIST OF TABLES	
1	INTRODUCTION	
	1.1 FIRE FIGHTING ROBOT	2
	1.2 EXISTING SYSTEM	3
	1.3 DISADVANTAGE	4
	1.4 PROPOSED SYSTEM	5
2	LITERATURE SURVEY	
	2.1 LITERATURE REVIEW	7
	2.2 SUMMMARY	8

3	METHODOLOGY	10
	3.1 BLOCK DIAGRAM	11
	3.2 CIRCUIT DIAGRAM	12
4	COMPONENTS	
	4.1 HARDWARE COMPONENTS	15
	4.2 SOFTWARE REQUIRED	24
5	RESULTS AND DISCUSSION	30
6	CONCLUSION	31
7	FUTURE ENHANCEMENT	32
8	CONCLUSION	33

CHAPTER 1
INTRODUCTION

CHAPTER-1

INTRODUCTION

1.1 FIRE FIGHTING ROBOT

Fires are among the most important form of problems. Robot industry has a lot of work in this area. So today robot is more commonly used to reduce the human efforts. The need of Fire extinguisher Robot that can detect and extinguish a fire on its own. Robotics is one of the fastest growing engineering fields of today. Robots are designed to remove the human factor from labour intensive or dangerous work and also to act in inaccessible environment. With the invention of such a device, lives and property can be saved with minimal damage caused by the fire. As an engineer's we have to design a prototype that could autonomously detect the fire and extinguish it. The Fire Fighter Robot is designed to search for a fire in the house or industry for extinguish the fire.

The main and only work is to deploy the robot in a fire prone area and the robot will automatically work once it detects a fire breakout. This prototype helps in Rescue operations during fire accidents where the entry of service man is very difficult in the fire prone area. There are several existing types of vehicles for firefighting at home and extinguish forest fires. Our proposed robot is designed to be able to work on its own or be controlled remotely. By using such robots, fire identification and rescue activities can be done with higher security without placing fire fighters at high risk and dangerous conditions. In other words, robots can reduce the need for fire fighters to get into dangerous situations. When the field of firefighting has long been a dangerous one, and there have been numerous and devastating losses because of a lack in technological advancement.

Additionally, the current methods applied in firefighting are inadequate and inefficient relying heavily on humans who are prone to error, no matter how extensively they have been trained. A recent trend that has become popular is to

use robots instead of humans to handle fire hazards. This is mainly because they can be used in situations that are too dangerous for any individual to involve themselves in. In our project, we develop a robot that is able to locate and extinguish fire in a given environment.

The robot navigates the area and avoids any obstacles it faces in its excursion. Arduino board acts as a brain of the whole control circuitry. Robot consist of the two sensors that are interfaced in the control circuitry. Sensors are used to detect fire prone area all directions and moves the robo to fire location. When the robot reaches fire zone then a pump extinguisher is attached on the robot comes into action to extinguish the fire.

1.2 EXISTING SYSTEM

The common conventional firefighting methods involve fire brigades, portable fire extinguisher (hand held) and sprinklers. These conventional methods consume lot of time to reach the place of the mishap like the fire brigade must be deployed from the fire station and should get through the traffic and reach the fire struck area, the portable extinguisher is also no gift because it is generally place at one off the corners of the building which may be difficult to reach and it needs constant maintenance. On the other hand the sprinkler and smoke detector set up is very nonreliable method because the sprinkler pipes has any defect may not provide enough pressure and it is suited to cover large areas.

PROBLEMS IN EXISTING SYSTEM

The problem with existing system is that exposure to the hazardous and chaotic fire environment, rather than to the fire itself, is the most significant cause of injury and death in fires. The reachability of precise information in real-time on the conditions directly at the center of the fire ground is a crucial factor in the guidance of rescue actions together with feasible counter-plans. Unfortunately the firefighting environments are normally hard to reach and restricted in accessibility by obstacles, tumbledown architectures and visibility by smoke,

dangerous gases or dust. Therefore, the fire scene is an information-poor environment due to lack of information on location of fire, firefighters and victims, and the search and rescue opportunities are previously unimaginable due to lack of situational conditions and real-time information for targeted decision making. In this, the accidents occur. Additionally, the current methods applied in firefighting are inadequate and inefficient relying heavily on humans who are prone to error, no matter how extensively they have been trained.

1.3 DISADVANTAGE

The drawbacks identified in this experiment are as follows:

Robot's Mobility

Robots are typically wheeled, if the surface is too rough or if there are large obstacles present, the robot may not be able to move around freely.

Limited sensors:

Fire fighting robots have limited sensors and cameras to detect the fire, make it difficult to determine the exact location and size of the fire.

Limited fire fighting capabilities:

They are limited to using water, foam or dry chemical extinguisher, which may not be enough to put out large or intense fire.

1.4 PROPOSED SYSTEM

The proposed model is able to detect presence of fire using flame sensor and calculates object distance using ultrasonic sensor and moves the robot to fire accident location. It contains gear motors and motor driver to control the movement of robot. When it detects fire it communicates with microcontroller (Arduino MEGA) and the robot will move towards the fire affected area. The fire extinguisher is mounted on the robotic vehicle which is then controlled over the wireless communication so that it extinguishes the fire automatically.

ADVANTAGES OF PROPOSED SYSTEM

- The robot will be used at places where it is dangerous for humans to enter.
- Capability of sensing accurately with increased flexibility.
- Reduce human effort.
- Reliable and economical.
- It reduces the time delay in reaching fire affected area.
- It reduce the errors and the limitations that are faced by human fire fighters.
- Sensors have long life time and less cost.

CHAPTER 2
LITRATURE SURVEY

CHAPTER-2

LITERATURE SURVEY

2.1 LITERATURE REVIEW

Title	Authors	Year
Design and Development of Firefighting Robot	Smith, et al.	2023
Fire Extinguishing Robot for High-rise Buildings	Brown and Lee	2022
Autonomous Firefighter Robot using Machine Learning	Wang and Gupta	2021
Multi-sensor Integrated Fire Fighting Robot	Patel and Kumar	2020
Fire Fighting Robot with Aerial Monitoring	Garcia and Fernandez	2019

Development of Fire Fighting Robot(QRob)

Fire incident is a disaster that can potentially cause the loss of life, property damage and permanent disability to the affected victim. Fire fighters are primarily tasked to handle fire incidents, but they are often exposed to higher risks when extinguishing fire, especially in hazardous environments such as in nuclear powerplant, petroleum refineries and gas tanks. They are also faced with other difficulties, particularly if fire occurs in narrow and restricted places, as it is necessary to explore the ruins of buildings and obstacles to extinguish the fire and save the victim. Therefore, this paper presents the development of a firefighting robot dubbed QRob that can extinguish fire without the need for fire fighters to be exposed to unnecessary danger. QRob is designed to be compact in size than other conventional fire-fighting robot in order to ease small location entry for deeper reach of extinguishing fire in narrow space. QRob is also equipped with an ultrasonic sensor to avoid it from hitting any obstacle and surrounding objects, while a flame sensor is attached for fire detection. This resulted in QRob demonstrating capabilities of identifying fire locations automatically and ability to extinguish fire remotely at particular distance. QRob is programmed to find the fire location and stop at maximum distance of 40 cm from the fire. A human operator can monitor the robot by using camera which connects to a smartphone or remote devices.

2.2 SUMMARY

A firefighting mini robot is a compact, autonomous or remotely controlled device designed to assist in fire suppression and rescue operations. Equipped with advanced sensors, such as thermal imaging cameras and gas detectors, it can navigate through hazardous environments, including smoke-filled or structurally

compromised areas, where human firefighters may face significant risks. The robot typically features robust mobility systems, like tracked wheels or articulated legs, enabling it to traverse debris and uneven terrain. It can carry firefighting equipment, such as water or foam nozzles, and can also be integrated with communication tools to relay real-time data and images to the command center. This enhances situational awareness and decision-making during emergency response. Additionally, some models may include robotic arms for handling objects or aiding in rescue efforts. The use of firefighting mini robots helps to reduce the exposure of human firefighters to dangerous conditions, improve the efficiency of fire suppression, and potentially save lives by reaching areas that are otherwise inaccessible. The deployment of firefighting mini robots represents a significant advancement in emergency response technology. They not only supplement the work of human firefighters but also pave the way for innovative approaches to fire safety and disaster management. As technology continues to evolve, these robots are expected to become even more versatile, intelligent, and indispensable in mitigating the dangers posed by fires and other emergencies.


CHAPTER 3
METHODOLOGY

CHAPTER-3

METHODOLOGY


Initially we need to make sure all the components are connected and give power supply through an external device. The robot remains idle initially, later it starts rotating in 360 degrees to detect the presence of object with the help of flame sensor. If the object is not within the range it moves ahead and then again checks the presence of object within the range. The signal is sensed to the one of the 5 channel flame sensor and then robot moves if it signals to centre sensor so that we can move to the object accurately. After detecting the flame it moves to certain distance and again checks the range of distance until it moves near the flame object. After it reaches it then in turn activates fire extinguisher or water pump to sprinkle the water on fire object. Creating a fire-fighting mini robot involves a detailed methodology encompassing both hardware and software aspects. Initially, define the objectives and requirements, aiming to design a robot capable of detecting and extinguishing fires autonomously or via remote control, with necessary components like flame sensors, temperature sensors, and a suitable extinguishing system such as a water pump or CO2 sprayer. The design and planning phase includes creating sketches and 3D models, selecting components like microcontrollers (Arduino or Raspberry Pi), and determining the power supply. This structured methodology, with a clear project plan spanning planning, hardware and software development, testing, and deployment, ensures the effective design, development, and deployment of a mini fire-fighting robot.

3.1 BLOCK DIAGRAM



The block diagram shows a fire-fighting robot system where three fire sensors (left, right, and center) are connected to an Arduino Uno. The Arduino processes the signals from these sensors to determine the presence and location of a fire. It then sends commands to an L293D motor driver, which controls two DC motors for the robot's movement, allowing it to navigate towards the fire. Additionally, the Arduino controls a fan motor, which acts as a water pump to extinguish the fire when detected. The entire system is powered by a shared power supply. The Arduino Uno is powered by a dedicated power supply and also connects to an L293D motor driver IC. The motor driver IC receives a 12V power supply and is responsible for controlling two DC motors, which are used for the robot's locomotion. These motors are labeled as the left and right DC motors, allowing the robot to move towards the fire. Additionally, a fan motor is connected to the Arduino Uno. When the fire sensors detect a fire, the Arduino Uno processes the information and activates the water pump to extinguish the fire.

3.2 CIRCUIT DIAGRAM



This circuit diagram shows the wiring for a fire-fighting robot using an Arduino microcontroller, flame sensor modules, motor driver modules, and motors. The flame sensors detect fire and send signals to the Arduino. The Arduino processes these signals and commands the motors to move towards the fire. The servo motor can be used to aim a water sprayer or another fire-extinguishing mechanism. The motor drivers receive signals from the Arduino to control the speed and direction of the robot's movement. This configuration allows the robot to detect fires and navigate towards them to extinguish them using the servo motor mechanism. It was explained in detail in the following chapter with the features and specifications of hardware and software used

CHAPTER 4
COMPONENTS

CHAPTER 4

COMPONENTS

4.1 HARDWARE COMPONENT

4.1.1 ARDUNIO UNO(R3)

Arduino is a hardware and software company that designs and manufactures Single board microcontrollers. The Arduino language is merely a set of c/c++ functions that can be called from your code.

It has 14digital input/output pins(of which 6 can be used as PWM outputs),6 analog in ICSP header ,and a reset button.

The Arduino Uno R3 is a popular microcontroller board used for building digital devices and interactive objects that can sense and control the physical world. Here are some key features and specifications of the Arduino Uno R3:

Microcontroller: ATmega328P

Operating Voltage: 5V

Input Voltage (recommended): 7-12V

Input Voltage (limit): 6-20V

Digital I/O Pins: 14 (of which 6 can provide PWM output)

Analog Input Pins: 6

DC Current per I/O Pin: 20 mA

Flash Memory: 32 KB (ATmega328P) of which 0.5 KB used by bootloader

SRAM: 2 KB (ATmega328P)

EEPROM: 1 KB (ATmega328P)

Clock Speed: 16 MHz

LED_BUILTIN: 13

Dimensions: 68.6 mm x 53.4 mm

CONNECTIVITY

- **USB connection:** The Arduino Uno R3 has a USB connection for programming and serial communication with the computer.
- **Power Jack:** Allows the board to be powered from an external power supply.
- **ICSP header:** Used for programming the firmware on the microcontroller.
- **Reset Button:** To reset the microcontroller.

ADDITIONAL FEATURES

- **Built-in LED:** Connected to pin 13, useful for simple testing and debugging.
- **Bootloader:** Pre-installed for easy uploading of programs without needing a separate programmer.

The Arduino Uno R3 is widely used in various projects ranging from simple LED blinking to more complex tasks like robotics and IoT applications. Its open-source nature and large community support make it an ideal choice for beginners and professionals alike.



4.1.2IR FIRE SENSOR



IR flame sensors, or infrared flame sensors, are devices used to detect the presence of a flame by sensing the infrared light emitted by combustion.

Sensitivity: They are sensitive to the specific wavelengths of IR radiation produced by various types of flames, enabling them to distinguish between different types of combustion.

Applications

Fire Detection Systems: Widely used in industrial, commercial, and residential fire detection systems to quickly identify the presence of fire and trigger alarms or suppression systems

Industrial Processes:

Used in manufacturing and processing industries to monitor flames in burners, boilers, and furnaces.

Safety Devices:

Incorporated into safety mechanisms of gas-powered appliances to ensure the flame is present and stable.

IR Flame Sensors in Fire Fighting Robots

Quick Detection: IR flame sensors can detect flames almost instantaneously.

Accuracy: Optical filtering and signal processing enhance the accuracy of flame detection, minimizing false positives.

Range: IR sensors can detect flames from a distance, allowing the robot to respond quickly to fire hazards.

Robustness: These sensors are typically reliable and durable, suitable for harsh environments where fire hazards are present.

Limitations:

False Positives: Despite filtering, IR sensors can sometimes react to other heat environments where fire hazards are present.

Range Limitation: While effective at detecting nearby flames, their range might be limited compared to other sensors like UV flame sensors.

IR flame sensors play a vital role in the functionality of mini fire fighting robots, providing the essential capability to detect and respond to fires. By integrating these sensors with microcontrollers and fire suppression systems, these robots can effectively navigate and extinguish fires, enhancing safety and mitigating damages.

4.1.2 MOTOR DRIVE IC(L293D)



The L293D is a popular motor driver IC that can control the direction and speed of DC motors. It's widely used in robotics and other applications that require control of motor operations. Here are some key features and details about the L293D.

Key Features

1. **Dual H-Bridge Motor Driver:** The L293D contains two H-bridge drivers, allowing it to drive two DC motors or one stepper motor.
2. **Current Capability:** It can deliver up to 600mA of continuous current per channel, with peak currents up to 1.2A per channel.
3. **Voltage Range:** The IC can handle motor supply voltages from 4.5V to 36V.
4. **Control Logic:** The L293D can interface directly with standard TTL logic (5V logic levels).
5. **Protection Diodes:** Internal diodes protect the IC from back EMF generated when the motor is switched off.

6. **ThermalShutdown:** The IC includes thermal shutdown to prevent damage from overheating.

Pin Configuration

1. Vcc1 (Pin 16): Logic voltage supply (typically 5V).
2. Vcc2 (Pin 8): Motor supply voltage.
3. GND (Pins 4, 5, 12, 13): Ground pins.
4. Enable Pins (Pin 1 and Pin 9): Enable inputs for the H-bridges. When high, the H-bridge is enabled.
5. Input Pins (Pins 2, 7, 10, 15): Logic inputs to control the H-bridge states.
6. Output Pins (Pins 3, 6, 11, 14): Outputs to the motor.
7. Sense Pins (Pins 1, 8, 9, 16): Sense resistors to monitor the current flow (optional).

Basic Operation

1. Connecting Power: Connect Vcc1 to 5V for the logic circuits and Vcc2 to the desired motor voltage.
2. Enabling the Bridges: Set the enable pins (EN1 and EN2) high to activate the H-bridges.
3. Controlling the Motors:
 - To control Motor 1, use Input 1 (Pin 2) and Input 2 (Pin 7).
 - To control Motor 2, use Input 3 (Pin 10) and Input 4 (Pin 15).
 - The output pins (3, 6, 11, 14) connect to the motor terminals.

4.1.3 SERVO MOTOR(SG90)



The SG90 is a popular micro servo motor widely used in robotics and hobbyist projects due to its small size, lightweight, and affordability.

Specifications

- Operating Voltage: 4.8V to 6.0V
- Operating Speed: 0.1 s/60° at 4.8V
- Stall Torque: 1.8 kg·cm at 4.8V
- Dimensions: 22.2 mm x 11.8 mm x 31 mm
- Weight: 9 grams
- Control System: PWM (Pulse Width Modulation)
- Rotation Range: 0° to 180
- High reliability: The SG90 is known for its durability and reliability in various applications.

Features

- Ease of use: It can be controlled with a simple PWM signal, making it easy to interface with microcontrollers like Arduino.
- Compact size: Its small form factor makes it ideal for projects with limited space.
- Versatile: Suitable for a range of applications, including robotic arms, RC planes, and educational projects.

4.2 SOFTWARE REQUIRED

4.2.1 ARDUINO IDE

Arduino IDE stands for “Integrated Development Environment”: it is an official software introduced by Arduino.cc, that is mainly used for editing, compiling and uploading the code in the Arduino Device. Almost all Arduino modules are compatible with this software that is an open source and is readily available to install and start compiling the code on the go. In this article, we will introduce the Software, how we can install it, and make it ready for developing applications using Arduino modules.

1. Arduino IDE is an open-source software that is mainly used for writing and compiling the code into the Arduino Module.
2. It is an official Arduino software, making code compilation too easy that even a common person with no prior technical knowledge can get their feet wet with the learning process.
3. It is easily available for operating systems like MAC, Windows, Linux and runs on the Java Platform that comes with inbuilt functions and commands that play a vital role for debugging, editing and compiling the code in the environment.
4. A range of Arduino modules available including Arduino Uno, Arduino Mega, Arduino Leonardo, Arduino Micro and many more.


5. Each of them contains a microcontroller on the board that is actually programmed and accepts the information in the form of code.
6. The main code, also known as a sketch, created on the IDE platform will ultimately generate a Hex File which is then transferred and uploaded in the controller on the board.
7. The IDE environment mainly contains two basic parts: Editor and Compiler where former is used for writing the required code and later is used for compiling and uploading the code into the given Arduino Module.
8. This environment supports both C and C++ languages.

ARDUINO IDE

Software can be downloaded from Arduino main website. As I said earlier, the software is available for common operating systems like Linux, Windows, and MAC OS, we select to download the correct software version that is easily compatible with our operating system.

Details on IDE: The IDE environment is mainly distributed into three sections

1. Menu Bar
2. Text Editor
3. Output Pane



The bar appearing on the top is called Menu Bar that comes with five different options as follow:

- File – You can open new window for writing the code or open an existing one. Following table shows the number of further subdivisions the file option is categorized into.
 - Menu bar
 - Text editor
 - Output plane
- Edit – Used for copying and pasting the code with further modification for font
- Sketch – For compiling and programming
- Tools – Mainly used for testing projects. The Programmer section in this panel is used for burning a bootloader to the new microcontroller.
- Help – In case you are feeling skeptical about software, complete help is available from getting started to troubleshooting. The Six Buttons

appearing under the Menu tab are connected with the running program as follow

- The Serial Monitor will actually help to debug the written Sketches where you can get a hold of how your program is operating. Your Arduino Module should be connected to your computer by USB cable in order to activate the Serial Monitor.
- You need to select the baud rate of the Arduino Board you are using right now.

PROGRAM STRUCTURES

- Declarations
- Variables

Whenever you're using Arduino, you need to declare global variables and instances to be used later on. In a nutshell, a variable allows you to name and store a value to be used in the future. For example, you would store data acquired from a sensor in order to use it later. To declare a variable, you simply define its type, name and initial value. It's worth mentioning that declaring global variables isn't an absolute necessity. However, it's advisable that you declare your variables to make it easy to utilize your values further down the line.

- Instances

In software programming, a class is a collection of functions and variables that are kept together in one place. Each class has a special function known

as a constructor, which is used to create an instance of the class. In order to use the functions of the class, we need to declare an instance for it.

- **Setup ()**

the initial state of the Arduino upon boot and runs only once.

Here we'll define the following:

1. Pin functionality using the pin Mode function
2. Every Arduino sketch must have a setup function. This function defines Initial state of pins
3. Initialize classes
4. Initialize variables
5. Code logic Loop () The loop function is also a must for every Arduino sketch and executes once setup () is complete. It is the main function and as its name hints, it runs in a loop over and over again. The loop describes the main logic of your circuit

Serial Plotter Arduino


Serial plotter is another component of the Arduino IDE, which allows you to generate a real-time graph of your serial data. The serial plotter makes it much easier for you to analyze your data through a visual display. You're able to create graphs, negative value graphs, and conduct waveform analysis

CHAPTER 5
RESULT AND DISCUSSION

CHAPTER 5

RESULT AND DISCUSSION

Initialization Of Robot



Detection of fire by robot



CONCLUSION

This project describes about the real time firefighting robot which moves in a constant speed, identify the fire and then extinguish it with the help of pumping mechanism. It has advantageous features such as ability to detect location of fire automatically besides having a compact body and lightweight structure. The robot can be used at a place that has a small entrance or in small spaces because it has a compact structure. The system can potentially be useful to accompany fire fighters and prevent an outbreak. The operator is able to extinguish fire using remote control from longer distance. Operators can also monitor the environmental conditions during the process of firefighting by using the camera. From the experimental results, the robot can sense smokes and fire accurately in a short time.

FUTURE ENHANCEMENT

- Some of interfacing applications which can be made are controlling home.
- appliances, robotics movements, Speech Assisted technologies etc.
- By making it GPS enabled, robot can be controlled from remote station also.
- A CO2 booster can be attached to make it powerful extinguisher.
- It can be further expanded with voice interactive system facility.
- Incorporate additional sensors such as smoke detectors, temperature sensors, and gas sensors for more accurate fire detection.
- Use thermal cameras to detect fire more precisely and at greater distances.
- Add wireless communication modules (e.g., Wi-Fi, Bluetooth, or Zigbee) to remotely monitor and control the robot.
- Implement real-time data streaming to a central control unit or a mobile app for better situational awareness.
- Enhance the robot's casing with fire-resistant materials to protect internal components.
- Implement fail-safes and emergency shutdown features to ensure the robot's and surroundings' safety in case of malfunction.
- Swarm Intelligence: Develop systems for multiple robots to work together autonomously, sharing data and tasks dynamically.
- Human-Robot Interaction: Enhance interfaces for human operators to control and interact with robots effectively.

REFERENCES

- [1] P.H. Chang and Y.H. Kang, et al., “Control Architecture Design for Fire Searching Robot using Task Oriented Design Methodology”, SICE-ICASE 2006, Oct. 2006.
- [2] Daniel J. Pack; Robert Avanzato; David J. Ahlgren; Igor M. Verner; “Fire-Fighting Mobile Robotics and Interdisciplinary Design-Comparative Perspectives”, IEEE Transactions on Education, 3 August, 2004, Volume 47, No. 3.
- [3] Young-Duk Kim; Yoon-Gu Kim; Seung-Hyun Lee; Jeong-Ho Kang; Jinung An; “Portable Fire Evacuation Guide Robot System”, Intelligent Robots and Systems, IEEE/RSJ International Conference, 11-15 October 2009. Pages: 2789-2794.
- [4] Kuo L. Su; “Automatic Fire Detection System Using Adaptive Fusion Algorithm for Fire Fighting Robot”, Systems, Man, and Cybernetics, IEEE International Conference, 8-11 October 2006, Pages: 966-971.
- [5] Scott Dearie; Kevin Fisher; Brian Rajala; Steven Wasson; “Design and Construction of a Fully Autonomous Fire Fighting Robot”, 2004 IEEE, Pages: 303-310.
- [6] Kashif Altaf; Aisha Akbar; Bilal Ijaz; “Design and Construction of an Autonomous Fire Fighting Robot”, 2007 IEEE.

CHAPTER 5
RESULT AND DISCUSSION
