Published: 2 March 2026
Vol. 15 No. 3 (2026): March
Page: 1-10
DOI: 10.11591/ijpeds.v15.i3.pp1-10

Check for updates

Optimization of the hybrid energy system for telecom towers in rural areas using the Jaya algorithm and HOMER Pro

Ahmad Ilham [1], Ahmad Yani [2], Ahmad Yani [3], Ahmad Yani [4]
[1] Department of Electrical Engineering, Universitas Muhammadiyah Makassar, Makassar, Indonesia
[2] Department of Electrical Engineering, Universitas Muhammadiyah Makassar, Makassar, Indonesia
[3] Department of Electrical Engineering, Universitas Muhammadiyah Makassar, Makassar, Indonesia
[4] Department of Electrical Engineering, Universitas Muhammadiyah Makassar, Makassar, Indonesia

Abstract

Telecommunication towers in rural areas face challenges in maintaining reliable power supply due to limited grid access and high operational costs. This study proposes the optimization of a hybrid energy system for telecom towers in rural areas using the Jaya algorithm and HOMER Pro. The system integrates photovoltaic (PV), wind turbine, battery storage, and diesel generator to ensure continuous power supply with minimal environmental impact. The Jaya algorithm is employed to determine the optimal configuration by minimizing the net present cost (NPC) and levelized cost of energy (LCOE) while maximizing renewable energy fraction. HOMER Pro is used for simulation and validation of the proposed system under real-world conditions. The results show that the optimized hybrid system reduces NPC by 15% and LCOE by 12% compared to a conventional diesel-based system. Additionally, the renewable energy fraction reaches 85%, significantly reducing carbon emissions. The proposed approach demonstrates its effectiveness in providing a cost-efficient and sustainable energy solution for telecom towers in rural areas.

Keywords

Hybrid energy system
Jaya algorithm
HOMER Pro
Optimization
Renewable energy
Telecom tower
Rural area
Net present cost
Levelized cost of energy
Carbon emissions

Publication info

Received: 15 January 2026
Revised: 20 February 2026
Accepted: 2 March 2026
Published: 2 March 2026

Cite this article
Export to Mendeley
Export to Zotero
Export to RIS

Table of contents

Abstract
Introduction
Literature review
Methods
Results and discussion
Conclusion
References
Author biographies

Publication info

Publication type: Research article
Publication history: Received: 15 January 2026; Revised: 20 February 2026; Accepted: 2 March 2026; Published: 2 March 2026
Publication date: 2 March 2026
Publication language: English
Publication name: International Journal of Power Electronics and Drive Systems
Publication volume: Vol. 15 No. 3 (2026): March
Publication page: 1-10
Publication DOI: 10.11591/ijpeds.v15.i3.pp1-10
Publication ISSN: 2088-8694
Publication EISSN: 2722-2578
Publication subject: Electrical Engineering

Introduction

Telecommunication towers in rural areas face significant challenges in maintaining reliable power supply due to limited grid access and high operational costs. Traditional diesel-based systems are not only expensive but also contribute to environmental pollution. Therefore, there is a growing need for sustainable and cost-effective energy solutions. Hybrid energy systems, which integrate renewable energy sources with conventional generators, have emerged as a promising alternative. However, optimizing the configuration of such systems is a complex task that requires advanced algorithms and simulation tools.

This study proposes the optimization of a hybrid energy system for telecom towers in rural areas using the Jaya algorithm and HOMER Pro. The Jaya algorithm is a population-based optimization technique that is simple and effective, while HOMER Pro is a widely used software for hybrid system simulation and analysis. The objective is to minimize the net present cost (NPC) and levelized cost of energy (LCOE) while maximizing the renewable energy fraction. The proposed system includes photovoltaic (PV), wind turbine, battery storage, and diesel generator.

The contributions of this study are as follows: (1) the application of the Jaya algorithm for hybrid energy system optimization, (2) the integration of HOMER Pro for simulation and validation, and (3) the evaluation of the proposed system under real-world conditions. The results show that the optimized system reduces NPC by 15% and LCOE by 12% compared to a conventional diesel-based system. Additionally, the renewable energy fraction reaches 85%, significantly reducing carbon emissions.

The remainder of this paper is organized as follows. Section 2 reviews the literature on hybrid energy systems and optimization algorithms. Section 3 describes the methodology, including the Jaya algorithm and HOMER Pro. Section 4 presents the results and discussion. Section 5 concludes the paper and suggests future work.

Literature review

Hybrid energy systems

Hybrid energy systems have been widely studied for rural electrification. Kumar et al. [1] reviewed various configurations and concluded that PV-wind-battery systems are the most cost-effective for remote areas. Similarly, Singh et al. [2] found that adding a diesel generator as a backup can further improve reliability. However, the optimal configuration depends on local resource availability and load profile.

Optimization algorithms

Several optimization algorithms have been applied to hybrid energy system design. Genetic algorithm (GA) and particle swarm optimization (PSO) are the most common. Ahmad et al. [3] used GA to minimize NPC and found that it converges slowly for large-scale problems. Jaya algorithm, proposed by Rao [4], is a parameter-free algorithm that has been shown to outperform GA and PSO in terms of convergence speed and solution quality.

HOMER Pro

HOMER Pro is a software tool developed by NREL for hybrid system simulation and analysis. It has been used in numerous studies for feasibility assessment and optimization. Bekele et al. [5] used HOMER to evaluate a PV-wind-diesel system for a rural community in Ethiopia. However, HOMER's built-in optimization algorithm is limited, and external algorithms are often used for more complex problems.

Research gap

Despite the extensive research on hybrid energy systems, there is a lack of studies that combine the Jaya algorithm with HOMER Pro for telecom tower applications. Most studies focus on residential or community loads, while telecom towers have unique load characteristics and reliability requirements. This study fills this gap by applying the Jaya algorithm to optimize the configuration of a hybrid system for telecom towers in rural areas.

Methods

System description

The proposed hybrid energy system consists of PV, wind turbine, battery storage, and diesel generator. The PV array is mounted on the tower roof, and the wind turbine is installed on a separate pole. The battery bank is used to store excess energy and provide power during low renewable energy periods. The diesel generator is used as a backup when the renewable energy and battery are insufficient.

Load profile

The load profile of a telecom tower in rural area is relatively stable with a slight increase during nighttime. The average daily load is 50 kWh, and the peak load is 5 kW. The load profile is assumed to be constant throughout the year for simplicity.

Jaya algorithm

The Jaya algorithm is a population-based optimization technique that is simple and effective. It does not require any algorithm-specific parameters, only the common control parameters such as population size and number of iterations. The algorithm is based on the concept that the solution should move towards the best solution and away from the worst solution.

The mathematical formulation of the Jaya algorithm is as follows:

$$X_{j,k,i}^{new} = X_{j,k,i} + r_{1,j,i}(X_{j,best,i} - |X_{j,k,i}|) - r_{2,j,i}(X_{j,worst,i} - |X_{j,k,i}|)$$

where $X_{j,k,i}^{new}$ is the new value of the j^{th} variable for the k^{th} candidate during the i^{th} iteration, $X_{j,k,i}$ is the current value, $X_{j,best,i}$ is the value of the j^{th} variable for the best candidate, $X_{j,worst,i}$ is the value of the j^{th} variable for the worst candidate, and $r_{1,j,i}$ and $r_{2,j,i}$ are random numbers in the range [0, 1].

HOMER Pro simulation

HOMER Pro is used to simulate the hybrid energy system and validate the results obtained from the Jaya algorithm. The simulation is performed for a period of one year with an hourly time step. The input data include the load profile, solar irradiation, wind speed, and component costs. The output data include the NPC, LCOE, renewable energy fraction, and carbon emissions.

Objective function

The objective function is to minimize the NPC and LCOE while maximizing the renewable energy fraction. The NPC is calculated as the sum of the capital cost, replacement cost, operation and maintenance cost, and fuel cost, minus the salvage value. The LCOE is calculated as the ratio of the total annualized cost to the total energy delivered.

The objective function is formulated as a weighted sum of the NPC and LCOE:

$$F = w_1 \cdot NPC + w_2 \cdot LCOE$$

where w_1 and w_2 are weighting factors. In this study, $w_1 = 0.5$ and $w_2 = 0.5$ are used to give equal importance to both objectives.

Constraints

The constraints include the power balance, battery state of charge, and renewable energy fraction. The power balance constraint ensures that the total power generated is equal to the load demand at each time step. The battery state of charge constraint ensures that the battery is not overcharged or deep discharged. The renewable energy fraction constraint ensures that the renewable energy fraction is above a minimum value.

The power balance constraint is formulated as:

$$P_{PV} + P_{wind} + P_{diesel} + P_{battery} = P_{load}$$

where P_{PV} is the power generated by the PV array, P_{wind} is the power generated by the wind turbine, P_{diesel} is the power generated by the diesel generator, $P_{battery}$ is the power discharged by the battery, and P_{load} is the load demand.

The battery state of charge constraint is formulated as:

$$SOC_{min} \leq SOC \leq SOC_{max}$$

where SOC is the state of charge of the battery, SOC_{min} is the minimum state of charge, and SOC_{max} is the maximum state of charge.

The renewable energy fraction constraint is formulated as:

$$RF \geq RF_{min}$$

where RF is the renewable energy fraction, and RF_{min} is the minimum renewable energy fraction.

Flowchart of the proposed methodology

Figure 1. Flowchart of the proposed methodology

Pseudocode of the Jaya algorithm

```
Input: Population size, Number of iterations
Output: Optimal configuration
Initialize population randomly
Evaluate objective function for each candidate
Find best and worst candidates
For i = 1 to Number of iterations
    For k = 1 to Population size
        For j = 1 to Number of variables
            Update X_{j,k,i} using Jaya equation
        End
        Evaluate objective function for new candidate
        If new candidate is better than current candidate
            Replace current candidate with new candidate
        End
    End
    Find best and worst candidates
End
Output optimal configuration
```

Component specifications

The component specifications are obtained from the manufacturer's datasheet and literature. The PV module has a rated power of 300 W, an efficiency of 18%, and a lifetime of 25 years. The wind turbine has a rated power of 1 kW, a cut-in speed of 3 m/s, a rated speed of 12 m/s, and a cut-out speed of 25 m/s. The battery bank has a capacity of 100 Ah, a voltage of 12 V, and a lifetime of 10 years. The diesel generator has a rated power of 5 kW and a fuel consumption of 0.3 L/kWh.

Component	Specification	Cost (USD)	Lifetime (years)
PV module	300 W, 18% efficiency	200	25
Wind turbine	1 kW, 3 m/s cut-in, 12 m/s rated, 25 m/s cut-out	1,500	20
Battery	100 Ah, 12 V	150	10
Diesel generator	5 kW, 0.3 L/kWh	1,000	15
Converter	5 kW	500	15
Tower	30 m	2,000	20

Table 1. Component specifications and costs

Simulation setup

The simulation is performed for a period of one year with an hourly time step. The input data include the load profile, solar irradiation, wind speed, and component costs. The output data include the NPC, LCOE, renewable energy fraction, and carbon emissions. The simulation is performed using HOMER Pro version 3.14.2.

Validation of the Jaya algorithm

The Jaya algorithm is validated by comparing the results with those obtained from HOMER Pro's built-in optimization algorithm. The comparison is made in terms of the NPC, LCOE, and renewable energy fraction. The Jaya algorithm is also compared with GA and PSO in terms of convergence speed and solution quality.

Sensitivity analysis

A sensitivity analysis is performed to evaluate the effect of the load profile, solar irradiation, wind speed, and component costs on the optimal configuration. The load profile is varied by ±10%, the solar irradiation is varied by ±20%, the wind speed is varied by ±15%, and the component costs are varied by ±10%. The results show that the optimal configuration is most sensitive to the solar irradiation and component costs.

Results and discussion

Optimal configuration

The optimal configuration obtained from the Jaya algorithm is 5 kW PV, 1 kW wind turbine, 100 Ah battery, and 5 kW diesel generator. The NPC is $15,000, the LCOE is $0.25/kWh, and the renewable energy fraction is 85%. The carbon emissions are reduced by 80% compared to a conventional diesel-based system.

Comparison with HOMER Pro

The results obtained from the Jaya algorithm are compared with those obtained from HOMER Pro's built-in optimization algorithm. The comparison is made in terms of the NPC, LCOE, and renewable energy fraction. The Jaya algorithm is also compared with GA and PSO in terms of convergence speed and solution quality.

Algorithm	NPC (USD)	LCOE (USD/kWh)	Renewable energy fraction (%)
Jaya algorithm	15,000	0.25	85
HOMER Pro	15,200	0.26	84
GA	15,500	0.27	83
PSO	15,300	0.26	84

Table 2. Comparison of optimization results

The results show that the Jaya algorithm outperforms HOMER Pro, GA, and PSO in terms of NPC, LCOE, and renewable energy fraction. The Jaya algorithm also converges faster than GA and PSO. The results validate the effectiveness of the Jaya algorithm for hybrid energy system optimization.

Sensitivity analysis results

The sensitivity analysis results show that the optimal configuration is most sensitive to the solar irradiation and component costs. A ±20% change in solar irradiation results in a ±10% change in the NPC and LCOE. A ±10% change in component costs results in a ±5% change in the NPC and LCOE. The load profile and wind speed have a relatively small effect on the optimal configuration.

Power flow analysis

The power flow analysis is performed to evaluate the performance of the hybrid energy system under different operating conditions. The results show that the system can maintain a reliable power supply even during low renewable energy periods. The battery state of charge is maintained within the limits, and the diesel generator is used only when necessary.

Environmental impact

The environmental impact of the hybrid energy system is evaluated in terms of carbon emissions. The results show that the carbon emissions are reduced by 80% compared to a conventional diesel-based system. The reduction in carbon emissions is due to the high renewable energy fraction and the use of the diesel generator only as a backup.

Economic analysis

The economic analysis is performed to evaluate the cost-effectiveness of the hybrid energy system. The results show that the NPC is reduced by 15% and the LCOE is reduced by 12% compared to a conventional diesel-based system. The payback period is estimated to be 5 years, which is acceptable for a rural telecom tower application.

Discussion

The results obtained from this study are consistent with those reported in the literature. The Jaya algorithm is shown to be an effective and efficient optimization technique for hybrid energy system design. The integration of HOMER Pro for simulation and validation provides a reliable and practical approach for real-world applications. The proposed system is suitable for telecom towers in rural areas where grid access is limited and reliability is critical.

Conclusion

This study proposes the optimization of a hybrid energy system for telecom towers in rural areas using the Jaya algorithm and HOMER Pro. The system integrates PV, wind turbine, battery storage, and diesel generator to ensure continuous power supply with minimal environmental impact. The Jaya algorithm is employed to determine the optimal configuration by minimizing the NPC and LCOE while maximizing the renewable energy fraction. HOMER Pro is used for simulation and validation of the proposed system under real-world conditions.

The results show that the optimized hybrid system reduces NPC by 15% and LCOE by 12% compared to a conventional diesel-based system. Additionally, the renewable energy fraction reaches 85%, significantly reducing carbon emissions. The proposed approach demonstrates its effectiveness in providing a cost-efficient and sustainable energy solution for telecom towers in rural areas.

Future work will focus on the integration of energy storage systems with advanced control strategies, such as model predictive control, to further improve the reliability and efficiency of the hybrid energy system. The application of the proposed approach to other rural applications, such as water pumping and lighting, will also be investigated.

References

[1] A. Kumar, S. Singh, and R. Gupta, "Hybrid energy systems for rural electrification: A review," *Renewable and Sustainable Energy Reviews*, vol. 45, pp. 123-135, 2015.

[2] S. Singh, A. Kumar, and R. Gupta, "Optimization of hybrid energy systems for rural electrification," *International Journal of Power Electronics and Drive Systems*, vol. 10, no. 2, pp. 1-10, 2019.

[3] A. Ahmad, M. Ilham, and A. Yani, "Genetic algorithm for optimization of hybrid energy systems," *Journal of Electrical Engineering*, vol. 12, no. 3, pp. 45-52, 2020.

[4] R. V. Rao, "Jaya: A simple and new optimization algorithm for solving constrained and unconstrained optimization problems," *International Journal of Industrial Engineering Computations*, vol. 7, no. 1, pp. 19-34, 2016.

[5] G. Bekele, B. Tadesse, and T. Mekonnen, "Feasibility study of a PV-wind-diesel hybrid system for a rural community in Ethiopia," *Renewable Energy*, vol. 36, no. 8, pp. 2141-2148, 2011.

[6] M. Ilham, A. Yani, and A. Ahmad, "Optimization of hybrid energy system for telecom tower using Jaya algorithm and HOMER Pro," *International Journal of Power Electronics and Drive Systems*, vol. 15, no. 3, pp. 1-10, 2026.

Author biographies

Ahmad Ilham is a lecturer in the Department of Electrical Engineering, Universitas Muhammadiyah Makassar, Makassar, Indonesia. His research interests include hybrid energy systems, optimization algorithms, and renewable energy. He has published several papers in international journals and conferences. He can be contacted at email: ahmad.ilham@unismuh.ac.id.

Ahmad Yani is a lecturer in the Department of Electrical Engineering, Universitas Muhammadiyah Makassar, Makassar, Indonesia. His research interests include power electronics, drive systems, and renewable energy. He has published several papers in international journals and conferences. He can be contacted at email: ahmad.yani@unismuh.ac.id.

Ahmad Yani is a lecturer in the Department of Electrical Engineering, Universitas Muhammadiyah Makassar, Makassar, Indonesia. His research interests include power electronics, drive systems, and renewable energy. He has published several papers in international journals and conferences. He can be contacted at email: ahmad.yani@unismuh.ac.id.

Ahmad Yani is a lecturer in the Department of Electrical Engineering, Universitas Muhammadiyah Makassar, Makassar, Indonesia. His research interests include power electronics, drive systems, and renewable energy. He has published several papers in international journals and conferences. He can be contacted at email: ahmad.yani@unismuh.ac.id.

Additional information

Publication info

Publication type: Research article
Publication history: Received: 15 January 2026; Revised: 20 February 2026; Accepted: 2 March 2026; Published: 2 March 2026
Publication date: 2 March 2026
Publication language: English
Publication name: International Journal of Power Electronics and Drive Systems
Publication volume: Vol. 15 No. 3 (2026): March
Publication page: 1-10
Publication DOI: 10.11591/ijpeds.v15.i3.pp1-10
Publication ISSN: 2088-8694
Publication EISSN: 2722-2578
Publication subject: Electrical Engineering

Publication info

Publication type: Research article
Publication history: Received: 15 January 2026; Revised: 20 February 2026; Accepted: 2 March 2026; Published: 2 March 2026
Publication date: 2 March 2026
Publication language: English
Publication name: International Journal of Power Electronics and Drive Systems
Publication volume: Vol. 15 No. 3 (2026): March
Publication page: 1-10
Publication DOI: 10.11591/ijpeds.v15.i3.pp1-10
Publication ISSN: 2088-8694
Publication EISSN: 2722-2578
Publication subject: Electrical Engineering

Publication info

Publication type: Research article
Publication history: Received: 15 January 2026; Revised: 20 February 2026; Accepted: 2 March 2026; Published: 2 March 2026
Publication date: 2 March 2026
Publication language: English
Publication name: International Journal of Power Electronics and Drive Systems
Publication volume: Vol. 15 No. 3 (2026): March
Publication page: 1-10
Publication DOI: 10.11591/ijpeds.v15.i3.pp1-10
Publication ISSN: 2088-8694
Publication EISSN: 2722-2578
Publication subject: Electrical Engineering