A. Hayato and School

time limit per test 1 second
memory limit per test 256 megabytes
input standard input
output standard output

Rating: 800 | Tags: constructive algorithms, greedy | https://codeforces.com/problemset/problem/1780/A

Today Hayato came home from school with homework.

In the assignment, Hayato was given an array a of length n. The task was to find 3 numbers in this array whose sum is **odd**. At school, he claimed that there are such 3 numbers, but Hayato was not sure, so he asked you for help.

Answer if there are such three numbers, and if so, output indices i, j, and k such that $a_i + a_j + a_k$ is odd.

The odd numbers are integers that are not divisible by 2: 1, 3, 5, and so on.

Input

The first line contains a single integer t ($1 \le t \le 10^4$) — the number of test cases.

For each test case, the first line contains one integer n ($3 \le n \le 300$) — the length of a.

The second line contains n integers $a_1, a_2, \ldots, a_n$ ($1 \le a_i \le 10^5$) — the array a.

It is guaranteed that the sum of n over all test cases does not exceed $2 \cdot 10^5$.

Output

For each test case, in the first line print one word "YES" (without quotes) if there are 3 numbers with an odd sum or "NO" (without quotes) if there are no such 3 numbers.

If the answer exists, then on the second line print 3 distinct integers i, j, k ($1 \le i, j, k \le n$) — the indices of the numbers. If there are several answers, output any.

Example

Input

```
6
3
1 1 1
4
1 1 2 2
3
1 2 3
5
1 4 5 1 2
4
2 6 2 4
5
5 6 3 2 1
```

Output

```
YES
1 2 3
YES
3 4 1
NO
YES
1 3 4
NO
YES
1 3 5
```

Note

In the first test case, there is one way to choose 3 numbers, and since 1 + 1 + 1 = 3, this triple is fine for us.

In the second test case, you need to choose the numbers 1, 2, 2, since 1 + 2 + 2 = 5.

In the third test case, there is one way to choose three numbers, but 1 + 2 + 3 = 6 is an even number, so the required triple does not exist.

In the fifth test case, no matter what three numbers we choose, their sum is even.