## Object-Oriented Python: Takeaways ₪

by Dataquest Labs, Inc. - All rights reserved © 2023

## Syntax

• Define an empty class:

```
class MyClass:
pass
```

• Instantiate an object of a class:

```
class MyClass:
    pass
mc_1 = MyClass()
```

• Define an init function in a class to assign an attribute at instantiation:

```
class MyClass:
    def __init__(self, param_1):
        self.attribute_1 = param_1
mc_2 = MyClass("arg_1")
```

• Define a method inside a class and call it on an instantiated object:

```
class MyClass:
    def __init__(self, param_1):
        self.attribute_1 = param_1
    def add_20(self):
        self.attribute_1 += 20

mc_3 = MyClass(10) # mc_3.attribute is 10

mc_3.add_20() # mc_3.attribute is 30
```

## Concepts

- In **Object-Oriented Programming**, the fundamental building blocks are objects.
  - It differs from **Procedural** programming, which executes sequential steps.
- An **object** is an entity that stores data.
- A class describes an object's type. It defines the following:
  - What data is stored in the object, known as attributes
  - What actions the object can do, known as methods
- An attribute is a variable that belongs to an instance of a class.
- A **method** is a function that belongs to an instance of a class.
- We access attributes and methods using **dot notation**. Attributes do not use parentheses, whereas methods do.
- An **instance** describes a specific example of a class. For instance, in the code x = 3, x is an instance of the type int.
  - We call creating an object instantiation.

- A **class definition** is code that defines how a class behaves, including all methods and attributes.
- The init method is a special method that runs at the moment of an object's instantiation.
  - The init method ( \_\_init\_\_() ) is one of a number of special methods that Python defines.
- All methods must include self , representing the object instance, as their first parameter.
- It is convention to start the name of any attributes or methods that we don't intend for external use with an underscore.

## Resources

• Python Documentation: Classes

Takeaways by Dataquest Labs, Inc. - All rights reserved © 2023