

ACTIVITY01

API Data Contract

How the React frontend (activity01-frontend) communicates with the Spring Boot backend (edu.cit.sibi.activity01).

Base URL

http://localhost:8080/api

All requests and responses use Content-Type: application/json. There is no authentication token — the login endpoint returns the matched user record, which the frontend stores client-side (password field stripped) to represent the active session.

01 · ENDPOINT	
Method & URL	POST /api/register
Purpose	Creates a new user account in the l23y19w39 MySQL database.
Request headers	Content-Type: application/json
Request body	<i>JSON object with the following fields:</i> username — string, required email — string, required password — string, required
Successful response	201 Created Returns the saved user record, including its generated id.
Error response(s)	400 Bad Request Username already exists, or a required field is missing/invalid.
SAMPLE REQUEST	
<pre>{ "username": "juandelacruz", "email": "juan@example.com", "password": "somepassword" }</pre>	
SAMPLE SUCCESS RESPONSE	
<pre>{ "id": 1, "username": "juandelacruz", "email": "juan@example.com", "password": "somepassword" }</pre>	
SAMPLE ERROR RESPONSE	
<pre>"Username already exists"</pre>	

02 · ENDPOINT	
Method & URL	POST /api/login
Purpose	Verifies a username/password pair and returns the matching user record.

Request headers	Content-Type: application/json
Request body	<i>JSON object with the following fields:</i> username — string, required password — string, required
Successful response	200 OK Returns the authenticated user record.
Error response(s)	401 Unauthorized Username not found, or password does not match.
SAMPLE REQUEST	
<pre>{ "username": "juandelacruz", "password": "somepassword" }</pre>	
SAMPLE SUCCESS RESPONSE	
<pre>{ "id": 1, "username": "juandelacruz", "email": "juan@example.com", "password": "somepassword" }</pre>	
SAMPLE ERROR RESPONSE	
<pre>"Invalid username or password"</pre>	

03 · ENDPOINT	
Method & URL	GET /api/user/{id}
Purpose	Fetches a single user by numeric id. Not currently called by the frontend UI, but available for future use (e.g. refreshing profile data).
Request headers	None required
Request body	None
Successful response	200 OK Returns the matching user record.
Error response(s)	404 Not Found No user exists with the given id.
SAMPLE REQUEST	
<pre>GET /api/user/1 (no request body)</pre>	
SAMPLE SUCCESS RESPONSE	
<pre>{ "id": 1, "username": "juandelacruz", "email": "juan@example.com",</pre>	

```
"password": "somepassword"
}
```

SAMPLE ERROR RESPONSE

```
"User not found"
```

Frontend request field ↔ backend field mapping

Field names in the React forms match the backend request bodies exactly (username, email, password), so no field renaming or transformation happens client-side before a request is sent.

Client-side handling note

Although `/api/register`, `/api/login`, and `/api/user/{id}` currently echo the password field back in their JSON response, the React app never persists or displays it. The password field is stripped before the logged-in user is saved to `sessionStorage` (see `src/api/session.js` in the frontend repo).