

DATASHEET




Description:

- Unshielded Copper cable, 4 pairs, category 6, stranded (patch)
- Cable is used for indoor installation
- Application: Patch Cord wiring in LAN

Materials:

- Conductive material: Copper Clad Aluminium (CCA)
- Conductor insulation: HDPE
- The cable jacket: LSZH



1 - Jacket

2 - Twisted pairs stranded (patch)

Technical characteristics:

Conductor diameter:	7 x 0.008" (0.2 mm) (24 AWG)
Insulated conductor diameter:	0.039" ± 0.001" (0.99 ± 0.02 mm)
Outer cable diameter:	6 ± 0.2 mm
Minimum bend radius:	4 outer cable diameters
Conductor elongation:	14% minimum
Installation temperature:	0°C – +50°C (+32°F – +122°F)
Operating temperature:	-20°C – +75°C (-4°F – +167°F)
Weight per 1000 ft: Standard	10.4 kg (22.8 lbs)
package:	100 m.

DATASHEET

Twisted Pair Cable UTP, 4 pairs, Cat.6, Stranded (Patch),

Available variants

Article no.	Title	Length	Colour outer sheath	Number of cores	Type	Outer diameter approx.
IDL0210100	Raw cable Cat.6, UTP, LSZH, black, 100m ring	100.0 m	black	8	simplex	6
IDL0216100	Raw cable Cat.6, UTP, LSZH, blue, 100m ring	100.0 m	blue	8	simplex	6
IDL0211100	Raw cable Cat.6, UTP, LSZH, brown, 100m ring	100.0 m	brown	8	simplex	6
IDL0218100	Raw cable Cat.6, UTP, LSZH, grey, 100m ring	100.0 m	grey	8	simplex	6
IDL0215100	Raw cable Cat.6, UTP, LSZH, green, 100m ring	100.0 m	green	8	simplex	6
IDL0213100	Raw cable Cat.6, UTP, LSZH, orange, 100m ring	100.0 m	orange	8	simplex	6
IDL0212100	Raw cable Cat.6, UTP, LSZH, red, 100m ring	100.0 m	red	8	simplex	6
IDL0218100	Raw cable Cat.6, UTP, LSZH, violet, 100m ring	100.0 m	violet	8	simplex	6
IDL0210100	Raw cable Cat.6, UTP, LSZH, white, 100m ring	100.0 m	white	8	simplex	6
IDL0214100	Raw cable Cat.6, UTP, LSZH, yellow, 100m ring	100.0 m	yellow	8	simplex	6