

DATASHEET

Full metal cover 45°

TECHNICAL SPECIFICATIONS

Material: Zinc, Ni-plated
Temp. range: -40°C - 120°C
Cable strain relief: Steel fibre reinfo

Steel fibre reinforced PC (UL94 V-0) for EMI/RFI screening

Cable diameter: 3.0 - 13.0 mm


Locking screws: Long solid jackscrews

with groove for indication of thread


Cable outlet: Angled


Attenuation factor: > 40 dB between 30 MHZ

and 1 GHz









PART NUMBERING SYSTEM

	DVZK15 -	- BULK
Series: ————————————————————————————————————		
M2.5		ı
M2.6		ı
M3.0		ı
Packaging:		
K = Kit package		
BULK = Bulk / 100 pcs		

FEATURES

- Available in sizes 9, 15, 25, 37 and 50
- Minimise interference from electromagnetic and RF sources
- Unique metal filled plastic cable strain relief guarantee 360° shielding
- Non-static parts avoid ESD problems
- Accept round foil and braided cable types
- Approved according VDE 0871, FCC 20780 and 89/336/EU
- Printed logotype available upon request
- Long jackscrews with UNC 4-40 thread as standard, M2.5, M2.6 or M3.0 as option
- For custom designed solutions, please consult factory

