

DATASHEET

Cat.6 S/FTP VOIP-Patch Cable



The special boot design prevents cable caused wobbling of devices (e.g. Cisco IP Phone 7970) on the desktop
TIA/EIA 568B coded
Flame retardant IEC 60332-1, halogenfree IEC 60754-2, low smoke IEC 61034
Extremely short moulded strain relief boot with latch protection

Category:	6
Cable type:	S/FTP
Type of connector connection 1:	RJ45 8(8)
Type of connector connection 2:	RJ45 8(8)
Colour outer sheath:	black
Anti-kink sleeve:	plugged in
Locking lever:	True
Colour anti-kink sleeve:	black
Flame retardant version:	True
Halogen free:	False
Oil resistant (acc. EN 60811-2-1):	False
Cable construction:	4x2
NVP value:	- %
Pin assignment:	1:1
AWG-size:	26

Article no.	Title	Length m
K2460.1	VOIP-Patchcable, S/FTP, Cat.6 1.0m black, short boot	1.0
K2460.2	VOIP-Patchcable, S/FTP, Cat.6 2.0m black, short boot	2.0
K2460.3	VOIP-Patchcable, S/FTP, Cat.6 3.0m black, short boot	3.0
K2464.1	VOIP-Patchcable, S/FTP, Cat.6 1.0m black, short boot	1.0
K2464.2	VOIP-Patchcable, S/FTP, Cat.6 2.0m black, short boot	2.0
K2464.3	VOIP-Patchcable, S/FTP, Cat.6 3.0m black, short boot	3.0
K2464.5	VOIP-Patchcable, S/FTP, Cat.6 5.0m black, short boot	5.0
K2464.10	VOIP-Patchcable, S/FTP, Cat.6 10.0m black, short boot	10.0
