DATASHEET



FTTH IP65 Connection Box 8 ports

Article no.

FTTH-BOX-OUT-2







Description

Application:

Optical Telecommunication Networks LAN, Optical fiber Communication Network CATV Networks FTTH access Network PON, G-PON

Delivery unassembled (8x shrink protection and material for wall mounting included)

When using crimp splice protectors, order holder 53100.21 and glue in place

General data		
Scope of application	Outdoor	
Mounting	Wall mounting	
Possibility of mast mounting	yes	
Material	Plastic	
Colour	White	
Cable entry without cable gland	8x max. 3mm / 1x max. 9mm	
Cable entry with cable gland	2x PG13,5	
Number of Fibres	8	
Type of Splice protection	Thermo	

This datasheet was created automatically on 10-09-2018. Technical changes reserved.







FTTH IP65 Connection Box 8 ports

Article no.

FTTH-BOX-OUT-2

General data	
Suitable for adapter	SC Simplex/LC Duplex/E2000®
Max. Assembly (Adapter)	8
With Fiber overlength cassette	yes
Hinged splice cassette	yes
Holder for splitter	yes
Holder for gas blocker	No
Cable sheath support	yes

Mechanical characteristics		
IP Protection	IP65	
Foreign body and contact protection	Protection against ingrees of dust	
Water protection	Protection against jet water	

Dimensions	
Dimensions	213x163x47 mm

Environmental conditions	
Temperature Range	-25 – 70 °C

Available variants		
Article no.	Title	Access Control
FTTH-BOX-OUT	-2 FTTH IP65 Connectionbox for 8fiber, 8adapter and Fiber overlength box	Special screw

