DATASHEET

Power Cable UK BS1363A - C5 180°, black





Description

2.5 A / 250 V with fuse 3 A Colour black

Suitable for UK, Ireland, Singapur, Malaysia

General data					
Connection 1	Other / BS1363A				
Connection 2	Other / IEC C5 ("Mickey Mouse")				
Number of cores	3				
Spiralized cable	False				
Protective conductor	True				
With cord switch	False				
Colour outer sheath	Black				

Cable sheath

Material outer sheath	PVC	
Temperature resistance	0 – 70 °C	

Electrical characteristics

Nominal voltage 250 V

Standards, approvals, certifications

Oil resistant (acc. EN 60811-2-1)

Available variants

This datasheet was created automatically on 05-01-2021 . Technical changes reserved.

DATASHEET

Power Cable UK BS1363A - C5 180°, black

Article no. Title		Title	Nominal cross section conductor	Outer diameter approx.	Length
	EK499.1,8	Power Cable UK BS1363A - C5 180°, black, 1.8 m, $3 \times 0.75 \text{ mm}^2$	0.75 mm²	6.8 mm	1.8 m
	EK499.3	Power Cable UK BS1363A - C5 180°, black, 3.0 m, $3 \times 0.75 \text{ mm}^2$	0.75 mm²	6.8 mm	3.0 m
	EK499.5	Power Cable UK BS1363A - C5 180°, black, 5.0 m, $3 \times 0.75 \text{ mm}^2$	0.75 mm²	6.8 mm	5.0 m