

DATASHEET

Cat.6 Patch Cable U/UTP 250MHz LSZH, black



1 Gigabit Ethernet Cat.6 250 MHz patch cable, unshielded
2 x RJ45 plug UTP, IEC 60603-7
U/UTP 4x2xAWG24/7 LSZH Ø=5.9 mm
Flame retardant IEC 60332-1, halogenfree IEC 60754-2, low
smoke IEC 61034
TIA/EIA 568B coded
Moulded strain relief with latch protection

Category:	6
Cable type:	U/UTP
Type of connector connection 1:	RJ45 8(8)
Type of connector connection 2:	RJ45 8(8)
Colour outer sheath:	black
Anti-kink sleeve:	plugged in
Locking lever:	True
Colour anti-kink sleeve:	black
Flame retardant version:	True
Halogen free:	True
Oil resistant (acc. EN 60811-2-1):	False
Cable construction:	4x2
NVP value:	- %
Pin assignment:	1:1
AWG-size:	24

Article no.	Title	Length m
K8104SW.1	RJ45 Patch Cable, Cat.6 U/UTP, LSZH, black, 1.0 m	1.0
K8104SW.1,5	RJ45 Patchkabel U/UTP, Cat.6,1,5 m, schwarz, LSZH	1.5
K8104SW.2	RJ45 Patch Cable, Cat.6 U/UTP, LSZH, black, 2.0 m	2.0
K8104SW.3	RJ45 Patch Cable, Cat.6 U/UTP, LSZH, black, 3.0 m	3.0
K8104SW.5	RJ45 Patch Cable, Cat.6 U/UTP, LSZH, black, 5.0 m	5.0
K8104SW.7,5	RJ45 Patch Cable, Cat.6 U/UTP, LSZH, black, 7.5 m	7.5
K8104SW.10	RJ45 Patch Cable, Cat.6 U/UTP, LSZH, black, 10.0 m	10.0
K8104SW.15	RJ45 Patchkabel U/UTP, Cat.6,15 m, schwarz, LSZH	15.0
K8104SW.20	RJ45 Patchkabel U/UTP, Cat.6,20 m, schwarz, LSZH	20.0