DIGITUS Professional Line-Interactive UPS, 1000 VA/600 W

DN-170024-1 4016032345107



DIGITUS Line-Interactive UPS, 1000VA/600W 12V/7Ah x2 battery, 4x CEE 7/7, AVR, USB, RS232, RJ11/RJ45, LCD display

The DIGITUS® Line-Interactive UPS come with a compact size and an excellent microprocessor control, which guarantees high reliability. With an user friendly operation they provide high performance protection for your business and office computer systems against data loss and damage. Features like overload-, discharge and overcharge protection, cold start functions and energy saving features, as well as an acoustic alarm system are just a few advantages of the DIGITUS® Line-Interactive UPS units. You can download the mangement software under following link: http://www.powersoftware-download.com/viewpower.html



- Excellent micro process management guarantees a high reliability in case of electricity failure
- 1 Auto restart while AC is recovering
- Cold start function
- USB/RS232 communication terminal and RJ11/45 telephone protection
- Connection Type: 4x safety outlets, 2x RJ11/RJ45, 1x RS232, 1x USB 2.0 Typ B
- Input voltage: 230 VAC
- l Voltage range: 162-290 VAC
- Frequency range: 50 Hz (auto sensing)
- l Output voltage: 230 VAC ± 10%
- AC voltage regulation (battery mode): 10%
- Capacity: 1000 VA/600 W
- Frequency range (battery mode): 50 Hz ± 1%
- Typical transfer time: 2-6 ms
- Waveform (battery mode): Simulated sine wave
- Battery: 12V/7Ah x 2
- Typical recharge time: 4 hours to recover 90% of capacity
- 1 Alarm sounds: Battery mode (sounding every 10 sec.), low battery (sounding every second), overload (sounding every 0.5 seconds), fault (continously sounding)
- Humidity: 0-90% RH @ 0 °C to +40 °C (non condensing)
- Noise level: Less than 40 dB
- With overload-, discharge-, and overcharge protection
- Boost and buck AVR for voltage stabilization
- Dimensions (HxWxD): 160x350x146 mm
- Net weight: 8.0 kg
- ViewPower software link: http://www.power-software-download.com/viewpower.html

www.assmann.com

DIGITUS Professional Line-Interactive UPS, 1000 VA/600 W

DN-170024-1 4016032345107



→ Logistics	Number	Weight	Depth	Width	Height	cm³
	(pcs)	(kg)	(cm)	(cm)	(cm)	
Packaging Unit Carton	1	8,90	44,50	19,50	25,50	22127,63
Packaging Unit Inside	1	8,90	44,50	19,50	25,50	22127,63
Packaging Unit Single	1	8,90	44,50	19,50	22,50	19524,38
Net single without Packaging	1	0,00	0,00	0,00	0,00	0,00

www.assmann.com 2/2