

FTTH IP65 Connection Box 8 ports

Article no.

CAE8F



Description

Application:

Optical Telecommunication Networks
LAN, Optical fiber Communication Network
CATV Networks
FTTH access Network
PON, G-PON

Delivery unassembled (8x shrink protection and material for wall mounting included)

When using crimp splice protectors, order holder 53100.21 and glue in place

General data

Scope of application	Outdoor
Mounting	Wall mounting
Possibility of mast mounting	yes
Material	Plastic
Colour	White
Cable entry without cable gland	8x max. 3mm / 1x max. 9mm
Cable entry with cable gland	2x PG13,5
Number of Fibres	8
Type of Splice protection	Thermo

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.

FTTH IP65 Connection Box 8 ports

Article no.

CAE8F

General data

Suitable for adapter	SC Simplex/LC Duplex/E2000®
Max. Assembly (Adapter)	8
With Fiber overlength cassette	yes
Hinged splice cassette	yes
Holder for splitter	yes
Holder for gas blocker	No
Cable sheath support	yes

Mechanical characteristics

IP Protection	IP65
Foreign body and contact protection	Protection against ingrees of dust
Water protection	Protection against jet water

Dimensions

Dimensions	213x163x47 mm
------------	---------------

Environmental conditions

Temperature Range	-25 – 70 °C
-------------------	-------------

Available variants

Article no.	Title	Access Control
CAE8F	FTTH IP65 Connectionbox for 8fiber, 8adapter and Fiber overlength box	Special screw

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.