

DATASHEET

Keystone Jack, RJ11 Cat.3

CNH11A



Product Feature

- 01. Much helpful for the easier and faster installation.
- 02. Its well match with Blank patch panels and Mounting boxes and Faceplates.
- 03. Cat. 3 is available.
- 04. Various colors are option.

Technique Characteristics:

- 1. Keystone Jack, Cat.3, for connecting application of communication ports in working area.
- 2. A compact & ingenious designing, with the punching sequence direction Marks on the sides of keystone jack. That can provide a correct and quick Guide for punching and connection operation. And the fastener hats will make sure the cable can be fixed reliably in the IDC clips.
- 3.According to the standard of ISO/IEC 11801: 2002 class & ANSI/TIA/EIA 568- B. 2-1 CAT. 3, T568A punching sequence and T568B punching sequence are both compatible.
- 4. Connection type: FCC connector for RJ45 patch cord and IDC for 4-pair Cat. 3 cables.
- 5. Fitting for the Cat. 3 general cable distribution system. Compatible for Cat. 3 systems.

Mechanical

- 1.Meet TIA/EIA-568-A and TIA/EIA-568-B Category 3 requirements.
- 2.Meet TIA/EIA TSB-40
- 3.Meet ISO/IEC Generic Cabling Standard 11801
- 4.Meet CENELEC Generic Cabling Standard EN50173
- 5.Termination: 110
- 6.Electrical: According to UL 1863
 7.Current rating: 1.5 Amp Max.
 8.Voltage rating: 150 Volts
 9. Contact resistance: 20 m-ohm
- 9. Contact resistance: 20 m-onm 10.Insulation Resistance: 500M-ohm
- 11. Dielectric Withstand Voltage: 1000 V AC RMS, 60Hz 1min