IDEAL Professional Wallplate for Keystone Modules, Frame 80x80mm

IDEAL Faceplate for Keystone Jacks, 2x RJ45
dust cover, 80x80 mm + 2x 22.5 mm modular insert, color pure white

The IDEAL Faceplates are suitable for the connection of all IDEAL Keystone Modules. Included dust protection shutters provide a perfect protection. Their connection way of the module is 45° vertical (German Layout) or 90° horizontal (French Layout).

- Layout keystone entry: 90° outlet
- Area of application: Cavity socket, trunking, surface mount box
- Norms: ISO/IEC 11801 2nd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
- Suitable for installation in trunking, flush and surface mount
- Integrated dust cover
- Plastic label field
- Design compatible to current switch ranges of switch manufacturers
- Technical properties:
- Wall outlet material: Die-cast metal
- Central plate material: ABS UL 94V-0
- Frame material: ABS UL 94V-0
- Surface mount box material: ABS UL 94V-0
- Physical properties:
- Operation temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.