DATASHEET

Keystone Jack, RJ12 Cat.3 CNH3B

Product Feature

01. Much helpful for the easier and faster installation.
02. Its well match with Blank patch panels and Mounting boxes and Faceplates.
03. Cat. 3 is available.
04. Various colors are option.

Technique Characteristics:

1. Keystone Jack, Cat.3, for connecting application of communication ports in working area.
2. A compact & ingenious designing, with the punching sequence direction Marks on the sides of keystone jack. That can provide a correct and quick Guide for punching and connection operation. And the fastener hats will make sure the cable can be fixed reliably in the IDC clips.
3. According to the standard of ISO/IEC 11801: 2002 class & ANSI/TIA/EIA 568- B. 2-1 CAT. 3, T568A punching sequence and T568B punching sequence are both compatible.
4. Connection type: RJ12 6/6
5. Fitting for the Cat. 3 general cable distribution system. Compatible for Cat. 3 systems.

Mechanical

1. Meet TIA/EIA-568-A and TIA/EIA-568-B Category 3 requirements.
2. Meet TIA/EIA TSB-40
3. Meet ISO/IEC Generic Cabling Standard 11801
4. Meet CENELEC Generic Cabling Standard EN50173
5. Angle: 90 Degree
6. Termination: Tool free
7. Electrical: According to UL 1863
8. Current rating: 1.5 Amp Max.
9. Voltage rating: 150 Volts
10. Contact resistance: 20 m-ohm
11. Insulation Resistance: 500M-ohm
12. Dielectric Withstand Voltage: 1000 V AC RMS, 60Hz 1min

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.