SPECNo.:	UIP CAT	T.6 FLATCA	BLE(7/0.0	18BC)*4P										
Customer:	ıstomer: ULStyle: Date					RE	V.		N	No.				
		Construction	nstruction Item											
Conductors			Construction AWC			A	WG	1P:32# (7/0.08) + 150D	P:32# (7/0.08)			1P:32# (7/0.08) + 150D		
			Material					BARECOPPER	BARECOPP				BARECOPPER	
			Pitch			1	mm	5~ 7	5~7 5~7 5~7		5~ 7			
Insulators			Material					HD-PE				HD-PE		
		,	Diameter			1	mm	0.5~ 0.55		0.5~ 0.55		0.5~ 0.55		
			Average Thickness			1	mm	0.128			0.128		0.128	
			Color					ORANGE/WHITE&CRANGE	GREENWHITE&G		BLUE/WHITE&		BROWNWHITE&BROWN	
			Pitch			1	mm	13.7±0.3	10.1±0.3 11.3±0.3 14.				14.3±0.3	
Outside Layer			Filer Material						-					
		-	Direction			-	mm		-					
			Pitch Motorial						-					
Outside-Tape Wrap			Material Conduction Side											
		, 	Conductive Side				%							
Drain wire			Overlap Rate Construction AWG				.WG							
		-	Material			7								
Outside-Shield			Shield											
		8	Construction AWG											
			Conductors Size			1	nm							
			Material											
		*	Coverage				%							
Outside Jacket			Material				50P PVC							
			Diameter			1	nm	($0(1.4 \pm 0.15)$)*(6.0=	± 0.2)m	ım		
			Average Thickness			1	nm							
			Extrusion											
			Surface											
			Color						W	hite				
Marking		Col	or	White	Fon	t		High	ı		Space			
		Marl	king NO.											
WHITE &ORANGE		CONDUCTORS	ONDUCTORS D-PE,ID:0.5~ 0.55mm		ІТЕМІЮ:.			Ι±Τ						
		cor becreate												
		HD-PE,ID:0.5∼ 0								26.5				
WHITE & BLUE	$\widecheck{\odot}$													
WHITE&BROWN	<u></u>	DNAC OLITED IAO	OUTER JACKET											
,		INDI												
CORDS	PECIFICAT	HON												
				ĺ	1				1	T				