DATASHEET



Power Cable CEE7/7 90° - C13 90°, black





Description

10 A / 250 V VDE tested

Colour black

Suitable for Germany, Belgium, France and further (see overview)

,				
General data				
Connection 1	SCHUKO plug, angled			
Connection 2	Cold device plug angled, female			
Number of cores	3			
Spiralized cable	False			
Protective conductor	True			
With cord switch	False			
Colour outer sheath	Black			

Kabelmantel

Material outer sheath	PVC
Temperature resistance	0 – 70 °C

Electrical characteristics

Nominal voltage 250 V

Standards, approvals, certifications

Oil resistant (acc. EN 60811-2-1)

Available variants

Article no. Title		Nominal cross section conductor	Outer diameter approx.	Length
CAB535.2	Power Cable Schuko 90° - C13 90°, black, 2.0 m, 3 x 0.75 mm²	0.75 mm²	6.8 mm	2.0 m
CAB535.3	Power Cable Schuko 90° - C13 90°, black, 3.0 m, 3 x 1.00 mm²	1.00 mm²	7.1 mm	3.0 m
CAB535.5	Power Cable Schuko 90° - C13 90°, black, 5.0 m, 3 x 1.00 mm²	1.00 mm²	7.1 mm	5.0 m

Ideal Technology has a policy of continuous improvement. Specifications are subject to change without notice.