

AUDIO

PROF. DAVID ROSSITER

AFTER THIS PRESENTATION

- You'll be able to handle audio

ELEMENTS & ATTRIBUTES WE WILL LOOK AT

`<audio>` `src` attribute

`autoplay` attribute

`controls` attribute

`loop` attribute

~~`alt` attribute~~

HANDLING SOUND

`<audio>` by itself adds a soundfile, but doesn't play it

```
<audio src="beets_turnips.mp3"></audio>
```

`autoplay` makes the sound start as soon as the page loads


```
<audio src="beets_turnips.mp3" autoplay></audio>
```

Open [the example](#) to experience it

SOUND CONTROLS

```
<audio src="beets_turnips.mp3" controls></audio>
```

Add controls to tell the browser to show playback controls



LOOPING SOUND

Add loop to repeat the sound indefinitely

```
<audio src="drum_loop.mp3" autoplay loop></audio>
```

Open [the example](#) to experience it

SOUND IN OLDER BROWSERS

In general, for sound it's wise to use MP3 format sound

This is supposed to work in all modern browsers

HANDLING NEW TAGS IN OLDER BROWSERS

Older browsers can't handle newer HTML tags

To be friendly, you can warn the user:

```
<this_new_html_tag>  
    <p>Sorry, your browser can't handle <i>this_new_html_tag</i>!</p>  
</this_new_html_tag>
```

- An older browser ignores `<this_new_html_tag>` because it doesn't understand it, but it does understand `<p>` so it correctly displays the paragraph
- A newer browser understands everything, but deliberately ignores the paragraph

AN EXAMPLE OF HANDLING OLDER BROWSERS

Here's an example using audio:

```
<audio src="drum_loop.mp3" autoplay>  
  <p>Sorry! Your browser does not support the <i>audio</i> tag</p>  
</audio>
```