

Capital.com API - WebSocket Streaming & Reconnect

Part 10 for CapitalDemoBroker / Codex

Source basis: official Capital.com Public API 1.0.0, accessed 10 Aug 2026. This is a Codex-oriented technical reference; unsupported behavior is explicitly marked as unresolved rather than guessed.

1. Endpoint and session

wss://api-streaming-capital.backend-capital.com/connect

WebSocket API uses CST and X-SECURITY-TOKEN values in authenticated messages. Capital.com documents a 10-minute WebSocket session duration and instructs clients to use ping to keep the session live.

Changing the active financial account via PUT /session causes WebSocket streaming to fall off.

2. Subscription capacity

Maximum documented subscription scope is 40 instruments at a time.

3. OHLC streaming

```
{
  "destination": "OHLCMarketData.subscribe",
  "correlationId": "3",
  "cst": "REDACTED_CST",
  "securityToken": "REDACTED_SECURITY_TOKEN",
  "payload": {
    "epics": ["GOLD"],
    "resolutions": ["MINUTE"],
    "type": "classic"
  }
}
```

OHLC events expose resolution, epic, type, priceType, timestamp and OHLC values. The documented example uses priceType=bid; therefore the consumer must preserve priceType rather than assume midpoint data.

4. Reconnect safety

The public documentation does not establish a universal global sequence ID/gap-replay mechanism that would let the bot prove it received every event across a disconnect. Therefore reconnect must not simply resume the old state machine.

- Pause strategy transitions on disconnect.
- Restore REST authentication if needed.
- GET /positions and GET /workingorders.
- Resolve persisted dealReferences through /confirms.
- Use activity/history for ambiguous operations.
- Reconcile local SQLite state.
- Reconnect WebSocket and resubscribe.
- Resume only after broker-state reconciliation.

5. Source

Official Capital.com Public API: FAQ limitations, Session switching and WebSocket API/OHLC market data.