

Deep Learning

M.Tech. Data Science, Second Year, NMIMS

By,

Bilal Hungund, Data Scientist, Halliburton

Artificial Intelligence (Observing behaviour)

Machine Learning (Explicitly learn)


Deep Learning

(Extract Pattern from
Neural Network)

Why Deep Learning

- Time Consuming and brittle in Unstructured data
- Hard engineered features are not scalable
- Ways to learn underlying features for unstructured data

Evolution of Deep Learning





Why now?

- 1) Big Data
- 2) Hardware (GPUs, TPUs)
- 3) Software (Pytorch, TensorFlow)

Perceptron

$$\hat{y} = g \left(w_0 + \sum_{i=1}^m a_i w_i \right)$$



Simplify to Matrix

$$\hat{y} = g(w_0 + X^T W)$$

$$X = \begin{bmatrix} a_1 \\ \vdots \\ a_m \end{bmatrix} \quad W = \begin{bmatrix} w_1 \\ \vdots \\ w_m \end{bmatrix}$$

Hyperbolic Tangent (\tanh)

$$g(z) = \frac{e^z - e^{-z}}{e^z + e^{-z}}$$


$$g'(z) = 1 - g(z)^2$$

Rectified Linear Unit (ReLU)

$$g(z) = \max(0, z)$$


$$g'(z) = \begin{cases} 1, & z > 0 \\ 0, & \text{otherwise} \end{cases}$$

Multi Output Perceptron




$$z_i = w_{0,i} + \sum_{j=1}^m x_j w_{j,i}$$

Single Layer Neural Network




Deep Neural Network k # hidden layers



$$z_{k,i} = w_{0,i}^{(k)} + \sum_{j=1}^{n_{k-1}} g(z_{k-1,j}) w_{j,i}^{(k)}$$

Keep stacking hidden layers

Neural Networks



Quantifying Loss

It measures the cost incurred from incorrect predictions

$$\underbrace{L\left(\underbrace{f(x^{(i)}; w)}_{\text{Predicted}}, \underbrace{y^{(i)}}_{\text{Actual}}\right)}$$

$J(w) \rightarrow$ Empirical Loss

Binary Cross Entropy Loss

$$J(w) = \frac{1}{n} \sum_{i=1}^n y^{(i)} \log(\hat{y}^{(i)}) + (1 - y^{(i)}) \log(1 - \hat{y}^{(i)})$$

Diagram illustrating the terms in the Binary Cross Entropy Loss formula:

- $y^{(i)}$ is labeled **Actuals** (red line).
- $\hat{y}^{(i)}$ is labeled **Predicted** (green line).
- $(1 - y^{(i)})$ is labeled **Actuals** (red line).
- $(1 - \hat{y}^{(i)})$ is labeled **Predicted** (green line).

Mean Squared Error Loss

$$J(w) = \frac{1}{n} \sum_{i=1}^n \left(\underbrace{y^{(i)}}_{\text{Actuals}} - \underbrace{\hat{y}^{(i)}}_{\text{Predicted}} \right)^2$$


$$\mathbf{W}^* = \operatorname{argmin}_{\mathbf{W}} \frac{1}{n} \sum_{i=1}^n \mathcal{L}(f(\mathbf{x}^{(i)}; \mathbf{W}), y^{(i)})$$

$$\mathbf{W}^* = \operatorname{argmin}_{\mathbf{W}} J(\mathbf{W})$$

Gradient Descent

Algorithm

1. Initialize weights randomly $\sim \mathcal{N}(0, \sigma^2)$
2. Loop until convergence:
3. Compute gradient, $\frac{\partial J(\mathbf{W})}{\partial \mathbf{W}}$
4. Update weights, $\mathbf{W} \leftarrow \mathbf{W} - \eta \frac{\partial J(\mathbf{W})}{\partial \mathbf{W}}$
5. Return weights



$$\frac{\partial J(\mathbf{W})}{\partial w_1} = \underbrace{\frac{\partial J(\mathbf{W})}{\partial y}}_{\text{purple}} * \underbrace{\frac{\partial y}{\partial z_1}}_{\text{red}} * \underbrace{\frac{\partial z_1}{\partial w_1}}_{\text{blue}}$$

Repeat this for **every weight in the network** using gradients from later layers

Optimization

- Learning Rate
- Regularization
- Dropout
- Early Checkpoint