OPERATING SYSTEM EXPERIMENT - 7 CODE & OUTPUT

AIM: Implementation of Bankers Algorithm

CODE:

```
import java.util.*;
class Bankers
   static int P=5;
   static int R=3;
   static void printMatrix(int m[][])
        for(int i=0;i<P;i++)</pre>
            for(int j=0;j<R;j++)</pre>
                System.out.print(m[i][j] +" ");
            System.out.println();
        }
   static void calculateNeed(int need[][], int max[][],int alloc[][])
        for (int i = 0 ; i < P ; i++)</pre>
            for (int j = 0; j < R; j++)
                need[i][j] = max[i][j] - alloc[i][j];
            }
        System.out.println("\nNeed Matrix :");
```

```
printMatrix(need);
   }
   static void isSafe(int processes[], int avail[], int max[][],int
alloc[][])
   {
        int [][]need = new int[P][R];
        calculateNeed(need, max, alloc);
        boolean []finish = new boolean[P];
        int []safeSeq = new int[P];
        int []work = new int[R];
        for (int i = 0; i < R; i++)
            work[i] = avail[i];
        }
        int count = 0;
        while (count < P)</pre>
        {
            boolean found = false;
            for (int p = 0; p < P; p++)
                if (finish[p] == false)
                {
                    int j;
                    for (j = 0; j < R; j++)
                        if (need[p][j] > work[j])
                            break;
                    if (j == R)
                        for (int k = 0; k < R; k++)
                        {
                            work[k] += alloc[p][k];
                        safeSeq[count++] = processes[p];
                        finish[p] = true;
                        found = true;
                    }
                }
            }
            if (found == false)
                System.out.print("\nSystem is not in safe state. Deadlock
can occur.");
                return;
            }
        System.out.print("\nSystem is in safe state.\nSafe sequence is: ");
```

```
for (int i = 0; i < P-1; i++)
    {
        System.out.print("P" + safeSeq[i] + "->");
    System.out.print(safeSeq[P-1]);
public static void main(String[] args)
{
    Scanner sc = new Scanner(System.in);
    System.out.println("Enter the no of processes : ");
    P = sc.nextInt();
    int processes[] = new int [P];
    for(int i=0;i<P;i++)</pre>
        processes[i]=i+1;
    System.out.println("Enter total no of resources : ");
    R = sc.nextInt();
    int totalResources[] = new int[R];
    System.out.println("Enter total no of resources present : ");
    for(int i=0;i<R;i++)</pre>
        totalResources[i]=sc.nextInt();
    int avail[] = new int[R];
    int max[][] = new int[P][R];
    int alloc[][] = new int[P][R];
    System.out.println("Enter Maximum need Matrix :");
    for(int i=0;i<P;i++)</pre>
        for(int j=0;j<R;j++)</pre>
        {
            max[i][j]=sc.nextInt();
    System.out.println("Enter Allocation Matrix :");
    for(int i=0;i<P;i++)</pre>
    {
        for(int j=0;j<R;j++)</pre>
        {
            alloc[i][j]=sc.nextInt();
    for(int i=0;i<R;i++)</pre>
        avail[i]=0;
        for(int j=0;j<P;j++)</pre>
        {
```

```
avail[i]=avail[i] + alloc[j][i];
}
avail[i]=totalResources[i]-avail[i];
}
System.out.println("Available Matrix :");
for(int i=0;i<R;i++)
{
    System.out.print(avail[i] + " ");
}
System.out.println("\nMaximum Need Matrix :");
printMatrix(max);
System.out.println("\nAllocated Matrix :");
printMatrix(alloc);
isSafe(processes, avail, max, alloc);
sc.close();
}
</pre>
```

OUTPUT:

```
Enter the no of processes:
Enter total no of resources:
Enter total no of resources present :
5
7
Enter Maximum need Matrix:
7 5 3
3 2 2
9 0 2
4 2 2
5 3 3
Enter Allocation Matrix:
0 1 0
2 0 0
3 0 2
2 1 1
002
Available Matrix:
3 3 2
Maximum Need Matrix:
7 5 3
3 2 2
9 0 2
4 2 2
5 3 3
Allocated Matrix:
0 1 0
200
3 0 2
2 1 1
0 0 2
Need Matrix:
7 4 3
1 2 2
6 0 0
2 1 1
5 3 1
System is in safe state.
Safe sequence is: P2->P4->P5->P1->3
```