



Hochschule
Bonn-Rhein-Sieg
University of Applied Sciences



R&D Project

Qualitative Representation for Perception and Control of Mobile Platforms

Mihir Patil

Submitted to Hochschule Bonn-Rhein-Sieg,
Department of Computer Science
in partial fulfilment of the requirements for the degree
of Master of Science in Autonomous Systems

Supervised by

Nico Huebel
Santosh Thoduka
Paul Ploger

January 2019

I, the undersigned below, declare that this work has not previously been submitted to this or any other university and that it is, unless otherwise stated, entirely my own work.

Date

Mihir Patil

Abstract

Your abstract

Acknowledgements

Thanks to

Contents

1	Introduction	1
1.1	Motivation	3
1.1.1	3
1.1.2	3
1.2	Challenges and Difficulties	3
1.2.1	3
1.2.2	5
1.2.3	5
1.3	Problem Statement	5
1.3.1	5
1.3.2	7
1.3.3	7
2	State of the Art	9
2.1	Forms of qualitative spatial representations	10
2.1.1	Topological Representations	10
2.1.2	Directional Representations	10
2.1.3	Distance Representations	11
2.1.4	Moving object Representations	12
2.1.5	Conclusion	15
2.2	Analyzing qualitative calculi for navigation	15
2.2.1	Qualitative Trajectory calculus	15
2.2.2	Qualitative Rectilinear Projection calculus	20
2.2.3	Qualitative Distance calculus	23
2.3	Implementations utilizing qualitative representations for navigation in robots	25

2.4	Limitations of previous work	35
3	Approach	37
3.1	Proposed approach	37
3.2	Implementation details	37
4	Methodology	39
4.1	Hardware Setup	39
4.2	Software Framework	41
4.3	Integration of Qualitative representations	41
5	Results and Validation	45
5.1	Use case 1	45
5.2	Use case 2	45
5.3	Use case 3	45
5.4	Experimental Setup	45
5.5	Experimental Evaluation	45
5.6	Result	45
6	Conclusions	47
6.1	Contributions	47
6.2	Lessons learned	47
6.3	Future work	47
	Appendix A Design Details	49
	Appendix B Parameters	51
	References	53

List of Figures

2.1	The eight jointly exhaustive and pairwise disjoint relations of region connection calculus (RCC8). The arrows show which relation is the next relation a configuration would transit to, assuming the continuous movements or deformations [?] , [?] , [?]	10
2.2	The point based and projection based direction representations [7] .	11
2.3	An representation of the combination of cone-shaped direction and absolute distance: very close(vc), close(cl), commensurate(cm), far(fr) and very far(vf), [10].	12
2.4	Basic relations of basic Qualitative Trajectory Calculus (QTCB) in a conceptual neighborhood diagram. The solid dots represent the stationary objects and the open dots represent the moving objects [?] , [?]	13
2.5	A graphical representation of the QTC_C calculus for a relation between two moving objects 'k' and 'l', where t_1 and t_2 are the two distinctive time instances and RL refers to the reference line and the double crosses($RL \perp 1$, $RL \perp 2$) for the two objects [43]	18
2.6	Relative position of O_i w.r.t the left-right dichotomy of O_j for crossed projections [24].	21
2.7	Some of the spatial configurations of the intersection point with respect to the front-back dichotomy of two objects for crossed projections $(CO_i^{FB})(CO_j^{FB})$, [24].	22
2.8	The point based and projection based direction representations [?] .	22
2.9	Various levels of distance and orientation distinctions. These figures show typical distance/orientation granularity configurations [10]. .	24

2.10	The funnel lane created by the two constraints(distance from the principal point and the relative signs of the distances), and when it has turned by an angle α , here μ^C and μ^D represent the horizontal pixel coordinates of the reference and the current frame.	27
2.11	The hypothesized qualitative representation with the left most value being the distance, followed by the direction to move in and finally the speed with which to move [33].	29
2.12	figure showing the ‘Qmap’ for a given line segment, the 0’s and 1’s indicate the inactive and active sensors while ‘S’, ‘I’, ‘D’ indicate the distance relations of each sensor w.r.t the obstacle(grey cell) [37].	30
2.13	Situation Graph Tree of the human motion behaviour and relative robot actions [5].	33
2.14	The velocity costmap prototypes. The area enclosed by the partial circle represents the low cost area, everything outside is assigned the highest cost value. The black dot on the right represents a human that can have any possible QTC state (except for QTC_B 0) [15]. . .	35
4.1	The youBot robot platform	40
4.2	youBot arm at full extension	40
4.3	A flow chart detailing the inner workings of the QSRLib library [1], [23].	43

List of Tables

2.1	Key features of the more representative models(calculi) of qualitative representations of spatial or temporal domains in the existing literature [24].	14
-----	--	----

Introduction

[33] says that qualitative representations can better compensate for vague data and also, that quantitative representations compute upto an unnecessary level of accuracy. qualitative representations are good for human robot interactions.

[31], Qualitative spatial calculi offer a method to describe spatial configurations in a framework based on a finite set of relations that abstracts from the underlying mathematical theory. opira is oriented point algebra [30] movement of people

Perception and control are two essential components of any successful robot navigation system. While perception deals with the spatial representations of the environment as perceived by the robot, control derives the required parameters necessary for navigation based on the perceived data. Traditionally such a task of navigation is achieved using quantitative approaches involving precise numerical information. Though useful such precise representations may not always be a prerequisite [?] [39].

Consider the case of a robot tasked with driving along a corridor towards the end without colliding with the walls. In such a scenario where precise perception and control are deemed surplus to requirements, the robot can be controlled using qualitative inputs in the context of an approximate map (spatial representations) [39]. The significant benefit of using a qualitative representation is that we no longer try to follow a pre-planned, precise trajectory. Therefore eliminating

the need to constantly issue control commands. This implies that a qualitative approach would be more efficient [7] (in terms of CPU usage [?], battery usage etc.).

Furthermore, humans often communicate basic navigation tasks to each other using approximate spatial relationships to observable landmarks [?] [7] ,without requiring a precise map (for example, walk past the computers and take a left at the elevator) [39]. Hence by using qualitative representations we would be emulating a similar communication pattern which in turn facilitates a better human robot interaction [16].

- Qualitative representations(calculi) are useful in cases such as dynamic environments [?], where precise metric maps or precise trajectories often/may fail due to the constant and often unprecedented changes to the environment [39].
- Qualitative calculi can be used to make simple and intuitive inferences that can be used to achieve robust control(navigation) [13] [?] of a mobile platform.

- Most robot navigation tasks are composed of two basic steps, namely precise perception to localize the mobile robot on a given map and the control the platform along the precisely generated trajectory. While this approach works successfully in a number of cases it is not necessarily efficient [?] especially in terms of the continuous monitoring of the path by issuing a prolix of control commands.
- High level robot programming should be carried out without having to refer to numeric data. Ideally, a robot programmer should describe the task to the robot in terms that they would use to describe it when doing it themselves (“task-level” programming). People do not naturally think of physical actions in terms of joint angles or numeric co-ordinates, so high level robot programming should be done in non-numeric terms [?].
- Qualitative calculi exhibit a step forward in the direction of generalizing 2-D space [?] for use in various robotic tasks such as navigation [?] [13] and control.

1.1 Motivation

1.1.1 ...

1.1.2 ...

1.2 Challenges and Difficulties

1.2.1 ...

Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetur eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consetetur tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo.

Aliquam lectus. Vivamus leo. Quisque ornare tellus ullamcorper nulla. Mauris porttitor pharetra tortor. Sed fringilla justo sed mauris. Mauris tellus. Sed non leo. Nullam elementum, magna in cursus sodales, augue est scelerisque sapien, venenatis congue nulla arcu et pede. Ut suscipit enim vel sapien. Donec congue. Maecenas urna mi, suscipit in, placerat ut, vestibulum ut, massa. Fusce ultrices nulla et nisl.

Etiam ac leo a risus tristique nonummy. Donec dignissim tincidunt nulla. Vestibulum rhoncus molestie odio. Sed lobortis, justo et pretium lobortis, mauris turpis condimentum augue, nec ultricies nibh arcu pretium enim. Nunc purus neque, placerat id, imperdiet sed, pellentesque nec, nisl. Vestibulum imperdiet neque non sem accumsan laoreet. In hac habitasse platea dictumst. Etiam condimentum facilisis libero. Suspendisse in elit quis nisl aliquam dapibus. Pellentesque auctor sapien. Sed egestas sapien nec lectus. Pellentesque vel dui vel neque bibendum viverra. Aliquam porttitor nisl nec pede. Proin mattis libero vel turpis. Donec rutrum mauris et libero. Proin euismod porta felis. Nam lobortis, metus quis elementum commodo, nunc lectus elementum mauris, eget vulputate ligula tellus eu neque. Vivamus eu dolor.

Nulla in ipsum. Praesent eros nulla, congue vitae, euismod ut, commodo a, wisi. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Aenean nonummy magna non leo. Sed felis erat, ullamcorper in, dictum non, ultricies ut, lectus. Proin vel arcu a odio lobortis euismod. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Proin ut est. Aliquam odio. Pellentesque massa turpis, cursus eu, euismod nec, tempor congue, nulla. Duis viverra gravida mauris. Cras tincidunt. Curabitur eros ligula, varius ut, pulvinar in, cursus faucibus, augue.

1.2.2 ...

1.2.3 ...

1.3 Problem Statement

1.3.1 ...

Etiam pede massa, dapibus vitae, rhoncus in, placerat posuere, odio. Vestibulum luctus commodo lacus. Morbi lacus dui, tempor sed, euismod eget, condimentum at, tortor. Phasellus aliquet odio ac lacus tempor faucibus. Praesent sed sem. Praesent iaculis. Cras rhoncus tellus sed justo ullamcorper sagittis. Donec quis orci. Sed ut tortor quis tellus euismod tincidunt. Suspendisse congue nisl eu elit. Aliquam tortor diam, tempus id, tristique eget, sodales vel, nulla. Praesent tellus mi, condimentum sed, viverra at, consectetur quis, lectus. In auctor vehicula orci. Sed pede sapien, euismod in, suscipit in, pharetra placerat, metus. Vivamus commodo dui non odio. Donec et felis.

Etiam suscipit aliquam arcu. Aliquam sit amet est ac purus bibendum congue. Sed in eros. Morbi non orci. Pellentesque mattis lacinia elit. Fusce molestie velit in ligula. Nullam et orci vitae nibh vulputate auctor. Aliquam eget purus. Nulla auctor wisi sed ipsum. Morbi porttitor tellus ac enim. Fusce ornare. Proin ipsum enim, tincidunt in, ornare venenatis, molestie a, augue. Donec vel pede in lacus sagittis porta. Sed hendrerit ipsum quis nisl. Suspendisse quis massa ac nibh pretium cursus. Sed sodales. Nam eu neque quis pede dignissim ornare. Maecenas eu purus ac urna tincidunt congue.

Donec et nisl id sapien blandit mattis. Aenean dictum odio sit amet risus. Morbi purus. Nulla a est sit amet purus venenatis iaculis. Vivamus viverra purus vel magna. Donec in justo sed odio malesuada dapibus. Nunc ultrices aliquam nunc. Vivamus facilisis pellentesque velit. Nulla nunc velit, vulputate dapibus, vulputate id, mattis ac, justo. Nam mattis elit dapibus purus. Quisque enim risus, congue non, elementum ut, mattis quis, sem. Quisque elit.

Maecenas non massa. Vestibulum pharetra nulla at lorem. Duis quis quam

id lacus dapibus interdum. Nulla lorem. Donec ut ante quis dolor bibendum condimentum. Etiam egestas tortor vitae lacus. Praesent cursus. Mauris bibendum pede at elit. Morbi et felis a lectus interdum facilisis. Sed suscipit gravida turpis. Nulla at lectus. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Praesent nonummy luctus nibh. Proin turpis nunc, congue eu, egestas ut, fringilla at, tellus. In hac habitasse platea dictumst.

Vivamus eu tellus sed tellus consequat suscipit. Nam orci orci, malesuada id, gravida nec, ultricies vitae, erat. Donec risus turpis, luctus sit amet, interdum quis, porta sed, ipsum. Suspendisse condimentum, tortor at egestas posuere, neque metus tempor orci, et tincidunt urna nunc a purus. Sed facilisis blandit tellus. Nunc risus sem, suscipit nec, eleifend quis, cursus quis, libero. Curabitur et dolor. Sed vitae sem. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Maecenas ante. Duis ullamcorper enim. Donec tristique enim eu leo. Nullam molestie elit eu dolor. Nullam bibendum, turpis vitae tristique gravida, quam sapien tempor lectus, quis pretium tellus purus ac quam. Nulla facilisi.

Duis aliquet dui in est. Donec eget est. Nunc lectus odio, varius at, fermentum in, accumsan non, enim. Aliquam erat volutpat. Proin sit amet nulla ut eros consectetur cursus. Phasellus dapibus aliquam justo. Nunc laoreet. Donec consequat placerat magna. Duis pretium tincidunt justo. Sed sollicitudin vestibulum quam. Nam quis ligula. Vivamus at metus. Etiam imperdiet imperdiet pede. Aenean turpis. Fusce augue velit, scelerisque sollicitudin, dictum vitae, tempor et, pede. Donec wisi sapien, feugiat in, fermentum ut, sollicitudin adipiscing, metus.

Donec vel nibh ut felis consectetur laoreet. Donec pede. Sed id quam id wisi laoreet suscipit. Nulla lectus dolor, aliquam ac, fringilla eget, mollis ut, orci. In pellentesque justo in ligula. Maecenas turpis. Donec eleifend leo at felis tincidunt consequat. Aenean turpis metus, malesuada sed, condimentum sit amet, auctor a, wisi. Pellentesque sapien elit, bibendum ac, posuere et, congue eu, felis. Vestibulum mattis libero quis metus scelerisque ultrices. Sed purus.

Donec molestie, magna ut luctus ultrices, tellus arcu nonummy velit, sit amet pulvinar elit justo et mauris. In pede. Maecenas euismod elit eu erat. Aliquam augue wisi, facilisis congue, suscipit in, adipiscing et, ante. In justo. Cras lobortis neque ac ipsum. Nunc fermentum massa at ante. Donec orci tortor, egestas sit

amet, ultrices eget, venenatis eget, mi. Maecenas vehicula leo semper est. Mauris vel metus. Aliquam erat volutpat. In rhoncus sapien ac tellus. Pellentesque ligula.

Cras dapibus, augue quis scelerisque ultricies, felis dolor placerat sem, id porta velit odio eu elit. Aenean interdum nibh sed wisi. Praesent sollicitudin vulputate dui. Praesent iaculis viverra augue. Quisque in libero. Aenean gravida lorem vitae sem ullamcorper cursus. Nunc adipiscing rutrum ante. Nunc ipsum massa, faucibus sit amet, viverra vel, elementum semper, orci. Cras eros sem, vulputate et, tincidunt id, ultrices eget, magna. Nulla varius ornare odio. Donec accumsan mauris sit amet augue. Sed ligula lacus, laoreet non, aliquam sit amet, iaculis tempor, lorem. Suspendisse eros. Nam porta, leo sed congue tempor, felis est ultrices eros, id mattis velit felis non metus. Curabitur vitae elit non mauris varius pretium. Aenean lacus sem, tincidunt ut, consequat quis, porta vitae, turpis. Nullam laoreet fermentum urna. Proin iaculis lectus.

Sed mattis, erat sit amet gravida malesuada, elit augue egestas diam, tempus scelerisque nunc nisl vitae libero. Sed consequat feugiat massa. Nunc porta, eros in eleifend varius, erat leo rutrum dui, non convallis lectus orci ut nibh. Sed lorem massa, nonummy quis, egestas id, condimentum at, nisl. Maecenas at nibh. Aliquam et augue at nunc pellentesque ullamcorper. Duis nisl nibh, laoreet suscipit, convallis ut, rutrum id, enim. Phasellus odio. Nulla nulla elit, molestie non, scelerisque at, vestibulum eu, nulla. Ut odio nisl, facilisis id, mollis et, scelerisque nec, enim. Aenean sem leo, pellentesque sit amet, scelerisque sit amet, vehicula pellentesque, sapien.

1.3.2 ...

1.3.3 ...

State of the Art

Over the years, research into qualitative spatial representations has led to the development of various models which can be used to represent the visually observable space. From a more scientific perspective these models are known as “Qualitative calculi”, the current state of the art calculi rely on a single spatial primitive such as distance, direction, topology etc., to describe a set of relationships amongst the observable objects. In general each calculi comes with its own set of benefits and drawbacks as each one of them has been tailored to exploit different aspects of space[?].

For the case of robot navigation, current state of the art approaches utilize qualitative calculi that can provide both spatial and temporal information such as the QTC [?] or QRPC [?]. There exist comprehensive surveys that provide detailed information about each of the existing qualitative calculi[?], hence this state of the art aims to provide only a concise overview of the qualitative calculi that are advantageous to our application. We shall look into the relationships afforded by each of these calculi and their classification based on the domain of their utility.

2.1 Forms of qualitative spatial representations

2.1.1 Topological Representations

\square $[?]$ $[?]$: This is the most fundamental spatial representation, wherein the observed space is divided into distinctive regions based either on distinctive points in space or on separable objects found in the space. Topological representations draw heavily from the field of “Mereology” (the theory of parthood) to describe relations between the distinctive regions. Qualitative calculi such as RCC, Interval Algebra, n-intersections etc. belong to this category. Such representations deal with the “invariant properties that are under continuous deformations of objects, including translating, rotating and scaling”, and often include only spatial information while completely disregarding temporal data.





Figure 2.1: The eight jointly exhaustive and pairwise disjoint relations of region connection calculus (RCC8). The arrows show which relation is the next relation a configuration would transit to, assuming the continuous movements or deformations $[?]$, $[?]$, $[?]$.


2.1.2 Directional Representations

[7] : The relative direction between two different objects can be represented using directional relations/representations. These representations rely on three

primary elements, a reference object, a reference frame and a target object to define a valid relation between two different objects. Directional representations are widely classified into two categories, point based and projection based with the discerning factor being the dimension of the objects involved and distinction of space using either cone shaped spatial sectors or by using vertical and horizontal lines to create smaller rectangular sectors. Furthermore, the directional calculus isn't restricted to using only cardinal directions, it also allows the use of nominal directional information such as left ,right etc to describe the directional relations. Qualitative calculi such as CDC, OPRA, CyCord etc utilize the directional representation. Being based of topological representations, directional representations also include only spatial information while disregarding temporal data.



(a) Cone-shaped direction relations [26]



(b) Projection-based direction relations [27]

Figure 2.2: The point based and projection based direction representations [7]

2.1.3 Distance Representations

[7] : The qualitative representation of spatial distance can be classified into two groups namely absolute and relative. This classification is made solely on the basis of the presence/absence of an extraneous referential object in the relation between two objects. This distinction can be clearly illustrated by the following example, 'the distance between A and B is 8 meters' or 'A is near B', this is a absolute approach as the distance is measured directly between two objects. Whereas saying that 'A is closer to B than that to C' classifies as a relative approaches as

this involves the comparison to a third object. Furthermore, it has been shown that absolute approaches can be qualitative or quantitative, but relative approaches are commonly qualitative [?]. Qualitative calculi such as the ARGD(or Delta) and TPCC use the distance representations to describe the observable space. Distance based relations have found to be insufficient by themselves when it comes to the task of robot manipulation/navigation and hence are often used in combination with distance representations to yield a fairly suitable and complete representation of the environment [?]. Like with the direction representations this calculi also lacks temporal data in the encoded relations and is hence unsuitable for applications involving moving objects.




Figure 2.3: An representation of the combination of cone-shaped direction and absolute distance: very close(vc), close(cl), commensurate(cm), far(fr) and very far(vf), [10].

2.1.4 Moving object Representations

[7] : Topological representations, directional representations and distance representations describe relations between stationary objects, this limitation encouraged

the development of a moving object representation which can qualitatively represent moving objects and their trajectories. These representations effectively deal with both spatial and temporal data to describe valid relations among mobile objects, while these relations include some directional information they mainly describe the relative motion between two objects and not relative direction. The relative motion between two objects is described using oriented line segments which are approximations of the trajectory of the objects in motion. QTC, QRPC are the two prominent calculi that utilize moving object representations. Moving object representations and the calculi using these representations have been proven to have solved the problem of representing moving objects but since these relations lack any distance information, they are still prone to failure and often need a complimentary distance calculi to ensure that a mobile object(robot) can successfully move around in the given environment without collisions.




Figure 2.4: Basic relations of basic Qualitative Trajectory Calculus (QTCB) in a conceptual neighborhood diagram. The solid dots represent the stationary objects and the open dots represent the moving objects $[?]$, $[?]$.

2.1. Forms of qualitative spatial representations

Domain	Model Name	Type of objects	Number and granularity of relationships	Description
Temporal	Interval Algebra [3]	Time Intervals	13 relationships, Binary relationships	It does not consider time instants.
	Extended Interval Algebra [21]	Time intervals and extreme points of the intervals	29 (13 IA(Interval algebra) + 16 extremes), binary	It extends IA(Interval Algebra) model by considering new relationships including the extremes of the interval and it introduces the notion of conceptual neighborhood.
Spatial	Region Connection Calculus [35]	Sets	8 or 5 relationships, Binary Relationships	It uses the geometric properties associated to the connection between two sets to establish relationships that are no longer linear but planar, and which are invariant to translation, rotation and scaling.
	Cardinal Reference System(CRS) [20]	Generic objects	9 (8 cardinals + 1 neutral) relations, Binary Relationships	It describes the position of any object by using a cardinal orientation as reference system and by adding also a neutral region
	FFC (Flip Flop Calculus) [29]	Points	8 (6 + 1 double + 1 triple), Ternary Relations	It is based on the possible positions of a point C with respect to a segment AB defined by other two points, A and B.
	SCC (Single Cross Calculus) [21]	Points	11 (8 +B=C+1 double + 1 triple), Ternary Relations	Describes the possible positions of a point C with respect to a segment AB and the orthogonal line to segment AB on B.
	DCC (Double Cross Calculus) [22]	Points	17 (15 regions + 1 double + 1 triple), Ternary Relations	Describes the possible positions of a point C with respect to a segment AB and two orthogonal lines to segment AB on A and B.
	Oriented point based Reasoning [32]	Oriented Points	4, Binary Relations	It is based on the relative orientation between pairs of oriented points in terms of two qualitative spatial dichotomies: the frontback and leftright.
	DRA (Dipole Relation Algebra) [17], [18]	Dipoles (or oriented segments)	24, Binary Relations	It is based on the relative position of oriented segments.
	OPRA (Oriented Point Relation Algebra) [19]	Oriented points	Depends on the granularity, Binary Relations	As DRA model, it is also based on the relative position two oriented points, but it supports different levels of granularity.
Spatio-temporal	QTC (Qualitative Trajectory Calculus) [42]	Points	81, Binary Relations	It describes the possible relations among two moving points in terms of the frontback and leftright dichotomies.
	QRPC (Qualitative Rectilinear Projection Calculus) [24]	Oriented points	Depends on the chosen granularity (up to 48), Ternary Relations	It establishes the possible relations of an object with respect to the trajectory of another object depending on the cross-point of the trajectories and the relative position among them

Table 2.1: Key features of the more representative models(calculi) of qualitative representations of spatial or temporal domains in the existing literature [24].

2.1.5 Conclusion

From the above breakdown of the representations and the calculi, it is easy to summarize that distance representations and moving object representations are the most promising representations for our application in mobile robot navigation. Consequently the calculi associated with these representations will be the ones that are further scrutinized in the following section. The reasoning behind this conclusion is fairly simple moving object representations are basically spatio-temporal representations which take into account both the spatial and temporal data to create abstractions of the objects trajectory, this is crucial when dealing with mobile objects as this gives a more concrete representation of the objects in motion. In the case of distance representations although these representations deal only with spatial information, they provide explicit information on how close or far the objects under consideration are. Thus effectively capturing the possibility of a collision between the objects, this sort of information cannot be found in the direction and topological representations hence rendering them unfavorable for our application in mobile robot navigation. [7], [11], [12], [13], [45].

2.2 Analyzing qualitative calculi for navigation

This section aims to provide a through understanding at a selective group of qualitative calculi based on the conclusions drawn from the previous section. Namely we shall look at the qualitative calculi such as the QTC, QRPC and ARGD which use moving object representations and distance representations and function in the spatio-temporal and spatial domains respectively.

2.2.1 Qualitative Trajectory calculus

[41], [44], [43] The QTC calculus was developed to solve the problem of inadequate representation of mobile objects in the spatio-temporal domain, which until then were represented only in the spatial domain using either the RCC or the n-intersections calculi. The major drawbacks of those calculi was their failure to deal with temporal data. Hence mobile objects were often abstracted as stationary

regions using either 'disconnected from' relation (DC) in RCC or 'disjoint' relation in the 9-intersection model, with the exception of a few limiting cases where the two objects meet, such as a collision between two mobile robots. Thus, the limiting factor of these formalisms was that all the DC relations were non-differentiable, due to the ignorance of information regarding relative motion between the two objects.

The QTC calculus constitutes of two major variants the QTC_B and the QTC_C , with the major difference between the two being the inclusion of the directional information in the relationships (between two objects) of the QTC_C calculus. Both versions of the QTC are adept at dealing with qualitative movement of objects in one, two and three dimensions. In the QTC_B calculus, as the euclidean distance between two objects is taken as the only constraining dimension. The abstraction of movement is depicted using three qualitative values:

- 0: the object is stable with respect to the other object.
- -: the object is moving towards the other object.
- +: the object is moving away from the other object.

The assigning of these qualitative values to an object's movement depends upon the relative position (constrained by distance) and relative speed of the two objects with respect to each other. This can be illustrated by the following example, consider two objects 'j' and 'k', the possible values for 'j' :

- based on relative position at a time 't' are:
 1. 0 (stable): if there is no change in the relative position with respect to 'k' (no change in relative distance).
 2. - (moving towards): if there is a change in the relative position with respect to 'k', such that the relative distance between the objects decreases.
 3. + (moving away): if there is a change in the relative position with respect to 'k', such that the relative distance between the objects increases.
- based on relative speed at a time 't' are:

1. 0 (stable): if speed of 'j' is equal to the speed of 'k'.
2. - (moving towards): if speed of 'j' is lesser than the speed of 'k'.
3. + (moving away): if speed of 'j' is greater than the speed of 'k'.

Hence a valid QTC_B relation between qualitative trajectories of two objects is represented as such '-,+,-' (for object 1) and '+,-,+' (for object two). Wherein the value in the first position is the relative position of the object in consideration, the second value is the relative position of the other object and the third value is the relative speed of the current object with respect to the other object. The benefit of having a relation that includes both relative position and speed comes to light when dealing with the movement of objects in higher dimensions (2D, 3D) for instance in 2D, the value '0' (stable) may be interpreted as either the distance being stable or the speed being stable, this confusion during interpretation is avoided by using unique values for both the relative distance and speed and hence the size of the resulting relations is a set of three. Interpretation of these relations is pretty straight-forward when dealing with movements one dimension.

The QTC_C variation of the QTC calculus is often seen as an extension of the QTC_B calculus, since it uses the same qualitative values to represent the qualitative trajectories of the objects. The only difference between the two versions comes from the integration of directional information which denotes the direction of movement of the current object in relation to a line segment between the two objects. This version of the QTC calculus was inspired in part by the 'Double cross calculus' [46], hence the name. The QTC_C calculus is an improvement on the double cross calculus, as it can define qualitative trajectories and direction for single as well as multiple objects at once, whereas the double cross calculus can only deal with single objects at any given instance of time.




Figure 2.5: A graphical representation of the QTC_C calculus for a relation between two moving objects 'k' and 'l', where t_1 and t_2 are the two distinctive time instances and RL refers to the reference line and the double crosses ($RL \perp 1$, $RL \perp 2$) for the two objects [43] .

The relations of the QTC_C calculus, while following the same basic principles of the QTC_B , have been tweaked slightly to allow inferencing of the objects position in terms of the relative direction to the reference line. The assignment of the qualitative values to the object's movements can be illustrated using two objects 'k' and 'l', the possible values for 'l' at any given time interval are based on the following reasoning:

- based on movement relative to the respective perpendicular reference line:
 1. 0 (stable): if there is no change in the relative distance with respect to 'k' or with respect to the reference line.
 2. - (moving towards): if there is an increase in the relative distance between the objects.
 3. + (moving away): if there is an increase in the relative distance between the objects.
- based on movement relative to the directed perpendicular reference line(from 'l' to 'k'):

1. 0 (moving along the directed reference line): if the object moves along the line segment or if it was moving along the left/right and continues to do so in the given time interval.
2. - (moving to left side of the directed reference line): if the object moves from the right side of the line segment to the left side in the given time interval.
3. + (moving to right side of the directed reference line): if the object moves from the left side of the line segment to the right side in the given time interval.

Hence a valid QTC_C relation between qualitative trajectories of two objects is represented as such ‘-,+,-,0’(for object 1) and ‘+,-,-,0’(for object two). Wherein the value in the first position is the relative position of the object in consideration, the second value is the relative direction of its movement, the third value is the relative position of the other object and the fourth is it’s relative direction of movement.

Conclusion [41]In conclusion it is safe to say that the QTC_B calculi is more complete and robust in the sense that it can qualitatively and correctly represent all possible trajectories of the mobile object at a given instance of time, although due to it being developed to deal with mobile objects when they are in DC regions [44] it still cannot make a very robust or accurate relation regarding collision conditions, it provides a safer alternative to the QTC_C calculus as this calculus is still regarded as a work in progress [43]due to it’s inability to distinguish between the trajectories of a mobile object moving along the directed reference line and continuing to do so and a mobile object moving on either side of the directed reference line and continuing to do so. Thus this justifies the selection of QTC_B for our implementation, not only is it safer and simpler but it also allows easier integration with other complimentary calculi such as ARGD, RCC which may be used to deal with possible collision cases.

2.2.2 Qualitative Rectilinear Projection calculus

[24], [4] , [14] The qualitative rectilinear projection calculus(QRPC) presents a innovative approach to qualitatively representing motion patterns based on planar trajectories. In comparison to the QTC calculus, this representation has a richer description of the motion exhibited by mobile objects. The basis of this claim lies in the oriented rectilinear projection used to represent the trajectories, which allows this calculus to represent rotational motions of an mobile object, something that was not possible in the existing calculi such as the QTC. The QRPC is specifically tailored towards obstacle avoidance and geometric relationships between two objects are generated using the front-back and the left-right dichotomies. The relationships encompassed in the QRPC abstract the objects as points and use their rectilinear projections to make qualitative distinctions such as front-back and left-right, these atomic relations and their base notations are illustrated below:

1. Notations:

- $P_i P_j$: is the relative disposition between the oriented rectilinear projection of the object O_i and the oriented rectilinear projection of O_j .
- $O_i O_j^{LR}$: The relative position of O_i with respect to the left-right dichotomy of O_j .
- $(CO_i^{FB})(CO_j^{FB})$: The relative position of the point of intersection('C') of the oriented rectilinear projections with respect to the frontback dichotomy of both objects.
- $O_i O_j^{FB}$: The relative position of O_i with respect to the front-back dichotomy of O_j when the trajectories are superimposed.

Note: 'i' and 'j' denote the two different objects.

2. Qualitative (atomic)relations in each of the notations :

- The relative disposition between two oriented rectilinear projections($P_i P_j$):
 - $\uparrow\uparrow$: Parellel in same direction
 - $\uparrow\downarrow$: Parellel in opposite direction

- \uparrow : Coincident in same direction
- \updownarrow : Coincident in opposite direction
- X : Crossed/Intersecting rectilinear projections
- The relative position of O_i with respect to the left-right dichotomy of O_j , $(O_i O_j^{LR})$:
 - ‘-’ : if O_i is on the left of P_j .
 - ‘0’ : if O_i is over P_j .
 - ‘+’ : if O_i is on the right of P_j .




Figure 2.6: Relative position of O_i w.r.t the left-right dichotomy of O_j for crossed projections [24].

- The relative position of ‘C’ with respect to the front-back dichotomy of two objects $(CO_i^{FB})(CO_j^{FB})$:
 - $(+, +)$: if ‘C’ is in front of O_i and O_j .
 - $(0, +)$: if ‘C’ is at same position as O_i and in front of O_j .
 - $(+, -)$: if ‘C’ is in front of O_i and behind O_j .
 - $(0, -)$: if ‘C’ is at same position as O_i and behind O_j .
 - $(-, +)$: if ‘C’ is behind O_i and in front of O_j .
 - $(-, 0)$: if ‘C’ is behind O_i and in same position as O_j .
 - $(-, -)$: if ‘C’ is behind O_i and O_j .
 - $(+, 0)$: if ‘C’ is in front of O_i and at the same position as O_j .

In cases where the two projections do not intersect with each other ($\uparrow\uparrow$ or \updownarrow), this qualitative abstraction presents as conundrum

as the point of intersection ‘C’ may lie at either positive or negative infinity, hence in such cases the relation is abstracted to either $(+, +)$ or $(-, -)$.





Figure 2.7: Some of the spatial configurations of the intersection point with respect to the front-back dichotomy of two objects for crossed projections $(CO_i^{FB})(CO_j^{FB})$, [24].

- The relative position of O_i with respect to the front-back dichotomy of O_j when the trajectories are superimposed($O_i O_j^{FB}$):
 - ‘+’ : if O_i is in front of O_j after P_i is superimposed on P_j .
 - ‘0’ : if O_i is at the same position as O_j after P_i is superimposed on P_j .
 - ‘-’ : if O_i is behind O_j after P_i is superimposed on P_j .

Note: The after the rectilinear projection of O_i is rotated(such that the objects are always facing in opposing directions) along ‘C’ if it exists, before being superimposed on the rectilinear projection of O_j .



(a) The $(O_i O_j^{FB})$ feature for crossed projections. [24]

(b) The $(O_i O_j^{FB})$ feature for parallel projections. [24]

Figure 2.8: The point based and projection based direction representations [?]

Conclusion Hence a complete valid QRPC relation comprising of the above mentioned atomic relations can be written as $[(P_i P_j)(O_i O_j^{LR})((CO_i^{FB})(CO_j^{FB}))(O_i O_j^{FB})]$, with the various values replacing their respective placeholders. Thus proving to be a richer representation of the movements of the mobile objects as it can effectively distinguish between front-back, left-right as well as same or opposing direction of heading. While this calculus does present a compact view of the movements of the objects, like it's predecessors it still requires a sequence of qualitative(QRPC) states(individual sets of relations) to effectively represent the movement of an object, besides a completely theoretical formulation of the calculi without the backing of suitable empirical data or implementation makes it hard to believe that this calculi would function reliably in a real time mobile robot scenario. These drawbacks dissuade us from further pursuing this calculi for our purpose of achieving qualitative perception and control in mobile robots [24].

2.2.3 Qualitative Distance calculus

[10], [46] The qualitative description of distance is based on three primary elements, a primary object, a reference object and a reference frame. When making a statement such as 'A is near B' the qualitative inference is ambiguous without taking into consideration spatial entities such as metric distance between the objects, their respective sizes and shapes, their relative positions, the positions of other objects as well as the frame of reference with respect to the objects itself. Furthermore the distance between two objects varies with perspective, for instance looking at a moving object from two different perspectives leads to two different interpretations of the distance to the object, with respect to observing entity. The distance calculi aims to summarize all these varying spatial quantities into a single coherent qualitative description which can be used to reason about space in terms of qualitative distances.

The ARGD or Delta calculus are some of the common names used for the qualitative distance calculus. These calculi partition the physical space into circular regions of varying granularity. Since there is no restriction on the number of granular divisions that can be applied to a given physical space we may define

this in a manner that is suitable for our application. Commonly the granularity varies from anywhere between 2-5, with the respective labels being very close, close, commensurate, far, and very far.




Figure 2.9: Various levels of distance and orientation distinctions. These figures show typical distance/orientation granularity configurations [10].

The various granular regions in the distance calculi are always centered around the object in consideration, these granularities are subject to an inherent ‘greater than’ order amongst themselves such that the granular region closest to the object has the lowest distance value and the one that is farthest has the highest order. Consider ‘ q_n ’ as the granularity of the distance representation, then the various instances are organized as such $[q_0 < q_1 < q_2 < \dots < q_n]$, with q_0 being the smallest distance to the object and q_n being the largest. By using this comparative approach for distance magnitudes the calculus effectively maps the granular symbols to one dimensional geometric intervals that represent the distance ranges.

Conclusion Since the applicability of the distance approach does not depend upon the number of distance relations, it allows the distance calculus to be highly adaptive to the users demands and hence provides a feasible alternative to collision free navigation in mobile objects. Also as mentioned previously the distance representation effectively divides the physical regions around the object into geometric intervals, hence making this approach suitable to define distance thresholds around the robot to avoid collisions with other objects as well as define a suitable safe

region around the robot, which in-turn ensures safe movement in the physical space. These benefits of the qualitative distance calculi make it favorable to our application, hence warranting its utilization [10], [30].

2.3 Implementations utilizing qualitative representations for navigation in robots

The goal of this section is to introduce the reader to the existing approaches that use qualitative spatial representations in some capacity to achieve efficient and collision free navigation in mobile robots. The merits and de-merits of each implementation is recognized and a brief summary is constructed based upon the same.

- [8], This approach relies heavily on the detection of tangible features in two sets of images one of which is a reference image that is taken during a teach phase (when the robot is taken manually through the desired path and allowed to take reference images through out its path traversal) and a second image that is taken during a replay phase during which the robot is allowed to navigate the desired path by itself, capturing new images all along. The features in both these images are detected and tracked using the Kanade-Lucas-Tomasi [6] feature tracker. The tracked features in the current image (taken during the replay phase) are compared with the features observed in the reference image (taken during the teach phase) and the difference in their positions and distance is used to make qualitative decisions regarding the corrections that have to be made to the robot's path with respect to the desired path. The underlying spatial entity that is compared is the corresponding distance between the tracked features (in both the reference and the current image and the reference image) with respect to a common principal point of the images. Based on this conditions the decisions are made as follows:
 - if the robot is moving from point A to B without deviating from the original path, then continue the current path until some deviation occurs.

2.3. Implementations utilizing qualitative representations for navigation in robots

- if the robot deviates laterally from the desired path and this is indicated in the signed distances between the features of the current and reference image, then:
 - * if the distance between the reference feature lying on the left/right of the image and the principle point is more than the distance between the current feature lying on the left/right of the image and the principle point then move left or right respectively.
 - * if the signed distance of the feature lying on the left/right of the image does not match with the sign of the feature lying on the left/right of the reference image then move right or left respectively.

Conclusion The merits of such an feature based approach seem to be apparent, yet this approach does not utilize any of the traditionally accepted qualitative calculi. Furthermore it's reliance on a teaching phase renders it invalid in cases where prior information about the environment is denied to the robot. The dependence on further factors such as lighting conditions, detection of features and inability to work efficiently in an outdoor environment (due to lack of contrast, the features are not detected) show that this is a highly constrained approach that can work only if a large amount of prerequisites are satisfied. The merit of this approach is still it's ability to function exceptionally well when the teach phase is executed properly, with the robot able to follow trajectories upto a 100 meters easily. The authors also mention the apparent improvement in efficiency (in terms of reduced cost and power consumption as well as increased robustness) when using such qualitative approaches, but fail to provide empirical proof for such statements.

- [9], The approach presented in this paper also utilizes detection of tangible features to extract pixel coordinates of these features and then compare these coordinates with the corresponding pixel coordinates of the feature in the reference frame. The resulting differences are then used to make decisions regarding the control of the robots trajectory, as previously introduced this approach also makes use of the teach-replay method. This paper extends the approach presented in [8] by combining the pixel coordinates with odometry

information to achieve a more robust navigation, also the use of the ‘funnel lane’ methodology is a novel concept that helps in localizing the robot. The underlying spatial entity uses in this approach is the relative positions of the features with respect to the principal point of the image, which yields signed (x,y) co-ordinate values. The distance between these reference points and the principal points is used to define a region called the ‘funnel lane’, while the robot lies in this region it is allowed to move directly towards the goal position, but if there are any violations such that the robot moves out of this ‘funnel lane’ then the controller updates the control commands to ensure the robot re-enters the ‘funnel lane’. Since the ‘funnel lane’ is oriented such that its origin is always at the goal position hence ensuring that the robot zeros in on the goal position.




Figure 2.10: The funnel lane created by the two constraints (distance from the principal point and the relative signs of the distances), and when it has turned by an angle α , here μ^C and μ^D represent the horizontal pixel coordinates of the reference and the current frame.

Conclusion Being an extension of the approach specified in [8], this implementation suffers from very much the same over-reliance on the teach phase to correctly capture the reference features, while completely failing to utilize any of the traditionally accepted qualitative calculi. Furthermore the authors fail to indicate the maximum number of features that can be considered

2.3. Implementations utilizing qualitative representations for navigation in robots

when constructing this ‘funnel lane’ and do not provide details about what happens when no feature is detected, making this a promising yet incomplete implementation as not all details are disclosed. The implementation is more robust thanks to the introduction of the funnel lane concept and utilization of odometry information which enable the robot to follow trajectories of upto 380m and at a speed of 1m/s. Again the authors mention the improvement in efficiency in terms of power consumption and computational requirements yet they fail to provide any conclusive evidence to validate these claims.

- [33], The approach followed in this implementation is also based on a teach-replay method, but instead of using RGB cameras and images to extract and compare features it uses a sonar array to find the distances from the obstacle. Since this implementation is deployed on a wheelchair in a indoor corridor environment, the sonar array is used to measure the distance from the wall. The primary use of qualitative representations is for human robot interaction and is not used for the navigation task as a suitable update rate for the qualitative representations was not possible, hence although the use of qualitative calculi based on the directional and distance representations was hypothesized it was not put to test in a factual manner. As mentioned above the proposed approach used a sonar array and dead reckoning to record desired paths and then autonomously replay them. The base assumption being that any path in an indoor environment is basically a combination of following walls and making turns at the corners, based on this assumption path were described with as a sequence of distances and angles with specific triggers wherever a corner or an immovable object was encountered so that a suitable maneuver may be performed. Being a teach and replay approach this implementation also compared data obtained during the replay stage with the reference data obtained during the replay stage and made decisions based on the differences so that the wheelchair follows a path that is as close as possible to the original path as possible.

Conclusion Since this is another teach-replay approach it’s major drawback is the over-reliance on the teach phase, furthermore being a teach replay

```
<close forward fast>  
<close right medium-speed>  
<close backward slow>  
<very-close left medium-speed>
```

Figure 2.11: The hypothesized qualitative representation with the left most value being the distance, followed by the direction to move in and finally the speed with which to move [33].

approach that utilizes sonar distances, angles and dead reckoning to obtain trajectories, the system cannot deal with dynamic objects such as humans that may be encountered during autonomous replay as these objects did not exist during the teach phase and hence no information about them exists in the systems knowledge of the environment. The authors also fail to provide concrete information regarding how the control decisions are made instead choosing to only mention that this is done based on the differences in the represented trajectories. One clear merit of this implementation was the hypothesis of how qualitative distance and direction calculi can be combined to achieve navigation in robots, but this is also it's drawback as this was only hypothesized and not tested or implemented on the mobile platform. Again the authors assume better efficiency in terms of power consumption and computational requirements due to the usage of qualitative representations yet they fail to provide any conclusive evidence as validation.

- [37], The approach presented in this project makes use of a unique qualitative map based representation, which is inherently based on distance relations. The authors propose the 'Qmap' framework which accepts as a input a line segment representing the desired path and . This line segment is then quantized into rectangular cells that form a part of the grid. Since the robot is equipped with a sensor array of 8 sonar's each placed at 45 degrees (in a manner similar to the layout of the cardinal directions) and orientation sensors the data received from each of these sensors is stored in a qualitative manner within the cells of the grid. Sensors that are in close proximity of obstacle are marked as active and their respective relations are indicated using either of the three distance primitives [I(increasing), D(decreasing), S(stable)], this

2.3. Implementations utilizing qualitative representations for navigation in robots

is the qualitative data that is stored in each cell during the off-line planning phase. During the run-time the implementation takes as input the generated ‘Qmap’ and the starting and ending positions. Additionally, data stored in each cell is compared with the real-time data and the control decisions are made based on the differences between the two. In cases where the difference between the reference data (simulated during the planning stage) and the real-time data is large such that can be caused by the presence of moving obstacles the preference in the control algorithm is given to the real time data such that it ensures that the robot stops moving completely until further intervention by a human controller.




Figure 2.12: figure showing the ‘Qmap’ for a given line segment, the 0’s and 1’s indicate the inactive and active sensors while ‘S’, ‘I’, ‘D’ indicate the distance relations of each sensor w.r.t the obstacle(grey cell) [37].


Conclusion The authors mention that the implementation deals with obstacles by marking those respective cells as blocked, but do not indicate how or when(planning or run-time) this information is provided to the map, also the stopping of the robot when dealing with moving objects is an obvious drawback when considering real world applications. The authors mention that a successful navigation was achieved in 60 percent of the cases out of a possible 15 experimental runs, with the causes of failure being the large size of the robot which in turn caused collisions when turning, the accumulation of errors in the orientation data due to inaccurate orientation sensors and errors in localizing the robot position on the ‘Qmap’ due to increasing uncertainty, especially when moving in large open spaces. Yet again the author’s mention the efficiency based benefits of the qualitative approach but do not provide

tangible proof for it and although this is a promising qualitative representation in relation to a global map of the environment it still does not use any of the traditionally accepted qualitative calculi.


- [38], This implementation also provides reasonable cause to prove the utility of qualitative representations in global planners. It uses as an input a hand-drawn map containing the desired path to be followed and a set of landmarks that can be used as a reference, this qualitative map does not have to be accurate but should be able to represent the approximate positions of the landmarks in the physical space. The planning module used in this approach utilizes this approximate way-point positions and the corresponding landmark positions to plan a valid path that can be further fed to a path following module which in-turn executes it on a low level. The path planning is modeled as a quadratic optimization problem, wherein each way-point is influenced by it's surrounding landmarks, such that the closest landmark has a higher bearing on the placement of the way-point rather than a landmark that is farther away. The uncertainty in the position of the landmark is also taken into account when placing a way-point in the final trajectory that is to be executed. Furthermore when planning the final path the relative qualitative relations between the robot and the landmarks are maintained which makes it easier to localize the robot based on the available landmarks and in-turn reduce the uncertainty in the positions of the landmarks themselves. Additionally the EKF-SLAM algorithm is used to make the localization and way-point planning more robust.

Conclusion This implementation represents a more reliable approach to the utilization of qualitative representations in a global planning based approach. The preservations of qualitative relations between the way-points and the landmarks combined with a SLAM implementation provide a robust platform on which the robot can securely navigate a given environment. In it's current state this approach lacks the knowledge of obstacle avoidance for both stationary and mobile objects, also the authors do not elaborate on how the robot knows which observed landmark is to be associated with which

2.3. Implementations utilizing qualitative representations for navigation in robots



(a) Landmarks (shown as red triangles) represented with linear springs to the proposed waypoint location (shown as a star). For each landmark, the spring constant is calculated as a function of the distance between waypoint and landmark, and the uncertainty in the estimated location of the landmark (represented by red ellipses) [39].



(b) The sketched map (blue, on left) includes six landmarks and a trajectory that slaloms between pairs of landmarks. In the true environment (red, on right), the robot must slalom more aggressively to pass between the landmark pairs [38].

reference position in the given map, although during implementation on a robot this problem was solved using an overhead camera this does not suggest a feasible real-time implementation. Furthermore the authors suggest the advantage in efficiency that qualitative approaches have over quantitative approaches but do little to prove this as the truth.

- [5], This implementation features the use of the qualitative trajectory calculus to create abstractions of human movements and then use these abstractions to reason and execute the corresponding motions of the robot. QTC_B is the selected calculi for creating these abstractions, since it takes into account the relative motion between two mobile objects. The abstractions are described as such:

- ‘-’ (moving towards) : if the distance between the two objects is decreasing at a time instant t_{-1} and t_{+1} , where the current time instant is t .
- ‘+’ (moving away) : if the distance between the objects is increasing at a time instant t_{-1} and t_{+1} , where the current time instant is t .
- ‘0’ (stable) : for every other case.

Using the above mentioned abstractions the relative motion between the robot's and the human trajectory is encoded as a qualitative representation. A graph structure is used to build a situation graph tree where each node represents a particular scenario or agent's states and the edges indicate the transition to the next possible states. A depth first approach is used to traverse the whole tree and a fuzzy-logic based interpreter(F-Limette) is used to interpret the states and convert them to a low-level motion command. For the sake of simplicity the authors have only implemented this approach in a restricted limited manner, wherein the robot either follows the human or stops following it based on the described qualitative scenarios.




Figure 2.13: Situation Graph Tree of the human motion behaviour and relative robot actions [5].

Conclusion The above mentioned approach was successfully implemented on the robot platform using laser range finders to track human feet, and create suitable abstractions. Yet it presents only a limited view on the applicability of qualitative representations for robot navigation, furthermore when using such graph structures the space and time complexity increases exponentially with increase in the number of scenarios. Thus contradicting the base assumption that using qualitative representations allow improvement to the computational efficiency for a given task. The authors do suggest the improvement of the current approach by replacing the QTC_B representation with a QTC_C representation that allows a finer control paradigm since it includes directional information(left-right) to be represented in addition to the nature of the existing motion(moving away-towards). Although this im-

2.3. Implementations utilizing qualitative representations for navigation in robots

plementation shows the utilization of the QTC calculi, it cannot be considered a robust implementation due to the lack of extensive testing and the limited experimentation that was carried out for this purpose.

- [15], This approach makes use of the qualitative trajectory calculus to depict relative motion between a human and a robot, in a restricted environment which in this case is a corridor. The use of qualitative representations to achieve robot trajectories that are perceived as safe and intuitive by humans is the main aim of this project and to that effect the ‘pass-by’(human and robot cross each other in opposite directions) scenarios are evaluated. The authors use ‘velocity costmaps based on the qualitative descriptions to limit the sample space of the dynamic window approach local planner to generate trajectories’ [15], that are safe for the robot and human as well as intuitive for the human. The authors combine the QTC_B and QTC_C calculus into a single calculus called the QTC_{BC} which allows the representation to switch between the QTC_B and QTC_C depending upon a distance threshold. This distance threshold is defined such that when the robot is in close proximity to the human agent the representation switches to QTC_C as this provides a more informed representation of the relative trajectories, at farther distances since it is sufficient to know whether the two objects are approaching each other or not, the QTC_B representation is used.

Conclusion The approach was tested by both simulation and application on a robot and the qualitative representation velocity costmaps far outperformed(in terms of minimum number of collisions) the costmaps that utilized cartesian coordinates as well as a naive dynamic window approach. This approach provides a concrete argument to the utility of qualitative representations in robot navigation as well as human robot interaction, yet it does not clarify the claim stating that the use of qualitative representations is more efficient when compared to a quantitative representation. Also, it’s evaluation on a single test scenario makes it likely that this approach is highly tuned to achieve greater success on the described task with no indication of it’s performance on a more generalized task such as navigation through a




Figure 2.14: The velocity costmap prototypes. The area enclosed by the partial circle represents the low cost area, everything outside is assigned the highest cost value. The black dot on the right represents a human that can have any possible QTC state (except for $QTC_B = 0$) [15].

corridor with or without multiple obstacles.

2.4 Limitations of previous work

The previous section brings to light a variety of implementations that utilize qualitative spatial representations in varying capacity to abstract spatial entities and relate them in a semantically cohesive manner. The concern that's highlighted immediately is that many of these approaches do not utilize the traditionally accepted qualitative calculi and hence often end up with provisional implementations that have been developed with reliance on a set of highly specific parameters, which if varied will most likely cause the developed algorithm to fail the given task. Thus showing that there is a lack of a generalized approach to the application of qualitative spatial representations in the domain of mobile robot navigation.

Furthermore all the approaches state the efficiency gain especially in terms of computation and power consumption as the motivation behind using qualitative spatial representations over quantitative ones, but none of them provide tangible proofs to establish the truth of this statement. There exists a lack of effort on this front as there are no comparative studies nor any empirical evidence to support this seemingly obvious claim.

Thus for the purpose of this project we will aim to address the above mentioned limitations, in the proposed approach.

Approach

The conclusions drawn in the previous chapter, allow us the liberty of focusing specifically on the two most promising qualitative calculi QTC_B and $ARGD$, for the purpose of developing an algorithm that centers around the utilization of either one or both of these calculi for the purpose of qualitatively representing physical space in our application of mobile robot navigation.

From the above analysis of the state of the art it is clear that the advantages of qualitative representations lie in the dealing with imprecise raw data, but it should be noted that these representations aren't a replacement for quantitative representation instead they are simply an alternative that can be harnessed to deal with scenarios where the need for crisp, precise data cannot be justified such as traversal in a fairly empty open spaces(halls, corridors etc.). Precise quantitative representations are still necessary when dealing with scenarios such as passing through a door.

3.1 Proposed approach

3.2 Implementation details

Methodology

This chapter aims to highlight both the hardware and software setup of the developed system. The integration of the software libraries and packages has been implemented and tested extensively on the ‘KUKA youBot’ which is the aforementioned hardware platform. The following sections briefly illustrate the applied hardware and explain the software packages and their integration with the QSRLib library, which allows us to express physical space qualitatively.

4.1 Hardware Setup

The applied robot platform for our application is the ‘KUKA youBot’. This is an omni-directional platform, equipped with a 5 Degree of freedom robotic arm, that features a two finger gripper. The robot base is equipped with two ‘Hokuyo URG-04LX’ laser range finders situated at the front and at the back respectively, this placement allows for robust localization and map-based navigation in known indoor environments [36]. Physically the dimensions of the robot are as follows length 58cm, width 38cm, height 14cm with a ground clearance of 2cm and a minimum and maximum velocity of 0.01m/s and 0.8m/s respectively [2]. The power to this applied platform comes from a 24 volt, 5 Ah lead-acid battery that has an approximate optimal runtime of 90 minutes, but this varies depending upon a multitude of factors such as the robot’s velocity, sensors used etc.



Figure 4.1: The youBot robot platform

The robotic arm plays host to a camera mounting which supports the ‘ASUS Xtion Pro Live’ RDB-D camera, which as the name suggests supports the perception of depth information in addition to the usual RGB or raw image data. This RGB-D camera has a detection range of 80cm - 3.5m with a field of view limited to 58° , 45° , 70° horizontally, vertically and diagonally respectively [40]. The image size for this camera is ‘320x240’ for a QVGA format at 60 frames per second, also being highly compatible with the ‘OpenNi development framework’ ensures it’s easy integration with the ROS packages by the ‘b-it-bots RoboCup@Work’ team, which has already developed scene segmentation and object detection applications centered around this sensor. The stock internal computer that comes issued with the youBot has been replaced with a ‘Intel Core i5’ processor that facilitates highly computational perception tasks to be run directly on the platform [36].




Figure 4.2: youBot arm at full extension

4.2 Software Framework

The software framework underpinning the applied robot platform has been developed by the ‘b-it bots @Work’ team and is based on ROS(Kinetic Kame version) or the robot operating system [34], which provides a modular and distributed structure to design a functional system based on the developer’s requirements. This modular architecture provides a rapid and robust communication infrastructure that is based on actions, services and clients to interchange data amongst the various different functional, software components of the applied platform. The framework provides an effective and efficient medium for interfacing various sensors and actuators such as laser scanners, cameras etc.

Another merit of the robot operating system is it’s provision of advanced tools for visualizing and testing various types of data and troubleshooting the entire system in cases of failures or errors. One such heavily utilized tool was ‘rosbag’, used particularly to capture data [25] and evaluate the developed implementation with varying parameters but always on the same set of captured data.

4.3 Integration of Qualitative representations

The current software framework, set-up on the robot consists of numerous packages that allow the control of it’s base as well as arm actuators while also providing an effective interface to it’s various sensors. This modular approach facilitates the use of these small components to develop a higher level task. In the instance of ‘Qualitative spatial representations’ we need to access the raw RGB image from the camera to detect features or objects and further extract their approximated pose in order to build a qualitative relation with respect to the robot. The nature of this relation depends upon the type of qualitative calculi that is being implemented in order to define these abstractions.

As the objective of this project is to show an generalized and efficient utilization of the existing qualitative calculi, we do not develop any of these calculi from scratch, instead deciding to exploit an existing qualitative spatial representations library called ‘QSRLib’ [23], this library contains ROS compatible python implementations of the various qualitative calculi, as discussed in the previous chapter.

Although this library can be used either as a standalone python package or a ROS catkin package, we use it primarily with ROS and hence shall focus on it's installation and integration with the same. The 'qsr_lib' package is the one that is being used in our implementation and has system dependencies on 'numpy' and 'matplotlib'. Installing the library is extremely easy as it involves directly cloning the repository(https://github.com/strands-project/strands_qsr_lib.git) from git, and moving the 'qsr_lib' package into the 'src' folder of our catkin workspace [1].

[1], [23]The pre-requisites for using any of the qualitative calculi implemented in the library is input data such as distinctive object id's or names for the various objects amongst which a qualitative relation is desired, a time-series of the states of the perceived objects and the Cartesian coordinates for each of the objects at every instance of the time series. This information is packaged into a custom input data object that is the default input data format of the library. Additional information such as the size of the object may also be included in the input data object, but it is mandatory to include the name of the qualitative calculi for which the qualitative spatial relations are to be computed. This input data structure is sent to a QSRLib service in the form of a request message, the server then computes the relationships and send the output in the form of a response message(client-service architecture in ROS) that details the qualitative relations between the objects constrained by their respective time stamps. The library comes built with the necessary functions that can be used to convert raw data into the data structure format required by the library. The output of the QSRLib can then be further inspected and employed to make decisions regarding the movement or path of the applied mobile platform.




Figure 4.3: A flow chart detailing the inner workings of the QSRLib library [1], [23].

Results and Validation

5.1 Use case 1

Describe results and analyse them

5.2 Use case 2

5.3 Use case 3

5.4 Experimental Setup

5.5 Experimental Evaluation

5.6 Result

6

Conclusions

6.1 Contributions

6.2 Lessons learned

6.3 Future work

A

Design Details

Your first appendix

B

Parameters

Your second chapter appendix

References

- [1] QSRLib online documentation documentation page. URL <https://qsrlib.readthedocs.io/en/latest/index.html>.
- [2] YouBot Detailed Specifications 3D model hardware description. URL [http://www.youbot-store.com/wiki/index.php/YouBot Detailed Specifications 3D model](http://www.youbot-store.com/wiki/index.php/YouBot_Detailed_Specifications_3D_model).
- [3] James F Allen. Maintaining knowledge about temporal intervals. In *Readings in qualitative reasoning about physical systems*, pages 361–372. Elsevier, 1990.
- [4] JV Álvarez-Bravo, JC Peris-Broch, JJ Álvarez-Sánchez, and MT Escrig-Monferrer. A guide for blind people using a quantitative+ qualitative spatial representation. In *Proceedings of the first international congress on domotics, robotics and remote-assistance for all*, pages 495–505, 2006.
- [5] Nicola Bellotto et al. Robot control based on qualitative representation of human trajectories. 2012.
- [6] Stan Birchfield. Klt: An implementation of the kanade-lucas-tomasi feature tracker. <http://www.ces.clemson.edu/~stb/klt/>, 2007.
- [7] Juan Chen, Anthony G Cohn, Dayou Liu, Shengsheng Wang, Jihong Ouyang, and Qiangyuan Yu. A survey of qualitative spatial representations. *The Knowledge Engineering Review*, 30(1):106–136, 2015.
- [8] Zhichao Chen and Stanley T Birchfield. Qualitative vision-based mobile robot navigation. In *Robotics and Automation, 2006. ICRA 2006. Proceedings 2006 IEEE International Conference on*, pages 2686–2692. IEEE, 2006.
- [9] Zhichao Chen and Stanley T Birchfield. Qualitative vision-based path following. *IEEE Transactions on Robotics*, 25(3):749–754, 2009.

-
- [10] Eliseo Clementini, Paolino Di Felice, and Daniel Hernandez. Qualitative representation of positional information. *Artificial intelligence*, 95(2):317–356, 1997.
 - [11] Anthony G Cohn. Qualitative spatial representation and reasoning techniques. In *Annual Conference on Artificial Intelligence*, pages 1–30. Springer, 1997.
 - [12] Anthony G. Cohn and Shyamanta M. Hazarika. Qualitative spatial representation and reasoning: An overview. *Fundamenta informaticae*, 46(1-2):1–29, 2001.
 - [13] Anthony G Cohn and Jochen Renz. Qualitative spatial representation and reasoning. *Foundations of Artificial Intelligence*, 3:551–596, 2008.
 - [14] Matthias Delafontaine, Anthony G Cohn, and Nico Van de Weghe. Implementing a qualitative calculus to analyse moving point objects. *Expert Systems with Applications*, 38(5):5187–5196, 2011.
 - [15] Christian Dondrup and Marc Hanheide. Qualitative constraints for human-aware robot navigation using velocity costmaps. In *Robot and Human Interactive Communication (RO-MAN), 2016 25th IEEE International Symposium on*, pages 586–592. IEEE, 2016.
 - [16] Christian Dondrup, Nicola Bellotto, Marc Hanheide, Kerstin Eder, and Ute Leonards. A computational model of human-robot spatial interactions based on a qualitative trajectory calculus. *Robotics*, 4(1):63–102, 2015.
 - [17] Frank Dylla and Reinhard Moratz. Empirical complexity issues of practical qualitative spatial reasoning about relative position. In *Workshop on Spatial and Temporal Reasoning at ECAI*, volume 2004, 2004.
 - [18] Frank Dylla and Reinhard Moratz. Exploiting qualitative spatial neighborhoods in the situation calculus. In *International Conference on Spatial Cognition*, pages 304–322. Springer, 2004.
 - [19] Frank Dylla and Jan Oliver Wallgrün. On generalizing orientation information in opra. In *Annual Conference on Artificial Intelligence*, pages 274–288. Springer, 2006.

- [20] Andrew U Frank. Qualitative spatial reasoning about distances and directions in geographic space. *Journal of Visual Languages & Computing*, 3(4):343–371, 1992.
- [21] Christian Freksa. Temporal reasoning based on semi-intervals. *Artificial intelligence*, 54(1):199–227, 1992.
- [22] Christian Freksa and Kai Zimmermann. On the utilization of spatial structures for cognitively plausible and efficient reasoning. In *Systems, Man and Cybernetics, 1992., IEEE International Conference on*, pages 261–266. IEEE, 1992.
- [23] Yiannis Gatsoulis, Muhannad Alomari, Chris Burbridge, Christian Dondrup, Paul Duckworth, Peter Lightbody, Marc Hanheide, Nick Hawes, DC Hogg, AG Cohn, et al. Qsrlib: a software library for online acquisition of qualitative spatial relations from video. 2016.
- [24] Francisco J Glez-Cabrera, Jose Vicente Alvarez-Bravo, and Fernando DiAz. Qrpc: A new qualitative model for representing motion patterns. *Expert systems with applications*, 40(11):4547–4561, 2013.
- [25] Frederik Hegger. 3D People Detection in Domestic Environments. Technical Report March, Department of Computer Science, Bonn-Rhein-Sieg University of Applied Sciences, Sankt Augustin, Germany, 2012. URL https://opus.bib.hochschule-bonn-rhein-sieg.de/files/8/brsu_techreport_02_2012_Fre
- [26] Amar Isli and Anthony G Cohn. A new approach to cyclic ordering of 2d orientations using ternary relation algebras. *Artificial Intelligence*, 122(1-2):137–187, 2000.
- [27] Amar Isli, Volker Haarslev, Ralf Möller, et al. *Combining cardinal direction relations and relative orientation relations in qualitative spatial reasoning*. Univ., Bibliothek des Fachbereichs Informatik, 2001.
- [28] Getmanskiy Andrey Konstantinovich, Dmitrienko Margarita Alexandrovna, and Mavridis Nikolaos. Applying qualitative trajectory calculus to human

- motion fnflysis: a case study towards robot social path planning. —, 12(2), 2016.
- [29] G É LIGOZAT. Reasoning about cardinal directions. *Journal of Visual Languages & Computing*, 9(1):23–44, 1998.
- [30] John Carl Lowe and S Moryadas. *The geography of movement*. Houghton Mifflin Boston, 1975.
- [31] Dominik Lücke, Till Mossakowski, and Reinhard Moratz. Streets to the oporafinding your destination with imprecise knowledge. In *IJCAI-2011 Workshop 27*, page 25. Citeseer, 2011.
- [32] Reinhard Moratz. Representing relative direction as a binary relation of oriented points. In *ECAI*, volume 6, pages 407–411, 2006.
- [33] Alexandra Musto, Klaus Stein, Andreas Eisenkolb, Thomas Röfer, et al. Qualitative and quantitative representations of locomotion and their application in robot navigation. In *IJCAI*, volume 99, pages 1067–1072. Citeseer, 1999.
- [34] Morgan Quigley, Ken Conley, Brian Gerkey, Josh Faust, Tully Foote, Jeremy Leibs, Rob Wheeler, and Andrew Y Ng. Ros: an open-source robot operating system. In *ICRA workshop on open source software*, volume 3, page 5. Kobe, Japan, 2009.
- [35] David A Randell, Zhan Cui, and Anthony G Cohn. A spatial logic based on regions and connection. *KR*, 92:165–176, 1992.
- [36] M. Roscoe, A. Moriarty, S. Alexandrov, P. Ramanujam, N. Giftsun, F. Hegger, N. Hochgeschwender, J. Paulus, and G. K. Kraetzschmar. The b-it-bots robocup@work 2012 team description paper. In *IROS Competition RoboCup@Work*, Vilamoura, Portugal, 2012. URL <http://mas-group.inf.h-brs.de/wp-content/uploads/2013/07/atworktdpiros2012.pdf>
- [37] Nikitas M Sgouros. Qualitative navigation for autonomous wheelchair robots in indoor environments. *Autonomous Robots*, 12(3):257–266, 2002.

- [38] Danelle C Shah and Mark E Campbell. A robust qualitative planner for mobile robot navigation using human-provided maps. In *Robotics and Automation (ICRA), 2011 IEEE International Conference on*, pages 2580–2585. IEEE, 2011.
- [39] Danelle C Shah and Mark E Campbell. A qualitative path planner for robot navigation using human-provided maps. *The International Journal of Robotics Research*, 32(13):1517–1535, 2013.
- [40] Daniel Maximilian Swoboda. A comprehensive characterization of the asus xtion pro depth sensor. 2014.
- [41] Nico Van de Weghe. *Representing and reasoning about moving objects: A qualitative approach*. PhD thesis, Ghent University, 2004.
- [42] Nico Van de Weghe, Anthony G Cohn, Philippe De Maeyer, and Frank Witlox. Representing moving objects in computer-based expert systems: the overtake event example. *Expert Systems with Applications*, 29(4):977–983, 2005.
- [43] Nico Van de Weghe, Bart Kuijpers, Peter Bogaert, and Philippe De Maeyer. A qualitative trajectory calculus and the composition of its relations. In *International Conference on GeoSpatial Semantics*, pages 60–76. Springer, 2005.
- [44] Nico Van de Weghe, Anthony Cohn, Guy De Tre, and Philippe De Maeyer. A qualitative trajectory calculus as a basis for representing moving objects in geographical information systems. *Control and Cybernetics*, 35(1):97–119, 2006.
- [45] Lv Yan, Peng Wang, and Zonghai Chen. Qualitative representation and reasoning in cognitive maps : A survey from spatial cognition perspective. 2012.
- [46] Kai Zimmermann and Christian Freksa. Qualitative spatial reasoning using orientation, distance, and path knowledge. *Applied intelligence*, 6(1):49–58, 1996.