## THE CHINESE WALL SECURITY POLICY

Dr. David F.C. Brewer and Dr. Michael J. Nash, 1989

November 06, 2015

Mikael Elkiær Christensen michrill@student.aau.dk

Department of Computer Science
Alborg University
Denmark





# Who is the enemy?

## CHINESE WALL

Mikael Elkiær Christensen

### Introduction

Bell-LaPadula

Department of Computer Science Aalborg University Denmark



# Who is the enemy?

## CHINESE WALL

Mikael Elkiær Christensen

## Introduction

Bell-LaPadula





# Who is the enemy?

### CHINESE WALL

Mikael Elkiær Christensen

#### Introduction

Bell-LaPadula







# Background

#### CHINESE WALL

Mikael Elkiær Christensen

#### Introduction

Bell-LaPadula

- ► Coined in 1929 following the Wall Street crash
- Chinese Wall policies are already in use
  - Not necessarily digital
  - Can have authority of law
- ▶ Other terms, as some find the original offensive
  - ► "Screen", "firewall", "cone of silence", and "ethical wall"

#### CHINESE WALL

Mikael Elkiær Christensen

#### Introduction

Bell-LaPadula

- ▶ Before 1989, most security policies were military
  - ► E.g. Bell-LaPadula (more about this later)
- Need of something that holds up in court
- ▶ Relevant anywhere conflicts of interest can exist



## Bell-LaPadula

#### CHINESE WALL

Mikael Elkiær Christensen

Introductio

Bell-LaPadula

- ► Proposed by Bell and LaPadula in 1973
- ► Security policy model
- ► Designed for military use

# Terminology

## CHINESE WALL

Mikael Elkiær Christensen

ntroductio

Bell-LaPadula

Object Data or program.

Classification Minimum security level.

Category Security group(s).

Subject Person or program.

Clearance Maximum security level. Need-to-know Security group(s).

Department of Computer Science Aalborg University Depmark

#### CHINESE WALL

Mikael Elkiær Christensen

ntroductio

Bell-LaPadula

Simple security: access is granted only if the subject's clearance is *greater* than the object's classification and the subject's need-to-know *includes* the object's category(ies)

\*-property: write access is granted only if the output object's classification is *greater* than the classification of all input objects, and its category *includes* the category(ies) of all input objects.




## CHINESE WALL

Mikael Elkiær Christensen

ntroduction

Bell-LaPadula






# Example (2)

#### CHINESE WALL

Mikael Elkiær Christensen

ntroductio

Bell-LaPadula



Department of Computer Science Aalborg University

# Questions?

