

A Decentralized Model for Information Flow Control

Andrew C. Myers and Barbara Liskov, 1997

September 23, 2015

Mikael Elkiær Christensen
michri11@student.aau.dk

Department of Computer Science
Aalborg University
Denmark



AALBORG UNIVERSITY
DENMARK



Introduction

Decentralized Label Model

Mikael Elkjær
Christensen

1

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

The result of this paper is a model for controlling information flow: **Decentralized Label Model (DLM)**.

13



Introduction

What it is not

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

2

It is not:



Introduction

What it is not

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

2

It is not:

► Access Control

13



Introduction

What it is not

Decentralized Label
Model

Mikael Elkjaer
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

2

It is not:

- ▶ Access Control
- ▶ Authentication, Authorization, Confidentiality, Integrity.



Introduction

What it is not

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

2

It is not:

- ▶ Access Control
- ▶ Authentication, Authorization, Confidentiality, Integrity.

This means that DLM will **not** ensure:

13



Introduction

What it is not

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

2

It is not:

- ▶ Access Control
- ▶ Authentication, Authorization, Confidentiality, Integrity.

This means that DLM will **not** ensure:

- ▶ secure communication between applications

13



Introduction

What it is not

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

2

It is not:

- ▶ Access Control
- ▶ Authentication, Authorization, Confidentiality, Integrity.

This means that DLM will **not** ensure:

- ▶ secure communication between applications
- ▶ limited access to data once released



Introduction

What it is

Decentralized Label Model

Mikael Elkizer
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

3

It is:

13



Introduction

What it is

Decentralized Label Model

Mikael Elkjær
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

3

It is:

► Information Flow Control

13



Introduction

What it is

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

3

It is:

- ▶ Information Flow Control
- ▶ Decentralized

13



Introduction

What it is

Decentralized Label Model

Mikael Elkizer
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

3

It is:

- ▶ Information Flow Control
- ▶ Decentralized

This means that DLM will help ensuring:

13



Introduction

What it is

Decentralized Label Model

Mikael Elkizer
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

3

It is:

- ▶ Information Flow Control
- ▶ Decentralized

This means that DLM will help ensuring:

- ▶ not releasing sensitive data

13



Introduction

What it is

Decentralized Label Model

Mikael Elkjær
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

3

It is:

- ▶ Information Flow Control
- ▶ Decentralized

This means that DLM will help ensuring:

- ▶ not releasing sensitive data
- ▶ not implicitly releasing sensitive data

13



Introduction

What it is

Decentralized Label Model

Mikael Elkjær
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

3

It is:

- ▶ Information Flow Control
- ▶ Decentralized

This means that DLM will help ensuring:

- ▶ not releasing sensitive data
- ▶ not implicitly releasing sensitive data
- ▶ not giving away hints of inner workings

13



Introduction

How it differs

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not

What it is

How it differs

4

DLM differs from previous solutions as it is:

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works



Introduction

How it differs

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

4

DLM differs from previous solutions as it is:

► decentralized

13



Introduction

How it differs

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

4

DLM differs from previous solutions as it is:

- ▶ decentralized
- ▶ less restrictive of allowed computations

13



Introduction

How it differs

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

4

DLM differs from previous solutions as it is:

- ▶ decentralized
- ▶ less restrictive of allowed computations
- ▶ not completely disallowing inter-application communication

13



Introduction

How it differs

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not

What it is

How it differs

DLM Basics

Terminology

Labels

Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

4

DLM differs from previous solutions as it is:

- ▶ decentralized
- ▶ less restrictive of allowed computations
- ▶ not completely disallowing inter-application communication
- ▶ meant to extend current programming languages with data flow annotations

13



DLM Basics

Decentralized Label Model

Mikael Elkizer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

5

DLM provides both static and dynamic checking of data flow.

13



DLM Basics

Terminology

Decentralized Label Model

Mikael Elkjær
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

Principals represent users and other authoritative entities (e.g. groups or roles).

6

13



DLM Basics

Terminology

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

Principals represent users and other authoritative entities (e.g. groups or roles).

Values are entities computations can manipulate.

6



DLM Basics

Terminology

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

6

Principals represent users and other authoritative entities (e.g. groups or roles).

Values are entities computations can manipulate.

Slots are value-holders (e.g. variables, objects, and other storage locations).



DLM Basics

Terminology

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

6

Principals represent users and other authoritative entities (e.g. groups or roles).

Values are entities computations can manipulate.

Slots are value-holders (e.g. variables, objects, and other storage locations).

Input channels are read-only sources that allow information to enter the system.

13



DLM Basics

Terminology

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

6

Principals represent users and other authoritative entities (e.g. groups or roles).

Values are entities computations can manipulate.

Slots are value-holders (e.g. variables, objects, and other storage locations).

Input channels are read-only sources that allow information to enter the system.

Output channels are information sinks that transmit information outside the system.

13

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

6

Principals represent users and other authoritative entities (e.g. groups or roles).

Values are entities computations can manipulate.

Slots are value-holders (e.g. variables, objects, and other storage locations).

Input channels are read-only sources that allow information to enter the system.

Output channels are information sinks that transmit information outside the system.

Labels are attached to values, slots or channels (more to follow).

13



DLM Basics

Labels

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

7

A label **L** is a set of owners, where each owner denotes its readers, e.g.:

$$\{o_1 : r_1, r_2; o_2 : r_2, r_3\}$$

where o_1, o_2, r_1, r_2, r_3 are principals.

13



DLM Basics

Labels

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

7

A label \mathbf{L} is a set of owners, where each owner denotes its readers, e.g.:

$$\{o_1 : r_1, r_2; o_2 : r_2, r_3\}$$

where o_1, o_2, r_1, r_2, r_3 are principals.

The effective reader set of a label is the intersection of every reader, for \mathbf{L} it is $\{r_2\}$.

13



DLM Basics

Key Principles

Decentralized Label Model

Mikael Elkiær
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

- ▶ Labels are comparable:
 - ▶ $L_1 \subseteq L_2$ signifies that L_2 is at least as restrictive as L_1 .

8

13



DLM Basics

Key Principles

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

8

- ▶ Labels are comparable:
 - ▶ $L_1 \sqsubseteq L_2$ signifies that L_2 is at least as restrictive as L_1 .
- ▶ Labels can be joined:
 - ▶ $L_1 \sqcup L_2$ results in a join of owners and intersection of readers.

13



DLM Basics

Key Principles

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

8

- ▶ Labels are comparable:
 - ▶ $L_1 \sqsubseteq L_2$ signifies that L_2 is at least as restrictive as L_1 .
- ▶ Labels can be joined:
 - ▶ $L_1 \sqcup L_2$ results in a join of owners and intersection of readers.
- ▶ Principals can act for other principals.

13



DLM Basics

Key Principles

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

8

- ▶ Labels are comparable:
 - ▶ $L_1 \sqsubseteq L_2$ signifies that L_2 is at least as restrictive as L_1 .
- ▶ Labels can be joined:
 - ▶ $L_1 \sqcup L_2$ results in a join of owners and intersection of readers.
- ▶ Principals can act for other principals.
- ▶ Relabeling can be done, further restricting or declassifying.

13

Example

Decentralized Label Model

Mikael Elkizer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

9




Figure 1: Medical Study Scenario

13

Example

Code Example

Decentralized Label Model

Mikael Elkizer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

10

```
pinfo = record [ names, passwords: string{chkr: chkr} ]
```

```
check_password (db: array[pinfo{⊥}]{⊥},
               user: string {⊥},
               password: string{client: chkr})
returns (ret: bool{client: chkr})
% Return whether password is the password of user
```

```
i: int {chkr: chkr} := 0           % ⊥
match: bool {client: chkr;       %
               chkr: chkr} := false % ⊥
while i < db.length() do         % ⊥
  if db[i].names = user &        % ⊥
    db[i].passwords = password then %
    match := true                % {client: chkr;
  end                             % chkr: chkr}
  i := i + 1                      % ⊥
end
ret := false                      % ⊥
if acts_for(check_password, chkr) then % ⊥
  ret := declassify(match, {client: chkr}) % ⊥
end
end check_password
```

Figure 6: Annotated password checker

13



Advanced

Decentralized Label Model

Mikael Elkjær
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

- ▶ Label polymorphism
- ▶ Run-time labels (`lb` type)
- ▶ Protected types (`protected[T]`)
- ▶ Inferred labels

11

13



Conclusion

Decentralized Label Model

Mikael Elkjær
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

► Decentralized Label Model

12

13



Conclusion

Decentralized Label Model

Mikael Elkjær
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

12

- ▶ Decentralized Label Model
- ▶ Control of information flow

13



Conclusion

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

- ▶ Decentralized Label Model
- ▶ Control of information flow
- ▶ Static and dynamic label checking

12

13



Conclusion

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

- ▶ Decentralized Label Model
- ▶ Control of information flow
- ▶ Static and dynamic label checking
- ▶ Possible to extend existing programming languages

12

13



Conclusion

Future Works

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

► Actual implementation (JIF – dead)

13

13



Conclusion

Future Works

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

13

- ▶ Actual implementation (JIF – dead)
- ▶ Support for user-defined data abstractions

13



Conclusion

Future Works

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

- ▶ Actual implementation (JIF – dead)
- ▶ Support for user-defined data abstractions
- ▶ Formal proofs

13

13



Conclusion

Future Works

Decentralized Label Model

Mikael Elkizer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

- ▶ Actual implementation (JIF – dead)
- ▶ Support for user-defined data abstractions
- ▶ Formal proofs
- ▶ Network systems

13

13



Conclusion

Future Works

Decentralized Label Model

Mikael Elkjaer
Christensen

Introduction

What it is not
What it is
How it differs

DLM Basics

Terminology
Labels
Key Principles

Example

Code Example

Advanced

Conclusion

Future Works

- ▶ Actual implementation (JIF – dead)
- ▶ Support for user-defined data abstractions
- ▶ Formal proofs
- ▶ Network systems
- ▶ Threading

13

13

Questions?



AALBORG UNIVERSITY
DENMARK