

Contents

1 Data Structures	2	6.5 Diophantine	11
1.1 Sparse Table	2	6.6 Chinese Remainder Theorem	11
1.2 Fenwick Tree	2	6.7 Rabin-Miller primality test	12
1.3 Segment Tree	2	6.8 Pollard's Rho prime factorization	12
1.4 Sigma Tree	2	6.9 Multiplicative Function (Sieve)	13
1.5 Persistent Segment Tree	2	6.10 Multiplicative Function	13
1.6 Hash Map	3	6.11 Discrete Logarithm	14
2 String	3	7 Geometry	14
2.1 Trie 1	3	7.1 Dot Product	14
2.2 Trie 2	3	7.2 Angle	14
2.3 Hash	4	7.3 Cross Product	14
2.4 KMP	4	7.4 Distance from a Point to a line	14
2.5 Manacher	4	7.5 Template 1	15
2.6 Aho - Corasick	4	7.6 Intersection of 2 lines and bla bla bla (I have no time bro)	15
2.7 Aho - Corasick (BFS)	4	7.7 Circle passing through 3 points	15
3 Sqrt Decomposition	5	7.8 Symmetry	15
3.1 MO	5	7.9 Rotation	16
4 Graph	5	7.10 Area of a Polygon	16
4.1 Joint and Bridge	5	7.11 Relative position of a point to a poly- gon $O(N)$	16
4.2 SCC	5	7.12 Relative position of a point to a poly- gon $O(\log N)$	16
4.3 Topology Sort 1	5	7.13 Pick Theorem	16
4.4 Topology Sort 2	5	7.14 Convex Hull (Graham scan)	17
4.5 Max Flow	5	7.15 Convex Hull (Monotone chain algorithm)	17
4.6 Bipartite Matching	6	7.16 More	17
4.7 Matching 2	6	8 Algebra	17
4.8 HLD	6	8.1 Matrix Multiplication	17
4.9 DSU on tree	7	8.2 Fast Fourier Transform	18
4.10 Centroid Decomposition	7	8.3 Number Theory Transform	18
4.11 Centroid Tree (CT)	7	9 Combinatoric	19
4.12 Virtual Tree	8	9.1 Formula	19
5 DP	8	9.2 Catalan	19
5.1 Digit DP	8	9.3 Derangement	19
5.2 SOS DP	9	9.4 Classical Sums	19
5.3 DP DNC	9	9.5 Useful Identities	19
5.4 Convex Hull Trick	9	9.6 Stirling Numbers	19
5.5 1D1D Optimization	9	10 Others	20
5.6 Knapsack on Tree	10	10.1 Test?	20
5.7 DP on Broken Profile	10	10.2 Big Int	20
6 Number Theory	10	10.3 CODE::BLOCK Set Up	21
6.1 Euler's totient function	10	10.4 Template	21
6.2 Euler's totient function from 1 to N	11	10.5 CODE::BLOCK shortcuts	21
6.3 Modular Inverse	11	10.6 Multiplication Function	22
6.4 Extended Euclidean Algorithm	11	10.7 Random Function	22

Data Structures

Sparse Table

```
int a[N], st[LG + 1][N];
void preprocess() {
    for (int i = 1; i <= n; ++i) st[0][i] = a[i];
    for (int j = 1; j <= LG; ++j)
        for (int i = 1; i + (1 << j) - 1 <= n; ++i)
            st[j][i] = min(st[j - 1][i], st[j - 1][i +
                (1 << (j - 1))]);
}

int query(int l, int r) {
    int k = __lg(r - l + 1);
    return min(st[k][l], st[k][r - (1 << k) + 1]);
}

//query sum:
int querySum(int l, int r) {
    int len = r - l + 1;
    int sum = 0;
    for (int j = 0; (1 << j) <= len; ++j)
        if (len >> j & 1) {
            sum = sum + st[j][l];
            l = l + (1 << j);
        }
    return sum;
}
```

```
void update(int id, int l, int r, int u, int v, int
    x){
    if (r < u || v < l) return;
    if (u <= l && r <= v){
        apply(id, x);
        return;
    }

    down(id, l, r);

    int mid = (l + r) >> 1;
    update(id << 1, l, mid, u, v, x);
    update(id << 1 | 1, mid + 1, r, u, v, x);

    st[id] = merge(st[id << 1], st[id << 1 | 1]);
}

int get(int id, int l, int r, int u, int v){
    if (r < u || v < l) return -INF;
    if (u <= l && r <= v) return st[id];

    down(id, l, r);

    int mid = (l + r) >> 1;
    return merge(get(id << 1, l, mid, u, v), get(id
        << 1 | 1, mid + 1, r, u, v));
}
} ST;
```

Fenwick Tree

```
void update(int i, int val){
    for (; i <= n; i += i & -i) bit[i] += val;
}

int get(int i){
    int res = 0;
    for (; i; i -= i & -i) res += bit[i];
    return res;
}
```

Sigma Tree

```
struct Sigma_Tree{
    int st[2 * N];

    void init(){
        For(i, 1, n) st[i + n - 1] = a[i];
        ForD(i, n - 1, 1) st[i] = merge(st[i << 1],
            st[i << 1 | 1]);
    }

    void update(int p, int val){
        p += n - 1;
        st[p] = val;
        for (; p > 1; p >>= 1) st[p >> 1] = merge(st[p],
            st[p ^ 1]);
    }

    int get(int l, int r){
        int res = 0;
        for (l += n - 1, r += n - 1; l <= r; l >>= 1,
            r >>= 1){
            if (l & 1) res = merge(res, st[l++]);
            if (!(r & 1)) res = merge(res, st[r--]);
        }
        return res;
    }
} ST;
```

Segment Tree

```
struct Segment_tree{
    int st[4 * N], lazy[4 * N];

    void apply(int id, int c){
        update(st[id], c);
        update(lazy[id], c);
    }

    void down(int id, int l, int r){
        int c = lazy[id]; lazy[id] = 0;
        apply(id << 1, c); apply (id << 1 | 1, c);
    }

    void build(int id, int l, int r){
        if (l == r){
            st[id] = a[l];
            return;
        }

        int mid = (l + r) >> 1;
        build(id << 1, l, mid);
        build(id << 1 | 1, mid + 1, r);

        st[id] = merge(st[id << 1], st[id << 1 | 1]);
    }
}
```

Persistent Segment Tree

```
struct Node {
    int left, right; // ID of left child & right
        child
    long long ln; // Max value of node
    Node() {}
    Node(long long ln, int left, int right) : ln(ln),
        left(left), right(right) {}
}
```

```

} it[N]; // Each node has a position in this array,
        called ID
int nNode;

int ver[N]; // ID of root in each version

// Update max value of a node
inline void refine(int cur) {
    it[cur].ln = max(it[it[cur].left].ln, it[it[cur].right].ln);
}

// Update a range, and return new ID of node
int update(int l, int r, int u, int x, int oldId) {
    if (l == r) {
        ++nNode;
        it[nNode] = Node(x, 0, 0);
        return nNode;
    }

    int mid = (l + r) >> 1;
    int cur = ++nNode;

    if (u <= mid) {
        it[cur].left = update(l, mid, u, x, it[oldId].left);
        it[cur].right = it[oldId].right;
        refine(cur);
    }
    else {
        it[cur].left = it[oldId].left;
        it[cur].right = update(mid+1, r, u, x, it[oldId].right);
        refine(cur);
    }

    return cur;
}

// Get max of range. Same as usual IT
int get(int nodeId, int l, int r, int u, int v) {
    if (v < l || r < u) return -1;
    if (u <= l && r <= v) return it[nodeId].ln;

    int mid = (l + r) >> 1;
    return max(get(it[nodeId].left, l, mid, u, v),
               get(it[nodeId].right, mid+1, r, u, v));
}

// When update:
++nVer;
ver[nVer] = update(1, n, u, x, ver[nVer-1]);

// When query:
res = get(ver[t], 1, n, u, v);

```

Hash Map

```

//faster than unordered_map
struct hash_map {
    const static int SZ = 2e4 + 9;
    int nxt[SZ >> 3], val[SZ >> 3];
    int key[SZ >> 3];
    int h[SZ + 5], cnt;
    vector<int>vec;

    void clear(){
        for (int i : vec) h[i] = 0;
    }

```

```

        for (int i = 1; i <= cnt; i++)
            val[i] = nxt[i] = 0, key[i] = 0;

        vec.clear();
        cnt = 0;
    }

    int hash(int u) {
        return u % SZ;
    }

    int &operator[](int u) {
        int x = hash(u);

        for (int i = h[x]; i; i = nxt[i])
            if (key[i] == u) return val[i];

        if (!h[x]) vec.push_back(x);

        ++cnt;
        key[cnt] = u;
        val[cnt] = 0;
        nxt[cnt] = h[x];
        h[x] = cnt;
        return val[cnt];
    }

    int qry(int u) {
        int x = hash(u);
        for (int i = h[x]; i; i = nxt[i])
            if (key[i] == u) return val[i];

        return 0;
    }
} hs;

```

String

Trie 1

```

struct node{
    node *g[26];
    node(){
        rep(i, 26) g[i] = NULL;
    }
} *root = new node();

void Insert(string s){
    node *p = root;
    for (char t: s){
        if (p->g[t - 'a'] == NULL)
            p->g[t - 'a'] = new node();

        p = p->g[t - 'a'];
    }
}

```

Trie 2

```

int nNode = 0;
int g[N][26];

void Insert(string s){
    int p = 0;
    for (char t: s){
        if (!g[p][t - 'a']) g[p][t - 'a'] = ++nNode;
        p = g[p][t - 'a'];
    }
}

```

Hash

```

11 getHashT(int i, int j) {
    return (hashT[j] - mul(hashT[i - 1], POW[j - i +
        1]) + MOD) % MOD;
}

// Precalculate base^i
for (int i = 1; i <= lenT; i++)
    POW[i] = (POW[i - 1] * base) % MOD;

// Calculate hash value of T[1..i]
for (int i = 1; i <= lenT; i++)
    hashT[i] = (hashT[i - 1] * base + (T[i] - 'a' +
        1)) % MOD;

```

KMP

```

//prefix function: length of the longest prefix of
the substring s[1..i] that is also a suffix of
this same substring
int k = 0;
For(i, 2, n){ //1-indexed
    while (k && s[k + 1] != s[i]) k = kmp[k];
    kmp[i] = (s[k + 1] == s[i]) ? ++k : 0;
}

```

Manacher

```

vector<int> manacher_odd(string s) {
    int n = s.size();
    s = "$" + s + "^";
    vector<int> p(n + 2);
    int l = 0, r = 1;
    for(int i = 1; i <= n; i++) {
        p[i] = min(r - i, p[l + (r - i)]);
        while(s[i - p[i]] == s[i + p[i]]) {
            p[i]++;
        }
        if(i + p[i] > r) {
            l = i - p[i], r = i + p[i];
        }
    }
    return vector<int>(begin(p) + 1, end(p) - 1);
}

vector<int> manacher(string s) {
    string t;
    for(auto c: s) {
        t += string("#") + c;
    }
    auto res = manacher_odd(t + "#");
    return vector<int>(begin(res) + 1, end(res) - 1);
}

```

Aho - Corasick

```

namespace Trie{
    struct Node{
        int child[26], p = -1, cnt = 0;
        char pch;
        int link = -1, go[26];
        Node(int p = -1, char ch = '#'): p(p), pch(ch){
            fill(begin(child), end(child), -1);
            fill(begin(go), end(go), -1);
        }
    };
};

```

```
vector<Node> g(1);
```

```

void add(string s){
    int v = 0;
    for (char t: s){
        int c = t - 'a';
        if (g[v].child[c] == -1){
            g[v].child[c] = g.size();
            g.emplace_back(v, t);
        }
        v = g[v].child[c];
    }
    g[v].cnt++;
}

```

```
int go(int v, char c);
```

```

int get_link(int v){
    if (g[v].link == -1){
        if (!v || !g[v].p) g[v].link = 0;
        else g[v].link = go(get_link(g[v].p), g[v].pch);
    }
    return g[v].link;
}

```

```

int go(int v, char t){
    int c = t - 'a';
    if (g[v].go[c] == -1){
        if (g[v].child[c] != -1) g[v].go[c] = g[v].
            child[c];
        else g[v].go[c] = (v == 0) ? 0 : go(get_link(v),
            t);
    }
    return g[v].go[c];
}
}

```

Aho - Corasick (BFS)

```

struct trie{
    struct Node{
        Node *child[26], *link;
        int cnt = 0;
        Node(){
            cnt = 0;
            rep(i, 26) child[i] = NULL;
            link = NULL;
        }
    } *root = new Node();

    void add(string &s){
        Node* p = root;
        for (char &t: s){
            int c = t - 'a';
            if (p->child[c] == NULL) p->child[c] = new Node();
            p = p->child[c];
        }
        p->cnt++;
    }

    void AhoCorasick(){
        root->link = root;
        queue<Node*> q; q.push(root);
        while (!q.empty()){
            Node* p = q.front(); q.pop();
            rep(i, 26) if (p->child[i]){

```

```

Node* k = p->link;
while (k != root && k->child[i] == NULL) k =
    k->link;

if (k->child[i] && k != p) p->child[i]->link
    = k->child[i];
else p->child[i]->link = root;

p->child[i]->cnt += p->child[i]->link->cnt;
q.push(p->child[i]);
    }
}
};

```

SQRT Decomposition

MO

```

struct query{
    int l, r, id;
}

bool cmp(const query &a, const query &b){
    if(a.l / S != b.l / S) return a.l < b.l;

    if((a.l / S) & 1)
        return a.r < b.r;
    else
        return a.r > b.r
}

long long res = 0;

void update(...);

////////////////////////////////////
sort(q + 1, q + Q + 1, cmp);

int l = 1, r = 0;
for(int i = 1; i <= Q; i++){
    while(l < q[i].l) update(a[l++], ...);
    while(l > q[i].l) update(a[--l], ...);
    while(r < q[i].r) update(a[++r], ...);
    while(r > q[i].r) update(a[r--], ...);
    ans[q[i].id] = res;
}

```

Graph

Joint and Bridge

```

void dfs(int u, int pre) {
    int child = 0;
    num[u] = low[u] = ++timer;
    for (int v: g[u]) {
        if (v == pre) continue;
        if (!num[v]) {
            dfs(v, u);
            low[u] = min(low[u], low[v]);
            if (low[v] == num[v]) bridge++;
            child++;
            if (u == pre){
                if (child > 1) joint[u] = true;
            }
            else if (low[v] >= num[u]) joint[u] = true;
        }
        else low[u] = min(low[u], num[v]);
    }
}

```

```

}
}

```

SCC

```

void dfs(int u) {
    num[u] = low[u] = ++timer;
    st.push(u);
    for (int v : g[u]) {
        if (!num[v]){
            dfs(v);
            low[u] = min(low[u], low[v]);
        }
        else low[u] = min(low[u], num[v]);
    }
    if (low[u] == num[u]) {
        scc++;
        int v;
        do {
            v = st.top();
            st.pop();
            num[v] = INF;
        }
        while (v != u);
    }
}

```

Topology Sort 1

```

//u -> v
//++deg[v]
for (int u = 1; u <= n; ++u)
    if (!deg[u]) q.push(u);

while (!q.empty()) {
    int u = q.front();
    q.pop();
    topo.push_back(u);
    for (auto v : g[u]) {
        deg[v]--;
        if (!deg[v]) q.push(v);
    }
}

```

Topology Sort 2

```

void dfs(int u) {
    visit[u] = 1;
    for (auto v : g[u]) {
        assert(visit[v] != 1);
        //graph contains a cycle
        if (!visit[v]) dfs(v);
    }
    topo.push(u);
    visit[u] = 2;
}

```

Max Flow

```

struct edge{
    int to, rev, flow, cap;
};

void add_edge(int u, int v, int cap){
    edge e1 = {v, sz(g[v]), 0, cap};
    edge e2 = {u, sz(g[u]), 0, 0};
    g[u].pb(e1); g[v].pb(e2);
}

```

```

bool bfs(){
    memset(dist, 0x3f, sizeof dist);
    queue<int> q;
    q.push(source); dist[source] = 0;
    while (!q.empty()){
        int u = q.front(); q.pop();
        for (edge e: g[u]){
            int v = e.to, flow = e.flow, cap = e.cap;
            if (flow < cap && minimize(dist[v], dist[u] +
                1))
                q.push(v);
        }
    }
    return dist[sink] < INF;
}

int dfs(int u, int mn){
    if (u == sink) return mn;
    for (int &i = lazy[u]; i < sz(g[u]); ++i){
        auto &[v, rev, flow, cap] = g[u][i];
        if (dist[v] == dist[u] + 1 && flow < cap){
            int cur = dfs(v, min(mn, cap - flow));
            if (cur > 0){
                flow += cur;
                g[v][rev].flow -= cur;
                return cur;
            }
        }
    }
    return 0;
}

int main(){
    //...
    int res = 0;
    while (bfs()){
        memset(lazy, 0, sizeof lazy);
        while (int del = dfs(source, INF))
            res += del;
    }

    cout << res;
    return 0;
}

```

Bipartite Matching

```

bool dfs(int u){
    if (seen[u]) return 0;
    seen[u] = 1;

    for (int v: g[u])
        if (!mt[v] || dfs(mt[v]))
            return mt[v] = u, 1;

    return 0;
}

//memset(mt, 0, sizeof mt);
//For(i, 1, n){
//    //memset(seen, 0, sizeof seen);
//    //dfs(i);
//}

```

Matching 2

```

bool bfs(){
    bool res = 0;
    queue<int> q;
    For(i, 1, n){
        if (!mx[i]){
            q.push(i), dist[i] = 0;
        }
        else{
            dist[i] = -1;
        }
    }

    while (!q.empty()){
        int u = q.front(); q.pop();
        for (int v: g[u]){
            if (!my[v]) res = 1;
            else if (dist[my[v]] < 0){
                dist[my[v]] = dist[u] + 1;
                q.push(my[v]);
            }
        }
    }

    return res;
}

bool dfs(int u){
    for (int v: g[u]){
        if (!my[v]){
            mx[u] = v; my[v] = u;
            return 1;
        }
        else if (dist[my[v]] == dist[u] + 1 && dfs(my[v])){
            mx[u] = v; my[v] = u;
            return 1;
        }
    }
    return 0;
}

////////////////////////////////////
while (bfs()){
    For(i, 1, n) if (!mx[i]){
        dfs(i);
    }
}

```

HLD

```

void dfs(int u){
    sz[u] = 1;
    for (int v: g[u]) if (v != par[u]){
        par[v] = u;
        dfs(v);
        sz[u] += sz[v];
    }
}

void hld(int u){
    if (!Head[nChain]) Head[nChain] = u;
    idChain[u] = nChain;

    pos[u] = ++timer;
    node[timer] = u;

    int bigC = 0;
    for (int v: g[u]) if (v != par[u])
        if (!bigC || sz[v] > sz[bigC])

```

```

        bigC = v;

    if (bigC) hld(bigC);
    for (int v: g[u]) if (v != par[u] && v != bigC){
        ++nChain;
        hld(v);
    }
}

//LCA
int LCA(int u, int v){
    while (idChain[u] != idChain[v]){
        if (idChain[u] > idChain[v])
            u = par[Head[idChain[u]]];
        else
            v = par[Head[idChain[v]]];
    }

    if (h[u] < h[v]) return u;
    return v;
}

int get(int u, int v){
    int res = 0;
    while (idChain[u] != idChain[v]){
        if (idChain[u] > idChain[v]){
            maximize(res, ST.get(pos[Head[idChain[u]]],
                                pos[u]));
            u = par[Head[idChain[u]]];
        }
        else{
            maximize(res, ST.get(pos[Head[idChain[v]]],
                                pos[v]));
            v = par[Head[idChain[v]]];
        }
    }

    if (pos[u] < pos[v])
        maximize(res, ST.get(pos[u], pos[v]));
    else
        maximize(res, ST.get(pos[v], pos[u]));

    return res;
}

```

DSU on tree

```

void dfs(int u, int prev = -1){
    in[u] = ++timer; node[timer] = u;
    for (int v: g[u]) if (v != prev)
        dfs(v, u);
    out[u] = timer;
}

#define sz(u) out[u] - in[u]

void calc(int u, int prev = -1){
    int bigC = 0;
    for (int v: g[u]) if (v != prev)
        if (sz(v) > sz(bigC))
            bigC = v;

    for (int v: g[u]) if (v != prev && v != bigC){
        calc(v, u);
        //reset(v)...
    }

    if (bigC) calc(bigC, u);
}

```

```

for (int v: g[u]) if (v != prev && v != bigC){
    For(t, in[v], out[v]){
        int x = node[t];
        //...
    }
}
}

```

Centroid Decomposition

```

int size(int u, int prev){
    sz[u] = 1;
    for (int v: g[u]) if (!del[v] && v != prev)
        sz[u] += size(v, u);
    return sz[u];
}

int centroid(int u, int prev){
    for (int v: g[u]) if (!del[v] && v != prev)
        if (sz[v] > n/2)
            return centroid(v, u);
    return u;
}

void dfs(int u, int prev){
    in[u] = ++timer; node[timer] = u;
    for (int v: g[u]) if (!del[v] && v != prev){
        dfs(v, u);
        //...
    }
    out[u] = timer;
}

void calc(int u){
    n = size(u, 0);
    u = centroid(u, 0);

    timer = 0;
    dfs(u, 0);

    for (int v: g[u]) if (!del[v]){
        //subtree v...
    }
    //reset
    del[u] = 1;
    for (auto [v, c]: g[u]) if (!del[v])
        calc(v);
}

```

Centroid Tree (CT)

Centroid Tree properties:

- Centroid tree height $\leq \log(n)$
- $LCA(u, v)$ in CT lies on the path from u to v in the original tree

```

int size(int u, int prev){
    sz[u] = 1;
    for (int v: g[u]) if (v != prev && !del[v]){
        sz[u] += size(v, u);
    }
    return sz[u];
}

int centroid(int u, int prev, int m){
    for (int v: g[u]) if (v != prev && !del[v])

```

```

    if (sz[v] > m/2)
        return centroid(v, u, m);
    return u;
}

int cd(int u){
    int m = size(u);
    u = centroid(u, 0, m);
    del[u] = 1;
    for (int v: g[u]) if (!del[v]){
        v = cd(v);
        par[v] = u;
    }
    return u;
}

//example problems:
void solve(){
    dfs(1, 0); init(); //to calculate the dist(u, v)
                        from the original tree
    cd(1);

    memset(d, 0x3f, sizeof d);

    c[1] = 1; //color
    int pp = 1;
    while (pp){
        minimize(d[pp], dist(pp, 1));
        pp = par[pp];
    }

    while (q--){
        int t; cin >> t;
        if (t == 1){
            int u; cin >> u;
            c[u] = 1;

            int p = u;
            while (p){
                minimize(d[p], dist(p, u));
                p = par[p];
            }
        }
        else{
            int u; cin >> u;
            if (c[u]) {
                cout << 0 << endl; continue;
            }

            int p = u, res = INF;
            while(p){
                minimize(res, dist(u, p) + d[p]);
                p = par[p];
            }

            cout << res << endl;
        }
    }
}

```

Virtual Tree

```

void dfs(int u){
    in[u] = ++timer;
    for (int v: g[u]) if (v != up[u][0]){
        up[v][0] = u;
        For(j, 1, 17) up[v][j] = up[up[v][j-1]][j-1];
        dfs(v);
    }
}

```

```

    out[u] = timer;
}

bool is_anc(int u, int v){
    if (!u) return 1;
    return in[u] <= in[v] && in[v] <= out[u];
}

//short LCA
int lca(int u, int v){
    if (is_anc(u, v)) return u;
    ForD(j, 17, 0){
        if (!is_anc(up[u][j], v)){
            u = up[u][j];
        }
    }
    return up[u][0];
}

bool cmp(int u, int v){
    return in[u] < in[v];
}

void query(){
    cin >> k;
    For(i, 1, k) cin >> a[i], sz[a[i]] = 1;

    sort(a + 1, a + k + 1, cmp);
    For(i, 1, k - 1) a[i + k] = lca(a[i], a[i + 1]);

    sort(a + 1, a + k + k, cmp);
    k = unique(a + 1, a + k + k) - a - 1;

    stack<int> st; st.push(a[1]);
    For(i, 2, k){
        while (!is_anc(st.top(), a[i])) st.pop();
        g[st.top()].pb(a[i]);
        st.push(a[i]);
    }

    res = 0; calc(a[1]);
    cout << res << endl;

    For(i, 1, k) sz[a[i]] = 0, g[a[i]].clear();
}

void solve(){
    //...
    dfs(1);
    For(i, 1, n) g[i].clear();
    while (q--) query();
}

```

DP

Digit DP

```

int f(int id, bool sml, ...){
    if (id < 0) return ...;
    if (!sml && dp[id][...] != -1) return dp[id][...];

    int lim = sml ? a[id] : 9;
    int res = ...;
    For(c, 0, lim){
        update(res, f(id - 1, sml && c == lim, ...));
    }
    if (!sml) dp[id][...] = res;
    return res;
}

```



```

}

int get(int x){
    int n = 0;
    while (x){
        a[n++] = x % 10;
        x /= 10;
    }
    return f(n - 1, 1, ...);
}

```

SOS DP

```

for (int k = 0; k < n; k++)
    for (int mask = 0; mask < (1 << n); mask++)
        if (mask & (1 << k))
            dp[mask] += dp[mask ^ (1 << k)];

```

DP DNC

Solving problems that have the form:

$$dp(i, j) = \min_{0 \leq k \leq j} (dp(i-1, k-1) + C(k, j))$$

The cost function has to satisfy the quadrangle inequality: $C(a, c) + C(b, d) \leq C(a, d) + C(b, c)$ for all $a \leq b \leq c \leq d$.

Example:

$C(j, i) = f(i - j)$ where f is convex.

$C(j, i) = (i - j)$

$C(j, i) = (i - j)^2$

```

int m, n;
vector<int> dp_before(n + 1), dp_cur(n + 1);

// cost function
int C(int l, int r);

// calculate dp_cur[l], ..., dp_cur[r]
void compute(int l, int r, int optl, int optr) {
    if (l > r) return;

    int mid = (l + r) >> 1;
    pair<int, int> best = {INT_MAX, -1};
    //calculate dp_cur[mid] & opt[i][mid] depend on
    dp_before and cost func
    for (int k = optl; k <= min(mid, optr); ++k) {
        minimize(best, {dp_before[k] + C(k, mid), k});
    }
    dp_cur[mid] = best.first;
    int opt = best.second;

    compute(l, mid - 1, optl, opt);
    compute(mid + 1, r, opt, optr);
}

int solve() {
    for (int i = 0; i <= n; ++i)
        dp_before[i] = C(0, i);

    for (int i = 1; i < m; ++i) {
        compute(0, n, 0, n);
        dp_before = dp_cur;
    }

    return dp_before[n];
}

```

Convex Hull Trick

Adding lines $y = kx + m$ and querying minimum values at integer x .

```

struct Line {
    int k, m;
    mutable int p;

    int eval(int x){
        return k * x + m;
    }

    bool operator < (const Line& l) const {
        return k < l.k;
    }
    bool operator < (const int &x) const {
        return p < x;
    }
};

struct ConvexHull : multiset<Line, less<>> {
    int div(int a, int b) {
        return a / b - ((a ^ b) < 0 && a % b);
    }

    bool bad(iterator x, iterator y) {
        if (y == end()) {
            x->p = LINF;
            return 0;
        }

        if (x->k == y->k) x->p = x->m > y->m ? LINF : -LINF;
        else x->p = div(y->m - x->m, x->k - y->k);

        return x->p >= y->p;
    }

    void add(int k, int m) {
        auto z = insert({k, m, 0}), y = z++, x = y;
        while (bad(y, z)) z = erase(z);

        if (x != begin() && bad(--x, y)) bad(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            bad(x, erase(y));
    }

    int query(int x) {
        assert(!empty());
        Line l = *lower_bound(x);
        return l.eval(x);
    }
} CH;

//If you want maximum, just flip signs:
CH.add(-k, -m);
int res = -CH.query(x);

```

1D1D Optimization

Solving problems that have the form:

$$dp(i) = \min_{0 \leq j < i} (dp(j) + C(j, i)),$$

```

struct item {
    int l, r, p;
};

long long w(int j, int i) {
    //cost function
}

void solve() {
    deque<item> dq;
    dq.push_back({1, n, 0});
    for (int i = 1; i <= n; ++i) {
        f[i] = f[dq.front().p] + w(dq.front().p, i);
        ++dq.front().l;

        if (dq.front().l > dq.front().r) {
            dq.pop_front();
        }

        while (!dq.empty()) {
            auto [l, r, p] = dq.back();
            if (f[i] + w(i, l) < f[p] + w(p, l)) {
                dq.pop_back();
            }
            else break;
        }

        if (dq.empty()) {
            dq.push_back({i + 1, n, i});
            // h[i+1]=h[i+2]=...=h[n]=i
        }
        else {
            auto& [l, r, p] = dq.back();
            int low = l, high = r;
            int pos = r + 1, mid;
            while (low <= high) {
                mid = (low + high) / 2;
                if (f[i] + w(i, mid) < f[p] + w(p, mid)) {
                    pos = mid, high = mid - 1;
                }
                else {
                    low = mid + 1;
                }
            }

            r = pos - 1;
            if (pos <= n) {
                dq.push_back({pos, n, i});
                // h[pos]=h[pos+1]=...=h[n]=i
            }
        }
    }
}

```

Knapsack on Tree

Problem: Given a tree T with N vertices rooted at vertex 1 ($1 \leq N \leq 5000$). The i -th vertex has a value C_i and a constraint K_i ($|C_i| \leq 10^9$, $1 \leq K_i \leq N$). Choose a subset of vertices such that, in the subtree of every vertex i , there are at most K_i chosen vertices, and the total sum of the chosen vertices' values is maximized.

```

void calc(int V){
    int n = child[V].size();

```

```

    for(int v_i: child[V]) {
        calc(v_i);
    }

    for(int i = 0; i <= n; i++) fill(fV[i], fV[i] + N + 1, -INF);
    fV[0][0] = 0;

    for(int i = 1; i <= n; i++){
        int v_i = child[V][i - 1];
        for(int a = 0; a <= sz[V]; a++){
            for(int b = 0; b <= sz[v_i]; b++){
                fV[i][a+b] = max(fV[i][a+b], fV[i-1][a] + dp[v_i][b]);
            }
            sz[V] += sz[v_i];
        }
    }

    for(int k = 0; k <= N; k++){
        if(k > K[V]) dp[V][k] = -INF;
        else {
            if(k > 0) dp[V][k] = max(fV[n][k], fV[n][k-1] + C[V]);
            else dp[V][k] = fV[n][k];
        }
    }
    sz[V]++;
}

long long solve() {
    calc(1);
    return *max_element(dp[1], dp[1] + N + 1);
}

```

DP on Broken Profile

count the number of ways you can fill an $n \times m$ grid using 1×2 and 2×1 tiles. ($1 \leq n \leq 10, 1 \leq m \leq 1000$)

```

dp[0][0] = 1;
for (int j = 0; j < m; j++)
    for (int i = 0; i < n; i++) {
        for (int mask = 0; mask < (1 << n); mask++) {
            dp[mask][1] = dp[mask ^ (1 << i)][0]; //
            Horizontal or no tile
            if (i && !(mask & (1 << i)) && !(mask & (1 << i - 1))) // Vertical tile
                dp[mask][1] += dp[mask ^ (1 << i - 1)][0];
            if (dp[mask][1] >= MOD) dp[mask][1] -= MOD;
        }
        for (int mask = 0; mask < (1 << n); mask++)
            dp[mask][0] = dp[mask][1];
    }
cout << dp[0][0] << '\n';

```

Number Theory

Euler's totient function

```

int phi(int n) {
    int res = n;
    for (int i = 2; i * i <= n; i++) {
        if (n % i == 0) {
            while (n % i == 0) n /= i;
            res -= res / i;
        }
    }
}

```

```

    if (n > 1) res -= res / n;
    return res;
}

```

Euler's totient function from 1 to N

```

void preCompute(int n) {
    iota(phi, phi + N, 0); //phi[i] = i
    for (int i = 2; i <= n; i++) {
        if (phi[i] == i) {
            for (int j = i; j <= n; j += i)
                phi[j] -= phi[j] / i;
        }
    }
}

```

Modular Inverse

```

//if MOD is a prime number then phi(MOD)= MOD - 1
int inv(int x, int MOD){
    return Pow(x, phi(MOD) - 1);
}

```

Extended Euclidean Algorithm

```

//computing gcd(a, b) and finding (x, y) that
//ax + by = gcd(a, b)

//recursive version
int gcd(int a, int b, int& x, int& y) {
    if (b == 0) {
        x = 1; y = 0;
        return a;
    }
    int x1, y1;
    int d = gcd(b, a % b, x1, y1);
    x = y1;
    y = x1 - y1 * (a / b);
    return d;
}

//iterative version
int gcd(int a, int b, int& x, int& y) {
    x = 1, y = 0;
    int x1 = 0, y1 = 1, a1 = a, b1 = b;
    while (b1) {
        int q = a1 / b1;
        tie(x, x1) = make_tuple(x1, x - q * x1);
        tie(y, y1) = make_tuple(y1, y - q * y1);
        tie(a1, b1) = make_tuple(b1, a1 - q * b1);
    }
    return a1;
}

```

Diophantine

```

bool find_any_solution(int a, int b, int c, int &x0,
    int &y0, int &g) {
    g = gcd(abs(a), abs(b), x0, y0);
    if (c % g) return false;

    x0 *= c / g; y0 *= c / g;
    if (a < 0) x0 = -x0;
    if (b < 0) y0 = -y0;
    return true;
}

//all the solutions have the form:

```

```

//x = x0 + k * b/g
//y = y0 - k * b/g

```

//IN A GIVEN INTERVAL:

```

void shift(int & x, int & y, int a, int b, int cnt) {
    x += cnt * b;
    y -= cnt * a;
}

int find_all_solutions(int a, int b, int c, int minx,
    int maxx, int miny, int maxy) {
    int x, y, g;
    if (!find_any_solution(a, b, c, x, y, g)) return
        0;
    a /= g; b /= g;

    int sign_a = a > 0 ? +1 : -1;
    int sign_b = b > 0 ? +1 : -1;

    shift(x, y, a, b, (minx - x) / b);
    if (x < minx) shift(x, y, a, b, sign_b);
    if (x > maxx) return 0;
    int lx1 = x;

    shift(x, y, a, b, (maxx - x) / b);
    if (x > maxx) shift(x, y, a, b, -sign_b);
    int rx1 = x;

    shift(x, y, a, b, -(miny - y) / a);
    if (y < miny) shift(x, y, a, b, -sign_a);
    if (y > maxy) return 0;
    int lx2 = x;

    shift(x, y, a, b, -(maxy - y) / a);
    if (y > maxy) shift(x, y, a, b, sign_a);
    int rx2 = x;

    if (lx2 > rx2) swap(lx2, rx2);
    int lx = max(lx1, lx2);
    int rx = min(rx1, rx2);

    if (lx > rx) return 0;
    return (rx - lx) / abs(b) + 1;
}

```

Chinese Remainder Theorem

```

// Combine two congruences:
// x = a1 (mod m1), x = a2 (mod m2)
// Returns (x, lcm) or (-1,-1) if no solution
pair<ll, ll> crt2(ll a1, ll m1, ll a2, ll m2) {
    int x, y;
    ll g = gcd(m1, m2, x, y);

    if ((a2 - a1) % g != 0) {
        return {-1, -1}; // no solution
    }

    ll lcm = m1 / g * m2;

    ll k = (a2 - a1) / g;
    ll mult = (1LL * x * k) % (m2 / g);

    ll ans = (a1 + m1 * mult) % lcm;
    if (ans < 0) ans += lcm;

    return {ans, lcm};
}

```

```
//solve a system of congruences:
//x = a1 (mod m1)
//x = a2 (mod m2)
//...
//x = ak (mod mk)
pair<ll, ll> crt(vector<ll> a, vector<ll> m) {
    pair<ll, ll> res = {a[0], m[0]};
    for (int i = 1; i < sz(a); i++) {
        res = crt2(res.first, res.second, a[i], m[i]);
        ;
        if (res.first == -1) return {-1, -1};
    }
    return res;
}

//x = sol.first (mod sol.second)
```

Rabin-Miller primality test

```
bool test(ll a, ll n, ll k, ll m){
    ll mod = Pow(a, m, n);
    if (mod == 1 || mod == n - 1) return 1;
    for (int l = 1; l < k; ++l){
        mod = (mod * mod) % n;
        if (mod == n - 1) return 1;
    }
    return 0;
}

//check if n is a prime number
bool RabinMiller(ll n){
    if (n == 2 || n == 3 || n == 5 || n == 7) return 1;
    if (n < 11) return 0;

    ll k = 0, m = n - 1;
    while (!(m & 1)){
        m >>= 1;
        k++;
    }

    const static int repeatTime = 3;
    for (int i = 0; i < repeatTime; ++i){
        ll a = rand() % (n - 3) + 2;
        if (!test(a, n, k, m)) return 0;
    }
    return 1;
}
```

Pollard's Rho prime factorization

- Average Time Complexity: $O(\sqrt[4]{N} \log^2(N))$
- Space Complexity: $O(\log N)$

```
using ll = long long;
using ull = unsigned long long;
using ld = long double;
ll mult(ll x, ll y, ll md) {
    ull q = (ld)x * y / md;
    ll res = ((ull)x * y - q * md);
    if (res >= md) res -= md;
    if (res < 0) res += md;
    return res;
}

ll powMod(ll x, ll p, ll md) {
```

```
    if (p == 0) return 1;
    if (p & 1) return mult(x, powMod(x, p - 1, md), md);
    return powMod(mult(x, x, md), p / 2, md);
}

bool checkMillerRabin(ll x, ll md, ll s, int k) {
    x = powMod(x, s, md);
    if (x == 1) return true;
    while (k--) {
        if (x == md - 1) return true;
        x = mult(x, x, md);
        if (x == 1) return false;
    }
    return false;
}

bool isPrime(ll x) {
    if (x == 2 || x == 3 || x == 5 || x == 7) return true;
    if (x % 2 == 0 || x % 3 == 0 || x % 5 == 0 || x % 7 == 0) return false;
    if (x < 121) return x > 1;
    ll s = x - 1;
    int k = 0;
    while (s % 2 == 0) {
        s >>= 1;
        k++;
    }
    if (x < 1LL << 32) {
        for (ll z : {2, 7, 61}) {
            if (!checkMillerRabin(z, x, s, k)) return false;
        }
    } else {
        for (ll z : {2, 325, 9375, 28178, 450775, 9780504, 1795265022}) {
            if (!checkMillerRabin(z, x, s, k)) return false;
        }
    }
    return true;
}

mt19937_64 rng(chrono::steady_clock::now().time_since_epoch().count());
long long get_rand(long long r) {
    return uniform_int_distribution<long long>(0, r - 1)(rng);
}

void pollard(ll x, vector<ll> &ans) {
    if (isPrime(x)) {
        ans.push_back(x);
        return;
    }
    ll c = 1;
    while (true) {
        c = 1 + get_rand(x - 1);
        auto f = [&](ll y) {
            ll res = mult(y, y, x) + c;
            if (res >= x) res -= x;
            return res;
        };
        ll y = 2;
        int B = 100;
        int len = 1;
        ll g = 1;
```

```

while (g == 1) {
    ll z = y;
    for (int i = 0; i < len; i++) {
        z = f(z);
    }
    ll zs = -1;
    int lft = len;
    while (g == 1 && lft > 0) {
        zs = z;
        ll p = 1;
        for (int i = 0; i < B && i < lft; i++) {
            p = mult(p, abs(z - y), x);
            z = f(z);
        }
        g = gcd(p, x);
        lft -= B;
    }
    if (g == 1) {
        y = z;
        len <= 1;
        continue;
    }
    if (g == x) {
        g = 1;
        z = zs;
        while (g == 1) {
            g = gcd(abs(z - y), x);
            z = f(z);
        }
    }
    if (g == x) break;
    assert(g != 1);
    pollard(g, ans);
    pollard(x / g, ans);
    return;
}

// return list of all prime factors of x (can have
// duplicates)
vector<ll> factorize(ll x) {
    vector<ll> ans;
    for (ll p : {2, 3, 5, 7, 11, 13, 17, 19}) {
        while (x % p == 0) {
            x /= p;
            ans.push_back(p);
        }
    }
    if (x != 1) {
        pollard(x, ans);
    }
    sort(ans.begin(), ans.end());
    return ans;
}

// return pairs of (p, k) where x = product(p^k)
vector<pair<ll, int>> factorize_pk(ll x) {
    auto ps = factorize(x);
    ll last = -1, cnt = 0;
    vector<pair<ll, int>> res;
    for (auto p : ps) {
        if (p == last)
            ++cnt;
        else {
            if (last > 0) res.emplace_back(last, cnt);
            last = p;

```

```

        cnt = 1;
    }
}
if (cnt > 0) {
    res.emplace_back(last, cnt);
}
return res;
}

```

Multiplicative Function (Sieve)

- For all coprimes $n, m \in N$, we have $f(m, n) = f(m)f(n)$
- ex: $I(N) = 1$, $id(n) = n$, $id_k(n) = n^k$, $gcd(n, const)$, $\varphi(n)$, $\mu(n)$, $f_k(n) = \sum_{d|n} d^k$, $\mu(n)$
- Dirichlet Convolution: $h(n) = \sum_{d|n} f(d) \times g(n/d)$ is also a multiplicative function

```

const int MN = 1e6 + 11;

int sieve[MN];
pair<int, int> pk[MN];
int ndiv[MN];

int main() {
    for (int i = 2; i <= 1000; i++)
        if (!sieve[i]) {
            for (int j = i*i; j <= 1000000; j += i)
                sieve[j] = i;
        }

    ndiv[1] = 1;

    for (int i = 2; i <= 1000000; i++) {
        if (!sieve[i]) {
            pk[i] = make_pair(i, 1);
            ndiv[i] = 2;
        }
        else {
            int p = sieve[i];

            if (pk[i/p].first == p) {
                pk[i] = make_pair(p, pk[i/p].second + 1);
                ndiv[i] = pk[i].second + 1;
            }
            else {
                pk[i] = make_pair(-1, 0);
                int u = i, v = 1;
                while (u % p == 0) {
                    u /= p;
                    v = v * p;
                }
                ndiv[i] = ndiv[u] * ndiv[v];
            }
        }
    }
}

```

Multiplicative Function

```

int n;
int res = 1;

```

```
for (int i = 2; i*i <= n; i++) {
    if (n % i == 0) {
        int u = 1, k = 0;
        while (n % i == 0) {
            n /= i;
            u = u * i;
            k += 1;
        }
        res = res * f(i, k);
    }
}

if (n > 1) {
    res = res * f(n, 1);
}
```

Discrete Logarithm

- To find min x that $a^x \equiv b \pmod{m}$
- Find $\text{ord}_m(a) = \min x \text{ that } a^x \equiv 1 \pmod{m}$ in $O(\sqrt{m} \log m)$

```
//gcd(a, m) == 1
int discrete_log_BSGS_coprime(int a, int b, int m) {
    a %= m, b %= m;
    int n = sqrt(m) + 1;
    unordered_map<int, int> vals;
    for (int q = 0, cur = b; q <= n; ++q) {
        vals[cur] = q;
        cur = 1LL * cur * a % m;
    }
    int step = binpow(a, n, m);
    for (int p = 1, f1 = 1; p <= n; p++) {
        f1 = 1LL * f1 * step % m;
        if (vals.count(f1)) {
            return n * p - vals[f1];
        }
    }
    return -1;
}

//gcd != 1
int discrete_log_BSGS(int a, int b, int m) {
    a %= m, b %= m;
    int n = sqrt(m) + 1;

    int k = 1, add = 0, g;
    while ((g = __gcd(a, m)) > 1) {
        if (b == k) return add;
        if (b % g) return -1;
        b /= g, m /= g, ++add;
        a %= m;
        k = (k * 111 * a / g) % m;
    }
    unordered_map<int, int> vals;
    for (int q = 0, cur = b; q <= n; ++q) {
        vals[cur] = q;
        cur = 1LL * cur * a % m;
    }
    int step = binpow(a, n, m);
    for (int p = 1, f1 = k; p <= n; p++) {
        f1 = 1LL * f1 * step % m;
        if (vals.count(f1)) {
            int ans = n * p - vals[f1] + add;
            return ans;
        }
    }
    return -1;
}
```

```
}

//ord_m(a):
using ll = long long;
ll powMod(ll x, ll p, ll md);
ll gcd(ll x, ll y);
vector<ll> factorize(ll x); //Pollard's Rho

ll phi(ll n) {
    auto ps = factorize(n);
    ll res = n;
    ll last = -1;
    for (auto p : ps) {
        if (p != last) {
            res = res / p * (p - 1);
            last = p;
        }
    }
    return res;
}

ll ord(ll a, ll m) {
    if (gcd(a, m) != 1) return -1;
    ll res = phi(m);
    auto ps = factorize(res);
    for (auto p : ps)
        if (powMod(a, res / p, m) == 1) res /= p;
    return res;
}
```

Geometry

Dot Product

```
//remember that u * v = 0 -> u is perpendicular with v
//or (u, v) = pi/2
double dotProduct(Vector u, Vector v){
    return u.x * v.x + u.y * v.y;
}
```

Angle

```
//u * v = |u| * |v| * cos(theta)
//-> theta = acos (u * v / (|u| * |v|))
double Cos(Vector u, Vector v){
    return dotProduct(u, v)/(u.len * v.len);
}

double theta(Vector u, Vector v){
    return acos(Cos(u, v));
}
```

Cross Product

```
//u * v = |u| * |v| * sin(theta)
//u * v = u.x * v.y - u.y * v.x
//|u * v| = area of a parallelogram formed by adjacent vectors u and v
//= double the area of the triangle
double crossProduct(Vector u, Vector v){
    return u.x * v.y - u.y * v.x;
}
```

Distance from a Point to a line

$$d(C, AB) = |\vec{AB} * \vec{AC}| / AB$$

```
// Compute the distance from AB to C
// if isSegment is true, AB is a segment, not a line.
```

```
double linePointDist(Point A, Point B, Point C, bool
    isSegment){
    double res = abs(cross(A, B, C)) / dist(A, B);
    if (isSegment){
        int dot1 = dot(B, A, C);
        if (dot1 < 0) return distance(B, C);
        int dot2 = dot(A, B, C);
        if (dot2 < 0) return distance(A, C);
    }
    return res;
}
```

Template 1

```
struct vec {
    db x, y;
    vec(db _x = 0, db _y = 0) : x(_x), y(_y) {}
    db dot(const vec &other) { // Compute the dot
        product
        return x * other.x + y * other.y;
    }
    db cross(const vec &other) { // Compute the cross
        product
        return x * other.y - y * other.x;
    }
    db length() const {
        return sqrt(x * x + y * y);
    }
};
using point = vec; // or use 'typedef vec point'
vec operator - (const point &B, const point &A) { //
    vecAB = B - A
    return vec(B.x - A.x, B.y - A.y);
}

// if isSegment is true, AB is a segment, not a line.
db linePointDist(const point &A, const point &B,
    const point &C, bool isSegment) {
    db dist = abs((B - A).cross(C - A)) / (A - B).
        length();
    if (isSegment) {
        db dot1 = (A - B).dot(C - B);
        if (dot1 < 0) return (B - C).length();
        db dot2 = (B - A).dot(C - A);
        if (dot2 < 0) return (A - C).length();
    }
    return dist;
}
```

Intersection of 2 lines and bla bla bla (I have no time bro)

Lines will have the form: $ax + by = c$.

$\vec{AB} \times \vec{AC} > 0 \Rightarrow A, B, C$ are counterclockwise.

$\vec{AB} \times \vec{AC} < 0 \Rightarrow A, B, C$ are clockwise.

$\vec{AB} \times \vec{AC} = 0 \Rightarrow A, B, C$ are collinear.

```
const double eps = 1e-9;
int sign(double x) {
    if (x > eps) return 1;
    if (x < -eps) return -1;
    return 0;
}
double cross(Vec AB, Vec AC) {
    return AB.x * AC.y - AC.x * AB.y;
}
double dot(Vec AB, Vec AC) {
    return AB.x * AC.x + AB.y * AC.y;
```

```
}
//intersection of 2 segments
bool intersect(Point A, Point B, Point C, Point D) {
    int ABxAC = sign(cross(B - A, C - A));
    int ABxAD = sign(cross(B - A, D - A));
    int CDxCA = sign(cross(D - C, A - C));
    int CDxCB = sign(cross(D - C, B - C));
    if (ABxAC == 0 || ABxAD == 0 || CDxCA == 0 ||
        CDxCB == 0) {
        // C on segment AB if ABxAC = 0 and CA.CB <=
        0
        if (ABxAC == 0 && sign(dot(A - C, B - C)) <=
            0) return true;
        if (ABxAD == 0 && sign(dot(A - D, B - D)) <=
            0) return true;
        if (CDxCA == 0 && sign(dot(C - A, D - A)) <=
            0) return true;
        if (CDxCB == 0 && sign(dot(C - B, D - B)) <=
            0) return true;
        return false;
    }
    return (ABxAC * ABxAD < 0 && CDxCA * CDxCB < 0);
}
```

Circle passing through 3 points

```
struct Point {
    double x, y;
    Point() { x = y = 0.0; }
    Point(double x, double y) : x(x), y(y) {}

    Point operator + (const Point &a) const { return
        Point(x + a.x, y + a.y); }
    Point operator - (const Point &a) const { return
        Point(x - a.x, y - a.y); }
    Point operator * (double k) const { return Point(
        x * k, y * k); }
    Point operator / (double k) const { return Point(
        x / k, y / k); }
};

struct Line { // Ax + By = C
    double a, b, c;
    Line(double a = 0, double b = 0, double c = 0) :
        a(a), b(b), c(c) {}
    Line(Point A, Point B) {
        a = B.y - A.y;
        b = A.x - B.x;
        c = a * A.x + b * A.y;
    }
};

Line Perpendicular_Bisector(Point A, Point B) {
    Point M = (A + B) / 2;
    Line d = Line(A, B);
    // the equation of a perpendicular line has the
    form: -Bx + Ay = D
    double D = -d.b * M.x + d.a * M.y;
    return Line(-d.b, d.a, D);
}

//Intersection of 2 Perpendicular Bisector is the
center of the circle
```

Symmetry

```
struct Line { // Ax + By = C
    double a, b, c;
```

```

Line(double a = 0, double b = 0, double c = 0) :
    a(a), b(b), c(c) {}
};

Point intersect(Line d1, Line d2) {
    double det = d1.a * d2.b - d2.a * d1.b;
    // det != 0 because d1 is perpendicular to d2
    return Point((d2.b * d1.c - d1.b * d2.c) / det, (
        d1.a * d2.c - d2.a * d1.c) / det);
}

Point Symmetry(Point X, Line d) {
    // the equation of a perpendicular line has the
    // form: -Bx + Ay = D
    double D = -d.b * X.x + d.a * X.y;
    Line d2 = Line(-d.b, d.a, D);
    Point Y = intersect(d, d2);
    Point X2 = Point(2 * Y.x - X.x, 2 * Y.y - X.y);
    return X2;
}

```

Rotation

To rotate $A(x, y)$ counterclockwise by an angle θ around the origin, we can easily use this formula:

$$x' = x \cos \theta - y \sin \theta$$

$$y' = x \sin \theta + y \cos \theta$$

```

Point Rotations(Point A, Point C, double rad) {
    Point A2 = A - C;
    Point B2 = Point(A2.x * cos(rad) - A2.y * sin(rad),
        A2.x * sin(rad) + A2.y * cos(rad));
    Point B = B2 + C;
    return B;
}

```

Area of a Polygon

```

double polygonArea(const vector<Point>& poly) {
    int n = poly.size();
    double area = 0.0;
    for (int i = 0; i < n; i++) {
        int j = (i + 1) % n;
        area += poly[i].x * poly[j].y - poly[j].x *
            poly[i].y;
    }
    return fabs(area) / 2.0;
}

```

Relative position of a point to a polygon $O(N)$

```

//using Area
//Time Complexity: O(N) per query
PointPolygonPosition position(Polygon plg, Point p) {
    long long sSumTris = 0;
    for (int i = 0; i < plg.nVertices; i++) {
        int i1 = (i + 1) % plg.nVertices;
        Polygon tri(p, plg.vertices[i], plg.vertices[i1]);
        auto sTri = tri.area2(); //2 * area
        if (!sTri) {
            return BOUNDARY;
        }
        sSumTris += sTri;
    }
    return (sSumTris == plg.area2() ? INSIDE :
        OUTSIDE);
}

```

Relative position of a point to a polygon $O(\log N)$

```

//using binary search
bool isCW(Point a, Point b, Point c) {
    return (Vector(a, b) ^ Vector(a, c)) < 0;
}

PointPolygonPosition position(Polygon plg, Point p) {
    // Check if P is on A_1A_n
    Vector pa1(p, plg.vertices[0]);
    Vector pan(p, plg.vertices[plg.nVertices - 1]);
    if (pa1 ^ pan == 0) { //cross product
        if (1ll * pa1.x * pan.x <= 0) {
            return BOUNDARY;
        }
        return OUTSIDE;
    }

    int l = 1, r = plg.nVertices;
    while (r - l > 1) {
        int mid = (l + r) >> 1;
        if (isCW(plg.vertices[0], p, plg.vertices[mid])) {
            l = mid;
        } else {
            r = mid;
        }
    }

    int k = l;
    if (k == plg.nVertices - 1) {
        return OUTSIDE;
    }

    // Check if P is on the triangle
    if (Vector(p, plg.vertices[k]) ^ Vector(p, plg.vertices[k + 1]) == 0) {
        return BOUNDARY;
    }
    long long ss = 0;
    ss += Polygon(p, plg.vertices[0], plg.vertices[k]).area2();
    ss += Polygon(p, plg.vertices[k], plg.vertices[k + 1]).area2();
    ss += Polygon(p, plg.vertices[k + 1], plg.vertices[0]).area2();
    if (ss == Polygon(plg.vertices[0], plg.vertices[k],
        plg.vertices[k + 1]).area2()) {
        return INSIDE;
    }
    return OUTSIDE;
}

```

Pick Theorem

$$A = I + B/2 - 1$$

- A = Area of the Polygon
- I = Number of interior lattice points (strictly inside the polygon)
- B = Number of boundary lattice points (on the polygon edges)

Convex Hull (Graham scan)

```
// Cross Product of AB and AC
long long cross(const Point &A, const Point &B, const
    Point &C) {
    return 1LL * (B.x - A.x) * (C.y - A.y) - 1LL * (C
        .x - A.x) * (B.y - A.y);
}

// A -> B -> C clockwise (-1), collinear (0),
    counterclockwise (1)
int ccw(const Point &A, const Point &B, const Point &
    C) {
    long long S = cross(A, B, C);
    if (S < 0) return -1;
    if (S == 0) return 0;
    return 1;
}

//convex hull listed in counterclockwise order
vector<Point> convexHull(vector<Point> p, int n) {
    for (int i = 1; i < n; ++i) {
        if (p[0].y > p[i].y || (p[0].y == p[i].y && p
            [0].x > p[i].x)) {
            swap(p[0], p[i]);
        }
    }

    sort(p.begin() + 1, p.end(), [&p](const Point &A,
        const Point &B) {
        int c = ccw(p[0], A, B);
        if (c > 0) return true;
        if (c < 0) return false;
        return A.x < B.x || (A.x == B.x && A.y < B.y)
            ;
    });

    vector<Point> hull;
    hull.push_back(p[0]);

    for (int i = 1; i < n; ++i) {
        while (hull.size() >= 2 && ccw(hull[hull.size
            () - 2], hull.back(), p[i]) < 0) {
            hull.pop_back();
        }
        hull.push_back(p[i]);
    }
    return hull;
}
```

Convex Hull (Monotone chain algorithm)

```
bool ccw(const Point &A, const Point &B, const Point
    &C) {
    return 1LL * (B.x - A.x) * (C.y - A.y) - 1LL * (C
        .x - A.x) * (B.y - A.y) > 0;
}

vector<Point> convexHull(vector<Point> p, int n) {
    sort(p.begin(), p.end(), [](const Point &A, const
        Point &B) {
        if (A.x != B.x) return A.x < B.x;
        return A.y < B.y;
    });

    vector<Point> hull;
    hull.push_back(p[0]);

    for (int i = 1; i < n; ++i) {
```

```
        while (hull.size() >= 2 && ccw(hull[hull.size
            () - 2], hull.back(), p[i]) < 0) {
            hull.pop_back();
        }
        hull.push_back(p[i]);
    }

    for (int i = n - 2; i >= 0; --i) {
        while (hull.size() >= 2 && ccw(hull[hull.size
            () - 2], hull.back(), p[i]) < 0) {
            hull.pop_back();
        }
        hull.push_back(p[i]);
    }

    if (n > 1) hull.pop_back();

    return hull;
}
```

More

- Number of triangles with no polygon side (no two vertices adjacent): $n(n-4)(n-5)/6$.
- Number of intersection points of diagonals in a convex n -gon: $n(n-1)(n-2)(n-3)/24$
- Number of triangles formed by one diagonal + a third vertex: $\binom{n}{2}(n-4)$
- Partitions of the polygon into triangles using non-crossing diagonals: $C_{n-2} = \frac{1}{n-1} \binom{2n-4}{n-2}$ where C_k is the k -th Catalan number.
- Number of ways to choose a set of non-crossing diagonals C_{n-2}
- Number of ways to choose k non-crossing diagonals in a convex = $N(n, k) = \frac{1}{k+1} \binom{n-3k}{k}$.
- You are given a convex polygon with n sides. You then connect all of the points by drawing lines among the diagonals of the polygon, then cut through the lines all at once. The maximum number of pieces: $R(N) = (n-1)(n-2)(n^2 - 3n + 12)/24$
- With a circle: $+ = n$ (n edges).

Algebra

Matrix Multiplication

Example:

$$\begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix} \begin{bmatrix} 5 & 6 \\ 7 & 8 \end{bmatrix} = \begin{bmatrix} 1 \cdot 5 + 2 \cdot 7 & 1 \cdot 6 + 2 \cdot 8 \\ 3 \cdot 5 + 4 \cdot 7 & 3 \cdot 6 + 4 \cdot 8 \end{bmatrix} = \begin{bmatrix} 19 & 22 \\ 43 & 50 \end{bmatrix}$$

```
#define vi vector<int>
struct Matrix{
    vector<vi> a;
    int r, c;
    Matrix(){
        a.clear(); r = c = 0;
    }
    Matrix(vector<vi> a, int r, int c): a(a), r(r), c(c)
    {}
```

```

Matrix operator * (const Matrix &B) const{
    vector<vi> res(r, vi(B.c, 0));
    vector<vi> b = B.a;

    rep(i, r){
        rep(j, B.c){
            rep(k, c){
                res[i][j] += a[i][k] * b[k][j] % MOD;
                res[i][j] %= MOD;
            }
        }
    }

    return Matrix(res, r, B.c);
}

Matrix Pow(Matrix A, int b){
    vector<vi> a(A.r, vi(A.c, 0));
    rep(i, A.r) a[i][i] = 1;

    Matrix res(a, A.r, A.c);

    while (b){
        if (b & 1) res = res * A;
        A = A * A;
        b >>= 1;
    }

    return res;
}

```

Fast Fourier Transform

```

namespace FFT{

#define cd complex<long double>
#define vc vector<cd>

const long double PI = acos(-1.0L);
const int N = 1e6 + 5;
int rev[N];

void fft(vc &a, bool inverse = 0){
    int n = sz(a);
    rep(i, n) if (i < rev[i]){
        swap(a[i], a[rev[i]]);
    }

    for (int len = 2; len <= n; len <<= 1){
        cd wn = polar(1.0L, PI/len * (inverse ? -2
            : 2));
        for (int i = 0; i < n; i += len){
            cd w = 1;
            rep(j, len/2){
                rep(k, len/2){
                    cd u = a[i + j];
                    cd v = a[i + j + len/2] * w;
                    a[i + j] = u + v;
                    a[i + j + len/2] = u - v;
                    w *= wn;
                }
            }
        }
    }

    if (inverse){
        for (cd &x: a){

```

```

            x /= n;
        }
    }

    vi operator * (const vi &a, const vi &b){
        if (a.empty() || b.empty()) return {};

        vc fa(all(a));
        vc fb(all(b));

        int n = 1, L = 0;
        while (n < sz(a) + sz(b) - 1) n <<= 1, ++L;
        rep(i, n){
            rev[i] = (rev[i >> 1] | (i & 1) << L) >>
                1;
        }

        fa.resize(n); fb.resize(n);

        fft(fa); fft(fb);

        rep(i, n) fa[i] *= fb[i];
        fft(fa, 1);

        n = sz(a) + sz(b) - 1;
        vi res(n);
        rep(i, n) res[i] = (int)(real(fa[i]) + 0.5);

        return res;
    }
}

```

Number Theory Transform

```

namespace NTT{
    const int MOD = 998244353;
    const int g = 3; //primitive root
    int rev[N];

    void ntt(vi &a, bool inverse = 0){
        int n = sz(a);
        rep(i, n) if (i < rev[i]){
            swap(a[i], a[rev[i]]);
        }

        for (int len = 2; len <= n; len <<= 1){
            int wn = Pow(g, (MOD - 1)/len);
            if (inverse) wn = Pow(wn, MOD - 2);

            for (int i = 0; i < n; i += len){
                int w = 1;
                rep(j, len/2){
                    int u = a[i + j];
                    int v = mul(w, a[i + j + len/2]);

                    a[i + j] = sum(u, v);
                    a[i + j + len/2] = dif(u, v);

                    w = mul(w, wn);
                }
            }
        }

        if (inverse){
            int div_n = Pow(n, MOD - 2);
            rep(i, n) a[i] = mul(a[i], div_n);
        }
    }
}

```

```

}

vi operator * (const vi &a, const vi &b){
    if (a.empty() || b.empty()) return {};

    vi fa(all(a)), fb(all(b));

    int n = 1, L = 0;
    while (n < sz(a) + sz(b) - 1) n <= 1, ++L;
    rep(i, n){
        rev[i] = (rev[i >> 1] | (i & 1) << L) >>
            1;
    }

    fa.resize(n); fb.resize(n);
    ntt(fa); ntt(fb);

    rep(i, n) fa[i] = mul(fa[i], fb[i]);
    ntt(fa, 1);

    fa.resize(sz(a) + sz(b) - 1);
    return fa;
}
}

```

- Number of full binary trees with n internal nodes.

Derangement

```

//Principle of Inclusion-Exclusion
int c = 1;
for (int i = 1; i <= n; i++) {
    c = (c * i) + (i % 2 == 1 ? -1 : 1);
    cout << c << ' ';
}

//DP
//dp[n] = (n - 1)(dp[n - 2] + dp[n - 1])

```

Classical Sums

$$\sum_{k=0}^n \binom{n}{k} = 2^n$$

$$\sum_{k=0}^n k \binom{n}{k} = n \cdot 2^{n-1}, \quad \sum_{k=0}^n k^2 \binom{n}{k} = n(n+1) \cdot 2^{n-2}$$

$$\sum_{k=0}^n (-1)^k \binom{n}{k} = 0 \quad (n > 0)$$

$$\sum_{k=0}^n \binom{n}{k}^2 = \binom{2n}{n}$$

$$\sum_{k=0}^r \binom{m}{k} \binom{n}{r-k} = \binom{m+n}{r} \quad (\text{Vandermonde})$$

Combinatoric Formula

```

//DP version:
void preCompute(){
    for (int i = 0; i <= n; i++){
        C[i][0] = 1;
        for (int k = 1; k <= i; k++){
            C[i][k] = C[i-1][k-1] + C[i-1][k];
        }
    }
}

//"you know what it is" version:
int C(int n, int k){
    if (n < k || k < 0) return 0;
    return mul(fact[n], mul(ifact[n-k], ifact[k]))
}

```

Catalan

$$C_n = \sum_{k=0}^{n-1} C_k C_{n-1-k} = \frac{1}{n+1} \binom{2n}{n}$$

Applications

- Number of ways to triangulate a convex polygon with $n+2$ vertices.
- Number of Dyck words of length $2n$ (strings of n X and n Y, every prefix has $\#X \geq \#Y$).
- Number of valid parentheses sequences with n pairs.
For $n=3$: $((()))$, $((()))$, $((()))$, $(()())$, $(())()$.
- Number of ways to parenthesize $(n+1)$ factors.
Example ($n=3$):
 $((ab)c)d$, $(a(bc))d$, $(ab)(cd)$, $a((bc)d)$, $a(b(cd))$

Useful Identities

$$\sum_{k=r}^n \binom{k}{r} = \binom{n+1}{r+1} \quad (\text{Hockey-stick})$$

$$\sum_{k=0}^r (-1)^k \binom{r}{k} \binom{n+k}{m} = \binom{n}{m-r}$$

$$\binom{n}{k_1, k_2, \dots, k_m} = \frac{n!}{k_1! k_2! \dots k_m!}, \quad \sum k_i = n$$

Stirling Numbers

$$S(n, k) = S(n-1, k-1) + kS(n-1, k)$$

$$x^n = \sum_{k=0}^n S(n, k)(x)_k, \quad (x)_k = x(x-1) \dots (x-k+1)$$

Others

Test?

```
11 rand(11 l, 11 r){
    return rd() % (r - l + 1) + 1;
}

int w[N];

main()
{
    // freopen(name".inp", "r", stdin); freopen(name".
    out", "w", stdout); w
    srand(time(0));
    int c = 0;
    ios_base::sync_with_stdio(false); cin.tie(0);
    cout.tie(0);
    for (int i = 1; i <= 1000; i++){
        ofstream fo("a.inp");
        int n = 1000;
        fo << n << endl;
        REP(i, n) fo << rand(1, 100000000) << endl;
        REP(i, n) fo << rand(1, 100000000) << endl;
        system("ac.exe");
        system("trau.exe");
        if (system("fc a1.out a2.out") == 1) exit(0);
    }
    return 0;
}
```

Big Int

```
#include <bits/stdc++.h>
using namespace std;

struct BigInt {
    static const int base = 1000000000; // 1e9
    static const int base_digits = 9;
    vector<int> a; // little-endian (a[0] is least
        significant block)
    int sign;

    // Constructors
    BigInt(): sign(1) {}
    BigInt(long long v) { *this = v; }
    BigInt(const string &s) { read(s); }

    // Assign from integer
    BigInt& operator=(long long v) {
        sign = 1;
        if (v < 0) sign = -1, v = -v;
        a.clear();
        for (; v > 0; v /= base) a.push_back(v % base
            );
        return *this;
    }

    // Remove leading zeroes
    void trim() {
        while (!a.empty() && a.back() == 0) a.
            pop_back();
        if (a.empty()) sign = 1;
    }

    // Read from string
    void read(const string &s) {
        sign = 1;
        a.clear();
```

```
int pos = 0;
while (pos < (int)s.size() && (s[pos] == '-' || s[pos] == '+')) {
    if (s[pos] == '-') sign = -sign;
    pos++;
}
for (int i = s.size()-1; i >= pos; i -=
    base_digits) {
    int x = 0;
    for (int j = max(pos, i - base_digits + 1)
        ; j <= i; j++)
        x = x * 10 + (s[j] - '0');
    a.push_back(x);
}
trim();
}

// Output
friend ostream& operator<<(ostream &os, const
    BigInt &v) {
    if (v.sign == -1 && !v.isZero()) os << '-';
    if (v.a.empty()) { os << 0; return os; }
    os << v.a.back();
    for (int i = (int)v.a.size()-2; i >= 0; i--)
        os << setw(base_digits) << setfill('0') <<
            v.a[i];
    return os;
}

// Compare absolute values
static int cmpAbs(const BigInt &a, const BigInt &
    b) {
    if (a.a.size() != b.a.size()) return a.a.size
        () < b.a.size() ? -1 : 1;
    for (int i = (int)a.a.size()-1; i >= 0; i--)
        if (a.a[i] != b.a[i]) return a.a[i] < b.a[
            i] ? -1 : 1;
    return 0;
}

// Comparison operators
bool operator<(const BigInt &v) const {
    if (sign != v.sign) return sign < v.sign;
    int cmp = cmpAbs(*this, v);
    return sign == 1 ? cmp < 0 : cmp > 0;
}
bool operator==(const BigInt &v) const { return
    sign == v.sign && a == v.a; }
bool operator!=(const BigInt &v) const { return
    !(*this == v); }
bool operator>(const BigInt &v) const { return v
    < *this; }
bool operator<=(const BigInt &v) const { return
    !(v < *this); }
bool operator>=(const BigInt &v) const { return
    !(*this < v); }

bool isZero() const { return a.empty(); }

// Addition
BigInt operator+(const BigInt &v) const {
    if (sign == v.sign) {
        BigInt res = v;
        int carry = 0;
        for (size_t i = 0; i < max(a.size(), v.a.
            size()) || carry; i++) {
            if (i == res.a.size()) res.a.push_back
                (0);
```

```

        long long sum = res.a[i] + carry + (i
        < a.size() ? a[i] : 0);
        carry = sum >= base;
        if (carry) sum -= base;
        res.a[i] = sum;
    }
    return res;
}
return *this - (-v);
}

// Negation
BigInt operator-() const {
    BigInt res = *this;
    if (!res.isZero()) res.sign = -sign;
    return res;
}

// Subtraction
BigInt operator-(const BigInt &v) const {
    if (sign == v.sign) {
        if (cmpAbs(*this, v) >= 0) {
            BigInt res = *this;
            int carry = 0;
            for (size_t i = 0; i < v.a.size() ||
                carry; i++) {
                res.a[i] -= carry + (i < v.a.size()
                    ? v.a[i] : 0);
                carry = res.a[i] < 0;
                if (carry) res.a[i] += base;
            }
            res.trim();
            return res;
        }
        return -(v - *this);
    }
    return *this + (-v);
}

// Multiplication
BigInt operator*(const BigInt &v) const {
    BigInt res;
    res.sign = sign * v.sign;
    res.a.assign(a.size()+v.a.size(), 0);
    for (size_t i = 0; i < a.size(); i++) {
        long long carry = 0;
        for (size_t j = 0; j < v.a.size() || carry
            ; j++) {
            long long cur = res.a[i+j] + carry +
                1LL * a[i] * (j < v.a.size() ? v.a[
                    j] : 0);
            res.a[i+j] = int(cur % base);
            carry = cur / base;
        }
    }
    res.trim();
    return res;
}

// Division and modulo
BigInt divmod(const BigInt &v, BigInt &rem) const
{
    int norm = base / (v.a.back() + 1);
    BigInt a = abs() * norm;
    BigInt b = v.abs() * norm;
    BigInt q; q.a.assign(a.a.size(), 0);
    rem = 0;
    rem.a.resize(a.a.size());

```

```

    for (int i = (int)a.a.size()-1; i >= 0; i--)
    {
        rem.shiftRight();
        rem.a[0] = a.a[i];
        rem.trim();
        int s1 = rem.a.size() <= b.a.size() ? 0 :
            rem.a[b.a.size()];
        int s2 = rem.a.size() <= b.a.size()-1 ? 0
            : rem.a[b.a.size()-1];
        long long d = ((long long)base * s1 + s2)
            / b.a.back();
        BigInt tmp = b * d;
        while (rem < tmp) { d--; tmp = tmp - b; }
        rem = rem - tmp;
        q.a[i] = d;
    }
    q.sign = sign * v.sign;
    rem.sign = sign;
    q.trim();
    rem.trim();
    return q;
}

BigInt operator/(const BigInt &v) const {
    BigInt rem;
    return divmod(v, rem);
}

BigInt operator%(const BigInt &v) const {
    BigInt rem;
    divmod(v, rem);
    return rem;
}

// Helpers
BigInt abs() const {
    BigInt res = *this;
    res.sign = 1;
    return res;
}

void shiftRight() {
    if (a.empty()) a.push_back(0);
    a.insert(a.begin(), 0);
}
};

```

CODE::BLOCK Set Up

*
 Settings -> Compiler... -> Selected compiler:
 GNU GCC Compiler
 Have g++ follow the C++17 ISO C++ language
 standard [-std=c++17]
 Enable all common compiler warnings (-Wall)
 Enable extra compiler warnings (-Wextra)
 -O2

Template

Settings -> Editor -> Abbreviations -> Add
 Ctrl + J to use

CODE::BLOCK shortcuts

*
 • Ctrl + Space → Autocomplete (symbols, func-
 tions, variables).

- Ctrl + Shift + C → Comment selected block.
- Ctrl + Shift + X → Uncomment selected block.
- Ctrl + D → Duplicate current line/selection.
- Ctrl + Shift + ↑ / ↓ → Move current line/selection up or down.
- Ctrl + L → Delete current line.
- Ctrl + Shift + K → Insert new line above current line.
- Ctrl + Shift + J → Insert new line below current line.
- Ctrl + G → Go to line.
- Ctrl + Shift + V → Paste without indentation (useful when pasting code from outside).

Multiplication Function

```
ll mult(ll x, ll y, ll md) {  
    ull q = (ld)x * y / md;  
    ll res = ((ull)x * y - q * md);  
    if (res >= md) res -= md;  
    if (res < 0) res += md;  
    return res;  
}
```

Random Function

```
mt19937_64 rng(chrono::steady_clock::now().  
    time_since_epoch().count());  
long long get_rand(long long r) {  
    return uniform_int_distribution<long long>(0, r -  
        1)(rng);  
}
```