



the right side of the browser under the **Run** tab, you will see a **Create** button. Click on this.


- You will notice that underneath the **Create** button shows a new section with the name of the contract and



Note:

- The Remix UI was changed recently. There is no longer a button labeled "create." The **"deploy"** button does the same thing.
- This means that the **smart contract** (yes, it's not very smart at this point) lives at an **address**.
- To see this **full address** along with other information, in the **debugger** if you click on the **Details** button with more information:






• Step 2: Smart Contract Variables & Types

- The most simple concept in any language is the **variable**. Because Solidity is **statically typed** (that is, the type of the variable must be defined before **compile time**), you must specify the type of the variable.
- Let's define a string variable in our contract:

```
pragma solidity ^0.4.18;
contract Coursetro {
    string Name = "Gary";
}
```

- In Solidity, you define a variable by first specifying its type.
 - bool**
This is a Boolean, which returns true or false.
 - int / uint**
Both int and uint represent integers, or number values. The primary difference between int and uint (Unsigned Integer), is that int can hold negative numbers as values.
 - address**
The address type represents a 20 byte value, which is meant to store an Ethereum address. Variables that are typed as address also have members, including balance and transfer.
 - bytes1 through 32**
This is a fixed-size byte array.
 - bytes**
A dynamically-sized byte array.
 - string**
A dynamically signed string.
 - mapping**
Hash tables with key types and value types. We will look at mappings more in depth later on in the course.
 - struct**
Structs allow you to define new types. We will also cover this more in depth shortly.
- Let's also define my **age**. No one can have a negative age, so we will use an unsigned integer for this:

```
pragma solidity ^0.4.18;
contract Coursetro {
    string Name = "Gary";
    uint age;
```



Student Index

Exercises for Dev

Lab 2: Ethereum

npu85.npu.edu/~henry/npu/classes/building...

Apps

Bookmarks

Bookmarks

HSJ

School

White Love | Daisuk...

Wheel Decide

bytes1 through 32

This is a fixed-size byte array.

bytes

A dynamically-sized byte array.

string

A dynamically signed string.

mapping

Hash tables with key types and value types. We will look at mappings more in depth later on in the course.

struct

Structs allow you to define new types. We will also cover this more in depth shortly.

Let's also define my age. No one can have a negative age, so we will use an unsigned integer for this:

```
pragma solidity ^0.4.18;
contract Coursetro {
    string fName = 'Gary';
    uint age = 34;
}
```

Hit **Create** to create the **contract**. At this point, if you look under details or try to **drop down the contract** on the **right column**, you will see nothing.

Where are our variables?

Step 3: Public and Private

Solidity has four types of **visibilities** for both functions and variables:

Public

This allows you to define functions or variables that can be called **internally** or through **messages**.

Private

Private variables and functions are only available to the **current contract** and not **derived contracts**.

Internal

Functions and variables that can only be accessed **internally** (current contract or **derived**).

External

Functions that can be called from **other contracts** and **transactions**. They cannot be called **internally**, except with **"this.functionName()"**.

Let's add the **public** visibility to our variables:

Remix - Ethereum IDE

where is run tab in new remix ve

Remix Documentation

Not secure | remix.ethereum.org/#optimize=false&evmVersion=null&version=soljs...

Apps

Bookmarks

Bookmarks

HSJ

School

White Love | Daisuk...

Wheel Decide

Bay Area counties a...

DEPLOY & RUN TRANSACTIONS

Environment

JavaScript VM

Account

0xCA3...a733c (99.9)

Gas limit

3000000

Value

0

wei

Coursetro - browser/Coursetro.sol

Deploy

or

At Address

Load contract from Address

Transactions recorded:

Deployed Contracts

Coursetro at 0x692...77b3A (memory)

Home

Coursetro.sol

// This line defines the version of solidity you're going to use.

pragma solidity ^0.4.18;

contract Coursetro {

string fName = 'Gary';

uint age = 34;

}

listen on network

Search with transaction hash or address

[vm] from:0xca3...a733c to:Coursetro.(constructor) value:0 wei data:0x00...30029 logs:0 hash:0x3c0...a433

Debug

Student Index

Exercises for Dev

Lab 2: Ethereum

npu85.npu.edu/~henry/npu/classes/building...

Apps

Bookmarks

Bookmarks

HSJ

School

White Love | Daisuk...

Wheel Decide

bytes1 through 32

This is a fixed-size byte array.

bytes

A dynamically-sized byte array.

string

A dynamically signed string.

mapping

Hash tables with key types and value types. We will look at mappings more in depth later on in the course.

struct

Structs allow you to define new types. We will also cover this more in depth shortly.

Let's also define my age. No one can have a negative age, so we will use an unsigned integer for this:

```
pragma solidity ^0.4.18;
contract Coursetro {
    string fName = 'Gary';
    uint age = 34;
}
```

Hit **Create** to create the **contract**. At this point, if you look under details or try to **drop down the contract** on the **right column**, you will see nothing.

Where are our variables?

Step 3: Public and Private

Solidity has four types of **visibilities** for both functions and variables:

Public

This allows you to define functions or variables that can be called **internally** or through **messages**.

Private

Private variables and functions are only available to the **current contract** and not **derived contracts**.

Internal

Functions and variables that can only be accessed **internally** (current contract or **derived**).

External

Functions that can be called from **other contracts** and **transactions**. They cannot be called **internally**, except with **"this.functionName()"**.

Let's add the **public** visibility to our variables:

Remix - Ethereum IDE

where is run tab in new remix ve

Remix Documentation

Not secure | remix.ethereum.org/#optimize=false&evmVersion=null&version=soljs...

Apps

Bookmarks

Bookmarks

HSJ

School

White Love | Daisuk...

Wheel Decide

Bay Area counties a...

DEPLOY & RUN TRANSACTIONS

Environment

JavaScript VM

Account

0xCA3...a733c (99.9)

Gas limit

3000000

Value

0

wei

Coursetro - browser/Coursetro.sol

Deploy

or

At Address

Load contract from Address

Transactions recorded:

Deployed Contracts

Coursetro at 0x692...77b3A (memory)

Coursetro at 0xb8F...732d (memory)

Home

Coursetro.sol

// This line defines the version of solidity you're going to use.

pragma solidity ^0.4.18;

contract Coursetro {

string fName = 'Gary';

uint age = 34;

}

listen on network

Search with transaction hash or address

status

0x1 Transaction mined and execution succeed

transaction hash

0x0e97277773a3e9a5e4711c208350e2e7d4d8781d1a359457056698c...

contract address

0xb8f289d844208c16dc8474795c748aff07732db

from

0xca307d915450af540ded06dfe2f44d8fa733c

to

Coursetro.(constructor)

gas

3000000

transaction cost

68794

gas

18646

execution cost

0x0e97277773a3e9a5e4711c208350e2e7d4d8781d1a359457056698c...

hash

0x0e97277773a3e9a5e4711c208350e2e7d4d8781d1a359457056698c...

input

0x00...

decoded input

()

decoded output

-

logs

()

value

0 wei

Student Index

Exercises for Dev

Lab 2: Ethereum

npu85.npu.edu/~henry/npu/classes/building...

Where are our variables?

• Step 3: Public and Private

Solidity has four types of **visibilities** for both functions and variables:

Public

This allows you to define functions or variables that can be called **internally** or through **messages**.

Private

Private variables and functions are only available to the **current contract** and not **derived contracts**.

Internal

Functions and variables that can only be accessed **internally** (**current contract** or **derived**).

External

Functions that can be called from **other contracts** and **transactions**. They cannot be called **internally**, except with **"this.functionName()"**.

Let's add the **public** visibility to our variables:

```
pragma solidity ^0.4.18;

contract Coursetro {
    string public fName = 'Gary';
    uint public age = 34;
}
```

Click **Create**, we can now see on the **right** that we have **2 blue buttons** with the name of our **variables** and the **associated values**.

When you define **public state variables**, the **EVM** creates **getter functions** for them.

So, you can actually click on these **buttons** and it will return the value, as if it were a **function**.

• Step 4: Smart Contract Constructor

Every smart contract has a **constructor** function. This constructor is called when a contract is created. Inside of it, you can define the values of variables.

Let's re-adjust our code with a constructor:

npu85.npu.edu/~henry/npu/classes/building...

Where are our variables?

• Step 4: Smart Contract Constructor

Click **Create**, we can now see on the **right** that we have **2 blue buttons** with the name of our **variables** and the **associated values**.

When you define **public state variables**, the **EVM** creates **getter functions** for them.

So, you can actually click on these **buttons** and it will return the value, as if it were a **function**.

• Step 5: Constant Variables

Variables can be declared as being **constant**. As the name suggests, these are variables with a constant value that does not change.

Let's transform the **fName** variable to a constant variable:

Remix - Ethereum IDE

where is run tab in new remix ve

Remix Documentation

DEPLOY & RUN TRANSACTIONS

Environment: JavaScript VM

Account: 0xCA3...a733c (99.9)

Gas limit: 3000000

Value: 0 wei

Deploy

or

At Address: Load contract from Address

Transactions recorded:

Deployed Contracts

Coursetro at 0x692...77b3A (memory)

Coursetro at 0xb8F...732dB (memory)

Coursetro at 0x0DC...97caf (memory)

status: Transaction mined and execution succeed

transaction hash: 8x1898884c17efce448ea1e29e5339c36c597a89cc888f2f3ac5d8

contract address: 876c8

from: 0xb8fcd2f92394c41875c25b0b0b0f4d66297c4ef

to: 0xca337d91546ae94b0d606dfe2f44e6fa733c

gas: 3000000

transaction cost: 68794 gas

execution cost: 13666 gas

hash: 8x1898884c17efce448ea1e29e5339c36c597a89cc888f2f3ac5d8

input: 8x088...b8c29

decoded input: ()

decoded output: -

logs: []

value: 0 wei

npu85.npu.edu/~henry/npu/classes/building...

Where are our variables?

• Step 4: Smart Contract Constructor

Click **Create**, we can now see on the **right** that we have **2 blue buttons** with the name of our **variables** and the **associated values**.

When you define **public state variables**, the **EVM** creates **getter functions** for them.

So, you can actually click on these **buttons** and it will return the value, as if it were a **function**.

• Step 5: Constant Variables

Variables can be declared as being **constant**. As the name suggests, these are variables with a constant value that does not change.

Let's transform the **fName** variable to a constant variable:

Remix - Ethereum IDE

where is run tab in new remix ve

Remix Documentation

DEPLOY & RUN TRANSACTIONS

Environment: JavaScript VM

Account: 0xCA3...a733c (99.9)

Gas limit: 3000000

Value: 0 wei

Deploy

or

At Address: Load contract from Address

Transactions recorded:

Deployed Contracts

Coursetro at 0x692...77b3A (memory)

Coursetro at 0xb8F...732dB (memory)

Coursetro at 0x0DC...97caf (memory)

Coursetro at 0x5E7...2bef9 (memory)

status: Transaction mined and execution succeed

transaction hash: 8x5d3b8de2f51315c98c8c1565af848cd07d26fe76723dbf664938f7da8

contract address: 43d29

from: 0xb8fcd2f92394c41875c25b0b0b0f4d66297c4ef

to: 0xca337d91546ae94b0d606dfe2f44e6fa733c

gas: 3000000

transaction cost: 68794 gas

execution cost: 13666 gas

hash: 8x5d3b8de2f51315c98c8c1565af848cd07d26fe76723dbf664938f7da8

input: 43d29

decoded input: ()

decoded output: -

logs: []

value: 0 wei

