

Fun with higher-order functions: continuations 2

Jacob Thomas Errington

20 March 2019

Recap

On Monday, we saw a few things.

- ▶ Why do we care about tail recursion?

Recap

On Monday, we saw a few things.

- ▶ Why do we care about tail recursion? Stack space is limited!

Recap

On Monday, we saw a few things.

- ▶ Why do we care about tail recursion? Stack space is limited!
- ▶ How to convert to continuation-passing style.
 1. Change the type.
... \rightarrow A becomes

Recap

On Monday, we saw a few things.

- ▶ Why do we care about tail recursion? Stack space is limited!
- ▶ How to convert to continuation-passing style.
 1. Change the type.
... -> A becomes ... -> (A -> 'r) -> 'r.

Recap

On Monday, we saw a few things.

- ▶ Why do we care about tail recursion? Stack space is limited!
- ▶ How to convert to continuation-passing style.
 1. Change the type.
... \rightarrow A becomes ... \rightarrow (A \rightarrow 'r) \rightarrow 'r.
 2. Change the implementation.
 - ▶ Instead of returning?

Recap

On Monday, we saw a few things.

- ▶ Why do we care about tail recursion? Stack space is limited!
- ▶ How to convert to continuation-passing style.
 1. Change the type.
 $\dots \rightarrow A$ becomes $\dots \rightarrow (A \rightarrow 'r) \rightarrow 'r$.
 2. Change the implementation.
 - ▶ Instead of returning? Call the continuation!

Recap

On Monday, we saw a few things.

- ▶ Why do we care about tail recursion? Stack space is limited!
- ▶ How to convert to continuation-passing style.
 1. Change the type.
... \rightarrow A becomes ... \rightarrow (A \rightarrow 'r) \rightarrow 'r.
 2. Change the implementation.
 - ▶ Instead of returning? Call the continuation!
 - ▶ Work that happens after the recursive call goes where?

Recap

On Monday, we saw a few things.

- ▶ Why do we care about tail recursion? Stack space is limited!
- ▶ How to convert to continuation-passing style.
 1. Change the type.
 $\dots \rightarrow A$ becomes $\dots \rightarrow (A \rightarrow 'r) \rightarrow 'r$.
 2. Change the implementation.
 - ▶ Instead of returning? Call the continuation!
 - ▶ Work that happens after the recursive call goes where? In the continuation!

Exercise: find all

Last class, we saw how to find *one* element of a tree satisfying a predicate. What if we want to find *all* elements of a tree satisfying a predicate?

Exercise: find all

Last class, we saw how to find *one* element of a tree satisfying a predicate. What if we want to find *all* elements of a tree satisfying a predicate?

In five minutes, write the function

```
find_all : ('a -> bool) -> 'a tree -> 'a list
```

that finds all elements of the tree satisfying the predicate.

Hint: use the @ operator to concatenate the two lists resulting from the recursive calls:

$$[1;2] @ [3;4] \mapsto [1;2;3;4].$$

Recall:

```
type 'a tree = Empty | Node of 'a tree * 'a * 'a tree
```

Exercise: convert to CPS

Now in five minutes, write `find_all_k`, a CPS version of `find_all`.

Exercise: convert to CPS

Now in five minutes, write `find_all_k`, a CPS version of `find_all`.

Remember the basic strategy:

- ▶ Instead of returning, call the continuation.
- ▶ Work that would go after the recursive call(s) goes into the continuation.

Regular expressions

What is a regular expression?

A **regular expression** (regex) is a way of defining a set of *strings*.

For example, to represent the set {apple, apply}, we can write the regular expression `appl(e|y)`.

In general, regular expressions are defined inductively.

- ▶ Each individual letter is a regex.

The regex c consisting of a character c represents the singleton set $\{c\}$.

In general, regular expressions are defined inductively.

- ▶ Each individual letter is a regex.

The regex c consisting of a character c represents the singleton set $\{c\}$.

- ▶ If R_1 and R_2 are regexes, then $R_1|R_2$ is a regex.

It represents the union of the two sets.

For example, “apple” matches the regex apple|pear .

In general, regular expressions are defined inductively.

- ▶ Each individual letter is a regex.

The regex c consisting of a character c represents the singleton set $\{c\}$.

- ▶ If R_1 and R_2 are regexes, then $R_1|R_2$ is a regex.

It represents the union of the two sets.

For example, “apple” matches the regex apple|pear .

- ▶ If R_1 and R_2 are regexes, then $R_1 R_2$ is a regex.

It represents the concatenation of strings.

For example, if “app” matches R_1 and “le” matches R_2 , then “apple” matches $R_1 R_2$.

In general, regular expressions are defined inductively.

- ▶ Each individual letter is a regex.

The regex c consisting of a character c represents the singleton set $\{c\}$.

- ▶ If R_1 and R_2 are regexes, then $R_1|R_2$ is a regex.

It represents the union of the two sets.

For example, “apple” matches the regex apple|pear .

- ▶ If R_1 and R_2 are regexes, then $R_1 R_2$ is a regex.

It represents the concatenation of strings.

For example, if “app” matches R_1 and “le” matches R_2 , then “apple” matches $R_1 R_2$.

- ▶ If R is a regex, then R^* is a regex.

It represents repetition of a string zero or more times.

Consider the regex ba(na)^* . The following strings match it: “ba”, “bana”, “banana”, “bananana”, ...

Plus two special cases

- ▶ The empty *regex*, \emptyset , which represents the empty set. No string matches this regex.

Plus two special cases

- ▶ The empty *regex*, \emptyset , which represents the empty set. No string matches this regex.
- ▶ The empty *string*, ϵ . This is useful for creating optional parts in a regex.
For example, the strings “great” and “greatest” match the regex `great(est| ϵ)`.

Our goal

Input: a regex and a string

Output: whether the string matches the regex.

Our goal

Input: a regex and a string

Output: whether the string matches the regex.

Intuitively, we want to implement a function of type

`string -> regex -> bool`

Our goal

Input: a regex and a string

Output: whether the string matches the regex.

Intuitively, we want to implement a function of type

`string -> regex -> bool`

But first, what's `regex`?

Defining `regex` in OCaml

It turns out that encoding inductive definitions in OCaml is a piece of cake.

Defining `regex` in OCaml

It turns out that encoding inductive definitions in OCaml is a piece of cake.

```
type regex =  
  | Epsilon (* empty string *)  
  | Empty   (* empty regex *)  
  | Single of char  
  | Cat of regex * regex  
  | Alt of regex * regex  
  | Star of regex
```

The regex $b(a)^*$ is represented in code as

```
let r1 = Cat (Single 'b', Star (Single 'a')).
```

A few more things to clear up

`string` doesn't have *structure*! So instead, we'll use a `char list` as input.

A few more things to clear up

`string` doesn't have *structure*! So instead, we'll use a `char list` as input.

We will *generalize* the matching algorithm. Rather than check whether the *whole string* matches the regex, we will check whether a *prefix* of the string matches the regex. If so, we return the remaining characters of the string.

What return type?

For example,

- ▶ `accept ['b'; 'a'; 'n'] r1` returns `['n']`; the “n” is left over.
- ▶ `accept ['b'; 'a'] r1` returns `[]`; the matched prefix *is* the whole string.
- ▶ `accept ['e'] r1` fails, since there is no prefix match.

What return type?

For example,

- ▶ `accept ['b'; 'a'; 'n'] r1` returns `['n']`; the “n” is left over.
- ▶ `accept ['b'; 'a'] r1` returns `[]`; the matched prefix *is* the whole string.
- ▶ `accept ['e'] r1` fails, since there is no prefix match.

Given these examples, **what should the return type be?**

`char list -> regex -> ?`

What return type?

For example,

- ▶ `accept ['b'; 'a'; 'n'] r1` returns `['n']`; the “n” is left over.
- ▶ `accept ['b'; 'a'] r1` returns `[]`; the matched prefix *is* the whole string.
- ▶ `accept ['e'] r1` fails, since there is no prefix match.

Given these examples, **what should the return type be?**

`char list -> regex -> char list option`

What return type?

For example,

- ▶ `accept ['b'; 'a'; 'n'] r1` returns `['n']`; the “n” is left over.
- ▶ `accept ['b'; 'a'] r1` returns `[]`; the matched prefix *is* the whole string.
- ▶ `accept ['e'] r1` fails, since there is no prefix match.

Given these examples, **what should the return type be?**

`char list -> regex -> (char list -> 'r) -> (unit -> 'r) -> 'r`

And now we convert to CPS, expanding the option into separate success and failure continuations.

Now it's code it!

Basic type theory

option vs success and failure continuations

option vs success and failure continuations

Or, why are algebraic data types called “algebraic”?

What's a type anyway?

Let's be more precise about what a “type” is.

$$\text{Type } T ::= \text{unit} \mid T_1 * T_2 \mid T_1 + T_2 \mid T_1 \rightarrow T_2$$

What's a type anyway?

Let's be more precise about what a “type” is.

Type $T ::= \text{unit} \mid T_1 * T_2 \mid T_1 + T_2 \mid T_1 \rightarrow T_2$

`unit`

What's a type anyway?

Let's be more precise about what a “type” is.

Type $T ::= \text{unit} \mid T_1 * T_2 \mid T_1 + T_2 \mid T_1 \rightarrow T_2$

$t1 * t2$

What's a type anyway?

Let's be more precise about what a “type” is.

$$\text{Type } T ::= \text{unit} \mid T_1 * T_2 \mid \textcolor{red}{T_1} + \textcolor{red}{T_2} \mid T_1 \rightarrow T_2$$

`type ('a, 'b) either = Left of 'a | Right of 'b`

What's a type anyway?

Let's be more precise about what a “type” is.

$$\text{Type } T ::= \text{unit} \mid T_1 * T_2 \mid T_1 + T_2 \mid T_1 \rightarrow T_2$$

`t1 -> t2`

What's a type anyway?

Let's be more precise about what a “type” is.

$$\text{Type } T ::= \text{unit} \mid T_1 * T_2 \mid T_1 + T_2 \mid T_1 \rightarrow T_2$$

These are all the basic ways we can combine types. We can form functions with \rightarrow , form alternatives with $+$, and we can form pairs with $*$.

Combinatorics of types

- ▶ How many values of type `unit` are there?

Combinatorics of types

- ▶ How many values of type `unit` are there?
Just one, by definition.

Combinatorics of types

- ▶ How many values of type `unit` are there?
Just one, by definition.
- ▶ How many values of type `unit + unit` are there?

Combinatorics of types

- ▶ How many values of type `unit` are there?
Just one, by definition.
- ▶ How many values of type `unit + unit` are there?
Recall that this is as if we had defined in pseudo-OCaml
`type unit + unit = Left of unit | Right of unit.`
How many different ways can we make values of this type?

Combinatorics of types

- ▶ How many values of type `unit` are there?
Just one, by definition.
- ▶ How many values of type `unit + unit` are there?
Recall that this is as if we had defined in pseudo-OCaml
`type unit + unit = Left of unit | Right of unit.`
How many different ways can we make values of this type?
Two, one for each constructor, since there's only one
possibility for each `unit` inside.

Combinatorics of types

- ▶ How many values of type `unit` are there?
Just one, by definition.
- ▶ How many values of type `unit + unit` are there?
Recall that this is as if we had defined in pseudo-OCaml
`type unit + unit = Left of unit | Right of unit.`
How many different ways can we make values of this type?
Two, one for each constructor, since there's only one
possibility for each `unit` inside.
- ▶ How many values of type `(unit + unit) * (unit + unit)` are there?

Combinatorics of types

- ▶ How many values of type `unit` are there?
Just one, by definition.
- ▶ How many values of type `unit + unit` are there?
Recall that this is as if we had defined in pseudo-OCaml
`type unit + unit = Left of unit | Right of unit.`
How many different ways can we make values of this type?
Two, one for each constructor, since there's only one
possibility for each `unit` inside.
- ▶ How many values of type `(unit + unit) * (unit + unit)` are there?
Four. Two possibilities for each component of the pair.

Combinatorics of types

- ▶ Suppose type **A** has n values. How many values of type `unit -> A` are there?

Combinatorics of types

- Suppose type **A** has n values. How many values of type `unit -> A` are there?

Remember, the values of this type are *functions*. How many different functions can you write having this type?

```
let f (() : unit) : A = (*value of type A *)
```

Combinatorics of types

- Suppose type **A** has n values. How many values of type `unit -> A` are there?

Remember, the values of this type are *functions*. How many different functions can you write having this type?

```
let f (() : unit) : A = (*value of type A *)
```

You can write n different functions; one for each value in **A**.

Combinatorics of types

- Suppose type A has n values. How many values of type $\text{unit} \rightarrow A$ are there?

Remember, the values of this type are *functions*. How many different functions can you write having this type?

```
let f (() : unit) : A = (*value of type A *)
```

You can write n different functions; one for each value in A .

- Suppose type A has k values and B has n values.

How many values of type $A \rightarrow B$ are there?

Hint: to determine the function, we have to choose for each input what its output is. In other words, how many input-output pairs are there?

Combinatorics of types

- ▶ Suppose type A has n values. How many values of type `unit -> A` are there?

Remember, the values of this type are *functions*. How many different functions can you write having this type?

```
let f (() : unit) : A = (*value of type A *)
```

You can write n different functions; one for each value in A .

- ▶ Suppose type A has k values and B has n values.

How many values of type `A -> B` are there?

Hint: to determine the function, we have to choose for each input what its output is. In other words, how many input-output pairs are there?

There are n^k different such functions.

The algebra of types

Now we understand the type constructors $*$, $+$, and \rightarrow through their combinatorics, i.e. by *counting* the values.

The algebra of types

Now we understand the type constructors $*$, $+$, and \rightarrow through their combinatorics, i.e. by *counting* the values.

Upshot: we can now use our knowledge of arithmetic to **refactor types!**

Isomorphic types

For example, $\text{unit} \rightarrow A$ has the same number of values as A , because $n^1 = n$.

This suggests that A and $\text{unit} \rightarrow A$ are **isomorphic types**; we can convert from one to the other and back.

Isomorphic types

For example, $\text{unit} \rightarrow A$ has the same number of values as A , because $n^1 = n$.

This suggests that A and $\text{unit} \rightarrow A$ are **isomorphic types**; we can convert from one to the other and back.

Proof:

```
let oneway (f : unit -> 'a) -> 'a =  
  f ()
```

```
let otherway (x : 'a) : unit -> 'a =  
  fun () -> x
```

All algebra you know now applies to types

$\text{unit} * \text{unit} \cong ?$

All algebra you know now applies to types

$$\text{unit} * \text{unit} \cong \text{unit}$$

All algebra you know now applies to types

$\text{unit} * \text{unit} \cong \text{unit}$
because $1 \times 1 = 1$

All algebra you know now applies to types

$$(\text{unit} + \text{unit}) * (\text{unit} + \text{unit}) \cong ?$$

All algebra you know now applies to types

$$(\text{unit} + \text{unit}) * (\text{unit} + \text{unit}) \cong \text{unit} + \text{unit} + \text{unit} + \text{unit}$$

All algebra you know now applies to types

$(\text{unit} + \text{unit}) * (\text{unit} + \text{unit}) \cong \text{unit} + \text{unit} + \text{unit} + \text{unit}$
because $2 \times 2 = 4$

All algebra you know now applies to types

$$(A * B) \rightarrow C \cong A \rightarrow B \rightarrow C$$

All algebra you know now applies to types

$$(A * B) \rightarrow C \cong A \rightarrow B \rightarrow C$$

because $n^{k_1 \times k_2} = (n^{k_2})^{k_1}$

All algebra you know now applies to types

$$(A * B) \rightarrow C \cong A \rightarrow B \rightarrow C$$

because $n^{k_1 \times k_2} = (n^{k_2})^{k_1}$

This is a combinatorial justification for **currying**

Refactoring `option`

Now we can fully understand the connection between `option` and success / failure continuations.

Refactoring `option`

Now we can fully understand the connection between `option` and success / failure continuations.

First, notice that `A option` is the same as `unit + A`.

- ▶ `None` is represented by the `unit` in the left branch.

Refactoring `option`

Now we can fully understand the connection between `option` and success / failure continuations.

First, notice that `A option` is the same as `unit + A`.

- ▶ `None` is represented by the `unit` in the left branch.
- ▶ `Some x` holds a value `x : A` and that's in the right branch.

Refactoring option

1. *A* option

Refactoring option

1. A option
2. $(\text{unit} + A)$

Refactoring option

1. A option

2. $(\text{unit} + A)$

Since $A \text{ option} \cong \text{unit} + A$

Refactoring option

1. A option
2. $(\text{unit} + A)$
Since $A \text{ option} \cong \text{unit} + A$
3. $((\text{unit} + A) \rightarrow R) \rightarrow R$
by CPS conversion.

Refactoring option

1. A option
2. $(\text{unit} + A)$
Since $A \text{ option} \cong \text{unit} + A$
3. $((\text{unit} + A) \rightarrow R) \rightarrow R$
by CPS conversion.
4. $((\text{unit} \rightarrow R) * (A \rightarrow R)) \rightarrow R$

Refactoring option

1. A option
2. $(\text{unit} + A)$
Since $A \text{ option} \cong \text{unit} + A$
3. $((\text{unit} + A) \rightarrow R) \rightarrow R$
by CPS conversion.
4. $((\text{unit} \rightarrow R) * (A \rightarrow R)) \rightarrow R$
because $n^{k_1+k_2} = n^{k_1} \times n^{k_2}$.

Refactoring option

1. A option
2. $(\text{unit} + A)$
Since $A \text{ option} \cong \text{unit} + A$
3. $((\text{unit} + A) \rightarrow R) \rightarrow R$
by CPS conversion.
4. $((\text{unit} \rightarrow R) * (A \rightarrow R)) \rightarrow R$
because $n^{k_1+k_2} = n^{k_1} \times n^{k_2}$.
5. $(\text{unit} \rightarrow R) \rightarrow (A \rightarrow R) \rightarrow R$

Refactoring option

1. A option
2. $(\text{unit} + A)$
Since $A \text{ option} \cong \text{unit} + A$
3. $((\text{unit} + A) \rightarrow R) \rightarrow R$
by CPS conversion.
4. $((\text{unit} \rightarrow R) * (A \rightarrow R)) \rightarrow R$
because $n^{k_1+k_2} = n^{k_1} \times n^{k_2}$.
5. $(\text{unit} \rightarrow R) \rightarrow (A \rightarrow R) \rightarrow R$
by currying.