lecture 6

radiometry

(illumination and reflectance)

How bright is a light ray?



How much power passes through a thin tube centered on the ray?

Angle (radians)



θ radians $= \frac{\pi}{180} \times \theta$ degrees

$\approx 2 \arctan\left(\frac{B'C'}{2}\right)$

Solid Angle (steradians)



Ω steradians (maximum 4π)

Solid Angle of a Cone



$$\Omega \approx \frac{\text{area of base of cone}}{(\text{height of cone})^2}$$

The approximation is due to the fact that a flat disk has different area than a slightly curved disk

Solid angle



$$\Omega \approx \frac{\text{cross sectional area of tube}}{(\text{length of tube})^2}$$

Radiance (of a ray)



$$L(X, \vec{\ell}) \equiv \frac{\text{light power through tube}}{(\text{area } A) * (\text{solid angle } \Omega)}$$

Assume A, Ω are both small.

Surface Irradiance E(X)



How much light power arrives at X per unit area?

Irradiance E(x)



Contribution from direction $\vec{\ell}$ to irradiance at X must be weighted by $\vec{n} \cdot \vec{\ell}$ to account for foreshortening.



A unit area on the surface gives a cross sectional area of $\cos\theta = n \cdot \ell$ in the tube. (Only a slice through areas are shown.)

Irradiance $E(x)$



$$dE = L(x,\vec{\ell})\ \vec{n}(x)\cdot\vec{\ell}\ d\Omega$$

$$\therefore E(x) = \int_{\text{hemisphere}} L(x,\vec{\ell})\ \vec{n}(x)\cdot\vec{\ell}\ d\Omega$$

Example - Sunlight

$L(x,\ell)$ is very high in a small range of directions

$$E(x) = \int L(x,\vec{\ell})\ \vec{n}(x)\cdot\vec{\ell}\ d\Omega$$

$$\approx L_{sun}\ \vec{n}(x)\cdot\ell_{sun}\ \Omega_{sun}$$

Sunlight



$$E(x) \approx L_{sun}\ \Omega_{sun}\ \vec{n}(x)\cdot\vec{\ell}_{sun}$$

Example: skylight (disk) window



What is the irradiance $E(x)$ on the floor?



Assume

- radiance from sky is constant L_o as on an overcast (cloudy) day
- center of disk skylight is $(0,0,0)$
- height of room is f

What is $E(x,y)$ on the floor?



$$\therefore E(x,y) = \int L(x,y,\vec{\ell})\ \vec{n}(x,y)\cdot\vec{\ell}(x,y)\ d\Omega$$

$$\approx L_o\ n(x,y)\cdot\vec{\ell}(x,y)\ \Omega$$



$$E(x,y) \approx L_o\ n(x,y)\cdot\vec{\ell}(x,y)\ \Omega$$

$$\Omega = \underbrace{\frac{A_{disk}}{x^2+y^2+f^2}}_{\text{recall def}^n \text{ of solid angle of a cone}}\ \underbrace{\vec{n}\cdot\vec{\ell}}_{\text{foreshorten the source disk}}$$

$$\ell(x,y) = \frac{(-x,-y,-f)}{\sqrt{x^2+y^2+f^2}}$$

$$n(x,y) = (0,0,-1)$$

$$n\cdot\ell = \frac{f}{\sqrt{x^2+y^2+f^2}}$$

Thus,

$$E(x,y) \approx L_o\ A_{disk}\ \frac{(n\cdot\vec{\ell})^4}{f^2}$$

Reflected Light

incoming (incident)

outgoing (exitant)



plastic

brushed metal

velvet

skin

polish the apple
(change its reflectance)

leather



http://www.merl.com/brdf/

Modelling Surface Reflectance



How does light reflected in direction $\vec{l}_{out}$ depend on light arriving from direction $\vec{l}_{in}$?



$$E(x) = \int L(x,\vec{l})\, \vec{n}(x)\cdot\vec{l}\; d\Omega$$

$$L(x, l_{out}) = \int \rho(x, \vec{l}_{in}, \vec{l}_{out})\; L(x,\vec{l}_{in})\, \vec{n}(x)\cdot\vec{l}_{in}\; d\vec{l}_{in}$$

↑ called "bidirection reflectance distribution function" BRDF

* property of surface material only

BRDF's are heavily used in computer graphics

- Phong model (early 1970's)
- Ward model (early 1990's)
- BSSRDF (2001)
  - subsurface scattering in skin, marble

Special Case : Lambertian surface (matte)



$$L(x, l_{out}) = \int \rho(x, l_{in}, l_{out})\; L(x,\vec{l}_{in})\, \vec{n}(x)\cdot\vec{l}_{in}\; d\vec{l}_{in}$$

$$= \int \rho(x)\; L(x, l_{in})\, \vec{n}(x)\cdot\vec{l}_{in}\; d\vec{l}_{in}$$

Special Case

- Sunlight
- Lambertian reflectance



$$L(x, l_{out}) \approx c\cdot\rho(x)\; n(x)\cdot\vec{l}_{sun}$$