360 Logistics — Session Summary

Trucking Operations & Delivery Tracking · 21–23 September 2026

Repository: github.com/Mike-Rp/360-LOGISTICS-SYSTEM | **Branch:** main
Supabase project: yeyfmyojdlqtgoqlwhsv | **Final commit:** 14c2d12
Stack: React 18 + TypeScript + Tailwind v4 + Vite, Supabase (Postgres, Auth, Storage)

1. Problem solved — admin login was failing

Symptom: correct email and password were rejected with *"Invalid email or password."*

Actual cause: the Supabase API key had been invalidated server-side. Every request was refused before the password was ever checked:

```
GET /auth/v1/settings  →  401 Unauthorized
sb-error-code: UNAUTHORIZED_INVALID_API_KEY
{"message":"Invalid API key"}
```

The key *looked* valid — correct project ref, correct `anon` role, expiry in 2036 — but the project had moved to the newer publishable-key system, which retires legacy JWT keys.

Why the error message misled: `loginFailure()` in `src/app/lib/db.ts:104` treats any HTTP 401 as bad credentials, so an API-key problem was displayed as a wrong password.

> **Resolved**
> `.env.local` now holds the new `sb_publishable_...` key. Verified: the same endpoint returns 200.

2. System documented

Database — 10 tables

Table	Purpose
`profiles`	Staff logins. No row here means no admin access. Holds role (admin / csr / viewer) and the Operation Manager flag
`drivers`	Driver records and the link to their Auth account
`driver_pins`	Readable copy of the 4-digit PIN, admin/csr only
`trucks`	Fleet: plate, status, classification, capacity
`assignments`	The core table. One table replaces three former arrays; `state` = active / completed / cancelled
`assignment_documents`	The six required documents per delivery, with approval status
`status_photos`	Photo proof per stage, including real GPS coordinates
`delay_reports`	Pickup and delivery delay reasons
`notifications`	Admin inbox. Deliberately no foreign key, so it outlives deleted assignments
`activity_log`	Append-only audit trail. No UPDATE or DELETE policy exists — history cannot be rewritten

Column audit — six columns carry no meaning

All 94 columns are read and written by the app, but six never hold real data:

Column	Finding
`drivers.current_location`	Always the placeholder "—", yet it **is displayed** on the admin screen. GPS plumbing already exists in `status_photos`, so this feature is roughly 90% built
`drivers.deliveries_today`	Set to 0 at registration, never incremented, never displayed
`drivers.rating`	Same — 0 forever
`profiles.is_demo`	Read into the session, then referenced by zero components
`profiles.invited_at`	Mapped but never rendered
`drivers.shift`	Two help screens instruct users to enter a shift, but the registration form has no shift field at all

3. Login screen redesigned

One file changed: `src/app/components/auth/LoginScreen.tsx` (+126 / -26). All authentication logic, Supabase calls, validation and routing left untouched.

- **Removed** the blue "Admin Login" and "Back" footer buttons and their divider
- **Added** a segmented Driver / Admin toggle below the logo, reusing the exact state resets of the buttons it replaced

- **Added** a "Reset PIN" dialog — floating, responsive, with the dispatch number as a tap-to-dial link, dismissible by button, backdrop or Escape
- **Updated** the subtitle and the admin email placeholder

> **No reset flow was invented**
> Drivers cannot reset their own PIN anywhere in this system — only an admin can regenerate one. The dialog is informational for that reason. The dispatch number lives in two constants, `DISPATCH_TEL` and `DISPATCH_DISPLAY`, at the top of the file.
> **Confirm 0938 403 3610 is the real line.**

4. Shipped to production

Commit	Contents
`6e3a53f`	Login screen redesign (the work above)
`948bb80`	Truck registration redesign, archiving, edit/cancel, deliveries sort, modals
`14c2d12`	New admin dashboard, DM Sans font, unified status colours, sidebar logo

The `dashboard-redesign` branch (62 files, +2,858 lines) was pulled, merged into `main` as a clean fast-forward, and pushed. Typecheck and production build both pass.

5. Database migrations applied

Both were applied by hand in the Supabase SQL editor and verified — the check returned all 11 expected rows (5 columns, 6 functions).

Migration	Unlocks
`20260923000000_assignment_edit_cancel.sql`	Edit and Cancel a delivery from the Monitor page
`20260924000000_archive_drivers_trucks.sql`	Archive drivers and trucks instead of deleting them; set a new driver PIN

Why these had to be database functions, not ordinary saves: the admin auto-save writes whatever changed in the browser, seconds later, and cannot ask "is this delivery *still* Assigned?" at the moment it writes. A stale tab could therefore rewrite a delivery the driver had already picked up. These functions lock the row, check its status and write in one step.

Password re-entry required

Three actions demand the password again within 5 minutes — enforced in the database, not just the UI, so bypassing the interface does not help:

Action	Password required
Edit delivery details	Yes
Archive a driver	Yes
Set a new driver PIN	Yes
Cancel a delivery	No — guarded by status instead
Archive a truck	No — deliberate

6. Security review

Passwords are hashed. Staff passwords and driver PINs are stored in Supabase Auth as bcrypt hashes via `crypt(password, gen_salt('bf'))`. The plaintext is never stored.

Two exceptions found:

- `driver_pins.pin` keeps a readable copy of the 4-digit PIN so admins can help a driver who forgot it. Deliberate, restricted to admin/csr, and of limited consequence since a 4-digit PIN is guessable regardless.
- `supabase/functions/server/index.tsx` — the dead legacy edge function — contains three **plaintext administrator passwords**, committed to the repository.

> **Action required**
> Those passwords are in the repository and in its git history. Deleting the file removes them from the current code but
> **not**
> from past commits. If any of them are still live on a real account, change the passwords — that matters far more than deleting the file.

7. Outstanding items

○ **Set the Supabase key on Vercel.** The live site still holds the old, rejected key, so nobody can sign in there. Set `VITE_SUPABASE_ANON_KEY` to the new publishable key and redeploy — Vite bakes these in at build time, so changing the variable alone does nothing.

○ **Confirm the dispatch number** shown to every driver in the Reset PIN dialog.

○ **Change the three exposed passwords** if any remain in use.

○ **Delete the legacy files** — `supabase/functions/server/index.tsx`, `supabase/functions/server/kv_store.tsx` and `supabase/config.toml` (which points at the old project and at a file being deleted). Optionally the nine files under `html-php-version/`. Do not touch `supabase/migrations/`, or `BUCKET` in `db.ts` — that is the live storage bucket.

○ **Test locally** — particularly setting a new PIN and then logging in as that driver, which exercises the new database function end to end.

8. Verified along the way

✓ TypeScript typecheck passes with no errors

✓ Production build succeeds (1,728 modules)

- ✓ Supabase API key accepted — 401 became 200
- ✓ Both migrations confirmed present in the live database
- ✓ Only intended files changed; `.env.local` is git-ignored and was never uploaded

---