

Xcode Build Setting Reference

Contents

Introduction 8

Build Setting Reference 11

Product Information Build Settings 11

- ARCHS (Architectures) 11
- DYLIB_COMPATIBILITY_VERSION (Compatibility Version) 11
- DYLIB_CURRENT_VERSION (Current Library Version) 12
- GENERATE_PKGINFO_FILE (Force Package Info Generation) 12
- MACH_O_TYPE 12
- PRODUCT_NAME 13
- PROJECT_NAME 13
- TARGET_NAME 13
- VALID_ARCHS (Valid Architectures) 14

Build Properties Build Settings 14

- ACTION 14
- BUILD_COMPONENTS 15
- BUILD_VARIANTS (Build Variants) 15
- COMPRESS_PNG_FILES (Compress .png files) 16
- CONFIGURATION 16
- CURRENT_ARCH 16
- CURRENT_VARIANT 16
- DEBUG_INFORMATION_FORMAT (Debug Information Format) 17
- DEPLOYMENT_POSTPROCESSING (Deployment Postprocessing) 17
- ENABLE_HEADER_DEPENDENCIES 18
- NATIVE_ARCH 18
- ONLY_ACTIVE_ARCH (Build Active Architecture Only) 18
- PATH_PREFIXES_EXCLUDED_FROM_HEADER_DEPENDENCIES 19
- RETAIN_RAW_BINARIES 19
- STRINGS_FILE_OUTPUT_ENCODING 19
- TARGETED_DEVICE_FAMILY (Targeted Device Family) 19
- VALIDATE_PRODUCT (Validate Built Product) 20

Build and Product Location Build Settings 20

- BUILT_PRODUCTS_DIR 20
- CACHE_ROOT 21

CONFIGURATION_BUILD_DIR (Per-Configuration Build Products Path)	21
CONFIGURATION_TEMP_DIR (Per-Configuration Intermediate File Path)	21
DEPLOYMENT_LOCATION (Deployment Location)	22
DERIVED_FILE_DIR	22
DSTROOT (Installation Build Products Location)	22
INSTALL_DIR	23
INSTALL_PATH (Installation Directory)	23
OBJECT_FILE_DIR	24
OBJECT_FILE_DIR_<VARIANT>	24
OBJROOT (Intermediate Build Files Path)	25
PROJECT_TEMP_DIR	25
REZ_COLLECTOR_DIR	25
REZ_OBJECTS_DIR	26
SDKROOT (Base SDK)	26
SHARED_PRECOMPS_DIR (Precompiled Headers Cache Path)	26
SKIP_INSTALL	27
SRCROOT	27
SYMROOT (Build Products Path)	27
TARGET_BUILD_DIR	28
TARGET_TEMP_DIR	29
Header-Map Build Settings	29
HEADERMAP_INCLUDES_FLAT_ENTRIES_FOR_TARGET_BEING_BUILT	30
HEADERMAP_INCLUDES_FRAMEWORK_ENTRIES_FOR_ALL_PRODUCT_TYPES	30
HEADERMAP_INCLUDES_PROJECT_HEADERS	30
C/C++ Compiler Build Settings	31
ALWAYS_SEARCH_USER_PATHS (Always Search User Paths)	31
FRAMEWORK_SEARCH_PATHS (Framework Search Paths)	31
GCC_AUTO_VECTORIZATION (Auto-Vectorization)	32
GCC_CW_ASM_SYNTAX (CodeWarrior-Style Inline Assembly)	32
GCC_DEBUGGING_SYMBOLS (Level of Debug Symbols)	32
GCC_DYNAMIC_NO_PIC	33
GCC_ENABLE_CPP_EXCEPTIONS (Enable C++ Exceptions)	33
GCC_ENABLE_CPP_RTTI (Enable C++ Runtime Types)	33
GCC_ENABLE_FIX_AND_CONTINUE (Fix & Continue)	34
GCC_ENABLE_OBJC_EXCEPTIONS (Enable Objective-C Exceptions)	34
GCC_ENABLE_OBJC_GC (Objective-C Garbage Collection)	34
GCC_ENABLE_SSE3_EXTENSIONS (Enable SSE3 Extensions)	35
GCC_ENABLE_SSE41_EXTENSIONS (Enable SSE4.1 Extensions)	35
GCC_ENABLE_SSE42_EXTENSIONS (Enable SSE4.2 Extensions)	35

GCC_ENABLE_SYMBOL_SEPARATION (Separate PCH Symbols)	35
GCC_FEEDBACK_DIRECTED_OPTIMIZATION (Feedback-Directed Optimization)	36
GCC_GENERATE_DEBUGGING_SYMBOLS (Generate Debug Symbols)	36
GCC_MODEL_TUNING (Instruction Scheduling)	37
GCC_OBJC_CALL_CXX_CDTORS (Call C++ Default Ctors/Dtors in Objective-C)	37
GCC_OPTIMIZATION_LEVEL (Optimization Level)	37
GCC_PRECOMPILE_PREFIX_HEADER (Precompile Prefix Header)	38
GCC_PREFIX_HEADER	38
GCC_PREPROCESSOR_DEFINITIONS (Preprocessor Macros)	38
GCC_PREPROCESSOR_DEFINITIONS_NOT_USED_IN_PRECOMPS (Preprocessor Macros Not Used In Precompiled Headers)	39
GCC_SYMBOLS_PRIVATE_EXTERN (Symbols Hidden by Default)	39
GCC_THREADSAFE_STATICS (Statics are Thread Safe)	40
GCC_UNROLL_LOOPS (Unroll Loops)	40
GCC_USE_NASM_FOR_ASM_FILETYPE (Use nasm to Process .asm Files)	40
GCC_VERSION	40
GCC_VERSION_IDENTIFIER	41
GCC_WARN_ABOUT_GLOBAL_CONSTRUCTORS (Global Construction or Destruction Required)	41
GCC_WARN_ABOUT_RETURN_TYPE (Mismatched Return Type)	42
GCC_WARN_UNUSED_VARIABLE (Unused Variables)	42
GCC_WARN_EFFECTIVE_CPLUSPLUS_VIOLATIONS (Effective C++ Violation)	42
GCC_WARN_HIDDEN_VIRTUAL_FUNCTIONS (Hidden Virtual Functions)	42
GCC_WARN_INHIBIT_ALL_WARNINGS (Inhibit All Warnings)	43
GCC_WARN_NON_VIRTUAL_DESTRUCTOR (Nonvirtual Destructor)	43
GCC_WARN_PEDANTIC (Pedantic Warnings)	43
GCC_WARN_SHADOW (Hidden Local Variables)	44
GCC_WARN_SIGN_COMPARE (Sign Comparison)	44
HEADER_SEARCH_PATHS (Header Search Paths)	44
INFOPLIST_OTHER_PREPROCESSOR_FLAGS (Info.plist Other Preprocessor Flags)	45
INFOPLIST_PREFIX_HEADER (Info.plist Preprocessor Prefix File)	45
INFOPLIST_PREPROCESS (Preprocess Info.plist File)	45
INFOPLIST_PREPROCESSOR_DEFINITIONS (Info.plist Preprocessor Definitions)	45
IPHONEOS_DEPLOYMENT_TARGET (iOS Deployment Target)	46
MACOSX_DEPLOYMENT_TARGET (OS X Deployment Target)	46
OTHER_CFLAGS (Other C Flags)	47
OTHER_CFLAGS_<VARIANT>	47
OTHER_CPLUSPLUSFLAGS (Other C++ Flags)	48
USER_HEADER_SEARCH_PATHS (User Header Search Paths)	48
WARNING_CFLAGS (Other Warning Flags)	49

Interface Builder Compiler Build Settings	49
IBC_FLATTEN_NIBS (Flatten Compiles XIB Files)	49
IBC_OTHER_FLAGS (Other Interface Builder Compiler Flags)	49
IBC_OVERRIDING_PLUGINS_AND_FRAMEWORKS_DIR (Overriding Plug-In and Framework Directory)	50
IBC_PLUGIN_SEARCH_PATHS (Plug-In Search Paths)	50
IBC_PLUGINS (Plug-Ins)	50
IBC_ERRORS (Show Errors)	50
IBC_NOTICES (Show Notices)	50
IBC_WARNINGS (Show Warnings)	51
Linker Build Settings	51
DEAD_CODE_STRIPPING (Dead Code Stripping)	51
EXPORTED_SYMBOLS_FILE (Exported Symbols File)	52
KEEP_PRIVATE_EXTERNS (Preserve Private External Symbols)	52
LD_DYLIB_INSTALL_NAME (Dynamic Library Install Name)	52
LD_RUNPATH_SEARCH_PATHS (Runpath Search Paths)	52
LIBRARY_SEARCH_PATHS	53
LINK_WITH_STANDARD_LIBRARIES (Link With Standard Libraries)	53
LINKER_DISPLAYS_FILE_FOR_UNDEFINED_SYMBOLS (Verbose Undefined Symbols Info)	53
LINKER_DISPLAYS_MANGLED_NAMES (Display Mangled Names)	54
OTHER_LDFLAGS (Other Linker Flags)	54
OTHER_LDFLAGS_<VARIANT>	54
PREBINDING (Prebinding)	55
PRESERVE_DEAD_CODE_INITS_AND_TERMS (Don't Dead-Strip Inits and Terms)	55
STANDARD_C_PLUS_PLUS_LIBRARY_TYPE (C++ Standard Library Type)	55
STRIP_INSTALLED_PRODUCT (Strip Linked Product)	56
STRIP_STYLE (Strip Style)	56
UNEXPORTED_SYMBOLS_FILE (Unexported Symbols File)	56
Product Layout Build Settings	57
CONTENTS_FOLDER_PATH	57
INFOPLIST_FILE	57
INFOPLIST_OUTPUT_FORMAT	58
INFOPLIST_PATH	58
INFOSTRINGS_PATH	58
FRAMEWORKS_FOLDER_PATH	58
GENERATE_PKGINFO_FILE	59
DOCUMENTATION_FOLDER_PATH	59
EXECUTABLES_FOLDER_PATH	59
EXECUTABLE_EXTENSION	59
EXECUTABLE_FOLDER_PATH	60

EXECUTABLE_NAME	60
EXECUTABLE_PATH	60
EXECUTABLE_PREFIX	61
EXECUTABLE_SUFFIX	61
PACKAGE_TYPE	61
PLUGINS_FOLDER_PATH	62
PRIVATE_HEADERS_FOLDER_PATH	62
PKGINFO_FILE_PATH	62
PUBLIC_HEADERS_FOLDER_PATH	62
SCRIPTS_FOLDER_PATH	63
SHARED_FRAMEWORKS_FOLDER_PATH	63
UNLOCALIZED_RESOURCES_FOLDER_PATH	63
WRAPPER_EXTENSION (Wrapper Extension)	63
WRAPPER_NAME	64
WRAPPER_SUFFIX	64
Code Signing Build Settings	64
CODE_SIGN_ENTITLEMENTS (Code Signing Entitlements)	65
CODE_SIGN_IDENTITY (Code Signing Identity)	65
CODE_SIGN_RESOURCE_RULES_PATH (Code Signing Resource Rules Path)	65
OTHER_CODE_SIGN_FLAGS (Other Code Signing Flags)	65
Copy Build Settings	65
COPY_PHASE_STRIP (Strip Debug Symbols During Copy)	65
INSTALLHDRS_COPY_PHASE	66
INSTALLHDRS_SCRIPT_PHASE	66
REMOVE_CVS_FROM_RESOURCES	66
REMOVE_SVN_FROM_RESOURCES	67
VERBOSE_PBXCP	67
User Location Build Settings	67
HOME	67
USER_LIBRARY_DIR	68
System Location Build Setting	68
SYSTEM_LIBRARY_DIR	68

Document Revision History 69

Objective-C 7

Index 73

Objective-CSwift

Introduction

Xcode uses build settings to specify aspects of the build process followed to generate a product. A build setting is a variable that determines how build tasks are performed.

You can customize most of the build settings listed in this document using the target and product editors in the Xcode application, configuration files, and `xcodebuild` invocations. However, there are build settings that can be customized only through indirect means and build settings that are not customizable. Build settings that are not customizable do not have a “Default value” entry in their reference.

In addition, Xcode lets you assign conditional values to build settings. The conditions include build factors such as the architecture you’re targeting and the SDK you’re using. Build settings with conditional values are known as *conditional build settings*.

This document is intended for developers who need to get a deep understanding of how the Xcode build system works.

To fully understand how a target’s build settings affect a build and how they relate to one another, this document uses the following terms to describe each build setting and the build settings that relate to it.

Alias

Additional name used to identify a build setting.

bundle file path or bundle directory path

String that represents a location inside a bundled product. See *Bundle Programming Guide* for information on product bundles.

C-based language

C, C++, Objective-C, and Objective-C++.

C++-based language

C++, and Objective-C++.

Companion

Build settings that are used in conjunction with the referring build setting to accomplish its action. If you customize the referring build setting, you should review the specifications of its companion build settings.

Default value

The buildtime value of a build setting when there’s no corresponding setting specification for the target.

Effector

Build setting whose value is used to compute the default value of the referring build setting.

Effect

Build setting whose default value is computed using the value of the referring build setting.

file path or directory path

String that represents a fully qualified filesystem path. When a path contains spaces, the path must be surrounded by single quotation marks (') or double quotation marks ("), or the spaces must be escaped with a backslash (\).

filename

String that may contain numbers, letters, dashes (-), periods (.) or underscores (_).

identifier

String that may contain digits, letters, dashes (-), plus signs (+), and underscores (_).

installed product

A product configured for distribution to its users.

installed product directory

Directory that represents the root directory (/) on a user's computer.

number

String that may contain only digits.

numeric identifier

String that may contain numbers and periods.

option specification

String that may contain the characters an identifier may contain as well as spaces. When an option specification contains spaces, it must be surrounded by single quotation marks (') or double quotation marks (").

Prerequisite

Expression that must be true for the referring build setting to take effect.

Prerequisite for

The referring build setting's value allows or suppresses the behavior specified by the referred build setting.

project file path or project directory path

String that represents a location inside a project directory.

Related to

Build setting with a conceptual relationship with the referring build setting except for prerequisites, companions, effects, and effectors.

uniform type identifier (UTI)

String that specifies a type. This string uses the reverse-DNS (Domain Name System) to uniquely identify an item in a way that other systems can recognize. See *Uniform Type Identifiers Overview* for details on uniform type identifiers.

Value

Value of a build setting at build time. This is not necessarily the build setting specification. See *Build Settings* for details.

This document assumes that all the Xcode SDKs are installed on your computer.

If you develop products using C++, you may need to customize these build settings in your targets:

- [GCC_ENABLE_CPP_EXCEPTIONS \(Enable C++ Exceptions\)](#) (page 33)
- [GCC_ENABLE_CPP_RTTI \(Enable C++ Runtime Types\)](#) (page 33)
- [GCC_WARN_EFFECTIVE_CPLUSPLUS_VIOLATIONS \(Effective C++ Violation\)](#) (page 42)
- [GCC_WARN_HIDDEN_VIRTUAL_FUNCTIONS \(Hidden Virtual Functions\)](#) (page 42)
- [GCC_WARN_NON_VIRTUAL_DESTRUCTOR \(Nonvirtual Destructor\)](#) (page 43)
- [OTHER_CPLUSPLUSFLAGS \(Other C++ Flags\)](#) (page 48)
- [LINKER_DISPLAYS_MANGLED_NAMES \(Display Mangled Names\)](#) (page 54)
- [STANDARD_C_PLUS_PLUS_LIBRARY_TYPE \(C++ Standard Library Type\)](#) (page 55)

Use these build settings to customize your debugging experience:

- [BUILD_VARIANTS \(Build Variants\)](#) (page 15)
- [DEBUG_INFORMATION_FORMAT \(Debug Information Format\)](#) (page 17)
- [GCC_DEBUGGING_SYMBOLS \(Level of Debug Symbols\)](#) (page 32)
- [GCC_GENERATE_DEBUGGING_SYMBOLS \(Generate Debug Symbols\)](#) (page 36)
- [DEAD_CODE_STRIPPING \(Dead Code Stripping\)](#) (page 51)
- [PRESERVE_DEAD_CODE_INITS_AND_TERMS \(Don't Dead-Strip Inits and Terms\)](#) (page 55)
- [STRIP_STYLE \(Strip Style\)](#) (page 56)

The following sections describe build settings you can use to customize a build or to inquire about a the configuration of a build at build time.

Build Setting Reference

SwiftObjective-C

Product Information Build Settings

These build settings specify properties of the product the target builds.

ARCHS (Architectures)

Description:	Space-separated list of identifiers. Specifies the architectures (ABIs, processor models) to which the binary is targeted. When this build setting specifies more than one architecture, the generated binary may contain object code for each of the specified architectures.
Values:	See VALID_ARCHS (Valid Architectures) (page 14).
Effector:	NATIVE_ARCH (page 18).
Default value:	\$NATIVE_ARCH
Example value:	ppc i386
Companion:	VALID_ARCHS (Valid Architectures) (page 14), ONLY_ACTIVE_ARCH (Build Active Architecture Only) (page 18).
Prerequisite for:	PREBINDING (Prebinding) (page 55).

DYLIB_COMPATIBILITY_VERSION (Compatibility Version)

Description:	Number. Specifies the compatibility version of a dynamic library product. See Dynamic Library Design Guidelines in <i>Dynamic Library Programming Topics</i> for details on assigning version numbers of dynamic libraries.
Default value:	1
Companion:	DYLIB_CURRENT_VERSION (Current Library Version) (page 12).

DYLIB_CURRENT_VERSION (Current Library Version)

Description:	Number. Specifies the current version of a dynamic library product. See “Dynamic Library Design Guidelines” in <i>Dynamic Library Programming Topics</i> for details on assigning version numbers of dynamic libraries.
Default value:	1
Companions:	DYLIB_COMPATIBILITY_VERSION (Compatibility Version) (page 11).

GENERATE_PKGINFO_FILE (Force Package Info Generation)

Description:	Boolean value. Specifies whether to generate the product’s package information file. For details on the package information file, see “Additional Configuration Tips” in <i>Runtime Configuration Guidelines</i> .
Values:	<ul style="list-style-type: none">• YES: Generates the product’s package information file.• NO: Does not generate the product’s package information file.
Default value:	<ul style="list-style-type: none">• YES: In application targets.• NO: In other target types.
Companions:	PKGINFO_FILE_PATH (page 62).

MACH_O_TYPE

Description:	Identifier. Specifies the binary’s type. For information on binary types, see “Building Mach-O Files” in <i>Mach-O Programming Topics</i> .
Effector:	Target type, specified at the time the target is created.
Default value:	<ul style="list-style-type: none">• <code>mh_executable</code>: Executable binary. Application, command-line tool, and kernel extension target types.• <code>mh_bundle</code>: Bundle binary. Bundle and plug-in target types.• <code>mh_object</code>: Relocatable object file.• <code>mh_dylib</code>: Dynamic library binary. Dynamic library and framework target types.• <code>staticlib</code>: Static library binary. Static library target types.

Affects:	GCC_ENABLE_SYMBOL_SEPARATION (Separate PCH Symbols) (page 35), EXECUTABLE_EXTENSION (page 59).
Specified in:	New Project Assistant, New Target Assistant.

PRODUCT_NAME

Description:	Identifier. Specifies the name of the product the target builds.
Default value:	The name of the target at the time it was created.
Example value:	MyProduct
Affects:	EXECUTABLE_NAME (page 60), WRAPPER_NAME (page 64).

PROJECT_NAME

Description:	Identifier. Specifies the name of the project that defines the target.
Default value:	The name of the project at the time it was created.
Example value:	MyProject
Affects:	DSTROOT (Installation Build Products Location) (page 22), PROJECT_TEMP_DIR (page 25).
Specified in:	Project navigator.

TARGET_NAME

Description:	Identifier. Identifies the target being processed.
Default value:	The name of the target at the time it was created.
Example value:	MyProduct
Affects:	TARGET_TEMP_DIR (page 29).
Specified in:	New Project Assistant.

VALID_ARCHS (Valid Architectures)

Description:	Space-separated list of identifiers. Specifies the architectures for which the binary may be built. During the build, this list is intersected with the value of ARCHS build setting; the resulting list specifies the architectures the binary can run on. If the resulting architecture list is empty, the target generates no binary.
Default value:	m68k i386 sparc hppa ppc ppc7400 ppc970 ppc64 x86_64 armv6 armv7
Affects:	CURRENT_ARCH (page 16).
Companion:	ARCHS (Architectures) (page 11).

Build Properties Build Settings

These build settings specify properties of a build performed by a target.

ACTION

Description:	Identifier. Identifies the type of build to perform on the target.
Values:	<ul style="list-style-type: none"><code>build</code>: Build the product and place it in the product build directory (<code>CONFIGURATION_BUILD_DIR</code>).<code>clean</code>: Remove the product and build files in the product build directory (<code>CONFIGURATION_BUILD_DIR</code>) and the intermediate build files directory (<code>CONFIGURATION_TEMP_DIR</code>).<code>install</code>: Build the product and place it in its installation destination (<code>INSTALL_PATH</code>).<code>installhdrs</code>: Copy the product's public and private header files into the public headers directory (<code>PUBLIC_HEADERS_FOLDER_PATH</code>) and the private headers directory (<code>PRIVATE_HEADERS_FOLDER_PATH</code>), respectively.<code>installsrc</code>: Copy the target's source files into the project directory (<code>SRCROOT</code>).
Default value:	<code>build</code> : In <code>xcodebuild</code> invocations.
Affects:	BUILD_COMPONENTS (page 15), DEPLOYMENT_POSTPROCESSING (Deployment Postprocessing) (page 17), DEPLOYMENT_LOCATION (Deployment Location) (page 22).

Companions:	CONFIGURATION_BUILD_DIR (Per-Configuration Build Products Path) (page 21), CONFIGURATION_TEMP_DIR (Per-Configuration Intermediate File Path) (page 21), INSTALL_DIR (page 23), SRCROOT (page 27), PRIVATE_HEADERS_FOLDER_PATH (page 62), PUBLIC_HEADERS_FOLDER_PATH (page 62), INSTALLHDRS_COPY_PHASE (page 66).
Specified in:	<ul style="list-style-type: none">Xcode application: Product menu.xcodebuild: <build_action> argument.

BUILD_COMPONENTS

Description:	Space-separated list of identifiers. Specifies subsets of the product.
Effectors:	ACTION (page 14)
Value:	<ul style="list-style-type: none">headers build: When <code>\$ACTION = build</code> or <code>\$ACTION = install</code>,headers: When <code>\$ACTION = installhdrs</code>,<i>Empty</i>: When <code>\$ACTION = installsrc</code>.

BUILD_VARIANTS (Build Variants)

Description:	Space-separated list of identifiers. Specifies the binary variants of the product. You can create additional variant names for special purposes. For example, you can use the name of a build configuration as a variant name to create highly customized binaries.
Values:	<ul style="list-style-type: none"><code>normal</code>: Use to produce a normal binary.<code>profile</code>: Use to produce a binary that generates profile information.<code>debug</code>: Use to produce a binary with debug symbols, additional assertions, and diagnostic code.
Default value:	<code>normal</code>
Affects:	CURRENT_VARIANT (page 16), OBJECT_FILE_DIR_<VARIANT> (page 24), OTHER_CFLAGS_<VARIANT> (page 47).

COMPRESS_PNG_FILES (Compress .png files)

Description:	Boolean value. Specifies whether to compress PNG files that are resources of the active target as they are copied to the application bundle. This applies only to iOS applications.
Values:	<ul style="list-style-type: none">YES: PNG files (those with the .png suffix) are compressed as they're copied to the application bundle.NO: No PNG compression takes place.
Default value:	YES

CONFIGURATION

Description:	Identifier. Identifies the build configuration (for example, Debug or Release) the target uses to generate the product.
Values:	Debug, Release, and custom build configuration names.
Affects:	CURRENT_VARIANT (page 16), CONFIGURATION_BUILD_DIR (Per-Configuration Build Products Path) (page 21), CONFIGURATION_TEMP_DIR (Per-Configuration Intermediate File Path) (page 21).
Specified in:	<ul style="list-style-type: none">Schema > Build phase.<code>xcodebuild -configuration</code>.

CURRENT_ARCH

Description:	Identifier. Identifies the architecture on which the build is being performed.
Values:	See ARCHS (Architectures) (page 11).
Example value:	i386
Same as:	NATIVE_ARCH (page 18).

CURRENT_VARIANT

Description:	Identifier. Identifies the build variant being processed.
--------------	---

Effectors:	BUILD_VARIANTS (Build Variants) (page 15), CONFIGURATION (page 16).
Value:	<ul style="list-style-type: none">• <code>\$CONFIGURATION</code>: When <code>\$CONFIGURATION</code> IN <code>\$BUILD_VARIANTS</code>.• <code>normal</code>: Is the alternative.
Example values:	<ul style="list-style-type: none">• <code>debug</code>: <code>\$CONFIGURATION = debug</code> AND <code>\$BUILD_VARIANTS = debug</code> profile.• <code>normal</code>: <code>\$CONFIGURATION = release</code> AND <code>\$BUILD_VARIANTS = debug</code> profile.

DEBUG_INFORMATION_FORMAT (Debug Information Format)

Description:	Identifier. Identifies the format used to store the binary's debug information.
Values:	<ul style="list-style-type: none">• <code>stabs</code>: Use the Stabs format and place the debug information in the binary.• <code>dwarf</code>: Use the DWARF format and place the debug information in the binary.• <code>dwarf-with-dsym</code>: Use the DWARF format and place the debug information in a dSYM file.
Default value:	<code>dwarf</code>
Prerequisite for:	GCC_ENABLE_SYMBOL_SEPARATION (Separate PCH Symbols) (page 35).

DEPLOYMENT_POSTPROCESSING (Deployment Postprocessing)

Description:	Boolean value. Specifies whether the binary receives deployment postprocessing. Deployment postprocessing involves stripping the binary, and setting its file mode, owner, and group.
Effectors:	ACTION (page 14).
Values:	<ul style="list-style-type: none">• <code>YES</code>: Binary receives deployment postprocessing.• <code>NO</code>: Binary does not receive deployment postprocessing.
Default value:	<ul style="list-style-type: none">• <code>YES</code>: When <code>\$ACTION = install</code>.• <code>NO</code>: Is the alternative.
Prerequisite for:	STRIP_INSTALLED_PRODUCT (Strip Linked Product) (page 56).

ENABLE_HEADER_DEPENDENCIES

Description:	Boolean value. Specifies whether data gathered from header-file scans is used in the build process.
Values:	<ul style="list-style-type: none">• YES: The build uses data gathered from header-file scans.• NO: The build does not use data gathered from header-file scans.
Default value:	YES
Companion:	PATH_PREFIXES_EXCLUDED_FROM_HEADER_DEPENDENCIES (page 19).

NATIVE_ARCH

Description:	Identifier. Identifies the architecture on which the build is being performed (same as CURRENT_ARCH).
Values:	See ARCHS (Architectures) (page 11).
Example value:	i386
Same as:	CURRENT_ARCH (page 16).
Companion:	ONLY_ACTIVE_ARCH (Build Active Architecture Only) (page 18).

ONLY_ACTIVE_ARCH (Build Active Architecture Only)

Description:	Boolean value. Specifies whether the product includes only object code for the native architecture.
Values:	<ul style="list-style-type: none">• YES: The product includes only code for the native architecture (NATIVE_ARCH (page 18)).• NO: The product includes code for the architectures specified in ARCHS (Architectures) (page 11).
Default value:	NO

PATH_PREFIXES_EXCLUDED_FROM_HEADER_DEPENDENCIES

Description:	Space-separated list of directory paths. Identifies the directories to exclude from header-file scans when the build uses header-file dependencies.
Default value:	<code>/usr/include /usr/local/include /System/Library/Frameworks /System/Library/PrivateFrameworks /Developer/Headers</code>
Companions:	ENABLE_HEADER_DEPENDENCIES (page 18).

RETAIN_RAW_BINARIES

Description:	Boolean value. Specifies whether the binary is stripped.
Values:	<ul style="list-style-type: none">• YES: Binary is not stripped.• NO: Binary is stripped.
Default value:	NO
Affects:	BUILT_PRODUCTS_DIR (page 20).
Companion:	DEPLOYMENT_LOCATION (Deployment Location) (page 22).
Related to:	SKIP_INSTALL (page 27).

STRINGS_FILE_OUTPUT_ENCODING

Description:	Identifier. Specifies the output encoding for strings files.
Values:	<ul style="list-style-type: none">• UTF-8• UTF-16
Default value:	UTF-16

TARGETED_DEVICE_FAMILY (Targeted Device Family)

Description:	Comma-separated list of numeric identifiers. Specifies the device families on which the product must be capable of running.
--------------	---

Identifiers:	<ul style="list-style-type: none">• 1: iPhone/iPod touch.• 2: iPad.
Default value:	1
Example value:	1, 2

VALIDATE_PRODUCT (Validate Built Product)

Description:	Boolean value. Specifies whether to run product-validation tests.
Values:	<ul style="list-style-type: none">• YES: The build runs validation tests on the generated product.• NO: The build does not run validation tests on the generated product.
Default value:	NO

Build and Product Location Build Settings

These build settings identify filesystem locations used by the build process as well as locations that specify where product files are placed.

BUILT_PRODUCTS_DIR

Description:	Directory path. Identifies the directory under which all the product's files can be found. This directory contains either product files or symbolic links to them. Run Script build phases can use the value of this build setting as a convenient way to refer to the product files built by one or more targets even when these files are scattered throughout a directory hierarchy (for example, when <code>DEPLOYMENT_LOCATION</code> is set to YES).
Effectors:	RETAIN_RAW_BINARIES (page 19), CONFIGURATION_BUILD_DIR (Per-Configuration Build Products Path) (page 21), DEPLOYMENT_LOCATION (Deployment Location) (page 22).
Value:	<ul style="list-style-type: none">• <code>\$SYMROOT/BuiltProducts</code>: When <code>DEPLOYMENT_LOCATION = YES</code> AND <code>RETAIN_RAW_BINARIES = YES</code>,• <code>\$CONFIGURATION_BUILD_DIR</code>: Is the alternative.

CACHE_ROOT

Description:	File path. Identifies the file used to cache build-time information that must persist between launches of the Xcode application.
Value:	<code>/var/folders/<some_directory>/com.apple.Xcode.<user_id></code>
Example value:	<code>/var/folders/Aq/AqPz2MexGfqyTWrWDAVs0E++12Q/-Caches-/com.apple.Xcode.501</code>
Affects:	SHARED_PRECOMPS_DIR (Precompiled Headers Cache Path) (page 26).
Alias:	CCHR00T

CONFIGURATION_BUILD_DIR (Per-Configuration Build Products Path)

Description:	Directory path. Identifies the directory under which all build-related files for the active build configuration are placed.
Effectors:	CONFIGURATION (page 16), SYMROOT (Build Products Path) (page 27).
Default value:	<code>\$SYMROOT/\$CONFIGURATION</code>
Example value:	<code>/Users/genica/MyProject/build/Debug</code>
Affects:	BUILT_PRODUCTS_DIR (page 20), TARGET_BUILD_DIR (page 28), TARGET_TEMP_DIR (page 29).

CONFIGURATION_TEMP_DIR (Per-Configuration Intermediate File Path)

Description:	Directory path. Identifies the directory that holds temporary files for the active build configuration.
Effectors:	CONFIGURATION (page 16), PROJECT_TEMP_DIR (page 25).
Default value:	<code>\$PROJECT_TEMP_DIR/\$CONFIGURATION</code>
Example value:	<code>/Users/genica/MyProject/build/MyProject.build/Debug</code>
Affects:	TARGET_TEMP_DIR (page 29).

DEPLOYMENT_LOCATION (Deployment Location)

Description:	Boolean value. Specifies whether product files are placed in the installation (specified by <code>DSTROOT</code>) or the build directory (identified by <code>SYMROOT</code>).
Effector:	ACTION (page 14).
Values:	<ul style="list-style-type: none">YES: Product files are placed in <code>\$DSTROOT</code>.NO: Product files are placed in <code>\$SYMROOT</code>.
Default value:	<ul style="list-style-type: none">YES: When <code>\$ACTION = install</code>.NO: Is the alternative.
Affects:	TARGET_BUILD_DIR (page 28).
Companions:	DSTROOT (Installation Build Products Location) (page 22), SYMROOT (Build Products Path) (page 27),.
Related to:	RETAIN_RAW_BINARIES (page 19), BUILT_PRODUCTS_DIR (page 20), SKIP_INSTALL (page 27).

DERIVED_FILE_DIR

Description:	Directory path. Identifies the directory into which derived source files—such as those generated by <code>lex</code> and <code>yacc</code> —are placed.
Effectors:	TARGET_TEMP_DIR (page 29).
Value:	<code>\$TARGET_TEMP_DIR/DerivedSources</code>
Aliases:	<code>DERIVED_FILES_DIR</code> , <code>DERIVED_SOURCES_DIR</code>

DSTROOT (Installation Build Products Location)

Description:	Directory path. Identifies the directory into which the product is placed. In this directory, the product is laid out exactly as it would be installed in a user's filesystem.
Effectors:	PROJECT_NAME (page 13).
Default value:	<code>/tmp/\$PROJECT_NAME.dst</code>

Example value:	/tmp/MyProject.dst
Affects:	INSTALL_DIR (page 23), TARGET_BUILD_DIR (page 28).

INSTALL_DIR

Description:	Directory path. Identifies the directory in the developer's filesystem into which the <i>installed</i> product is placed.
Effectors:	DSTROOT (Installation Build Products Location) (page 22), INSTALL_PATH (Installation Directory) (page 23).
Value:	\$DSTROOT/INSTALL_PATH
Example value:	/tmp/MyProduct.dst/Users/genica/Library/Bundles

INSTALL_PATH (Installation Directory)

Description:	Directory path. Identifies the directory in the user's filesystem into which the installed product is placed.
Effectors:	Product type (chosen when the project was created), DSTROOT (Installation Build Products Location) (page 22), SYSTEM_LIBRARY_DIR (page 68), USER_LIBRARY_DIR (page 68), HOME (page 67).
Default value:	<p>\$SYSTEM_LIBRARY_DIR/Extensions: Kernel extension project.</p> <p>\$USER_LIBRARY_DIR/Automator: Action project.</p> <p>\$HOME/Applications: Application project.</p> <p>\$HOME/Library/Bundles: Audio unit and bundle projects.</p> <p>\$HOME/bin: Command-line utility project.</p> <p>\$DSTROOT: Apple plug-in project (complete path depends on specific project template).</p> <p>/usr/local/lib: Dynamic library and static library projects.</p>
Affects:	INSTALL_DIR (page 23), TARGET_BUILD_DIR (page 28).

OBJECT_FILE_DIR

Description:	Directory path. Partially identifies the directory into which variant object files are placed. The complete specification is computed using the variants of this build setting.
Effectors:	TARGET_TEMP_DIR (page 29).
Value:	<code>\$TARGET_TEMP_DIR/Objects</code>
Example value:	<code>/Volumes/Users/genica/MyProject/build/MyProject.build/Debug/My-Product.build/Objects</code>
Affects:	OBJECT_FILE_DIR_<VARIANT> (page 24).

OBJECT_FILE_DIR_<VARIANT>

Description:	<p>Directory path. Fully identifies the directory into which variant object files are placed.</p> <p>For each build variant in <code>BUILD_VARIANTS</code>, Xcode generates an <code>OBJECT_FILE_DIR</code> build setting with the variant name as a suffix. The generated build setting's value is computed using <code>OBJECT_FILE_DIR</code> and the build variant name.</p>
Effectors:	BUILD_VARIANTS (Build Variants) (page 15), OBJECT_FILE_DIR (page 24).
Value:	<code>\$OBJECT_FILE_DIR-<VARIANT></code>
Example build settings and their values when <code>\$BUILD_VARIANTS = normal debug</code> :	<ul style="list-style-type: none"><code>\$OBJECT_FILE_DIR_normal = /Volumes/Users/genica/MyProject/build/MyProject.build/Debug/MyProduct.build/Objects-normal</code><code>\$OBJECT_FILE_DIR_debug = /Volumes/Users/genica/MyProject/build/MyProject.build/Debug/MyProduct.build/Objects-debug</code>
Related to:	BUILD_VARIANTS (Build Variants) (page 15), OTHER_CFLAGS_<VARIANT> (page 47).

OBJROOT (Intermediate Build Files Path)

Description:	Directory path. Identifies the directory in which the target's intermediate build files are placed. Intermediate build directories are named after the product name with the extension <code>.build</code> . For example, <code>MyProduct.build</code> .
Effectors:	SRCROOT (page 27), Xcode Preferences > Building > "Place Build Products in."
Default value:	<ul style="list-style-type: none"><code>\$SRCROOT/build</code>: When Xcode Preferences > Building > "Place Build Products in" is "Project directory."<code><custom_directory_path></code>: When Xcode Preferences > Building > "Place Build Products in" is "Customized location."
Example value:	<code>/Volumes/Users/genica/MyProject/build</code>
Affects:	PROJECT_TEMP_DIR (page 25).

PROJECT_TEMP_DIR

Description:	Directory path. Identifies the directory in which the project's intermediate build files are placed. This directory is shared between all the targets defined by the project. Run Script build phases should generate intermediate build files in the directory identified by <code>DERIVED_FILE_DIR</code> , not the location this build setting specifies.
Effectors:	PROJECT_NAME (page 13), OBJROOT (Intermediate Build Files Path) (page 25).
Value:	<code>\$OBJROOT/\$PROJECT_NAME.build</code>
Example value:	<code>/Volumes/Users/genica/MyProject/build/MyProject.build</code>
Affects:	CONFIGURATION_TEMP_DIR (Per-Configuration Intermediate File Path) (page 21).

REZ_COLLECTOR_DIR

Description:	Directory path. Specifies the directory in which the collected Resource Manager resources generated by <code>ResMerger</code> are stored before they are added to the product.
Effectors:	TARGET_TEMP_DIR (page 29).
Value:	<code>\$TARGET_TEMP_DIR/ResourceManagerResources</code>

Example value:	/Volumes/Users/genica/MyProject/build/MyProject.build/Debug/My-Product.build/ResourceManagerResources
Affects:	REZ_OBJECTS_DIR (page 26).

REZ_OBJECTS_DIR

Description:	Directory path. Specifies the directory in which compiled Resource Manager resources generated by Rez are stored before they are collected using ResMerger.
Effectors:	REZ_COLLECTOR_DIR (page 25).
Value:	\$REZ_COLLECTOR_DIR/Objects
Example value:	/Volumes/Users/genica/MyProject/build/MyProject.build/Debug/My-Product.build/ResourceManagerResources/Objects

SDKROOT (Base SDK)

Description:	Directory path. Specifies the directory of the base SDK to use to build the product.
Values:	<ul style="list-style-type: none">• <code>macosx10.5</code>: OS X v10.5.• <code>macosx10.6</code>: OS X v10.6.• <code>iphonesimulator3.2</code>: iPhone Simulator 3.2.• <code>iphonesimulator4.0</code>: iPhone Simulator 4.0.• <code>iphoneos3.2</code>: iPhone Device 3.2.• <code>iphoneos4.0</code>: iPhone Device 4.0.
Related to:	FRAMEWORK_SEARCH_PATHS (Framework Search Paths) (page 31), HEADER_SEARCH_PATHS (Header Search Paths) (page 44), IPHONEOS_DEPLOYMENT_TARGET (iOS Deployment Target) (page 46), MACOSX_DEPLOYMENT_TARGET (OS X Deployment Target) (page 46).

SHARED_PRECOMPS_DIR (Precompiled Headers Cache Path)

Description:	Directory path. Specifies the directory in which to place precompiled headers. Targets can share precompiled headers by using the same value for this build setting.
--------------	--

Effectors:	CACHE_ROOT (page 21).
Default value:	<code>\$CACHE_ROOT/SharedPrecompiledHeaders</code>
Example value:	<code>/var/folders/Aq/AqPz2MexGfqyTWrWDAVs0E++12Q/-Caches-/com.apple.Xcode.501/SharedPrecompiledHeaders/</code>

SKIP_INSTALL

Description:	Boolean value. Specifies whether to place the product at the location indicated by <code>DSTROOT</code> or the uninstalled products directory inside the directory indicated by <code>TARGET_TEMP_DIR</code> .
Values:	<ul style="list-style-type: none">YES: When <code>\$DEPLOYMENT_LOCATION = YES</code>, the product is placed in <code>\$TARGET_TEMP_DIR/UninstalledProducts</code>.NO: The product is placed in <code>\$DSTROOT</code>.
Default value:	NO
Affects:	TARGET_BUILD_DIR (page 28).
Companions:	DEPLOYMENT_LOCATION (Deployment Location) (page 22), DSTROOT (Installation Build Products Location) (page 22), TARGET_TEMP_DIR (page 29).

SRCROOT

Description:	Directory path. Identifies the directory containing the target's source files.
Value:	Path to the project file that defines the target.
Example value:	<code>/Volumes/Users/genica/MyProject</code>
Affects:	OBJROOT (Intermediate Build Files Path) (page 25), SYMROOT (Build Products Path) (page 27).
Alias:	<code>SOURCE_ROOT</code>

SYMROOT (Build Products Path)

Description:	Directory path. Identifies the root of the directory hierarchy that contains product files and intermediate build files. Product and build files are placed in subdirectories of this directory.
--------------	--

Effectors:	SRCROOT (page 27), Xcode Preferences > Build.
Default value:	<ul style="list-style-type: none">• <code>\$SRCROOT/build</code>: When Xcode Preferences > Build > “Place Build Products in” is “Project Directory.”• <code><custom_directory_path></code>: When Xcode Preferences > Build > “Place Build Products in” is “Custom location.”
Example values:	<ul style="list-style-type: none">• <code>/Volumes/Users/genica/MyProject/build</code>• <code>/Volumes/A_Volume/MyManyProducts</code>
Affects:	BUILT_PRODUCTS_DIR (page 20), CONFIGURATION_BUILD_DIR (Per-Configuration Build Products Path) (page 21).

TARGET_BUILD_DIR

Description:	<p>Directory path. Identifies the root of the directory hierarchy that contains the product’s files (no intermediate build files).</p> <p>Run Script build phases that operate on product files of the target that defines them should use the value of this build setting. But Run Script build phases that operate on product files of other targets should use BUILT_PRODUCTS_DIR (page 20) instead.</p>
Effectors:	CONFIGURATION_BUILD_DIR (Per-Configuration Build Products Path) (page 21), DEPLOYMENT_LOCATION (Deployment Location) (page 22), DSTROOT (Installation Build Products Location) (page 22), INSTALL_PATH (Installation Directory) (page 23), TARGET_TEMP_DIR (page 29), SKIP_INSTALL (page 27).
Value:	<ul style="list-style-type: none">• <code>\$CONFIGURATION_BUILD_DIR</code>: When <code>\$DEPLOYMENT_LOCATION</code> = NO,• <code>\$DSTROOT/\$INSTALL_PATH</code>: When <code>\$DEPLOYMENT_LOCATION</code> = YES, <code>\$SKIP_INSTALL</code> = NO, and <code>INSTALL_PATH</code> is defined,• <code>\$TARGET_TEMP_DIR/UninstalledProducts</code>: When <code>\$DEPLOYMENT_LOCATION</code> = YES AND <code>\$SKIP_INSTALL</code> = YES or <code>\$SKIP_INSTALL</code> = NO and <code>INSTALL_PATH</code> is not defined.
Example values:	<ul style="list-style-type: none">• <code>/Volumes/Users/genica/MyProject/build/Debug</code>• <code>/tmp/MyProject.dst/Users/genica/Applications</code>• <code>/Volumes/Users/genica/MyProject/build/UninstalledProducts</code>

Related to:	DEPLOYMENT_LOCATION (Deployment Location) (page 22), INSTALL_PATH (Installation Directory) (page 23), SKIP_INSTALL (page 27).
-------------	---

TARGET_TEMP_DIR

Description:	Directory path. Identifies the directory containing the target's intermediate build files. Run Script build phases should place intermediate files at the location indicated by <code>DERIVED_FILE_DIR</code> , not the directory identified by this build setting.
Effectors:	TARGET_NAME (page 13), CONFIGURATION_TEMP_DIR (Per-Configuration Intermediate File Path) (page 21).
Value:	<code>\$CONFIGURATION_TEMP_DIR/\$TARGET_NAME.build</code>
Example value:	<code>/Volumes/Users/genica/MyProject/build/MyProject.build/Debug/My-Product.build</code>
Affects:	DERIVED_FILE_DIR (page 22), OBJECT_FILE_DIR (page 24), REZ_COLLECTOR_DIR (page 25), TARGET_BUILD_DIR (page 28).

Header-Map Build Settings

Header maps (also known as “header maps”) are files Xcode uses to compile the locations of the headers used in a target. These files use the suffix `.hmap`. Xcode passes the header maps it puts together to C-based compilers through the `-I` argument.

They allow header and source files to include:

- Any header associated with the target using only its name (for example, `#include "MyClass.h"`) regardless of its location in the file system. See [HEADERMAP_INCLUDES_FLAT_ENTRIES_FOR_TARGET_BEING_BUILT](#) (page 30).
- Headers using framework syntax (for example, `MyFramework/MyHeader.h`). See [HEADERMAP_INCLUDES_FRAMEWORK_ENTRIES_FOR_ALL_PRODUCT_TYPES](#) (page 30).
- Headers that are part of the project, regardless of target membership. See [HEADERMAP_INCLUDES_PROJECT_HEADERS](#) (page 30).

Without header maps, you need to add each directory that contains headers to the target's header search paths (see [HEADER_SEARCH_PATHS](#) (Header Search Paths) (page 44) and [USER_HEADER_SEARCH_PATHS](#) (User Header Search Paths) (page 48)).

HEADERMAP_INCLUDES_FLAT_ENTRIES_FOR_TARGET_BEING_BUILT

Description:	Boolean value. Specifies whether the header map contains a name/path entry for every header in the target being built.
Values:	<ul style="list-style-type: none">• YES: The header map contains a name/path entry for every header in the target.• NO: The header map does not contain name/path entries for the headers that belong to the target.
Default value:	YES
Related to:	HEADERMAP_INCLUDES_FRAMEWORK_ENTRIES_FOR_ALL_PRODUCT_TYPES (page 30), HEADERMAP_INCLUDES_PROJECT_HEADERS (page 30).

HEADERMAP_INCLUDES_FRAMEWORK_ENTRIES_FOR_ALL_PRODUCT_TYPES

Description:	Boolean value. Specifies whether the header map contains a framework-name/path entry for every header in the target being built, including targets that do not build frameworks.
Values:	<ul style="list-style-type: none">• YES: The header map contains a framework-name/path entry for every header in the target.• NO: The header map does not contain framework-name/path entries for the headers in the target.
Default value:	YES
Related to:	HEADERMAP_INCLUDES_FLAT_ENTRIES_FOR_TARGET_BEING_BUILT (page 30), HEADERMAP_INCLUDES_PROJECT_HEADERS (page 30).

HEADERMAP_INCLUDES_PROJECT_HEADERS

Description:	Boolean value. Specifies whether the header map contains a name/path entry for every header in the project, regardless of the headers' target membership.
Values:	<ul style="list-style-type: none">• YES: The header map contains a name/path entry for every header in the project.• NO: The header map does not contain name/path entries for the headers that are part of the project.

Default value:	YES
Related to:	HEADERMAP_INCLUDES_FLAT_ENTRIES_FOR_TARGET_BEING_BUILT (page 30), HEADERMAP_INCLUDES_FRAMEWORK_ENTRIES_FOR_ALL_PRODUCT_TYPES (page 30).

C/C++ Compiler Build Settings

These build settings specify how source files are compiled into object files.

[ALWAYS_SEARCH_USER_PATHS](#) (Always Search User Paths)

Description:	Boolean value. Specifies whether the compiler searches for headers in the project directory before searching system directories. This build setting is used only with GCC 4.0 and later.
Values:	<ul style="list-style-type: none">• YES: Search project directory first.• NO: Search system directories first.
Default value:	YES. For backwards compatibility only. You should set this build setting to NO.

[FRAMEWORK_SEARCH_PATHS](#) (Framework Search Paths)

Description:	Space-separated list of directory paths. Specifies directories in which the compiler searches for frameworks to find included header files. This list is passed to the compiler in the <code>gcc -F</code> option. You may specify a recursive path by appending <code>**</code> to the path. When this build setting is defined, <code>\$SDKROOT</code> is added to the end of the path list that is passed to the compiler.
Default value:	None.
Example values:	<ul style="list-style-type: none">• <code>/Users/genica/TestFrameworks/**</code>• <code>/Volumes/Auryon/TeamFrameworks/**</code>
Companions:	SDKROOT (Base SDK) (page 26).

GCC_AUTO_VECTORIZATION (Auto-Vectorization)

Description:	Boolean value. Specifies whether the compiler performs automatic loop vectorization when appropriate. Automatic loop vectorization is supported only in the PPC architectures. And it's not supported by the Clang and LLVM-GCC compilers.
Prerequisite:	<code>\$GCC_OPTIMIZATION_LEVEL >= 2 AND \$ARCHS * \$VALID_ARCHS IN {ppc, ppc970, ppc64}</code>
Values:	<ul style="list-style-type: none">• YES: The compiler performs automatic loop vectorization when the prerequisite is met.• NO: The compiler does not perform automatic loop vectorization.
Default value:	NO
Companions:	ARCHS (Architectures) (page 11), VALID_ARCHS (Valid Architectures) (page 14), GCC_OPTIMIZATION_LEVEL (Optimization Level) (page 37).

GCC_CW_ASM_SYNTAX (CodeWarrior-Style Inline Assembly)

Description:	Boolean value. Specifies whether to use the CodeWarrior syntax for inline assembly code (in addition to the standard GCC syntax).
Values:	<ul style="list-style-type: none">• YES: Use CodeWarrior syntax for inline assembly code.• NO: Do not use CodeWarrior syntax for inline assembly code.
Default value:	YES

GCC_DEBUGGING_SYMBOLS (Level of Debug Symbols)

Description:	Option specification. Specifies the level of debug information included in the binary.
Values:	<code>used</code> : Referenced symbols only (<code>gcc -gused</code>). <code>full</code> : All symbols (<code>gcc -gfull</code>). <code>default</code> : Compiler default (<code>gcc -g</code>).
Default value:	<code>default</code>
Prerequisite for:	GCC_ENABLE_SYMBOL_SEPARATION (Separate PCH Symbols) (page 35), DEAD_CODE_STRIPPING (Dead Code Stripping) (page 51)

GCC_DYNAMIC_NO_PIC

Description:	Boolean value. Specifies whether the generated object code is nonrelocatable (external references remain relocatable). Making code nonrelocatable results in faster function calls. This feature is appropriate in applications but not dynamic libraries.
Values:	<ul style="list-style-type: none">• YES: Generated code is nonrelocatable (<code>gcc -mdynamic-no-pic</code>) when the prerequisite is met.• NO: Generated code is relocatable.
Default value:	NO

GCC_ENABLE_CPP_EXCEPTIONS (Enable C++ Exceptions)

Description:	Boolean value. Specifies whether the compiler generates code necessary for exception propagation.
Values:	<ul style="list-style-type: none">• YES: Compiler generates code necessary for exception propagation.• NO: Compiler does not generate code necessary for exception propagation.
Default value:	NO
Related to:	GCC_ENABLE_CPP_RTTI (Enable C++ Runtime Types) (page 33).

GCC_ENABLE_CPP_RTTI (Enable C++ Runtime Types)

Description:	Boolean value. Specifies whether the compiler generates information about every class with virtual functions. This information is used by the C++ runtime type identification features (<code>dynamic_cast</code> and <code>typeid</code>). If you do not use these features, you may save some space by not generating this information. However, when exceptions are enabled, this information is generated automatically.
Values:	<ul style="list-style-type: none">• YES: Binary includes information about virtual classes.• NO: Binary might not include information about virtual classes (<code>gcc -fno-rtti</code>).
Default value:	YES
Related to:	GCC_ENABLE_CPP_EXCEPTIONS (Enable C++ Exceptions) (page 33).

GCC_ENABLE_FIX_AND_CONTINUE (Fix & Continue)

Description:	Boolean value. Specifies whether the binary uses Fix And Continue..
Values:	<ul style="list-style-type: none">• YES: Binary uses Fix And Continue.• NO: Binary does not use Fix And Continue.
Default value:	NO

GCC_ENABLE_OBJC_EXCEPTIONS (Enable Objective-C Exceptions)

Description:	Boolean value. Specifies whether the compiler recognizes <code>@try</code> , <code>@catch</code> , and <code>@throw</code> directives.
Values:	<ul style="list-style-type: none">• YES: Recognize the Objective-C exception-handling directives (<code>gcc -fobjc-exceptions</code>).• NO: Do not allow the Objective-C exception-handling directives in source code.
Default value:	NO

GCC_ENABLE_OBJC_GC (Objective-C Garbage Collection)

Description:	Identifier. Specifies the level of garbage-collection support for the generated code.
Values:	<ul style="list-style-type: none">• <code>unsupported</code>: The application cannot load code that requires garbage collection. The loadable bundle cannot be loaded by an application that requires garbage collection.• <code>supported</code>: The application can load code that supports or requires garbage collection. The loadable bundle can be loaded by an application with any level of garbage-collection support.• <code>required</code>: The application can load only code that supports garbage collection. The loadable bundle can be loaded only by an application that supports garbage collection.
Default value:	<code>unsupported</code>

GCC_ENABLE_SSE3_EXTENSIONS (Enable SSE3 Extensions)

Description:	Boolean value. Specifies whether the binary uses the built-in functions that provide access to the SSE3 extensions to the IA-32 architecture.
Values:	<ul style="list-style-type: none">• YES: Binary uses SSE3 functions.• NO: Binary does not use SSE3 functions.
Default value:	NO

GCC_ENABLE_SSE41_EXTENSIONS (Enable SSE4.1 Extensions)

Description:	Boolean value. Specifies whether the binary uses the built-in functions that provide access to the SSE4.1 extensions to the IA-32 architecture.
Values:	<ul style="list-style-type: none">• YES: Binary uses SSE4.1 functions (<code>gcc -msse4.1</code>).• NO: Binary does not use SSE4.1 functions.
Default value:	NO

GCC_ENABLE_SSE42_EXTENSIONS (Enable SSE4.2 Extensions)

Description:	Boolean value. Specifies whether the binary uses the built-in functions that provide access to the SSE4.2 extensions to the IA-32 architecture.
Values:	<ul style="list-style-type: none">• YES: Binary uses SSE4.2 functions (<code>gcc -msse4.2</code>).• NO: Binary does not use SSE4.2 functions.
Default value:	NO

GCC_ENABLE_SYMBOL_SEPARATION (Separate PCH Symbols)

Description:	Boolean value. Specifies whether the compiler generates a separate file containing the debug symbols when compiling a precompiled (prefix) header (PCH). A separate file with debug symbols can improve build time.
Prerequisite:	<code>\$DEBUG_INFORMATION_FORMAT = stabs</code> AND <code>\$GCC_DEBUGGING_SYMBOLS = full</code>

Values:	<ul style="list-style-type: none">• YES: Generates separate file containing debug symbols for a precompiled header.• NO: Does not generate separate debug symbol file.
Default value:	<ul style="list-style-type: none">• YES: When <code>\$MACH_O_TYPE != staticlib</code>.• NO: Is the alternative.
Effector:	MACH_O_TYPE (page 12)
Companions:	DEBUG_INFORMATION_FORMAT (Debug Information Format) (page 17), GCC_DEBUGGING_SYMBOLS (Level of Debug Symbols) (page 32).

[GCC_FEEDBACK_DIRECTED_OPTIMIZATION \(Feedback-Directed Optimization\)](#)

Description:	<p>Boolean value. Specifies whether to use feedback-directed optimization.</p> <p>To optimize a binary, you must first generate a binary that produces profile trace files by setting this build setting to <code>GenerateProfile</code>. After running the binary mimicking the expected usage patterns (training), rebuild the binary with <code>UseProfile</code> as the value for this build setting. The resulting binary is optimized for the usage patterns observed in training. If the code paths taken during training are not representative of what happens in actual usage, the binary's performance may actually degrade.</p>
Values:	<ul style="list-style-type: none">• <code>Off</code>: Binary is not optimized and does not generate trace files.• <code>GenerateProfile</code>: Binary generates trace files (training).• <code>UseProfile</code>: Binary is optimized using the information from the profile trace files. Requires that the binary had been previously built with <code>GenerateProfile</code> and run to gather the information.
Default value:	<code>Off</code>

[GCC_GENERATE_DEBUGGING_SYMBOLS \(Generate Debug Symbols\)](#)

Description:	Boolean value. Specifies whether the binary includes debug symbols.
Values:	<ul style="list-style-type: none">• YES: Binary includes debugging symbols.• NO: Binary does not include debugging symbols.

Default value:	YES
Related to:	GCC_DEBUGGING_SYMBOLS (Level of Debug Symbols) (page 32).

GCC_MODEL_TUNING (Instruction Scheduling)

Description:	Option specification. Specifies the PowerPC architecture to which the compiler optimizes the instruction scheduling model. The generated code runs in earlier PowerPC architectures, too. See <code>-mtune</code> in the <code>gcc</code> man page for details.
Values:	<ul style="list-style-type: none">• None: Binary is not optimized for a particular PowerPC architecture.• G3: Binary is optimized for the PowerPC G3 architecture.• G4: Binary is optimized for the PowerPC G4 architecture.• G5: Binary is optimized for the PowerPC G5 architecture.
Default value:	G4

GCC_OBJC_CALL_CXX_CDTORS (Call C++ Default Ctors/Dtors in Objective-C)

Description:	Boolean value. Specifies whether to execute nontrivial default constructors and destructors for C++ instance variables of Objective-C classes.
Values:	<ul style="list-style-type: none">• YES: Binary executes default constructors and destructors for C++ instance variables of Objective-C classes (<code>gcc -fobjc-call-cxx-cdtors</code>).• NO: Binary does not execute default constructors for Objective-C-typed instance variables in C++ classes.
Default value:	NO

GCC_OPTIMIZATION_LEVEL (Optimization Level)

Description:	Option specification. Specifies the degree to which the generated code is optimized for speed and binary size.
--------------	--

Values:	<ul style="list-style-type: none">• 0: No optimization.• 1: Binary is optimized to <i>fast</i>.• 2: Binary is optimized to <i>faster</i>.• 3: Binary is optimized to <i>fastest</i>.• s: Binary is optimized to <i>fastest and smallest</i>.
Default value:	s

GCC_PRECOMPILE_PREFIX_HEADER (Precompile Prefix Header)

Description:	Boolean value. Specifies whether to create a prefix header for the target.
Prerequisite:	<code>\$GCC_PREFIX_HEADER</code> identifies an existing prefix header.
Values:	<ul style="list-style-type: none">• YES: Target generates a prefix header when the prerequisite is met.• NO: Target does not generate a prefix header.
Default value:	NO
Companion:	GCC_PREFIX_HEADER (page 38).

GCC_PREFIX_HEADER

Description:	Filename or file path. Identifies the target's prefix header.
Default value:	None.
Example value:	<code>MyProduct_Prefix.pch</code>
Prerequisite for:	GCC_PRECOMPILE_PREFIX_HEADER (Precompile Prefix Header) (page 38)

GCC_PREPROCESSOR_DEFINITIONS (Preprocessor Macros)

Description:	Space-separated list of option specifications. Specifies preprocessor macros in the form <code>foo</code> (for a simple <code>#define</code>) or <code>foo=1</code> (for a value definition). This list is passed to the compiler through the <code>gcc -D</code> option when compiling precompiled headers and implementation files.
--------------	--

Default value:	None.
Example value:	<code>test_mode=1 copious_logging=1</code>
Related to:	GCC_PREPROCESSOR_DEFINITIONS_NOT_USED_IN_PRECOMPS (Preprocessor Macros Not Used In Precompiled Headers) (page 39).

[GCC_PREPROCESSOR_DEFINITIONS_NOT_USED_IN_PRECOMPS](#) (Preprocessor Macros Not Used In Precompiled Headers)

Description:	Space-separated list of option specifications. Specifies preprocessor macros in the form <code>foo</code> (for a simple <code>#define</code>) or <code>foo=1</code> (for a value definition). This list is passed to the compiler through the <code>gcc -D</code> option only when compiling implementation files; they are not passed when compiling precompiled headers.
Prerequisite:	Definitions used only in implementation files, not precompiled headers.
Default value:	None.
Example value:	<code>test_mode=1 copious_logging=1</code>
Related to:	GCC_PREPROCESSOR_DEFINITIONS (Preprocessor Macros) (page 38).

[GCC_SYMBOLS_PRIVATE_EXTERN](#) (Symbols Hidden by Default)

Description:	Boolean value. Specifies whether symbols are hidden by default. See Controlling Symbol Visibility in C++ <i>Runtime Environment Programming Guide</i> .
Values:	<ul style="list-style-type: none">YES: Symbols that do not specify public visibility (with <code>__attribute__((visibility("default")))</code>, for example) are not exported (<code>gcc -fvisibility=hidden</code>).N0: Symbols that do not specify private visibility (with <code>__attribute__((visibility("hidden")))</code>, for example) are exported.
Default value:	YES
Prerequisite for:	STANDARD_C_PLUS_PLUS_LIBRARY_TYPE (C++ Standard Library Type) (page 55).

GCC_THREADSafe_STATICS (Statics are Thread Safe)

Description:	Boolean value. Specifies whether the binary uses the functions that implement thread-safe initialization of local statics for the IA-32 architecture. Binaries that use these functions contain less object code in sections that do not need to be thread safe.
Values:	<ul style="list-style-type: none">• YES: Binary uses the IA-32 ABI thread-safe initialization functions.• NO: Binary does not use the IA-32 ABI thread-safe initialization functions (<code>gcc -fno-threadsafe-statics</code>).
Default value:	YES

GCC_UNROLL_LOOPS (Unroll Loops)

Description:	Boolean value. Specifies whether the compiler generates a faster binary (containing code with fewer branches) by unrolling loops, which generates a larger binary.
Values:	<ul style="list-style-type: none">• YES: Compiler generates code with unrolled loops.• NO: Compiler does not unroll loops.
Default value:	NO

GCC_USE_NASM_FOR_ASM_FILETYPE (Use nasm to Process .asm Files)

Description:	Boolean value. Specifies whether <code>nasm</code> is used to compile Assembly <code>.asm</code> files.
Values:	<ul style="list-style-type: none">• YES: Assembly (<code>.asm</code>) files are compiled with <code>nasm</code> (<code>gcc -nasm</code>).• NO: Assembly files are not compiled with <code>nasm</code>.
Default value:	NO

GCC_VERSION

Description:	Numeric identifier. Identifies the GCC version to be used to compile the target's source files. When the target's "System C rule" is set to GCC System Version (instead of a specific version number), this build setting is not available in Run Script build phases.
--------------	--

Values:	<ul style="list-style-type: none">• 2.95.2• 3.1• 3.3• 4.0
Default value:	GCC system version.
Specified in:	<ul style="list-style-type: none">• Project Info > Rules > "System C rule."• Target Info > Rules > "System C rule."
Affects:	GCC_VERSION_IDENTIFIER (page 41).

[GCC_VERSION_IDENTIFIER](#)

Description:	Identifier. Identifies the version of GCC to be used to compile the target's source files. This build setting is unavailable in Run Script build phases when <code>GCC_VERSION</code> is not available in them.
Effectors:	GCC_VERSION (page 40)
Value:	The value of <code>GCC_VERSION</code> using underscores instead of periods.
Example value:	4_0

[GCC_WARN_ABOUT_GLOBAL_CONSTRUCTORS](#) (Global Construction or Destruction Required)

Description:	Boolean value. Specifies whether to warn about the use of static initializers.
Values:	<ul style="list-style-type: none">• YES: Warn about the use of static initializers (<code>gcc -Wglobal-constructors</code>).• NO: Do not warn about the use of static initializers.
Default value:	NO

GCC_WARN_ABOUT_RETURN_TYPE (Mismatched Return Type)

Description:	Boolean value. Specifies whether to warn about functions that do not have an explicit return type and about functions that contain <code>return</code> statements but whose return type is <code>void</code> .
Values:	<ul style="list-style-type: none">• YES: Warn about ambiguous function return types (<code>gcc -Wreturn-type</code>).• NO: Do not warn about ambiguous function return types.
Default value:	NO

GCC_WARN_UNUSED_VARIABLE (Unused Variables)

Description:	Boolean value. Specifies whether warn about unused local variables or unused nonconstant static variables.
Values:	<ul style="list-style-type: none">• YES: Warn about unused variables (<code>gcc -Wunused-variable</code>).• NO: Do not warn about unused variables.
Default value:	NO

GCC_WARN_EFFECTIVE_CPLUSPLUS_VIOLATIONS (Effective C++ Violation)

Description:	Boolean value. Specifies whether to warn about violations to certain code style guidelines described in <i>Effective C++</i> (by Scott Meyer).
Values:	<ul style="list-style-type: none">• YES: Warn about <i>Effective C++</i>–style violations (<code>gcc -Weffc++</code>).• NO: Do not warn about <i>Effective C++</i>–style violations.
Default value:	NO

GCC_WARN_HIDDEN_VIRTUAL_FUNCTIONS (Hidden Virtual Functions)

Description:	Boolean value. Specifies whether to warn about function declarations that hide virtual functions declared in a base class.
--------------	--

Values:	<ul style="list-style-type: none">• YES: Warn about function declarations that hide virtual functions declared in a base class (<code>gcc -Woverloaded-virtual</code>).• NO: Do not warn about function declarations that hide virtual functions declared in a base class
Default value:	NO

GCC_WARN_INHIBIT_ALL_WARNINGS (Inhibit All Warnings)

Description:	Boolean value. Specifies whether to suppress warnings.
Values:	<ul style="list-style-type: none">• YES: Suppress all warnings (<code>gcc -w</code>).• NO: Do not suppress warnings.
Default value:	NO

GCC_WARN_NON_VIRTUAL_DESTRUCTOR (Nonvirtual Destructor)

Description:	Boolean value. Specifies whether to warn about classes that declare a nonvirtual destructor that should be virtual (when the compiler determines that the class is used polymorphically). This build setting applies only to C++ and Objective-C++ source files.
Values:	<ul style="list-style-type: none">• YES: Warn about nonvirtual destructors that should be virtual (<code>gcc -Wnon-virtual-dtor</code>).• NO: Do not warn about nonvirtual destructors that should be virtual.
Default value:	NO

GCC_WARN_PEDANTIC (Pedantic Warnings)

Description:	Boolean value. Specifies whether to warn about source code that does not adhere to ISO C or ISO C++ standards.
Values:	<ul style="list-style-type: none">• YES: Warn about nonadherence to ISO C or ISO C++ standards (<code>gcc -pedantic</code>).• NO: Do not warn about nonadherence to ISO C or ISO C++ standards.

Default value:	NO
----------------	----

[GCC_WARN_SHADOW \(Hidden Local Variables\)](#)

Description:	Boolean value. Specifies whether to warn about local symbols that shadow another local variable, parameter, or global variable, built-in function.
Values:	<ul style="list-style-type: none">YES: Warn about shadowed symbols (<code>gcc -Wshadow</code>).NO: Do not warn about shadowed symbols.
Default value:	NO

[GCC_WARN_SIGN_COMPARE \(Sign Comparison\)](#)

Description:	Boolean value. Specifies whether to warn about comparisons between <code>signed</code> and <code>unsigned</code> values that could produce an incorrect result when the <code>signed</code> value is converted to <code>unsigned</code> .
Values:	<ul style="list-style-type: none">YES: Warn about sign discrepancies in comparisons (<code>gcc -Wsign-compare</code>).NO: Do not warn about sign discrepancies in comparisons.
Default value:	NO

[HEADER_SEARCH_PATHS \(Header Search Paths\)](#)

Description:	Space-separated list of directory paths. Specifies directories in which to search for header files. (In GCC, this list is passed in the <code>gcc -I</code> option.) When this build setting is defined, <code>\$SDKROOT</code> is added to the beginning of each system-header path passed to the compiler.
Default value:	None.
Example values:	<code>/Users/genica/TestHeaders/**</code> <code>/System/Library/Frameworks/AddressBook.framework</code>
Companion:	SDKROOT (Base SDK) (page 26).
Related to:	USER_HEADER_SEARCH_PATHS (User Header Search Paths) (page 48).

INFOPLIST_OTHER_PREPROCESSOR_FLAGS (Info.plist Other Preprocessor Flags)

Description:	Space-separated list of option specifications. Specifies additional options for preprocessing the info plist file.
Companion:	INFOPLIST_PREPROCESS (Preprocess Info.plist File) (page 45), INFOPLIST_FILE (page 57).
Related to:	INFOPLIST_PREFIX_HEADER (Info.plist Preprocessor Prefix File) (page 45), INFOPLIST_PREPROCESSOR_DEFINITIONS (Info.plist Preprocessor Definitions) (page 45).

INFOPLIST_PREFIX_HEADER (Info.plist Preprocessor Prefix File)

Description:	File path or project file path. Specifies the path to the prefix file to include when processing the info plist file.
Companion:	INFOPLIST_PREPROCESS (Preprocess Info.plist File) (page 45).

INFOPLIST_PREPROCESS (Preprocess Info.plist File)

Description:	Boolean. Specifies whether to preprocess the info plist file.
Values:	<ul style="list-style-type: none">• YES: Preprocesses the info plist file.• NO: Doesn't preprocess the info plist file.
Default value:	NO.
Companion:	INFOPLIST_FILE (page 57).
Related to:	INFOPLIST_PREFIX_HEADER (Info.plist Preprocessor Prefix File) (page 45).

INFOPLIST_PREPROCESSOR_DEFINITIONS (Info.plist Preprocessor Definitions)

Description:	Space-separated list of option specifications. Defines preprocessor macros used when preprocessing the info plist file.
Example value:	DEBUG=1.
Companion:	INFOPLIST_PREPROCESS (Preprocess Info.plist File) (page 45), INFOPLIST_FILE (page 57).

Related to:	INFOPLIST_OTHER_PREPROCESSOR_FLAGS (Info.plist Other Preprocessor Flags) (page 45).
-------------	---

IPHONEOS_DEPLOYMENT_TARGET (iOS Deployment Target)

Description:	Numeric identifier. Identifies the earliest iOS version the product is to run on. This build setting is available in Run Script build phases only when it is set to a specific iOS version.
Values:	<ul style="list-style-type: none">2.0: Product runs on iOS 2.0 and later.2.1: Product runs on iOS 2.1 and later.2.2: Product runs on iOS 2.2 and later.2.2.1: Product runs on iOS 2.2.1 and later.3.0: Product runs on iOS 3.0 and later.3.1: Product runs on iOS 3.1 and later.3.1.2: Product runs on iOS 3.1.2 and later.3.1.3: Product runs on iOS 3.1.3 and later.3.2: Product runs on iOS 3.2 and later.4.0: Product runs on iOS 4.0 and later.
Default value:	Compiler default. Product runs on the iOS version SDKROOT targets, and later.
Related to:	SDKROOT (Base SDK) (page 26).

MACOSX_DEPLOYMENT_TARGET (OS X Deployment Target)

Description:	Numeric identifier. Identifies the earliest OS X version the product is to run on. This build setting is available in Run Script build phases only when it is set to a specific OS X version.
--------------	---

Values:	<ul style="list-style-type: none">10.1: Product runs on 10.1 if no 10.2 or 10.3 API is used, on 10.2 with weak linking, and on 10.3 or later fully linked.10.2: Product runs on 10.2 with weak linking, and on 10.3 or later fully linked.10.3: Product runs only on 10.3 and later.10.4: Product runs only on 10.4 and later.10.5: Product runs only on 10.5 and later.10.6: Product runs only on 10.6 and later.
Default value:	Compiler default. Product runs on the OS X version SDKROOT targets, and later.
Related to:	SDKROOT (Base SDK) (page 26).

OTHER_CFLAGS (Other C Flags)

Description:	Space-separated list of option specifications. Specifies additional options for compiling C-based precompiled headers and implementation files. These options are passed (as given) to the compiler whether other build settings also specify values that correspond to these options. Therefore, you should look for the appropriate compiler build setting to specify a particular compiler option before using this build setting.
Default value:	None.
Example value:	-dM
Affects:	OTHER_CPLUSPLUSFLAGS (Other C++ Flags) (page 48).
Related to:	OTHER_CFLAGS_<VARIANT> (page 47).

OTHER_CFLAGS_<VARIANT>

Description:	Space-separated list of option specifications. Specifies additional options for compiling C-based (including C++) precompiled headers and implementation files for the specified variant. These options are passed (as given) to the compiler whether other build settings also specify values that correspond to these options. Therefore, you should look for the appropriate compiler build setting to specify a particular compiler option before using this build setting.
Default value:	None.

Related to:	BUILD_VARIANTS (Build Variants) (page 15), OBJECT_FILE_DIR_<VARIANT> (page 24), OTHER_CFLAGS (Other C Flags) (page 47), OTHER_CPLUSPLUSFLAGS (Other C++ Flags) (page 48).
-------------	---

OTHER_CPLUSPLUSFLAGS (Other C++ Flags)

Description:	Space-separated list of option specifications. Specifies additional options for compiling C++-based precompiled headers and implementation files. These options are passed (as given) to the compiler whether other build settings also specify values that correspond to these options. Therefore, you should look for the appropriate compiler build setting to specify a particular compiler option before using this build setting.
Effectors:	OTHER_CFLAGS (Other C Flags) (page 47).
Default value:	<code>\$OTHER_CFLAGS</code> .
Example value:	<code>-Wefc++</code>
Related to:	OTHER_CFLAGS_<VARIANT> (page 47).

USER_HEADER_SEARCH_PATHS (User Header Search Paths)

Description:	<p>Space-separated list of directory paths. Specifies directories to search for header files included in source files using quotation marks ("") instead of angle brackets (<>). User header files are supported in GCC 4.0 and later. Relative paths are relative to the project directory (SRCROOT (page 27)).</p> <p>Xcode build tools, such as GCC, are invoked with their working directory set to SRCROOT. Third-party build tools should take care not to change the working directory; otherwise, the relative search paths passed to them may produce unexpected results.</p>
Default value:	None.
Companion:	SRCROOT (page 27).
Related to:	HEADER_SEARCH_PATHS (Header Search Paths) (page 44).

WARNING_CFLAGS (Other Warning Flags)

Description:	Space-separated list of option specifications. Specifies additional warning options for compiling C-based (including C++) precompiled headers and implementation files. These options are passed (as given) to the compiler whether other build settings also specify values that correspond to these options. Therefore, you should look for the appropriate compiler build setting to specify a particular warning option before using this build setting.
Default value:	None.
Related to:	GCC_WARN... build settings.

Interface Builder Compiler Build Settings

These build settings specify options for the Interface Builder compiler.

IBC_FLATTEN_NIBS (Flatten Compiles XIB Files)

Description:	Boolean value. Specifies whether to strip nib files to reduce their size. The resulting nib file is more compact but is not editable.
Values:	<ul style="list-style-type: none">• YES: Strips nib files, making them uneditable.• NO: Does not strip nib files.
Default value:	YES.

IBC_OTHER_FLAGS (Other Interface Builder Compiler Flags)

Description:	Space-separated list of option specifications. Specifies additional options for compiling nib files. These options are passed (as given) to the compiler whether other build settings also specify values that correspond to these options. Therefore, you should look for the appropriate compiler build setting to specify a particular compiler option before using this build setting.
Default value:	None.

IBC_OVERRIDING_PLUGINS_AND_FRAMEWORKS_DIR (Overriding Plug-In and Framework Directory)

Description:	Directory path. Identifies the directory from which to load frameworks and Interface Builder plug-ins.
Example value:	<code>\$(BUILD_DIR)/\$(CONFIGURATION)\$(EFFECTIVE_PLATFORM_NAME)</code> . Loads frameworks and plug-ins from the built products directory of the active build configuration.
Default value:	None.

IBC_PLUGIN_SEARCH_PATHS (Plug-In Search Paths)

Description:	Space-separated list of directory paths. Identifies directories to be searched for Interface Builder plug-ins to load when compiling xib files.
Default value:	None.

IBC_PLUGINS (Plug-Ins)

Description:	Space-separated list of file paths. Identifies Interface Builder plug-ins to load when compiling xib files.
Default value:	None.

IBC_ERRORS (Show Errors)

Description:	Boolean value. Specifies whether to emit xib-file-compilation errors.
Values:	<ul style="list-style-type: none">YES: Emits xib-file-compilation errors.NO: Does not emit xib-file-compilation errors.
Default value:	YES.

IBC_NOTICES (Show Notices)

Description:	Boolean value. Specifies whether to emit xib-file-compilation notices.
--------------	--

Values:	<ul style="list-style-type: none">• YES: Emits xib-file-compilation notices.• NO: Does not emit xib-file-compilation notices.
Default value:	YES.

IBC_WARNINGS (Show Warnings)

Description:	Boolean value. Specifies whether to emit xib-file-compilation warnings.
Values:	<ul style="list-style-type: none">• YES: Emits xib-file-compilation warnings.• NO: Does not emit xib-file-compilation warnings.
Default value:	YES.

Linker Build Settings

These build settings specify linking options.

DEAD_CODE_STRIPPING (Dead Code Stripping)

Description:	Boolean value. Specifies whether dead code is stripped from the binary.
Prerequisite:	<code>\$GCC_DEBUGGING_SYMBOLS = full</code>
Values:	<ul style="list-style-type: none">• YES: Dead code is stripped from the binary when the prerequisite is met.• NO: Dead code is not stripped from the binary.
Default value:	NO
Companions:	GCC_DEBUGGING_SYMBOLS (Level of Debug Symbols) (page 32).
Prerequisite for:	<code>PRESERVE_DEAD_CODE_INITS_AND_TERMS</code>

EXPORTED_SYMBOLS_FILE (Exported Symbols File)

Description:	Project file path. Identifies a file containing the names of global symbols to be exported from the binary. All other symbols are treated as if they had been marked as private. See <i>Minimizing Your Exported Symbols</i> in <i>Code Size Performance Guidelines</i> and <code>ld -exported_symbols_list</code> for details on exporting symbols.
Default value:	None.
Example value:	<code>My_Public_Symbols</code>

KEEP_PRIVATE_EXTERNS (Preserve Private External Symbols)

Description:	Boolean value. Specifies whether private external symbols remain so in the binary.
Values:	<ul style="list-style-type: none">YES: Private external symbols in source code are private external in the binary (<code>ld -keep_private_externs</code>).NO: Private external symbols in source code are static symbols in the binary.
Default value:	NO

LD_DYLIB_INSTALL_NAME (Dynamic Library Install Name)

Description:	File path. Specifies the install name of a dynamic library. See <i>Dynamic Library Programming Topics</i> .
Default value:	None.
Example values:	<ul style="list-style-type: none"><code>/usr/lib/libfoo</code><code>@rpath/libfoo</code>
Related to:	LD_RUNPATH_SEARCH_PATHS (Runpath Search Paths) (page 52).

LD_RUNPATH_SEARCH_PATHS (Runpath Search Paths)

Description:	Space-separated list of directory paths. Specifies the run-path locations at which the dynamic loader searches for the product's run-path dependent libraries. See <i>Dynamic Library Programming Topics</i> .
--------------	--

Default value:	None.
Example values:	@loader_path/./Frameworks /usr/lib
Related to:	LD_DYLIB_INSTALL_NAME (Dynamic Library Install Name) (page 52).

LIBRARY_SEARCH_PATHS

Description:	Space-separated list of directory paths. Specifies directories in which the linker searches for included libraries to link the binary against. Adding ** to the end of a path specifies a recursive path. When this build setting is defined, \$SDKROOT is added to the beginning of each path passed to the linker.
Default value:	None.
Example value:	/Volumes/Sauron/Team/Libs
Companion:	SDKROOT (Base SDK) (page 26).

LINK_WITH_STANDARD_LIBRARIES (Link With Standard Libraries)

Description:	Boolean value. Specifies whether to link the binary against the standard libraries. When not linking against the standard libraries, you should use OTHER_LDFLAGS (Other Linker Flags) (page 54) to specify the libraries to link binary against.
Values:	<ul style="list-style-type: none">• YES: Binary is linked against standard libraries.• NO: Binary is not linked against standard libraries.
Default value:	YES

LINKER_DISPLAYS_FILE_FOR_UNDEFINED_SYMBOLS (Verbose Undefined Symbols Info)

Description:	Boolean value. Specifies whether the linker displays additional information about undefined symbols, such as the source file the symbol is used in and whether the file references or defines the symbol.
--------------	---

Values:	<ul style="list-style-type: none">• YES: The linker displays additional information about undefined symbols (<code>ld -Y</code>).• NO: The linker does not display additional information about undefined symbols.
Default value:	YES

LINKER_DISPLAYS_MANGLED_NAMES (Display Mangled Names)

Description:	Boolean value. Specifies whether the linker displays mangled names for C++ symbols. This information can help in diagnosing C++ linking problems.
Values:	<ul style="list-style-type: none">• YES: The linker displays mangled names for C++ symbols (<code>ld --no-demangle</code>).• NO: The linker does not display mangled names for C++ symbols.
Default value:	NO

OTHER_LDFLAGS (Other Linker Flags)

Description:	Space-separated list of option specifications. Specifies additional options for linking the binary. These options are passed (as given) to the linker whether other build settings also specify values that correspond to these options. Therefore, you should look for the appropriate linker build setting to specify a particular linker option before using this build setting.
Default value:	None.
Related to:	OTHER_LDFLAGS_<VARIANT> (page 54).

OTHER_LDFLAGS_<VARIANT>

Description:	Space-separated list of option specifications. Specifies additional options for linking the binary for the specified variant. These options are passed (as given) to the linker whether other build settings also specify values that correspond to these options. Therefore, you should look for the appropriate linker build setting to specify a particular linker option before using this build setting.
Default value:	None.
Related to:	OTHER_LDFLAGS (Other Linker Flags) (page 54).

PREBINDING (Prebinding)

Description:	Boolean value. Specifies whether to prebind the generated binary.
Prerequisite:	<code>(\$ARCHS * \$VALID_ARCHS) IN {ppc, ppc970}</code>
Values:	<ul style="list-style-type: none">YES: The binary is prebound when the prerequisite is met.NO: The binary is not prebound.
Default value:	YES
Companion:	ARCHS (Architectures) (page 11), VALID_ARCHS (Valid Architectures) (page 14).

PRESERVE_DEAD_CODE_INITS_AND_TERMS (Don't Dead-Strip Inits and Terms)

Description:	Boolean value. Specifies whether to prevent initialization and termination routines from being dead-code stripped.
Prerequisite:	<code>\$DEAD_CODE_STRIPPING = YES</code>
Values:	<ul style="list-style-type: none">YES: Prevents dead-code stripping of initializers and terminators when the prerequisite is met.NO: Does not prevent dead-code stripping of initializers and terminators.
Default value:	NO
Companion:	DEAD_CODE_STRIPPING (Dead Code Stripping) (page 51).

STANDARD_C_PLUS_PLUS_LIBRARY_TYPE (C++ Standard Library Type)

Description:	Identifier. Specifies how the binary is linked against the C++ standard library: As a dynamic library or as a static library.
Prerequisite:	<code>\$GCC_SYMBOLS_PRIVATE_EXTERN = YES</code> . See for details.
Values:	<code>dynamic</code> : The C++ standard library is linked as a dynamic library. <code>static</code> : The C++ standard library is linked as a static library when the prerequisite is met.
Default value:	<code>dynamic</code>

Companion:	GCC_SYMBOLS_PRIVATE_EXTERN (Symbols Hidden by Default) (page 39).
------------	---

STRIP_INSTALLED_PRODUCT (Strip Linked Product)

Description:	Boolean value. Specifies whether to strip symbol information from the binary.
Prerequisite:	<code>\$DEPLOYMENT_POSTPROCESSING = YES</code>
Values:	<ul style="list-style-type: none">YES: Strips the generated binary when the prerequisite is met.NO: Does not strip the generated binary.
Default value:	NO
Companion:	DEPLOYMENT_POSTPROCESSING (Deployment Postprocessing) (page 17).
Related to:	STRIP_STYLE (Strip Style) (page 56).

STRIP_STYLE (Strip Style)

Description:	Identifier. Specifies the level of stripping performed on the binary.
Values:	<ul style="list-style-type: none"><code>all</code>: Strips the binary completely, removing the symbol table and relocation information.<code>non-global</code>: Strips nonglobal symbols but saves external symbols.<code>debugging</code>: Strips debugging symbols but saves local and global symbols.
Default value:	<ul style="list-style-type: none"><code>all</code>: Application and command-line products.<code>non-global</code>: Bundle products.<code>debugging</code>: Library and framework products.
Related to:	STRIP_INSTALLED_PRODUCT (Strip Linked Product) (page 56).

UNEXPORTED_SYMBOLS_FILE (Unexported Symbols File)

Description:	Project file path. Identifies a file containing the names of global symbols to be hidden. See <i>Minimizing Your Exported Symbols</i> in <i>Code Size Performance Guidelines</i> and <code>ld -exported_symbols_list</code> for details on exporting symbols.
--------------	---

Default value:	None.
Example value:	My_Private_Symbols

Product Layout Build Settings

These build settings specify the layout of bundle-based products.

CONTENTS_FOLDER_PATH

Description:	Bundle directory path. Specifies the directory inside the generated bundle that contains the product's files.
Effector:	WRAPPER_NAME (page 64).
Default value:	<code>\$WRAPPER_NAME/Contents</code>
Example value:	<code>MyProduct.bundle/Contents</code>
Affects:	EXECUTABLE_PATH (page 60), FRAMEWORKS_FOLDER_PATH (page 58), INFOPLIST_PATH (page 58), PLUGINS_FOLDER_PATH (page 62), PRIVATE_HEADERS_FOLDER_PATH (page 62), PUBLIC_HEADERS_FOLDER_PATH (page 62), SCRIPTS_FOLDER_PATH (page 63), SHARED_FRAMEWORKS_FOLDER_PATH (page 63), UNLOCALIZED_RESOURCES_FOLDER_PATH (page 63).

INFOPLIST_FILE

Description:	Filename. Specifies the name of the information property list file that specifies the bundled product's runtime properties. For details on information property list files, see <i>Information Property List Files</i> in <i>Runtime Configuration Guidelines</i> . You should not change the value of this build setting from its default. Doing so produces a bundled product that may not work as expected in OS X.
Default value:	<code>Info.plist</code>
Affects:	INFOPLIST_PATH (page 58).
Related to:	INFOPLIST_OUTPUT_FORMAT (page 58)

INFOPLIST_OUTPUT_FORMAT

Description:	Identifier. Specifies the whether the information property list file is written using the binary format.
Values:	<ul style="list-style-type: none">• <code>binary</code>: Specifies the binary format.• <code><unspecified></code>: Specifies the XML-based format.
Related to:	INFOPLIST_FILE (page 57).

INFOPLIST_PATH

Description:	Bundle file path. Specifies the path to the bundle's information property list file.
Effectors:	INFOPLIST_FILE (page 57), CONTENTS_FOLDER_PATH (page 57).
Default value:	<code>\$CONTENTS_FOLDER_PATH/\$INFOPLIST_FILE</code>
Example value:	<code>MyProduct.bundle/Contents/Info.plist</code>

INFOSTRINGS_PATH

Description:	Bundle file path. Specifies the file that contains the bundle's localized strings file.
Default value:	<code>/InfoPlist.strings</code>

FRAMEWORKS_FOLDER_PATH

Description:	Bundle directory path. Specifies the directory that contains the product's embedded frameworks.
Effector:	CONTENTS_FOLDER_PATH (page 57).
Default value:	<code>\$CONTENTS_FOLDER_PATH/Contents/Frameworks</code>
Example value:	<code>MyProduct.bundle/Contents/Frameworks</code>

GENERATE_PKGINFO_FILE

Description:	Boolean value. Specifies whether to generate the file specified by <code>PKGINFO_FILE_PATH</code> , even when the file is not expected.
Values:	<ul style="list-style-type: none">• YES: Always generate the package information file.• NO: Do not generate the package information file.
Default value:	<ul style="list-style-type: none">• YES: In application targets.• NO: In other target types.
Companion:	PKGINFO_FILE_PATH (page 62).

DOCUMENTATION_FOLDER_PATH

Description:	Bundle directory path. Identifies the directory that contains the bundle's documentation files.
Default value:	<code>/Documentation</code>

EXECUTABLES_FOLDER_PATH

Description:	Bundle directory path. Identifies the directory that contains additional binary files.
Effector:	CONTENTS_FOLDER_PATH (page 57).
Default value:	<code>\$CONTENTS_FOLDER_PATH/Executables</code>
Example value:	<code>MyProduct.bundle/Contents/Executables</code>

EXECUTABLE_EXTENSION

Description:	Identifier. Specifies the extension of the binary the target produces.
Effectors:	MACH_O_TYPE (page 12)

Default values:	<ul style="list-style-type: none">• <code>bundle</code>: When <code>\$MACH_O_TYPE = mh_bundle</code>.• <code>dylib</code>: When <code>\$MACH_O_TYPE = mh_dylib</code>.• <code>a</code>: When <code>\$MACH_O_TYPE = staticlib</code>.• <code>none</code>: When <code>\$MACH_O_TYPE = mh_executable</code>.
Affects:	EXECUTABLE_SUFFIX (page 61).

EXECUTABLE_FOLDER_PATH

Description:	Bundle directory path. Identifies the directory that contains the binary the target builds.
Effector:	CONTENTS_FOLDER_PATH (page 57).
Default value:	<code>\$CONTENTS_FOLDER_PATH/MacOS</code>
Example value:	<code>MyProduct.app/Contents/MacOS</code>

EXECUTABLE_NAME

Description:	Filename. Specifies the name of the binary the target produces.
Effectors:	PRODUCT_NAME (page 13), EXECUTABLE_PREFIX (page 61), EXECUTABLE_SUFFIX (page 61).
Default value:	<code>\$EXECUTABLE_PREFIX\$PRODUCT_NAME\$EXECUTABLE_SUFFIX</code>
Example values:	<ul style="list-style-type: none">• <code>MyProduct</code>• <code>MyDynamicLibrary.dylib</code>
Affects:	EXECUTABLE_PATH (page 60).

EXECUTABLE_PATH

Description:	Bundle directory path. Specifies the path to the binary the target produces within its bundle.
Effectors:	CONTENTS_FOLDER_PATH (page 57), , EXECUTABLE_NAME (page 60).

Default value:	<code>\$CONTENTS_FOLDER_PATH\$EXECUTABLE_NAME</code>
Example values:	<ul style="list-style-type: none">• <code>MyApp.app/Contents/MacOS/MyApp</code>• <code>MyDynamicLibrary.dylib</code>

EXECUTABLE_PREFIX

Description:	File prefix. Specifies the prefix of the binary filename.
Default value:	None.
Affects:	EXECUTABLE_NAME (page 60).

EXECUTABLE_SUFFIX

Description:	File suffix. Specifies the suffix of the binary filename (including the character that separates the extension from the rest of the bundle name).
Effector:	EXECUTABLE_EXTENSION (page 59).
Default value:	<code>.\$EXECUTABLE_EXTENSION</code>
Example value:	<code>.bundle</code>
Affects:	EXECUTABLE_NAME (page 60).

PACKAGE_TYPE

Description:	Uniform type identifier. Identifies the type of the product the target builds. Some products may be made up of a single binary or archive. Others may comprise several files, which are grouped under a single directory. These container directories are known as <i>bundles</i> .
Value:	<code>com.apple.package-type.wrapper</code> : In kernel extension, application, bundle, and plug-in targets. <code>com.apple.package-type.wrapper.framework</code> : In framework targets. <code>com.apple.package-type.mach-o-executable</code> : In command-line utility targets. <code>com.apple.package-type.mach-o-dylib</code> : In dynamic library targets. <code>com.apple.package-type.static-library</code> : In static library targets.

PLUGINS_FOLDER_PATH

Description:	Bundle directory path. Specifies the directory that contains the product's plug-ins.
Effector:	CONTENTS_FOLDER_PATH (page 57).
Default value:	<code>\$CONTENTS_FOLDER_PATH/Contents/PlugIns</code>
Example value:	<code>MyProduct.bundle/Contents/PlugIns</code>

PRIVATE_HEADERS_FOLDER_PATH

Description:	Bundle directory path. Specifies the directory that contains the product's private header files.
Effector:	CONTENTS_FOLDER_PATH (page 57).
Default value:	<code>\$CONTENTS_FOLDER_PATH/Contents/PrivateHeaders</code>
Example value:	<code>MyProduct.bundle/Contents/PrivateHeaders</code>

PKGINFO_FILE_PATH

Description:	Bundle file path. Specifies the file that contains the bundle's package information file.
Effector:	CONTENTS_FOLDER_PATH (page 57).
Value:	<code>\$CONTENTS_FOLDER_PATH/PkgInfo</code>
Example value:	<code>MyProduct.bundle/Contents/PkgInfo</code>

PUBLIC_HEADERS_FOLDER_PATH

Description:	Bundle directory path. Specifies the directory that contains the product's public header files.
Effector:	CONTENTS_FOLDER_PATH (page 57).
Default value:	<code>\$CONTENTS_FOLDER_PATH/Contents/PublicHeaders</code>
Example value:	<code>MyProduct.bundle/Contents/PublicHeaders</code>

SCRIPTS_FOLDER_PATH

Description:	Bundle directory path. Specifies the directory that contains the product's scripts.
Effector:	CONTENTS_FOLDER_PATH (page 57).
Default value:	<code>\$(UNLOCALIZED_RESOURCES_FOLDER_PATH)/Scripts</code>
Example value:	<code>MyProduct.bundle/Contents/Resources/Scripts</code>

SHARED_FRAMEWORKS_FOLDER_PATH

Description:	Bundle directory path. Specifies the directory that contains the product's shared frameworks.
Effector:	CONTENTS_FOLDER_PATH (page 57).
Default value:	<code>\$CONTENTS_FOLDER_PATH/Contents/SharedFrameworks</code>
Example value:	<code>MyProduct.bundle/Contents/SharedFrameworks</code>

UNLOCALIZED_RESOURCES_FOLDER_PATH

Description:	Bundle directory path. Specifies the directory that contains the product's unlocalized resources.
Effector:	CONTENTS_FOLDER_PATH (page 57).
Default value:	<code>\$CONTENTS_FOLDER_PATH/Contents/Resources</code>
Example value:	<code>MyProduct.bundle/Contents/Resources</code>

WRAPPER_EXTENSION (Wrapper Extension)

Description:	Identifier. Specifies the extension of the product bundle name (not including the character that separates the extension from the rest of the bundle name).
Effector:	Product type choose when the target was created

Default value:	<code>app</code> : In application products. <code>kext</code> : In kernel extension products. <code>bundle</code> : In bundle and plug-in products. <code>framework</code> : In framework products. <code>none</code> : In command-line utility, dynamic library, and static library products.
Example value:	<code>bundle</code>
Affects:	WRAPPER_SUFFIX (page 64).

WRAPPER_NAME

Description:	Filename. Specifies the filename (including the appropriate extension) of the product bundle.
Effectors:	PRODUCT_NAME (page 13), WRAPPER_SUFFIX (page 64).
Value:	<code>\$PRODUCT_NAME.\$WRAPPER_SUFFIX</code>
Example value:	<code>MyProduct.bundle</code>
Related to:	PACKAGE_TYPE (page 61).

WRAPPER_SUFFIX

Description:	File suffix. Specifies the suffix of the product bundle name (including the character that separates the extension from the rest of the bundle name).
Effector:	WRAPPER_EXTENSION (Wrapper Extension) (page 63).
Default value:	<code>.\$WRAPPER_EXTENSION</code>
Example value:	<code>.bundle</code>
Affects:	WRAPPER_NAME (page 64).

Code Signing Build Settings

These build settings specify code signing options.

CODE_SIGN_ENTITLEMENTS (Code Signing Entitlements)

Description:	Filename. Specifies the name of the application's entitlements property-list file. This build setting applies only to iOS applications.
Example value:	Entitlements.plist

CODE_SIGN_IDENTITY (Code Signing Identity)

Description:	Identifier. Specifies the name of a code signing identity.
Example value:	iPhone Developer

CODE_SIGN_RESOURCE_RULES_PATH (Code Signing Resource Rules Path)

Description:	File path. Identifies a property-list file containing resource-scanning instructions that override the rules for identifying bundle resources to sign.
Example value:	ResourceRules.plist

OTHER_CODE_SIGN_FLAGS (Other Code Signing Flags)

Description:	Space-separated list of option specifications. Specifies additional options to <code>codesign</code> for code-signing binaries.
Example value:	-i MySigningIdentifier

Copy Build Settings

These build settings specify file-copying options.

COPY_PHASE_STRIP (Strip Debug Symbols During Copy)

Description:	Boolean value. Specifies whether copied binaries are stripped of debugging symbols.
--------------	---

Values:	<ul style="list-style-type: none">• YES: Copied binaries are stripped of debugging symbols. This does not cause the binary produced by the linker to be stripped. Use STRIP_INSTALLED_PRODUCT (Strip Linked Product) (page 56) to have the linker strip the binary.• NO: Copied binaries are not stripped of debugging symbols
Default value:	NO

INSTALLHDRS_COPY_PHASE

Description:	Boolean value. Specifies whether the target's Copy Files build phases are executed in install-header builds.
Values:	<ul style="list-style-type: none">• YES: Copy Files build phases are executed in install-header builds.• NO: Copy Files build phases are not executed in install-header builds.
Default value:	NO
Companion:	ACTION (page 14).

INSTALLHDRS_SCRIPT_PHASE

Description:	Boolean value. Specifies whether the target's Run Script build phases are executed in install-header builds. See ACTION for details on install-header builds.
Values:	<ul style="list-style-type: none">• YES: Run Script build phases are executed in install-header builds.• NO: Run Script build phases are not executed in install-header builds.
Default value:	NO
Companion:	ACTION (page 14).

REMOVE_CVS_FROM_RESOURCES

Description:	Boolean value. Specifies whether to remove CVS directories from bundle resources when they are copied.
--------------	--

Values:	<ul style="list-style-type: none">• YES: CVS directories are removed from copied bundle resources.• NO: CVS directories are not removed from copied bundle resources.
Default value:	YES

REMOVE_SVN_FROM_RESOURCES

Description:	Boolean value. Specifies whether to remove SVN directories from bundle resources when they are copied.
Values:	<ul style="list-style-type: none">• YES: SVN directories are removed from copied bundle resources.• NO: SVN directories are not removed from copied bundle resources.
Default value:	YES

VERBOSE_PBXCP

Description:	Boolean value. Specifies whether the target's Copy Files build phases generate additional information when copying files.
Values:	<ul style="list-style-type: none">• YES: Copy Files build phases generate additional information.• NO: Copy Files build phases do not generate additional information.
Default value:	NO

User Location Build Settings

These build settings represent locations in the User realm in the filesystem.

HOME

Description:	File path. Specifies the path to the user's home directory.
Value:	~: Fully qualified path to a user's home directory.
Example:	/Users/genica

Affects:	INSTALL_PATH (Installation Directory) (page 23).
----------	--

USER_LIBRARY_DIR

Description:	File path. Specifies the path the user's Library directory.
Value:	~/Library: Fully qualified path to the user's Library directory.
Affects:	INSTALL_PATH (Installation Directory) (page 23).

System Location Build Setting

This build setting represents a location in the System realm in the file system.

SYSTEM_LIBRARY_DIR

Description:	Directory path. Specifies the path of the /System/Library directory.
Value:	/System/Library
Affects:	INSTALL_PATH (Installation Directory) (page 23).

Document Revision History

This table describes the changes to *Xcode Build Setting Reference*.

Date	Notes
2010-10-05	<p>Added build settings for the Interface Builder compiler.</p> <p>Added Interface Builder Compiler Build Settings (page 49).</p> <p>Added VALIDATE_PRODUCT (Validate Built Product) (page 20).</p> <p>Added GCC_WARN_ABOUT_GLOBAL_CONSTRUCTORS (Global Construction or Destruction Required) (page 41).</p>
2010-07-01	<p>Made minor content corrections.</p> <p>Added TARGETED_DEVICE_FAMILY (Targeted Device Family) (page 19).</p> <p>Updated IPHONEOS_DEPLOYMENT_TARGET (iOS Deployment Target) (page 46) with new value information.</p> <p>Updated SDKROOT (Base SDK) (page 26) with new value information.</p>
2009-10-19	<p>Added information about SSE4.1 and SSE4.2 extensions.</p> <p>Added GCC_ENABLE_SSE41_EXTENSIONS (Enable SSE4.1 Extensions) (page 35).</p> <p>Added GCC_ENABLE_SSE42_EXTENSIONS (Enable SSE4.2 Extensions) (page 35).</p>
2009-05-28	<p>Updated default value for the Valid Architectures build setting.</p> <p>Updated VALID_ARCHS (Valid Architectures) (page 14).</p>
2009-03-04	<p>Added build settings to manage PNG-file compression, dependent libraries, and product architectures.</p> <p>Added COMPRESS_PNG_FILES (Compress .png files) (page 16).</p>

Date	Notes
	<p>Added EXECUTABLE_PATH (page 60), LD_DYLIB_INSTALL_NAME (Dynamic Library Install Name) (page 52), LD_RUNPATH_SEARCH_PATHS (Runpath Search Paths) (page 52).</p> <p>Added ONLY_ACTIVE_ARCH (Build Active Architecture Only) (page 18).</p>
2009-02-04	<p>Made minor corrections.</p> <p>Updated CACHE_ROOT (page 21) and SHARED_PRECOMPS_DIR (Precompiled Headers Cache Path) (page 26) with new value information.</p> <p>Corrected values in SCRIPTS_FOLDER_PATH (page 63).</p>
2008-11-19	<p>Made minor changes.</p> <p>Removed information about OTHER_LDFLAGS_<ARCH> and OTHER_LDFLAGS_<VARIANT>_<ARCH>.</p> <p>Added information about conditional build settings to Introduction (page 8).</p> <p>Undocumented ZeroLink.</p>
2008-10-15	<p>Added build settings and made content changes.</p> <p>Added GCC_ENABLE_OBJC_GC (Objective-C Garbage Collection) (page 34), INFOPLIST_OUTPUT_FORMAT (page 58), INFOPLIST_OTHER_PREPROCESSOR_FLAGS (Info.plist Other Preprocessor Flags) (page 45), INFOPLIST_PREFIX_HEADER (Info.plist Preprocessor Prefix File) (page 45), INFOPLIST_PREPROCESS (Preprocess Info.plist File) (page 45), INFOPLIST_PREPROCESSOR_DEFINITIONS (Info.plist Preprocessor Definitions) (page 45), IPHONEOS_DEPLOYMENT_TARGET (iOS Deployment Target) (page 46).</p> <p>Added information to USER_HEADER_SEARCH_PATHS (User Header Search Paths) (page 48).</p> <p>Added aliases for a few build settings.</p> <p>Corrected value information for TARGET_NAME (page 13) and PROJECT_NAME (page 13).</p>

Date	Notes
	Removed information about ONLY_LINK_ESSENTIAL_SYMBOLS (Only Link Essential Symbols), PER_ARCH_CFLAGS_<ARCH>.
2008-05-21	<p>Update for Xcode 3.1.</p> <p>Added STRINGS_FILE_OUTPUT_ENCODING to Build Properties Build Settings (page 14).</p> <p>Added armv6 to VALID_ARCHS (Valid Architectures) (page 14).</p>
2006-11-07	Added x86_64 to the default value of the VALID_ARCHS build setting.
2006-10-03	<p>Added information for the GCC_ENABLE_SYMBOL_SEPARATION and ONLY_LINK_ESSENTIAL_SYMBOLS build settings.</p> <p>Added information for GCC_ENABLE_SYMBOL_SEPARATION (Separate PCH Symbols) (page 35) and ONLY_LINK_ESSENTIAL_SYMBOLS (Only Link Essential Symbols).</p>
2006-05-23	New document that describes the build settings used in the Xcode build system to compile source code and produce binary files.



Apple Inc.
Copyright © 2010 Apple Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer or device for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-branded products.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple, the Apple logo, iPad, iPhone, iPod, iPod touch, Mac, Objective-C, OS X, and Xcode are trademarks of Apple Inc., registered in the U.S. and other countries.

IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

PowerPC and the PowerPC logo are trademarks of International Business Machines Corporation, used under license therefrom.

APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT, ERROR OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

Some jurisdictions do not allow the exclusion of implied warranties or liability, so the above exclusion may not apply to you.

Index

A

ACTION 14
ALWAYS_SEARCH_USER_PATHS 31
ARCHS 11

B

build settings
 always search user paths 31
 architectures 11
 auto-vectorization 32
 Base SDK 26
 build active architecture only 18
 build and product locations 20
 build products path 27
 build properties 14
 build variants 15
 C++ standard library type 55
 call C++ default constructors/destructors in
 Objective-C 37
 code signing 64
 code signing entitlements 65
 code signing identity 65
 code signing resource rules path 65
 CodeWarrior-style inline assembly 32
 compatibility version 11
 compiler 31
 compress .png files 16
 copy 65
 current library version 12
 dead code stripping 51
 debug information format 17
 deployment location 22
 deployment postprocessing 17
 display mangled names 54
 don't dead-strip inits and terms 55
 dynamic library install name 52
 effective C++ violation 42
 enable C++ exceptions 33
 enable C++ runtime types 33
 enable Objective-C exceptions 34
 enable SSE3 extensions 35
 enable SSE4.1 extensions 35
 enable SSE4.2 extensions 35
 exported symbols file 52
 feedback-directed optimization 36
 fix & continue 34
 flatten compiled xib files 49
 force package info generation 12
 framework search paths 31
 garbage collection support 34
 generate debug symbols 36
 global construction or destruction required 41
 header search paths 44
 hidden local variables 44
 inhibit all warnings 43
 installation build products location 22
 installation directory 23
 instruction scheduling 37
 intermediate build files path 25
 iOS Deployment Target 46
 level of debug symbols 32
 link with standard libraries 53
 linker 51
 mismatched return type 42
 nonvirtual destructor 43
 optimization level 37
 OS X deployment target 46

- other C flags [47](#)
 - other C++ flags [48](#)
 - other code signing flags [65](#)
 - other interface builder compiler flags [49](#)
 - other linker flags [54](#)
 - other warning flags [49](#)
 - overriding plug-in and framework directory [50](#)
 - pedantic warnings [43](#)
 - per-configuration build products path [21](#)
 - per-configuration intermediate file path [21](#)
 - plug-in search paths [50](#)
 - plug-ins [50](#)
 - prebinding [55](#)
 - precompile prefix header [38](#)
 - precompiled headers cache path [26](#)
 - preprocessor macros [38](#)
 - preprocessor macros not used in precompiled headers [39](#)
 - preserve private external symbols [52](#)
 - product information [11](#)
 - product layout [57](#)
 - runpath search paths [52](#)
 - separate PCH symbols [35](#)
 - show errors [50](#)
 - show notices [50](#)
 - show warnings [51](#)
 - sign comparision [44](#)
 - statics are thread safe [40](#)
 - strip debug symbols during copy [65](#)
 - strip linked product [56](#)
 - strip style [56](#)
 - symbols hidden by default [39](#)
 - system location [68](#)
 - targeted device family [19](#)
 - unexported symbols file [56](#)
 - unroll loops [40](#)
 - unused variables [42](#)
 - use nasm to process .asm files [40](#)
 - user header search paths [48](#)
 - user location [67](#)
 - validate built product [20](#)
 - verbose undefined symbols info [53](#)
 - wrapper extension [63](#)
 - BUILD_COMPONENTS [15](#)
 - BUILD_VARIANTS [15](#)
 - BUILT_PRODUCTS_DIR [20](#)
 - bundle directory path [8](#)
 - bundle file path [8](#)
-
- ## C
- C-based language [8](#)
 - CACHE_ROOT [21](#)
 - CC_OPTIMIZATION_LEVEL [37](#)
 - CODE_SIGN_ENTITLEMENTS [65](#)
 - CODE_SIGN_IDENTITY [65](#)
 - companion [8](#)
 - COMPRESS_PNG_FILES [16](#)
 - CONFIGURATION [16](#)
 - CONFIGURATION_BUILD_DIR [21](#)
 - CONFIGURATION_TEMP_DIR [21](#)
 - CONTENTS_FOLDER_PATH [57](#)
 - COPY_PHASE_STRIP [65](#)
 - CURRENT_ARCH [16](#)
 - CURRENT_VARIANT [16](#)
-
- ## D
- DEAD_CODE_STRIPPING [51](#)
 - DEBUG_INFORMATION_FORMAT [17](#)
 - DEPLOYMENT_LOCATION [22](#)
 - DEPLOYMENT_POSTPROCESSING [17](#)
 - DERIVED_FILE_DIR [22](#)
 - directory path [9](#)
 - DOCUMENTATION_FOLDER_PATH [59](#)
 - DSTROOT [22](#)
 - DYLIB_COMPATIBILITY_VERSION [11](#)
 - DYLIB_CURRENT_VERSION [12](#)

E

effector 9
ENABLE_HEADER_DEPENDENCIES 18
EXECUTABLES_FOLDER_PATH 59
EXECUTABLE_EXTENSION 59
EXECUTABLE_FOLDER_PATH 60
EXECUTABLE_NAME 60
EXECUTABLE_PATH 60
EXECUTABLE_PREFIX 61
EXECUTABLE_SUFFIX 61
EXPORTED_SYMBOLS_FILE 52

F

file path 9
filename 9
FRAMEWORKS_FOLDER_PATH 58
FRAMEWORK_SEARCH_PATHS 31

G

GCC_AUTO_VECTORIZATION 32
GCC_CW_ASM_SYNTAX 32
GCC_DEBUGGING_SYMBOLS 32
GCC_DYNAMIC_NO_PIC 33
GCC_ENABLE_CPP_EXCEPTIONS 33
GCC_ENABLE_CPP_RTTI 33
GCC_ENABLE_FIX_AND_CONTINUE 34
GCC_ENABLE_OBJC_EXCEPTIONS 34
GCC_ENABLE_OBJC_GC 34
GCC_ENABLE_SSE3_EXTENSIONS 35
GCC_ENABLE_SSE41_EXTENSIONS 35
GCC_ENABLE_SSE42_EXTENSIONS 35
GCC_ENABLE_SYMBOL_SEPARATION 35
GCC_FEEDBACK_DIRECTED_OPTIMIZATION 36
GCC_GENERATE_DEBUGGING_SYMBOLS 36
GCC_MODEL_TUNING 37
GCC_OBJC_CALL_CXX_CDTORS 37
GCC_PRECOMPILE_PREFIX_HEADER 38
GCC_PREFIX_HEADER 38

GCC_PREPROCESSOR_DEFINITIONS 38
GCC_PREPROCESSOR_DEFINITIONS_NOT_USED_IN_PRECOMPS 39
GCC_SYMBOLS_PRIVATE_EXTERN 39
GCC_THREADSAFE_STATICS 40
GCC_UNROLL_LOOPS 40
GCC_USE_NASM_FOR_ASM_FILETYPE 40
GCC_VERSION 40
GCC_VERSION_IDENTIFIER 41
GCC_WARN_ABOUT_GLOBAL_CONSTRUCTORS 41
GCC_WARN_ABOUT_RETURN_TYPE 42
GCC_WARN_EFFECTIVE_CPLUSPLUS_VIOLATIONS 42
GCC_WARN_HIDDEN_VIRTUAL_FUNCTIONS 42
GCC_WARN_INHIBIT_ALL_WARNINGS 43
GCC_WARN_NON_VIRTUAL_DESTRUCTOR 43
GCC_WARN_PEDANTIC 43
GCC_WARN_SHADOW 44
GCC_WARN_SIGN_COMPARE 44
GCC_WARN_UNUSED_VARIABLE 42
GENERATE_PKGINFO_FILE 12, 59

H

HEADERMAP_INCLUDES_FLAT_ENTRIES_FOR_TARGET_BEING_BUILT 30
HEADERMAP_INCLUDES_FRAMEWORK_ENTRIES_FOR_ALL_PRODUCT_TYPES 30
HEADERMAP_INCLUDES_PROJECT_HEADERS 30
HEADER_SEARCH_PATHS 44
HOME 67

I

IBC_ERRORS 50
IBC_FLATTEN_NIBS 49
IBC_NOTICES 50
IBC_OTHER_FLAGS 49
IBC_OVERRIDING_PLUGINS_AND_FRAMEWORKS_DIR 50
IBC_PLUGINS 50

IBC_PLUGIN_SEARCH_PATHS [50](#)
IBC_WARNINGS [51](#)
identifier [9](#)
INFOPLIST_FILE [57](#)
INFOPLIST_OTHER_PREPROCESSOR_FLAGS [45](#)
INFOPLIST_OUTPUT_FORMAT [58](#)
INFOPLIST_PATH [58](#)
INFOPLIST_PREFIX_HEADER [45](#)
INFOPLIST_PREPROCESS [45](#)
INFOPLIST_PREPROCESSOR_DEFINITIONS [45](#)
INFOSTRINGS_PATH [58](#)
installed product [9](#)
installed product directory [9](#)
INSTALLHDRS_COPY_PHASE [66](#)
INSTALLHDRS_SCRIPT_PHASE [66](#)
INSTALL_DIR [23](#)
INSTALL_PATH [23](#)
IPHONEOS_DEPLOYMENT_TARGET [46](#)

K

KEEP_PRIVATE_EXTERNS [52](#)

L

LD_DYLIB_INSTALL_NAME [52](#)
LD_RUNPATH_SEARCH_PATHS [52](#)
LIBRARY_SEARCH_PATHS [53](#)
LINKER_DISPLAYS_FILE_FOR_UNDEFINED_SYMBOLS
[53](#)
LINKER_DISPLAYS_MANGLED_NAMES [54](#)
LINK_WITH_STANDARD_LIBRARIES [53](#)

M

MACH_O_TYPE [12](#)
MACOSX_DEPLOYMENT_TARGET [46](#)

N

NATIVE_ARCH [18](#)

numeric identifier [9](#)

O

OBJECT_FILE_DIR [24](#)
OBJECT_FILE_DIR_<VARIANT> [24](#)
OBJROOT [25](#)
ONLY_ACTIVE_ARCH [18](#)
option specification [9](#)
OTHER_CFLAGS [47](#)
OTHER_CFLAGS_<VARIANT> [47](#)
OTHER_CODE_SIGN_FLAGS [65](#)
OTHER_CPLUSPLUSFLAGS [48](#)
OTHER_LDFLAGS [54](#)
OTHER_LDFLAGS_<VARIANT> [54](#)

P

PACKAGE_TYPE [61](#)
PATH_PREFIXES_EXCLUDED_FROM_HEADER_DEPENDENCIES
[19](#)
PKGINFO_FILE_PATH [62](#)
PLUGINS_FOLDER_PATH [62](#)
PREBINDING [55](#)
PRESERVE_DEAD_CODE_INITS_AND_TERMS [55](#)
PRIVATE_HEADERS_FOLDER_PATH [62](#)
PRODUCT_NAME [13](#)
project directory path [9](#)
project file path [9](#)
PROJECT_NAME [13](#)
PROJECT_TEMP_DIR [25](#)
PUBLIC_HEADERS_FOLDER_PATH [62](#)

R

REMOVE_CVS_FROM_RESOURCES [66](#)
REMOVE_SVN_FROM_RESOURCES [67](#)
RETAIN_RAW_BINARIES [19](#)
REZ_COLLECTOR_DIR [25](#)
REZ_OBJECTS_DIR [26](#)

S

SCRIPTS_FOLDER_PATH [63](#)
SDKROOT [26](#)
SHARED_FRAMEWORKS_FOLDER_PATH [63](#)
SHARED_PRECOMPS_DIR [26](#)
SKIP_INSTALL [27](#)
SRCROOT [27](#)
STANDARD_C_PLUS_PLUS_LIBRARY_TYPE [55](#)
STRINGS_FILE_OUTPUT_ENCODING [19](#)
STRIP_INSTALLED_PRODUCT [56](#)
STRIP_STYLE [56](#)
SYMROOT [27](#)
SYSTEM_LIBRARY_DIR [68](#)

T

TARGETED_DEVICE_FAMILY [19](#)
TARGET_BUILD_DIR [28](#)
TARGET_NAME [13](#)
TARGET_TEMP_DIR [29](#)

U

UNEXPORTED_SYMBOLS_FILE [56](#)
uniform type identifier [10](#)
UNLOCALIZED_RESOURCES_FOLDER_PATH [63](#)
USER_HEADER_SEARCH_PATHS [48](#)
USER_LIBRARY_DIR [68](#)

V

VALIDATE_PRODUCT [20](#)
VALID_ARCHS [14](#)
VERBOSE_PBXCP [67](#)

W

WARNING_CFLAGS [49](#)
WRAPPER_EXTENSION [63](#)
WRAPPER_NAME [64](#)
WRAPPER_SUFFIX [64](#)