



(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
06.10.2021 Bulletin 2021/40

(21) Application number: **19888827.3**

(22) Date of filing: **28.11.2019**

(51) Int Cl.:
A61L 9/18 ^(2006.01) **A61L 2/08** ^(2006.01)
F21V 33/00 ^(2006.01) **F21Y 115/10** ^(2016.01)

(86) International application number:
PCT/KR2019/016621

(87) International publication number:
WO 2020/111833 (04.06.2020 Gazette 2020/23)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
KH MA MD TN

(30) Priority: **29.11.2018 US 201862773138 P**
27.11.2019 US 201916697500

(71) Applicant: **Seoul Viosys Co., Ltd**
Ansan-si, Gyeonggi-do 15429 (KR)

(72) Inventors:
• **BAE, Hee Ho**
Ansan-si Gyeonggi-do 15429 (KR)
• **YOON, Yeong Min**
Ansan-si Gyeonggi-do 15429 (KR)
• **LEE, A Young**
Ansan-si Gyeonggi-do 15429 (KR)


(74) Representative: **Stolmár & Partner**
Patentanwälte PartG mbB
Blumenstraße 17
80331 München (DE)

(54) **LED LIGHTING DEVICE HAVING STERILIZING FUNCTION**

(57) A lighting device according to an embodiment comprises: a white light emitting device comprising at least one first light-emitting diode and a wavelength converter, thereby implementing white light; and at least one second light-emitting diode for emitting light appropriate for killing at least one pathogenic microorganism. The first light-emitting diode emits light having a center wavelength in the range of about 300-420 nm. The second light-emitting diode emits light having a center wavelength in the range of about 400-420 nm. The wave converter comprises wavelength conversion materials for

converting the light from the first light-emitting diode into blue light, green light, and red light. The white light implemented by the white light emitting device and the light produced by the second light-emitting diode are emitted outwards. In the radiation luminance spectrum of the white light implemented by the white light emitting device, the radiation luminance of the center wavelength of the light emitted by the first light-emitting diode is smaller than the radiation luminance of the peak wavelength of the blue light emitted by the blue wavelength conversion material.

FIG. 3



Description

[Technical Field]

- 5 **[0001]** Exemplary embodiments of the present disclosure relate to a lighting apparatus having a sterilizing function using LEDs.

[Background Art]

- 10 **[0002]** As an inorganic light source, light emitting diodes have been used in various fields including displays, vehicular lamps, general lighting, and the like. In particular, with various advantages such as long lifespan, low power consumption, and rapid response, light emitting diodes have been replacing existing light sources in the art.

- [0003]** Sunlight exhibits a broad spectrum of wavelengths in the ultraviolet, visible and infrared regions, and in particular, it is well known that ultraviolet rays have a sterilizing function. Accordingly, various light sources having the sterilizing function using ultraviolet LEDs have been developed.

- 15 **[0004]** However, ultraviolet rays with the sterilizing function are generally harmful to the human body, particularly to the human eyes or skin. For this reason, light sources using ultraviolet LEDs are subject to restrictions and must be used in a space without people. That is, ultraviolet LEDs with the sterilizing function are not generally suitable for use in lighting apparatuses in places where people are active.

20

[Disclosure]

[Technical Problem]

- 25 **[0005]** Exemplary embodiments of the present disclosure provide a lighting apparatus having a sterilizing function without harming the human body and a lighting system having the same.

[0006] Exemplary embodiments of the present disclosure provide a lighting apparatus having a sterilizing function without causing eye diseases or skin diseases and a lighting system having the same.

- 30 **[0007]** Exemplary embodiments of the present disclosure provide a lighting apparatus capable of changing color temperature over time like sunlight and having a sterilizing function and a lighting system having the same.

[0008] Exemplary embodiments of the present disclosure provide a lighting apparatus capable of changing color temperature in consideration of the color temperature of sunlight according to a region and time and having a sterilization function, and a lighting system having the same.

- 35 [Technical Solution]

- [0009]** An exemplary embodiment of the present disclosure provides a light emitting apparatus, including: a white light emitting device including at least one first light emitting diode and a wavelength converter to implement white light; and at least one second light emitting diode emitting light suitable for sterilizing at least one pathogenic microorganism, wherein the first light emitting diode emits light having a central wavelength in a range of about 300 nm to about 420 nm, the second light emitting diode emits light having a central wavelength in a range of about 400 nm to about 420 nm, the wavelength converter includes a plurality of wavelength conversion substances to convert light of the first light emitting diode into white light, the lighting apparatus emits the white light implemented in the white light emitting device and light generated by the second light emitting diode to the outside, and, in irradiance spectrum of the white light implemented in the white light emitting device, irradiance of the central wavelength of light emitted from the first light emitting diode is smaller than that of a peak wavelength of blue light emitted from a blue wavelength conversion substance of the wavelength conversion substances.

- [0010]** An exemplary embodiment of the present disclosure provides a light emitting apparatus, including: a first light emitting unit including a first first-light emitting diode emitting light having a central wavelength in a range of about 300 nm to about 420 nm and a first wavelength converter; a second light emitting unit including a first second-light emitting diode emitting light having a central wavelength in a range of about 300 nm to about 420 nm and a second wavelength converter; a third light emitting unit including a first third-light emitting diode emitting light having a central wavelength in a range of about 300 nm to about 420 nm and a third wavelength converter; at least one second light emitting diode emitting light having a central wavelength in a range of about 400 nm to about 420 nm, wherein the first to third wavelength converters include a blue wavelength conversion substance for converting light emitted from the light emitting diode into blue light, respectively, and, in irradiance spectrum of light emitted to the outside, irradiance of the central wavelength of light generated by each light emitting diode in the first to third light emitting units and emitted to the outside without wavelength conversion is smaller than that of a peak wavelength of blue light emitted from the corresponding respective

wavelength converters in the first to third light emitting units.

[0011] In addition, embodiments of the present disclosure provide a lighting system including the lighting apparatus mentioned above.

5 [Description of Drawings]

[0012]

FIG. 1 is a graph showing a degree of hazard according to wavelengths of blue light.

FIG. 2 shows a spectrum of a conventional white light source using a blue light emitting diode.

FIG. 3 is a schematic plan view illustrating a lighting apparatus according to an embodiment of the present disclosure.

FIG. 4 is a schematic cross-sectional view taken along the line A-A of FIG. 3.

FIG. 5 shows representative spectra of a lighting apparatus according to an embodiment of the present disclosure.

FIG. 6 is a schematic cross-sectional view illustrating a lighting apparatus according to another embodiment of the present disclosure.

FIG. 7 is a schematic cross-sectional view illustrating a lighting apparatus according to another embodiment of the present disclosure.

FIG. 8 is a schematic cross-sectional view illustrating a lighting apparatus according to another embodiment of the present disclosure.

FIG. 9 is a plan view illustrating a lighting apparatus according to another embodiment of the present disclosure.

FIG. 10 is a schematic cross-sectional view taken along the line B-B of FIG. 9.

FIG. 11 is a schematic cross-sectional view illustrating a light emitting unit according to another embodiment of the present disclosure.

FIG. 12 is a block diagram illustrating a lighting apparatus according to an embodiment of the present disclosure.

FIG. 13 is a flowchart illustrating a method of driving a light irradiation apparatus according to an embodiment of the present disclosure.

FIG. 14 is a flowchart illustrating a method of driving the light irradiation apparatus according to an embodiment of the present disclosure.

FIG. 15A and FIG. 15B are graphs illustrating results of sterilization experiment on *Escherichia coli* and *Staphylococcus aureus* according to doses of light of a second light emitting diode.

FIG. 16 shows photographs showing the result of sterilization experiment on *Escherichia coli* cultured in the medium according to doses of light of the second light emitting diode.

[Best Mode]

[0013] Hereinafter, exemplary embodiments of the present disclosure will be described in detail with reference to the accompanying drawings. The following embodiments are provided by way of example so as to fully convey the spirit of the present disclosure to those skilled in the art to which the present disclosure pertains. Accordingly, the present disclosure is not limited to the embodiments disclosed herein and can also be implemented in different forms. In the drawings, widths, lengths, thicknesses, and the like of elements can be exaggerated for clarity and descriptive purposes. When an element or layer is referred to as being "disposed above" or "disposed on" another element or layer, it can be directly "disposed above" or "disposed on" the other element or layer or intervening elements or layers can be present. Throughout the specification, like reference numerals denote like elements having the same or similar functions.

[0014] A lighting apparatus according to an embodiment of the present disclosure includes: a white light emitting device including at least one first light emitting diode and a wavelength converter to implement white light; and at least one second light emitting diode emitting light suitable for sterilizing at least one pathogenic microorganism, wherein the first light emitting diode emits light having a central wavelength in a range of about 300 nm to about 420 nm, the second light emitting diode emits light having a central wavelength in a range of about 400 nm to about 420 nm, the wavelength converter includes a plurality of wavelength conversion substances to convert light of the first light emitting diode into white light, the lighting apparatus emits the white light implemented in the white light emitting device and light generated by the second light emitting diode to the outside, and, in irradiance spectrum of the white light implemented in the white light emitting device, irradiance of the central wavelength of light emitted from the first light emitting diode is smaller than that of a peak wavelength of blue light emitted from a blue wavelength conversion substance of the wavelength conversion substances.

[0015] In this specification, sterilization means killing or damaging a pathogenic microorganism so as to reduce or prevent the growth of the pathogenic microorganism.

[0016] The lighting apparatus having a sterilizing function may be provided by using the second light emitting diode suitable for sterilizing pathogenic microorganisms together with the white light emitting device. Since irradiance of light

emitted from the first light emitting diode is smaller than that of the peak wavelength of blue light emitted from the blue wavelength conversion substance, the lighting apparatus may prevent the first light emitting diode from causing harm to the human body or from causing eye diseases or skin diseases.

[0017] In an embodiment, the wavelength converter may include wavelength conversion substances for converting light of the first light emitting diode into blue, green and red light. In another embodiment, the wavelength converter may include blue and orange wavelength conversion substances for converting light of the first light emitting diode into blue and orange light.

[0018] The white light and light emitted from the second light emitting diode may be mixed and emitted. For example, the lighting apparatus may further include a diffusion plate for mixing the white light and light emitted from the second light emitting diode.

[0019] The second light emitting diode may emit light having a central wavelength of about 405 nm. The wavelength of 405 nm is suitable for sterilizing pathogenic microorganisms without causing eye diseases or skin diseases in the visible region.

[0020] Meanwhile, the wavelength converter may include a phosphor or a quantum dot. For example, the wavelength converter may include a blue phosphor, a green phosphor and a red phosphor. In embodiments, these phosphors may be replaced individually or all with quantum dots.

[0021] In an embodiment, light emitted from the second light emitting diode may be emitted to the outside without passing through the wavelength converter. In another embodiment, a portion of light emitted from the second light emitting diode may be wavelength-converted by the wavelength converter.

[0022] Irradiance of light generated by the at least one second light emitting diode and emitted to the outside is greater than that of light generated by the at least one first light emitting diode and emitted to the outside without wavelength conversion. Accordingly, pathogenic microorganisms may be sterilized using the second light emitting diode.

[0023] The lighting apparatus may include a greater number of first light emitting diodes than that of the at least one second light emitting diode. Accordingly, the irradiance of the white light emitting device is greater than that of the second light emitting diode.

[0024] Meanwhile, irradiance of light generated by the at least one second light emitting diode and emitted to the outside may be smaller than or equal to 1W/m^2 .

[0025] The lighting apparatus may further include a circuit board for mounting the first light emitting diode and the second light emitting diode.

[0026] In a particular embodiment, the first light emitting diode may emit light having a central wavelength in a range of about 400 nm to about 420 nm. Furthermore, the first light emitting diode may emit light having a central wavelength of about 405 nm. In this case, a portion of light emitted from the first light emitting diode may be emitted to the outside without wavelength conversion to sterilize pathogenic microorganisms. In particular, when the white light emitting device implements white light of 6500K, since irradiance of light of the central wavelength emitted from the first light emitting diode in this white light is relatively large compared to white light of other color temperatures, the pathogenic microorganisms may be sterilized using the white light emitting device without using the second light emitting diode. Thus, in a particular embodiment, the second light emitting diode may be omitted.

[0027] Furthermore, since the irradiance of light of the central wavelength emitted from the first light emitting diode changes according to a color temperature of white light implemented by the white light emitting device, according to the change in this irradiance, irradiance of the light emitted from the second light emitting diode may be changed to provide irradiance suitable for sterilizing the pathogenic microorganisms.

[0028] Meanwhile, the lighting apparatus may include a location information receiver for receiving location information; and a controller for receiving the location information from the location information receiver and controlling a dose of light emitted from the white light emitting device; wherein the controller may calculate a dose of light to be emitted by the white light emitting device based on the location information, and may control the white light emitting device to emit light in an amount equivalent to the dose.

[0029] In an embodiment, the controller may calculate an appropriate dose based on the location information provided by the location information receiver, and may control the light source to emit the appropriate dose.

[0030] In another embodiment, the location information receiver may calculate location information of the lighting apparatus, the controller may receive the location information and calculate a dose of external light and an appropriate dose at the place where the lighting apparatus is located, and may control the white light emitting device to emit light in an amount equivalent to a difference between the appropriate dose and the dose of external light.

[0031] In an embodiment, the controller may calculate time information from the location information and may control a dose of light to be emitted by the white light emitting device according to the time information.

[0032] A lighting apparatus according to another embodiment of the present disclosure includes: a first light emitting unit including a first light emitting diode emitting light having a central wavelength in a range of about 300 nm to about 420 nm and a first wavelength converter; a second light emitting unit including a first second-light emitting diode emitting light having a central wavelength in a range of about 300 nm to about 420 nm and a second wavelength converter;

a third light emitting unit including a first third-light emitting diode emitting light having a central wavelength in a range of about 300 nm to about 420 nm and a third wavelength converter, at least one second light emitting diode emitting light having a central wavelength in a range of about 400 nm to about 420 nm; wherein the first to third wavelength converters include a blue wavelength conversion substance for converting light emitted from the light emitting diode into blue light, respectively, and, in irradiance spectrum of light emitted to the outside, irradiance of the central wavelength of light generated by each light emitting diode in the first to third light emitting units and emitted to the outside without wavelength conversion is smaller than that of a peak wavelength of blue light emitted from the corresponding respective wavelength converters in the first to third light emitting units.

[0033] The lighting apparatus includes a plurality of light emitting units, thereby implementing white light having various color temperatures.

[0034] Meanwhile, the first to third wavelength converters may further include a green wavelength conversion substance for converting light emitted from the first light emitting diode into green light and a red wavelength conversion substance for converting light emitted from the first light emitting diode into red light, respectively. Accordingly, the first to third light emitting units may implement white light, respectively.

[0035] The first first- to first third-light emitting diodes may emit light having a central wavelength in a range of about 400 nm to about 420 nm. The first first- to first third-light emitting diodes may emit light having the same peak wavelength, but are not limited thereto.

[0036] Light wavelength-converted by the wavelength converter and light emitted from the second light emitting diode may be mixed and emitted to the outside. The mixed light may be white light.

[0037] Furthermore, the lighting apparatus may further include a diffusion plate suitable for mixing light wavelength-converted by the wavelength converter and light emitted from the second light emitting diode.

[0038] Meanwhile, the first light emitting unit, the second light emitting unit and the third light emitting unit may emit white light having different color temperatures. In addition, the first light emitting unit, the second light emitting unit and the third light emitting unit may be driven independently of one another.

[0039] Accordingly, the lighting apparatus may change the color temperature to suit the change of sunlight over time.

[0040] Meanwhile, the first first- to first third-light emitting diodes may be disposed more than the at least one second light emitting diode, respectively.

[0041] The lighting apparatus may further include a circuit board on which the first first- to first third-light emitting diodes and the second light emitting diode are mounted.

[0042] In an embodiment, the lighting apparatus may further include a location information receiver for receiving location information, and a controller for controlling a dose of light emitted from the first to third light emitting units, wherein the controller may control the dose of light emitted from the first to third light emitting units based on the location information.

[0043] In an embodiment, the controller may calculate an appropriate dose based on the location information provided by the location information receiver, and may control the first to third light emitting units to emit the appropriate dose.

[0044] In an embodiment, the location information receiver may calculate location information of the lighting apparatus, the controller may receive the location information and calculate a dose of external light and an appropriate dose at the place where the lighting apparatus is located, and may control the first to third light emitting units to emit light in an amount equivalent to a difference between the appropriate dose and the dose of external light.

[0045] In an embodiment, the controller may calculate time information from the location information and may control a dose of the light according to the time information.

[0046] A lighting system according to other embodiments of the present disclosure includes a lighting apparatus installed indoors, wherein the lighting apparatus is one of the lighting apparatuses described above.

[0047] Hereinafter, embodiments of the present disclosure will be described in detail with reference to the accompanying drawings.

[0048] FIG. 1 is a graph showing a degree of hazard according to wavelengths of blue light.

[0049] Blue light is known to cause eye diseases and skin diseases. In particular, blue light exhibits the highest degree of hazard between 430 nm and 440 nm. A wavelength range of 420 nm to 455 nm exhibits about 90% or more degree of hazard with respect to the highest hazard value, and a wavelength range of 413 nm to 465 nm exhibits about 70% or more degree of hazard, and a wavelength range of 411 nm to 476 nm exhibits about 50% or more degree of hazard.

[0050] Meanwhile, ultraviolet rays harm the human body and exhibit the highest degree of hazard, especially between 270 nm and 280 nm.

[0051] FIG. 2 shows a spectrum of a conventional white light source using a blue light emitting diode.

[0052] Referring to FIG. 2, a conventional white light source according to the conventional art implements white light using a yellow phosphor, or a green phosphor and a red phosphor together with a blue light emitting diode. A type and the amount of phosphor may be controlled according to a desired color temperature, and an intensity of the blue light is increased as the desired color temperature is increased.

[0053] A blue light emitting diode used in the conventional white light source generally has a central wavelength (e.g.,

a peak wavelength) in a range of 430 nm to 470 nm. Blue light in this range has a relatively high degree of hazard as shown in FIG. 1. Therefore, as the color temperature of the white light source increases, the intensity of the blue light increases, thereby increasing the hazard of causing eye diseases or skin diseases.

[0054] FIG. 3 is a schematic plan view illustrating a lighting apparatus according to an embodiment of the present disclosure, and FIG. 4 is a schematic cross-sectional view taken along the line A-A of FIG. 3.

[0055] Referring to FIG. 3 and FIG. 4, the lighting apparatus may include a circuit board 11, a first light emitting diode 21, a wavelength converter 23 and a second light emitting diode 31.

[0056] The circuit board 11 may have a circuit pattern for supplying power to the first and second light emitting diodes 21 and 31. The circuit board 11 may be a printed circuit board, for example, a metal-PCB.

[0057] At least one first light emitting diode 21 is mounted on the circuit board 11 as a light source for implementing the white light. A plurality of first light emitting diodes 21 may be electrically connected to one another in various ways, for example, may be connected in series, in parallel or in series parallel.

[0058] The first light emitting diode 21 may have, for example, a central wavelength in a range of about 300 nm to 420 nm, and may further have a central wavelength in a range of 400 nm to 420 nm. In addition, since the first light emitting diode 21 has the central wavelength in this range, a substantial portion of light emitted from the first light emitting diode 21 may be wavelength-converted by the wavelength converter 23. When the first light emitting diode 21 emits ultraviolet rays, most of ultraviolet rays are wavelength-converted by the wavelength converter 23, thereby preventing ultraviolet rays from being emitted to the outside. Furthermore, when the first light emitting diode having the center wavelength in the range of 400 nm to 420 nm is used, safety problems caused by ultraviolet rays may be eliminated in advance.

[0059] The wavelength converter 23 converts a wavelength of light emitted from the first light emitting diode 21. The wavelength converter 23 may be, for example, a molding member containing a phosphor or a quantum dot. The wavelength converter 23 covers the first light emitting diode 21. When the plurality of first light emitting diodes 21 are mounted on the circuit board 11, the wavelength converter 23 may cover all of the plurality of first light emitting diodes 21.

[0060] The wavelength converter 23 includes a wavelength conversion substance for implementing the white light together with light of the first light emitting diode 21. In one embodiment, the wavelength converter 23 may include a blue phosphor, a green phosphor and a red phosphor. In another embodiment, the wavelength converter 23 may include a blue phosphor and an orange phosphor. In another embodiment, the wavelength converter may include a quantum dot.

[0061] Examples of the blue phosphor may include a BAM-based, a Halo-Phosphate-based or an aluminate-based phosphor, and may include, for example, $\text{BaMgAl}_{10}\text{O}_{17}:\text{Mn}^{2+}$, $\text{BaMgAl}_{12}\text{O}_{19}:\text{Mn}^{2+}$ or $(\text{Sr},\text{Ca},\text{Ba})\text{PO}_4\text{Cl}:\text{Eu}^{2+}$. The blue phosphor may have, for example, a peak wavelength in a range of 440 nm to 500 nm.

[0062] Examples of the green phosphor may include $\text{LuAG}(\text{Lu}_3(\text{Al},\text{Gd})_5\text{O}_{12}:\text{Ce}^{3+})$, $\text{YAG}(\text{Y}_3(\text{Al},\text{Gd})_5\text{O}_{12}:\text{Ce}^{3+})$, $\text{Ga-LuAG}((\text{Lu},\text{Ga})_3(\text{Al},\text{Gd})_5\text{O}_{12}:\text{Ce}^{3+})$, $\text{Ga-YAG}((\text{Ga},\text{Y})_3(\text{Al},\text{Gd})_5\text{O}_{12}:\text{Ce}^{3+})$, $\text{LuYAG}((\text{Lu},\text{Y})_3(\text{Al},\text{Gd})_5\text{O}_{12}:\text{Ce}^{3+})$, ortho-Silicate $((\text{Sr},\text{Ba},\text{Ca},\text{Mg})_2\text{SiO}_4:\text{Eu}^{2+})$, oxynitride $((\text{Ba},\text{Sr},\text{Ca})\text{Si}_2\text{O}_2\text{N}_2:\text{Eu}^{2+})$, or thio gallate $(\text{SrGa}_2\text{S}_4:\text{Eu}^{2+})$. The green phosphor may have a peak wavelength in a range of 500 nm to 600 nm.

[0063] Examples of the red phosphor may include a nitride-based, a sulfide-based, a fluoride or an oxynitride-based phosphor, and, specifically, may include $\text{CASN}(\text{CaAlSiN}_3:\text{Eu}^{2+})$, $(\text{Ba},\text{Sr},\text{Ca})_2\text{Si}_5\text{N}_8:\text{Eu}^{2+}$, $(\text{Ca},\text{Sr})\text{S}_2:\text{Eu}^{2+}$, or $(\text{Sr},\text{Ca})_2\text{SiS}_4:\text{Eu}^{2+}$. The red phosphor may have a peak wavelength in a range of 600 nm to 700 nm.

[0064] White light may be implemented by a combination of the first light emitting diode 21 and the wavelength converter 23. FIG. 5 shows spectra of white light having various color temperatures implemented by the combination of the first light emitting diode 21 and the wavelength converter 23.

[0065] As shown in FIG. 5, white light of each color temperature is implemented by the combination of light emitted from the first light emitting diode and light emitted from the phosphors. In addition, it can be confirmed that irradiance of light emitted from the first light emitting diode 21 at all color temperatures is less than that of light emitted from the blue phosphor. As the color temperature increases, although the irradiance of light emitted from the first light emitting diode 21 also increases, the irradiance of blue light emitted from the blue phosphor increases to a greater extent. In addition, the irradiance of light emitted from the first light emitting diode may be less than that of light emitted from the green phosphor and may be less than that of light emitted from the red phosphor.

[0066] Accordingly, the lighting apparatus may prevent eye diseases or skin diseases from being caused by light emitted from the first light emitting diode.

[0067] Referring back to FIG. 3 and FIG. 4, the second light emitting diode 31 may be spaced apart from the wavelength converter 23 to be mounted on the circuit board 11. Light emitted from the second light emitting diode 31 may be emitted to the outside without actually entering the wavelength converter 23. Accordingly, irradiance of light emitted from the second light emitting diode 31 may be improved.

[0068] The second light emitting diode 31 may be connected to the first light emitting diode 21 in series or in parallel, or may be driven independently from the first light emitting diode 21.

[0069] Meanwhile, the second light emitting diode 31 emits light suitable for sterilizing pathogenic microorganisms other than the white light. The second light emitting diode 31 may emit light having, for example, a central wavelength

of about 400 nm to about 420 nm, furthermore, a central wavelength of about 400 nm to about 410 nm, even furthermore, a central wavelength of about 405 nm. In general, ultraviolet light has a favorable sterilization capability, but it cannot be used indoors or in public places where people are active, because it is harmful to the human body. In the meantime, visible light of the short wavelength in the range of 400 nm to 420 nm is a relatively low hazard of eye diseases or skin diseases, and has a high sterilization capability, so that it may be suitably used in the lighting apparatus.

[0070] Further, since light in the range of 400 nm to 420 nm is in the wavelength range similar to that of the first light emitting diode 21, the second light emitting diode 31 may be efficiently used in the lighting apparatus employing the first light emitting diode 21.

[0071] In the present embodiment, to add the sterilizing function to the lighting apparatus, the irradiance of light emitted from the second light emitting diode 31 may be greater than that at the same wavelength of light emitted from the white light emitting device. Furthermore, the irradiance of light emitted from the second light emitting diode 31 may be greater than that of light emitted to the outside of the lighting apparatus from the first light emitting diode 21 having the central wavelength in the range of 300 nm to 420 nm. Accordingly, the lighting apparatus of the present embodiment has the major sterilizing function provided by the second light emitting diode 31, compared to the first light emitting diode 21.

[0072] Meanwhile, although a driving time of the second light emitting diode 31 and that of the first light emitting diode 21 may be the same, the present disclosure is not limited thereto, and the driving time of the second light emitting diode 31 may be adjusted according to an installation location of the lighting apparatus. In particular, a period of use of the second light emitting diode 31 or a magnitude of the irradiance may be adjusted in consideration of the hazard to the human body.

[0073] For example, the irradiance of the second light emitting diode 31 emitted from the lighting apparatus may be 1 W/m² or less, and further, may be 0.1 W/m² or less. 1 W/m² represents a limit value of risk group 1 for blue light in a range 300 nm to 700 nm in the Photobiological Safety Standard (IEC 62471), and 0.1 W/m² corresponds to an exempt. The lighting apparatus has the radiance of 1 W/m² or less, and thus the lighting apparatus may be driven to sterilize pathogenic microorganisms for a relatively long period of time.

[0074] In the present embodiment, the sterilizing function of the lighting apparatus is described above as being exerted by the second light emitting diode 31, however, a portion of light emitted from the first light emitting diode 21 may also contribute to sterilizing pathogenic microorganisms. In particular, as shown in FIG. 5, in a case of white light having a color temperature of 6500K, light having relatively strong irradiance intensity at a wavelength band suitable for sterilizing the pathogenic microorganisms, for example, a wavelength of about 400 nm to about 420 nm, more specifically about 405 nm, is emitted. Accordingly, when the first light emitting diode 21 emits light having the central wavelength of about 400 nm to about 420 nm, the first light emitting diode 21 may be used to sterilize the pathogenic microorganisms, and in this case, the second light emitting diode 31 may be omitted.

[0075] In addition, since white light having a color temperature lower than 6500 K also emits light having a wavelength suitable for sterilizing the pathogenic microorganisms, an illuminance of light emitted from the second light emitting diode 31 may be adjusted in consideration of the irradiance of light emitted from the first light emitting diode 21 among the white light spectrum.

[0076] According to the present embodiment, the lighting apparatus is capable of sterilizing pathogenic microorganisms not only in the indoor living space but also in a space where a large number of people are active such as an airport or a hospital, thereby preventing human infection by the pathogenic microorganisms.

[0077] FIG. 6 is a schematic cross-sectional view illustrating a lighting apparatus according to another embodiment of the present disclosure.

[0078] Referring to FIG. 6, the lighting apparatus according to the present embodiment is generally similar to the lighting apparatus described with reference to FIG. 3 and FIG. 4 except that wavelength converters 23 are formed on the first light emitting diodes 21, respectively. That is, the wavelength converter 23 in FIG. 3 and FIG. 4 covers all of the plurality of first light emitting diodes 21, but in this embodiment, each of the first light emitting diodes 21 is individually covered with the wavelength converter 23.

[0079] The wavelength conversion substances in the first light emitting diode 21 and the wavelength converter 23 are substantially the same as those described above, and thus, repeated descriptions thereof will be omitted.

[0080] Since the first light emitting diodes 21 are respectively covered with the wavelength converters 23, the second light emitting diode 31 may be disposed between the first light emitting diodes 21. That is, as shown in the drawing, the second light emitting diodes 31 may be uniformly disposed between the first light emitting diodes 21, and thus light emitted from the second light emitting diode 31 may be mixed with the white light. As such, the lighting apparatus of the present disclosure is capable of mitigating the external recognition of light emitted from the second light emitting diode 31. The second light emitting diodes 31 may be covered with a transparent molding member to protect it from the external environment.

[0081] In the present embodiment, the second light emitting diodes 31 may be connected in series or in parallel to the first light emitting diodes 21, but the present disclosure is not limited thereto, and the second light emitting diodes 31 may be mounted on the circuit board 11 to be driven independently from the first light emitting diodes 21.

[0082] Meanwhile, as described in the embodiment above, light emitted to the outside from the first light emitting diodes 21 may be used to sterilize pathogenic microorganisms, and thus, the second light emitting diodes 21 may be omitted.

[0083] FIG. 7 is a schematic cross-sectional view illustrating a lighting apparatus according to another embodiment of the present disclosure.

[0084] Referring to FIG. 7, the lighting apparatus according to the present embodiment is generally similar to the lighting apparatus described with reference to FIG. 3 and FIG. 4 except that the second light emitting diode 31 is also covered with the wavelength converter 23.

[0085] That is, the wavelength converter 23 covers not only the first light emitting diode 21 but also the second light emitting diode 31. Accordingly, the wavelength converter 23 may wavelength-convert a portion of light emitted from the second light emitting diode 31.

[0086] Meanwhile, since the portion of light emitted from the second light emitting diode 31 is wavelength-converted by the wavelength converter 23, more second light emitting diodes 31 than those in the previous embodiments may be used to implement the irradiance suitable for sterilization. Meanwhile, since light generated by the second light emitting diode 31 is wavelength-converted and used to implement the white light, the number of the first light emitting diodes 21 may be reduced.

[0087] Meanwhile, the second light emitting diodes 31 may be uniformly disposed between the first light emitting diodes 21, and thus uniform light may be emitted to the outside. However, the present disclosure is not necessarily limited thereto.

[0088] Meanwhile, when the first light emitting diode 21 emits light having the central wavelength in the range of 300 nm to 420 nm, the number and intensity of the second light emitting diodes 31 are adjusted so that the irradiance of light generated by the second light emitting diodes 31 and emitted to the outside without wavelength conversion is greater than that of light generated in the first light emitting diodes 21 and emitted to the outside without wavelength conversion.

[0089] In this manner, the lighting apparatus according to the present embodiment also provides an effective sterilizing function by the second light emitting diode 31.

[0090] In a particular embodiment, the first light emitting diodes 21 may emit the central wavelength in the range of about 400 nm to about 420 nm, the same as the second light emitting diode 31. Furthermore, the first light emitting diodes 21 and the second light emitting diodes 31 may emit light of the same wavelength, for example, light of 405 nm wavelength.

[0091] FIG. 8 is a schematic cross-sectional view illustrating a lighting apparatus according to another embodiment of the present disclosure.

[0092] Referring to FIG. 8, the lighting apparatus according to the present embodiment is generally similar to the lighting apparatus described with reference to FIG. 3 and FIG. 4 except that it further includes a diffusion plate 51.

[0093] The diffusion plate 51 may mix the white light and light emitted from the second light emitting diode 31 and provide a uniform light. Accordingly, visibility of light emitted from the second light emitting diode 31 may be reduced.

[0094] FIG. 9 is a schematic cross-sectional view illustrating a lighting apparatus according to another embodiment of the present disclosure, and FIG. 10 is a schematic cross-sectional view taken along the line B-B of FIG. 9.

[0095] Referring to FIG. 9 and FIG. 10, the lighting apparatus according to the present embodiment includes a substrate 11, a first light emitting unit 122, a second light emitting unit 124, a third light emitting unit 126 and a second light emitting diode 31. Since the substrate 11 and the second light emitting diode 31 are similar to those described with reference to FIG. 3 and FIG. 4, detailed descriptions thereof will be omitted to avoid redundancy.

[0096] Meanwhile, the first light emitting unit 122 includes a first first-light emitting diode 121a and a first wavelength converter 123a, the second light emitting unit 124 includes a first second-light emitting diode 121b and a second wavelength converter 123b, and the third light emitting unit 126 includes a first third-light emitting diode 121c and a third wavelength converter 123c.

[0097] Herein, the first first- to first third-light emitting diodes 121a, 121b, and 121c emit light having a central wavelength in a range of about 300 nm to about 420 nm, respectively. In particular, the first first- to first third-light emitting diodes 121a, 121b, and 121c may have a central wavelength in a range of about 400 nm to about 420 nm. These may be the same light emitting diodes, or may be light emitting diodes having different central wavelengths.

[0098] Meanwhile, the first to third wavelength converters 123a, 123b, and 123c include a blue wavelength conversion substance for converting light emitted from the light emitting diode into blue light, respectively. The first to third wavelength converters 123a, 123b, and 123c may also include a green wavelength conversion substance for converting light emitted from the light emitting diode into green light and a red wavelength conversion substance for converting light emitted from the light emitting diode into red light, respectively. The blue conversion substance, the green wavelength conversion substance and the red wavelength conversion substance may be selected from the blue phosphor, the green phosphor and the red phosphor described with reference to FIG. 3 and FIG. 4. These phosphors may also be replaced with quantum dots.

[0099] Meanwhile, the first to third light emitting units 122, 124, and 126 may emit white light having different color temperatures. As such, the first to third wavelength converters may include different wavelength conversion substances

or different amounts of wavelength conversion substances.

[0100] In addition, the first to third light emitting units 122, 124, and 126 may be independently driven. For example, the first light emitting unit 122 may implement white light having a color temperature of 2700K, the second light emitting unit 124 may implement white light having a color temperature of 4000K, and the third light emitting unit 126 may implement white light having a color temperature of 6000K or 6500K. As such, the first to third light emitting units are selectively driven for a day, and thus the color temperature of the lighting apparatus may be changed in accordance with the change of sunlight. In some embodiments, the first to third light emitting units 122, 124, and 126 may be driven together. White light having various color temperatures may be implemented by combining the first to third light emitting units 122, 124, and 126.

[0101] Meanwhile, in irradiance spectrum of light emitted to the outside, irradiance of the central wavelength of light generated by each of the light emitting diodes 121a, 121b, and 121c in the first to third light emitting units 122, 124, and 126 and emitted to the outside without wavelength conversion is smaller than that of a peak wavelength of blue light emitted from the corresponding respective wavelength converters 123a, 123b, and 123c. Accordingly, eye diseases or skin diseases may be prevented by the lighting apparatus.

[0102] The second light emitting diode 31 may be driven together when at least one of the first to third light emitting units 122, 124, and 126 is driven. In addition, the second light emitting diode 31 may be driven independently from the first to third light emitting units 122, 124, and 126, and thus the second light emitting diode 31 may be driven even when the first to third light emitting units 122, 124, and 126 are not driven. As such, the second light emitting diode 31 may operate to perform the sterilization even at night when the lighting apparatus is not used.

[0103] Meanwhile, light suitable for sterilizing pathogenic microorganisms may be emitted from the first to third light emitting units 122, 124, and 126. For example, when at least one of the first first to first third-light emitting diodes 121a, 121b, and 121c emits light having the central wavelength of about 400 nm to about 420 nm, more particularly, light having the central wavelength of 405 nm, these light emitting units may be used to implement white light and to sterilize pathogenic microorganisms. Accordingly, in consideration of irradiance of light emitted from the first to third light emitting units 122, 124, and 126, on/off of the second light emitting diodes 31 or irradiance of light emitted from the second light emitting diodes 31 may be adjusted.

[0104] Meanwhile, the first to third light emitting units 122, 124, and 126 may be disposed so that each of the light emitting units is evenly distributed. In the present embodiment, although the second light emitting diodes 31 are shown to be disposed outside of locations where the first to third light emitting units 122, 124, and 126 are disposed, the present disclosure is not necessarily limited thereto, and may be disposed together with the first to third light emitting units.

[0105] In the present embodiment, the first to third light emitting units 122, 124, and 126 have structures where the wavelength converters 123a, 123b, and 123c surround the light emitting diodes 121a, 121b, and 121c. For example, these light emitting units may be chip scale packages. However, the present disclosure is not limited thereto, but the light emitting units 122, 124, and 126 may be light emitting devices in the form of a conventional package.

[0106] FIG. 11 is a schematic cross-sectional view illustrating a light emitting unit according to another embodiment of the present disclosure. Herein, FIG. 11 schematically shows a light emitting device in the form of a conventional package.

[0107] Referring to FIG. 11, the first light emitting unit 122 includes a first first-light emitting diode 121a and a first wavelength converter 123a. The first first-light emitting diode 121a may be mounted in a cavity of a housing 120, and the first wavelength converter 123a covers the light emitting diode 121a in the cavity. Meanwhile, the first first-light emitting diode 121a may be electrically connected to lead electrodes through bonding wires.

[0108] The package of FIG. 11 is an example, and various kinds of packages may be used. In addition, the first wavelength converter 123a may cover the light emitting diode 121a in various shapes.

[0109] Meanwhile, although the first light emitting unit 122 is representatively described here, the second light emitting unit 124 and the third light emitting unit 126 may also be light emitting devices having the same package form.

[0110] In addition, the second light emitting diode 31 may also be provided as a light emitting device in a package form and mounted on the substrate 11. However, the second light emitting diode 31 may be covered with a transparent molding member instead of being covered with the wavelength converter.

[0111] Lighting apparatuses of the present disclosure may change the color temperature of white light in response to the change in the color temperature of sunlight over time. Furthermore, the lighting apparatuses of the present disclosure may change the color temperature of white light in consideration of the change in the color temperature of sunlight according to a region.

[0112] FIG. 12 is a block diagram illustrating a lighting apparatus 100 according to an embodiment of the present disclosure.

[0113] Referring to FIG. 12, the lighting apparatus 100 according to an embodiment of the present disclosure includes a light source 30 emitting light, a location information receiver 40 for receiving location information, and a controller 50 receiving the location information from the location information receiver and controlling a dose of light emitted from the light source 30. Herein, the location information refers to information that can be obtained by using a global positioning

system (GPS). Meanwhile, the light source 30 refers to a white light source that implements white light, and is an arbitrary light source capable of changing the color temperature. For example, the light source 30 may be the white light emitting device including the first light emitting diode 21 and the wavelength converter 23 or the first to third light emitting units 122, 124, and 126, but the light source 30 is not limited thereto.

[0114] The location information receiver 40 receives the location information from a satellite using GPS to calculate current location information of the lighting apparatus 100. That is, the location information may include latitude and longitude, and the location information such as current latitude and longitude of the lighting apparatus 100 may be obtained by location information received by the location information receiver 40. The location information obtained by using the location information signal is provided to the controller 50.

[0115] The controller 50 calculates a dose of light to be emitted by the light source 30 based on the location information provided by the location information receiver 40, and controls the light source 30 to emit light as much as the dose of light. In other words, the controller 50 may control whether the light is emitted or not, an amount of light, an intensity of light, an emission time, and the like. The controller 50 may also control a dose of light to be emitted from the second light emitting diode 31 to sterilize pathogenic microorganisms together with the dose of the light source 30. In particular, the controller 50 may control the dose of the light emitted from the second light emitting diode 31 according to the dose of the white light source 30.

[0116] The power supplier 60 is electrically connected to the controller 50 to supply power to the light source 30 and the location information receiver 40. In the drawing, the power supplier 60 is illustrated as supplying power to the light source 30 and the location information receiver 40 through the controller 50, but the present disclosure is not limited thereto. The light source 30 and the location information receiver 40 may be directly connected to the power supplier 60, respectively.

[0117] The light source 30 and the location information receiver 40 may be disposed on the substrate 11. However, the present disclosure is not limited thereto, and the location information receiver 40 may be disposed on a substrate different from the substrate 11 on which the light source 30 is disposed.

[0118] Sunlight is not irradiated at the same intensity to all places on the earth. As the latitude becomes lower, the dose of sunlight becomes greater, and, as the latitude becomes higher, the dose of sunlight becomes less. In addition, the altitude becomes higher, the dose of sunlight becomes greater, and, as the altitude becomes lower, the dose of sunlight becomes smaller. Accordingly, depending on which country and in which place a user of the lighting apparatus 100 is present, the time or degree of exposure to sunlight may vary.

[0119] In an embodiment of the present disclosure, a location of the lighting apparatus 100 is determined by using location information, a dose of sunlight is calculated at the location, and then the visible light corresponding to the dose of sunlight is irradiated to a user, and thus the user may obtain the effect of being exposed to sunlight within a harmless limit to the human body.

[0120] This will be described with reference to the drawings.

[0121] FIG. 13 is a flowchart illustrating a method of driving a light irradiation apparatus according to an embodiment of the present disclosure.

[0122] Referring to FIG. 13, a location information receiver receives location information: S11. For example, it may be determined that the light irradiation apparatus is located in city B of country A according to the location information obtained from the location information receiver.

[0123] The received location information is provided to a controller, and the controller checks or calculates an appropriate dose of light to be emitted by the light irradiation apparatus based on the location information: S13. For example, when city B of country A is determined, in addition to the latitude and longitude information of city B of country A, information such as sunrise time, sunset time, and average amount of sunshine may be calculated. When using the latitude and longitude information, the sunrise and sunset time on the latitude and longitude may be easily confirmed, and thus the controller may be configured to determine whether it is a day or night using an algorithm that calculates the sunrise and sunset time on the current latitude and longitude.

[0124] Using the information such as sunrise time, sunset time, and average amount of sunshine, the controller may calculate the turn-on time, turn-off time, light intensity, etc. of the light source, so as to have a similar dose to that of the actual sunlight, that is, to have an appropriate dose. In particular, the controller may properly adjust whether the light source is irradiated or not by accurately determining the day or night light without adding an illumination sensor.

[0125] The information such as sunrise time, sunset time, and average amount of sunshine at each location may be stored in a separate memory in the controller, or may be easily obtained by accessing a separate internet network or the like.

[0126] The controller may control irradiation of light in a dose corresponding to the appropriate dose calculated by turning on or off the light source, to the user from the light source (S15). The user may be irradiated with the dose substantially the same as that of sunlight at the place where the user is, even if the user does not go outdoors.

[0127] According to an embodiment of the present disclosure, even if the user is in an environment where he or she is hardly exposed to sunlight, for example, living indoors for a long time, being in a hospital room or a limited space, or

mainly being active at night, light similar to sunlight at the present location may be provided in an appropriate dose for a suitable time. Accordingly, the user may be in a familiar environment, psychological stability of the user may be possible, and the irradiation time may also be controlled by setting the sunrise or sunset time, thereby easily recovering the daily biorhythm.

[0128] In the embodiment described above, although it has been described that a single light is used instead of sunlight based on the location information, an embodiment of the present disclosure is not limited thereto. The light irradiation apparatus may be used as a correction light source that compensates for a lack of external light in the presence of natural light, ie, external light emitted from sunlight or lighting apparatuses. For example, in a place with high latitude, a amount of sunshine may be significantly lower than in a region with low latitude, in which case it is necessary to compensate for the lack of sunshine. When the amount of sunshine is low, not only light in the visible light wavelength band irradiated to the user may be insufficient, but also light in the ultraviolet light wavelength band may be insufficient. In this case, the light irradiation apparatus according to the embodiment of the present disclosure may serve to compensate for the insufficient light by additionally irradiating light of the visible light wavelength band and light of the ultraviolet wavelength band.

[0129] FIG. 14 is a flowchart illustrating a method of driving the light irradiation apparatus according to an embodiment of the present disclosure.

[0130] Referring to FIG. 14, a location information receiver receives location information (S21). For example, it may be determined that the light irradiation apparatus is located in city D of country C according to the location information obtained from the location information receiver.

[0131] The received location information is provided to a controller, and the controller calculates information such as sunrise time, sunset time, and average amount of sunshine at a current location based on the location information, and, using the information such as sunrise time, sunset time, and average amount of sunshine, calculates a current dose of actual sunlight (S23).

[0132] Next, a difference between an appropriate dose required for the user and the current dose is calculated: S25. For example, in the case of city D of country C which is located in a region with high latitude and an amount of sunshine is insufficient, an amount of sunshine actually required is the appropriate dose, and a value obtained by subtracting the current dose from the appropriate dose is an insufficient dose. The appropriate dose required for the user may be stored in a separate memory or the like in the controller, or may be easily obtained by connecting to a separate internet network or the like.

[0133] The controller is configured to irradiate light in a dose corresponding to the difference between the appropriate dose calculated by turning on or off the light source and the external light dose, that is, light with the insufficient dose, to a target object from the light source (S27).

[0134] The user may be irradiated with the predetermined light in the dose most appropriate to the user regardless of the place where the user is.

[0135] Although various lighting apparatuses have been described above, the present disclosure is not limited to these specific embodiments. In addition, the lighting apparatus may be installed in not only an indoor living space but also an indoor space used by a plurality of people, such as a hospital or an airport. Thus, a lighting system in which the lighting apparatus is installed may also be provided. This lighting system may be suitable for routinely sterilizing pathogenic microorganisms, and may operate the lighting apparatus to effectively sterilize pathogenic microorganisms even when people are inactive.

[0136] FIG. 15A and FIG. 15B are graphs illustrating results of sterilization experiment on *Escherichia coli* and *Staphylococcus aureus* according to doses of light of a second light emitting diode, and FIG. 13 shows photographs showing the result of sterilization experiment on *Escherichia coli* cultured in the medium according to the doses of light of the second light emitting diode. As the second light emitting diode, a light emitting diode having a central wavelength of 405 nm was used.

[0137] Each bacterium was plated in a bacterial culture medium and incubated at 35-37°C for one day, colonies formed on the culture medium were collected and clouded in physiological saline and centrifuged, after discarding a supernatant, physiological saline was added again to prepare a bacterial solution, and the bacterial solution was diluted to prepare a bacterial solution of a suitable concentration for the sterilization experiment.

[0138] Meanwhile, after installing a sterilizing light source at a specific distance from the container containing the bacterial solution, the bacterial solution was irradiated with light, and, to confirm the sterilization power from the irradiated bacterial solution, the bacterial solution was diluted and evenly applied onto the medium and then incubated at 35-37°C for one day.

[0139] The colonies formed on the bacterial culture medium were identified and multiplied by a dilution factor and counted.

[0140] Graphs in FIG. 15A and FIG. 15B show the sterilization power according to the doses of light compared to the control bacteria without the sterilizing light source installed. It can be confirmed that the sterilization capability on the pathogenic microorganism increases as the dose of light increases. Herein, numeral number one (1) on the y-axis

denotes 90% sterilization power, numeral number two (2) denotes 99% sterilization power, and numeral number three (3) denotes 99.9% sterilization power. As such, it can be seen that the dose of light in a range of about 20 J/cm² to about 30 J/cm² shows the sterilization power of about 90%, the dose of light in a range of about 50 J/cm² to about 60 J/cm² shows the sterilization power of about 99%, and the dose of light in a range of about 80 J/cm² to about 95 J/cm² shows the sterilization power of about 99.9%.

[0141] In addition, referring to FIG. 16, as the dose of light increases, the number of bacteria decreases, and it can be seen that a size of the colony increases as the number of bacteria decreases. Meanwhile, when the dose of light further increases, the bacteria are almost eliminated and not observed.

[0142] Meanwhile, Table 1 below shows relative intensities, relative light doses and relative sterilization powers of the 405 nm wavelength according to color temperatures of the white light source which are derived using the spectrum(FIG. 2) of conventional light sources (comparative example) and the spectrum(FIG. 5) of light sources (exemplary embodiment) of the present embodiment.

Table 1

Color	% Intensity (@405nm)		Relative Light Dose (J/cm ²)		Relative Sterilization Power					
					E. coli			S. aureus		
	Exem. Embodime nt	Comp. Example	Exem. Embodime nt	Comp. Example	Exem. Embodime nt	Comp. Example	Exem. Embodime nt	Exem. Embodime nt	Comp. Example	Comp. Example
6500K	100	7.75	90	7	100	8.01	100	100	14.58	14.58
5000K	40.9	14.62	37	13	41.1	14.87	45.3	45.3	20.94	20.94
4000K	46.5	14.25	42	13	46.6	14.49	50.4	50.4	20.59	20.59
3000K	28.3	4.24	26	4	28.5	4.52	33.6	33.6	11.33	11.33

[0143] Referring to Table 1, it shows that the intensity at the wavelength of 405 nm of the light source of the exemplary embodiment having the color temperature of 6500K is the largest and that of the light source of the exemplary embodiment having the color temperature of 3000K is relatively small. Meanwhile, the light source of the comparative example shows a very small intensity even at the color temperature of 6500K and shows a smaller intensity than that of the light source of the exemplary embodiment having the color temperature of 3000K at all color temperatures.

[0144] When a dose of light of the 6500K light source among the light sources of the embodiment is 90 J/cm², light doses of the different light sources under the same condition are listed together in the table. Among the light sources of the exemplary embodiments, the light sources having the color temperature of 5000K or less showed doses of light smaller than 1/2 of the dose of light having the color temperature of 6500K. Meanwhile, the light sources of the comparative example show a light dose smaller than that of 3000K in the exemplary embodiment.

[0145] For the sterilization power on *E. coli* and *Staphylococcus aureus* (*S. aureus*), the sterilization powers of other light sources at the same irradiation time are listed in the table as relative values when the sterilization power of the light source having the color temperature of 6500K among the light sources of the exemplary embodiment is 100%.

[0146] As shown in Table 1, it can be seen that the light source of the embodiment shows a relatively strong sterilization power at the color temperature of 6500K.

[0147] Although some exemplary embodiments have been described herein, it should be understood that these embodiments are provided for illustration only and are not to be construed in any way as limiting the present disclosure. It should be understood that features or components of one exemplary embodiment may also be applied to other exemplary embodiments without departing from the spirit and scope of the present disclosure.

Claims

1. A lighting apparatus, comprising:

a white light emitting device including at least one first light emitting diode and a wavelength converter to implement white light; and
at least one second light emitting diode emitting light suitable for sterilizing at least one pathogenic microorganism,
wherein the first light emitting diode emits light having a central wavelength in a range of about 300 nm to about 420 nm,
wherein the second light emitting diode emits light having a central wavelength in a range of about 400 nm to about 420 nm,
wherein the wavelength converter comprises a plurality of wavelength conversion substances to convert light of the first light emitting diode into white light,
wherein the lighting apparatus emits the white light implemented in the white light emitting device and light generated by the second light emitting diode to the outside, and
wherein, in irradiance spectrum of the white light implemented in the white light emitting device, irradiance of the central wavelength of light emitted from the first light emitting diode is smaller than that of a peak wavelength of blue light emitted from a blue wavelength conversion substance of the wavelength conversion substances.

2. The lighting apparatus of claim 1,
wherein the white light and light emitted from the second light emitting diode are mixed and emitted to the outside.

3. The lighting apparatus of claim 1,
wherein the first light emitting diode emits light having a central wavelength in a range of about 400 nm to about 420 nm, and
wherein the first light emitting diode emits light having a wavelength different from that of the second light emitting diode.

4. The lighting apparatus of claim 1,
wherein irradiance of light generated by the at least one second light emitting diode and emitted to the outside is greater than that of light generated by the at least one first light emitting diode and emitted to the outside without wavelength conversion.

5. The lighting apparatus of claim 4,
wherein the lighting apparatus comprises a greater number of first light emitting diodes than that of the at least one second light emitting diode.

6. The lighting apparatus of claim 4,
wherein irradiance of light generated by the at least one second light emitting diode and emitted to the outside is
smaller than or equal to 1W/m^2 .

7. The lighting apparatus of claim 1, comprising:

a location information receiver for receiving location information; and
a controller for receiving the location information from the location information receiver and controlling a dose
of light emitted from the white light emitting device;
wherein the controller calculates a dose of light to be emitted by the white light emitting device based on the
location information, and controls the white light emitting device to emit light in an amount equivalent to the dose.

8. The lighting apparatus of claim 7,
wherein the controller calculates an appropriate dose based on the location information provided by the location
information receiver, and controls the light source to emit the appropriate dose.

9. The lighting apparatus of claim 7,
wherein the location information receiver calculates location information of the lighting apparatus, the controller
receives the location information and calculates a dose of external light and an appropriate dose at the place where
the lighting apparatus is located, and controls the white light emitting device to emit light in an amount equivalent
to a difference between the appropriate dose and the dose of external light.

10. The lighting apparatus of claim 7,
wherein the controller calculates time information from the location information and controls a dose of light to be
emitted by the white light emitting device according to the time information.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15A




FIG. 15B





FIG. 16



INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR2019/016621

A. CLASSIFICATION OF SUBJECT MATTER

A61L 9/18(2006.01)i, A61L 2/08(2006.01)i, F21V 33/00(2006.01)i, F21Y 115/10(2016.01)i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61L 9/18; F21K 9/20; F21S 2/00; F21S 8/08; F21V 9/30; F21Y 115/10; H01L 33/50; H05B 37/02; A61L 2/08; F21V 33/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean utility models and applications for utility models: IPC as above

Japanese utility models and applications for utility models: IPC as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS (KIPO internal) & Keywords: lamp, sterilization, wavelength conversion material, irradiance

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	KR 10-2018-0054183 A (ZAM CO., LTD.) 24 May 2018 See paragraphs [0020]-[0031]; figures 1-2.	1-10
Y	KR 10-2018-0036728 A (VITAL VIO, INC.) 09 April 2018 See claims 1-16.	1-10
Y	KR 10-2016-0025223 A (TDC) 08 March 2016 See paragraphs [0010]-[0037]; figures 1-5; claim 1.	7-10
A	KR 10-2005-0106945 A (SEOUL OPTO DEVICE CO., LTD. et al.) 11 November 2005 See claims 1-10.	1-10
A	KR 10-1680488 B1 (KOREA PHOTONICS TECHNOLOGY INSTITUTE) 28 November 2016 See claim 1.	1-10
A	KR 10-1892996 B1 (KIM, Gab Su) 29 August 2018 See the entire document.	1-10

☐ Further documents are listed in the continuation of Box C.
 ☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family


Date of the actual completion of the international search

30 MARCH 2020 (30.03.2020)

Date of mailing of the international search report

30 MARCH 2020 (30.03.2020)

Name and mailing address of the ISA/KR


 Korean Intellectual Property Office
 Government Complex Daejeon Building 4, 189, Cheongsa-ro, Seo-gu,
 Daejeon, 35208, Republic of Korea
 Facsimile No. +82-42-481-8578

Authorized officer

Telephone No.

INTERNATIONAL SEARCH REPORT
 Information on patent family members

International application No.

PCT/KR2019/016621

Patent document cited in search report	Publication date	Patent family member	Publication date
KR 10-2018-0054183 A	24/05/2018	KR 10-1861622 B1	29/05/2018
KR 10-2018-0036728 A	09/04/2018	JP 2018-525848 A	06/09/2018
		US 10357582 B1	23/07/2019
		US 2017-0030555 A1	02/02/2017
		US 2018-0180253 A1	28/06/2018
		US 9927097 B2	27/03/2018
		WO 2017-019933 A1	02/02/2017
KR 10-2016-0025223 A	08/03/2016	KR 10-1744951 B1	09/06/2017
KR 10-2005-0106945 A	11/11/2005	EP 1766692 A1	28/03/2007
		EP 1766692 B1	06/04/2016
		JP 2007-536729 A	13/12/2007
		JP 5274009 B2	28/08/2013
		US 2009-0262515 A1	22/10/2009
		US 8071988 B2	06/12/2011
		WO 2005-109532 A1	17/11/2005
KR 10-1680488 B1	28/11/2016	None	
KR 10-1892996 B1	29/08/2018	None	