



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**06.10.2021 Bulletin 2021/40**

(51) Int Cl.:  
**H04W 8/22** (2009.01) **H04W 36/00** (2009.01)  
**H04W 76/27** (2018.01) **H04W 48/20** (2009.01)

(21) Application number: **21161562.0**

(22) Date of filing: **28.04.2010**

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR**

- **CHOI, Sung Ho**  
**443-470 Gyeonggi-do (KR)**
- **BAE, Beom Sik**  
**443-745 Gyeonggi-do (KR)**

(30) Priority: **28.04.2009 KR 20090037205**

(74) Representative: **Grünecker Patent- und Rechtsanwälte**  
**PartG mbB**  
**Leopoldstraße 4**  
**80802 München (DE)**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:  
**19191509.9 / 3 584 957**  
**10769941.5 / 2 425 551**

(71) Applicant: **Samsung Electronics Co., Ltd.**  
**Suwon-si, Gyeonggi-do 443-742 (KR)**

Remarks:


- This application was filed on 09-03-2021 as a divisional application to the application mentioned under INID code 62.
- Claims filed after the date of filing of the application / date of receipt of the divisional application (Rule 68(4) EPC).

(72) Inventors:  
• **LIM, Chae Gwon**  
**135-841 Seoul (KR)**  
• **JEONG, Kyeong In**  
**445-300 Gyeonggi-do (KR)**

(54) **METHOD AND APPARATUS FOR MANAGING USER EQUIPMENT HISTORY INFORMATION IN WIRELESS COMMUNICATION NETWORK**

(57) A method for managing user equipment history information in a wireless communication network is described. When a user equipment enters into an idle mode, it is determined if a recording event occurs. Information related to the recording event is recorded into idle mode user equipment history information, when the recording event occurs. The recorded idle mode user equipment history information is transmitted to a base station, when the user equipment accesses the base station.

[Fig. 1]



## Description

### Technical Field

**[0001]** The present invention relates to a wireless communication network, and more particularly, to a method and an apparatus for managing User Equipment (UE) history information in order to improve performance of the wireless communication network,

### Background Art

**[0002]** Generally, a Universal Mobile Telecommunications System (UMTS) is a third generation (3G) mobile communication system that uses Wideband Code Division Multiple Access (WCDMA) based on Global System for Mobile communications (GSM) and General Packet Radio Services (GPRS). A third Generation Partnership Project (3GPP) for standardization of the UMTS has suggested an Evolved Packet System (EPS) of the UMTS similar to the Long Term Evolution (LTE) system. In this case, the LTE system is a technology for implementing high-speed packet based communication.

**[0003]** In the EPS, while a source base station is downloading source data, a handover of a User Equipment (UE) can occur from the source base station to a target base station. At this time, the source base station forwards the source data to the target base station. Further, the target base station downloads the source data and next followed target data. In this case, the source base station records UE history information as a UE Context. Upon handover, the source base station transfers the UE history information to the target base station.

**[0004]** The UE history information may include cell ID, cell type (large, small, etc.), a time served from a cell, and information on a plurality of cells with information of a recent serving cell. The UE history information is used to prevent a ping-pong handover of a UE from a target cell (a continuous handover of the UE between two base stations within a short time) and for a radio resource allocation algorithm to the UE after estimation of a moving speed of the UE.

### Disclosure of Invention

#### Technical Problem

**[0005]** However, the UE does not process the UE history information even though the serving base station creates it. When the UE firstly accesses the serving base station, because the UE history information is not created, the serving base station cannot use the UE history information.

#### Solution to Problem

**[0006]** In accordance with an aspect of the present invention, a method for managing user equipment history

information in a wireless communication network includes determining if a recording event occurs when the user equipment enters into an idle mode; recording information relate with the recording event in idle mode user equipment history information when the recording event occurs; and transmitting the recorded idle mode user equipment history information to a base station when the user equipment accesses the base station.

**[0007]** In accordance with another aspect of the present invention, an apparatus for managing user equipment history information in a wireless communication network includes a user equipment history information generator which is configured to determine if a recording event occurs when the user equipment enters into an idle mode, and to record information related with the recording event in idle mode user equipment history information when the recording event occurs; a storage unit which is configured to store the recorded idle mode user equipment history information; and a user equipment history information transmitting controller which is configured to transmit the recorded idle mode user equipment history information to a base station when the user equipment accesses the base station.

**[0008]** In a method for managing UE history information in a wireless communication network accordance with the present invention, an UE transmits its UE history information to a serving base station, so that the serving base station can provide an efficient data transmission environment to the UE based on the UE history information. Further, the UE transmits its UE history information to an O&M (Operation and Management) server or a core network entity of a wireless communication network, so that a network operator can use the UE history information for managing the wireless communication network,

### Advantageous Effects of Invention

**[0009]** The present invention provides a method for managing UE history information in a wireless communication network that collects and provides its history information by an UE operating in an idle mode to the wireless communication network, thereby providing an efficient data transmission environment to the UE and providing valid information on an operation of a wireless communication system to the wireless communication network.

### Brief Description of Drawings

**[0010]** The objects, features and advantages of the present invention will be more apparent from the following detailed description in conjunction with the accompanying drawings, in which:

FIG. 1 is a diagram illustrating a configuration of a wireless communication network according to an embodiment of the present invention;  
FIG. 2 is a sequence diagram illustrating a method

for transmitting UE history information from a source base station to a target base station at the time of a handover between macro base stations according to an exemplary embodiment of the present invention;

FIG. 3 is a diagram illustrating history information recorded by a UE operating in an idle mode according to an embodiment of the present invention;

FIG. 4 is a diagram illustrating a procedure of recording UE history information by a UE operating in an idle mode according to an embodiment of the present invention;

FIG. 5 is a sequence diagram illustrating a procedure of transmitting idle mode UE history information to a base station by a UE in an idle mode according to an embodiment of the present invention;

FIG. 6 is a flow chart illustrating an operation of a UE according to an embodiment of the present invention; and

FIG. 7 is a block diagram illustrating an internal configuration of a UE according to an embodiment of the present invention.

### Mode for the Invention

**[0011]** Embodiments of the present invention are described with reference to the accompanying drawings in detail. The same reference numbers are used throughout the drawings to refer to the same or like parts. Detailed descriptions of well-known functions and structures incorporated herein may be omitted to avoid obscuring the subject matter of the present invention.

**[0012]** First, a configuration of a wireless communication network is described. The wireless communication network according to an embodiment of the present invention is configured based on a cellular system.

**[0013]** FIG. 1 is a diagram illustrating a configuration of a wireless communication network according to an embodiment of the present invention.

**[0014]** Referring to FIG. 1, the wireless communication network according to an embodiment of the present invention includes a User Equipment (UE) 101, an Evolved UMTS Radio Access Network (E-UTRAN) 102, a Mobility Management Entity (MME) 103, a Serving GateWay (SGW) 104, a Packet data network GateWay (PGW) 105, a Packet Data Network 106, and an Operator Network 107. The user equipment 101 may be fixed or mobile.

**[0015]** The E-UTRAN 102 accesses the UE 101 through a wireless channel. The E-UTRAN 102 is composed of a plurality of cells. The E-UTRAN 102 includes a plurality of evolved base stations, or Node Bs (eNBs) for controlling respective cells. The evolved base stations eNBs may be connected to each other through an X2 interface. The evolved base stations (eNBs) execute a radio bearer control function, a radio admission control function, a connection mobility control function, and a Radio Resource Management (RRM) function such as dynamic resource allocation to the UE 101. Further, the

evolved base stations eNBs execute an Internet Protocol (IP) header compression and data encryption function, a data routing function, a scheduling and transmitting function of a paging message, a scheduling and transmitting function of broadcast information, a measurement function for mobility and scheduling, and a measurement report set function. Namely, the evolved base stations eNBs receive downloading of data and transmits the downloaded data to the UE 101.

**[0016]** The E-UTRAN 102 includes a source base station and a target base station. The source base station indicates a base station currently being accessed by the UE 101. The target base station indicates a base station that the UE 101 wants to access through hand-over. Namely, upon a handover from the source base station to the target base station, the UE 101 terminates access to the source base station, and initiates access to the target base station. In other words, when the UE 101 accesses the source base station, the source base station downloads source data. Upon the hand-over from the source base station to the target base station, the source base station forwards source data to the target base station. Further, the target base station downloads target data followed by the source data. At this time, the source base station transmits UE history information recorded as an UE Context to the target base station at the time of the handover.

**[0017]** The MME 103 accesses the E-UTRAN 102 by a wired channel. In this case, the MME 103 is connected to the E-UTRAN 102 through an SI interface. The MME 103 executes a paging message distribution function to the evolved base station, a ciphering and integrity protection function of Non-Access Stratum (NAS) signaling, an idle state mobility control function, and a bearer control function.

**[0018]** The SGW 104 accesses the E-UTRAN 102 and the MME 103 by a wired channel. In this case, the SGW 104 is connected to the E-UTRAN 102 through an SI interface. The SGW 104 can be provided with plurality of SGWs. Namely, the SGW 104 accesses at least one evolved base station. Further, the SGW 104 executes a mobility control function of the UE 101 and the like,

**[0019]** The PGW 105 accesses the SGW 104 by a wired channel. The PGW 105 further accesses an IP network. The PGW 105 executes an IP address allocation function and a data filtering function for the UE 101. That is, the PGW 105 transmits data provided from an IP network 106 to the UE 101 through the SGW 104 and the E-UTRAN 102.

**[0020]** FIG. 2 is a sequence diagram illustrating a method for transmitting UE history information from a source base station to a target base station at the time of a handover between macro base stations according to an embodiment of the present invention.

**[0021]** Referring to FIG. 2, a User Equipment (UE) 201 detects a signal of a target base station (eNB) 203, and transmits a measurement report to a serving base station (eNB) 202 in step 205. Next, the serving base station 202

analyzes the received measurement report, checks which base station is a target base station of the UE 201, and decides a handover of the UE based on a Tracking Area ID (TAI) and a used frequency band of the target base station 203 in step 206. The serving base station 202 transfers a handover request message and UE history information to the target base station 202 in step 207. The target base station 203 transmits a response indicating a handover request ACK to the serving base station 202 in step 208. Then, the serving base station 202 instructs the UE 201 to perform a handover to the target base station 203 in step 209.

**[0022]** Subsequently, the UE 201 performs a handover to the target base station 203 in step 210. The target base station 203 informs in step 211 an MME 204 that the handover of the UE 201 is performed. The MME 204 transmits a response signal (e.g. Path switch ACK) to the target base station 203 in step 212, and instructs the service base station 202 to erase all UE information in step 213. The serving base station 202 informs the success of reception of the UE information and the resources used by the UE 201 to the MME 204 in step 214.

**[0023]** The UE history information in step 207 contains cell ID, cell type (large, small, etc.), a served time from a corresponding base station, and information on a plurality of base stations with recent information of a serving base station. The UE history information is used to prevent a ping-pong handover of a UE from a target cell, namely, a continuous handover of the UE between two base stations within a short time, and for a radio resource allocation algorithm to the UE after estimation of a moving speed of the UE.

**[0024]** The following is an explanation of a method for using history information of an UE operating in an idle mode according to an embodiment of the present invention. Herein, the idle mode is a state in which a Radio Resource Control (RRC) connection established between an UE and a base station is released. Meanwhile, an active mode means a state in which RRC connection between an UE and a base station is established.

**[0025]** FIG. 3 is a diagram illustrating history information recorded by a UE operating in an idle mode according to an embodiment of the present invention.

**[0026]** Referring to FIG. 3, when a recording event occurs in an idle mode, a UE directly records information about the occurred recording event in idle mode UE history information. Upon conversion to an active mode, namely, upon setting the RRC connection between the UE and a base station, the UE transmits the recorded UE history information to the connected base station.

**[0027]** In particular, as shown in FIG. 3, the UE operating in the idle mode manages the UE history information in a form of a table. The UE history information contains at least one of an occurrence event, an ID and related information thereof selected by the user equipment, Public Land Mobile Network (PLMN) information selected by the UE, a time influenced by each event, a time occupying a corresponding cell, and measuring information in the

idle mode UE history information. Although not shown, besides the items listed, measurement information items with a cell signal strength may be included in the table of FIG. 3. Here, the cell signal strength may include a self-cell signal strength, a neighbor cell signal strength, or a signal strength of currently camped frequency or different band frequencies. As described above, it should be considered that respective items are listed in the table shown in FIG. 3 by way of example only. The respective items can be removed as needed. In another case, different items can be included in history information recorded in a UE operating in an idle mode.

**[0028]** FIG. 4 is a diagram illustrating a procedure of recording UE history information by a UE operating in an idle mode according to an embodiment of the present invention.

**[0029]** Referring to FIG. 4, a UE 401 operating in an active mode converts to an idle mode in a first cell 404, moves to cell 04 407 in an idle mode, and again operates in the active mode in a fourth cell 407.

**[0030]** In detail, when an event 408 converting to an idle mode occurs in the first cell 404, the UE 401 records information regarding the occurred event 408 in idle mode UE history information. More particularly, an event with a change of a serving cell occurs in the UE, and the UE records a time stayed in a previous serving cell, namely, the first cell 404, and information about a second cell 405 being a current serving cell in the idle mode UE history information.

**[0031]** Next, when the UE enters into an impossible service zone (i.e. an area where no service is available) and a service impossibility event 410 occurs, the UE records a time stayed in a second cell 405 being a previous serving cell and current service impossibility information in the idle mode UE history information. When the UE enters into a third cell 406, it executes an event selecting a PLMN and a cell, and records the occurrence time of the service impossibility event and information about a current PLMN and service cell in the idle mode UE history information.

**[0032]** When the UE continuously moves and an event in which a serving cell changes from the third cell 460 to the fourth cell 407 occurs, the UE records a time stayed in the third cell 360 being a previous serving cell and information about the fourth cell 407 being a current serving cell in the idle mode UE history information.

**[0033]** When the UE accesses the fourth cell 407 and a conversion event from an idle mode to an active mode occurs, the UE records a time of the fourth cell 407 being a current serving cell operating in the idle mode in the idle mode UE history information. The idle mode UE history information recorded according to an embodiment of FIG. 4 is as shown in FIG. 3.

**[0034]** FIG. 5 is a sequence diagram illustrating a procedure of transmitting idle mode UE history information to a base station by a UE in an idle mode according to an embodiment of the present invention.

**[0035]** Referring to FIG. 5, after a connection between

a UE 501 in an idle mode and an RRC is established, i.e. when the UE 501 is converted to an active mode, in step 504, the UE 501 transmits idle mode UE history information to a base station 503 in step 506. In this case, step 506 can be performed by a request from the base station 502 in step 505 or independently while omitting step 505. **[0036]** Further, step 506 can be performed after step 504 or as a part of step 504. The base station 502 which received the idle mode UE history information may share the idle mode UE history information or information related thereto with another core network entity, i.e. a core network entity such as an O & M server or an MME in step 507. Meanwhile, the base station 503 may share the idle mode UE history information or information related thereto with another base station neighboring therewith. Another base station or another core network entity may estimate a moving speed of a UE and then use the idle mode UE history information in a radio resource allocation algorithm, in acquisition of information about its neighbor cells, PCI selection algorithm, problem discovery at the time of an enterpriser's cell planning or setting a cell parameter, a coverage problem discovery of an enterpriser cellular network, and automatic setting of other networks.

**[0037]** FIG. 6 is a flow chart illustrating an operation of a UE according to an embodiment of the present invention.

**[0038]** Referring to FIG. 6, a UE determines if it is in an idle mode in step 601. When the UE is in the idle mode, the UE executes Radio Frequency (RF) channel search in step 602. The UE determines if an idle mode event to be recorded occurs in step 603. When the idle mode event to be recorded occurs, the UE further records relation event information in the idle mode UE history information in step 604.

**[0039]** When the UE is not in an idle mode at step 601, the UE determines if it is attempting to access a base station in step 605. When the UE is attempting to access a base station, the UE determines if it succeeds in accessing the base station to be converted to an active mode in step 606. When the UE is converted to the active mode, the UE receives a request for the idle mode UE history information from the base station in step 607 and transmits the idle mode UE history information to the base station in step 608. In this case, step 608 may be performed according to the request for the idle mode UE history information from the base station 520 in step 607 or be performed independently while omitting step 607.

**[0040]** FIG. 7 is a block diagram illustrating an internal configuration of a UE according to an embodiment of the present invention. Referring to FIG. 7, the UE according to an embodiment of the present invention includes an RF communication unit 710, a storage unit 720, and a controller 730. The storage unit 720 may include a UE history information storing area 720A. The controller 730 may include a UE history information generator 730A and a UE history information transmitting controller 730B.

**[0041]** The RF communication unit 710 performs trans-

mitting and receiving functions of corresponding data for a wireless communication of the UE. The RF communication unit 710 may be composed of an RF transmitter that up-converts a frequency of a signal to be transmitted and amplifies the signal, and an RF receiver that low-noise amplifies a received signal and down-converts a frequency of the amplified signal. The RF communication unit 710 may receive data through a wireless channel, output the received data to the controller 730, and transmit data output from the controller 730 through the wireless channel. In particular, the RF communication unit 710 according to an embodiment of the present invention may transmit the idle mode UE history information generated from the UE in an idle mode to a base station.

**[0042]** The storage unit 720 stores programs and data necessary for the overall operation of the UE according to an embodiment of the present invention, and may include a UE history information storing area 720A. The UE history information storing area 720A stores idle mode UE history information generated in the UE in an idle mode,

**[0043]** The controller 730 controls signal transmission between respective blocks of another UE according to an embodiment of the present invention. In particular, the controller 730 controls a series of procedures for transmitting the idle mode UE history information according to an embodiment of the present invention. To do this, the controller 730 may include a UE history information generator 730A and the UE history information transmitting controller 730B.

**[0044]** The UE history information generator 730A determines if a UE is in an idle mode. When the UE is in the idle mode, the UE history information generator 730A performs RF channel search to determine if a recording event to be recorded in UE history information occurs. Referring to FIG. 4, the recording event may include at least one of an idle mode conversion event, a cell change event, an impossible service event, a cell re-selection event, and a cell change event.

**[0045]** When the recording event occurs, the UE history information generator 730A records relation information in the idle mode UE history information. As described above, the idle mode UE history information contains at least one of an occurrence event, an ID and related information thereof selected by the UE, Public Land Mobile Network (PLMN) information selected by the UE, a time influenced by each event, a time camped in a corresponding cell, a cell signal strength, and measuring information. The UE history information transmitting controller 730B controls the generated idle mode UE history information to be stored in the UE history information storing area 720B.

**[0046]** The UE history information transmitting controller 730B determines if a UE operating in an idle mode succeeds accessing a base station to be converted into an active mode. When being converted to the active mode from the idle mode, the UE history information transmitting controller 730B controls the idle mode UE

history information to be transmitted to the base station. In this case, the idle mode UE history information can be transmitted simultaneously with the accessing of the base station or according to a request from the base station.

**[0047]** In the method for managing UE history information according to the present invention, a UE may transmit its UE history information to a serving base station, and the serving base station may provide an efficient data transmission environment to the UE based on the UE history information.

**[0048]** Although exemplary embodiments of the present invention have been described in detail hereinabove, it should be clearly understood that many variations and modifications of the basic inventive concepts herein taught which may appear to those skilled in the present art will still fall within the spirit and scope of the present invention, as defined in the appended claims. The invention provides the following further ten aspects counted from one:

The aspect of a method for managing user equipment history information in a wireless communication network, the method comprising the steps of: determining if a recording event occurs, when the user equipment enters into an idle mode: recording information related to the recording event into idle mode user equipment history information, when the recording event occurs; and transmitting the recorded idle mode user equipment history information to a base station, when the user equipment accesses the base station.

**[0049]** The method according to the first aspect, wherein a recording event comprises at least one of an idle mode conversion event, a cell change event, a service non-available event, and a cell re-selection event.

**[0050]** The method according to the first aspect, wherein recording information comprises recording event information including at least one of an occurrence event, an ID of a cell selected by the user equipment and related information, Public Land Mobile Network (PLMN) information selected by the user equipment, a time influenced by each event, a time camped in a corresponding cell, and measuring information into the idle mode user equipment history information.

**[0051]** The method according to the first aspect, wherein transmitting the recorded idle mode user equipment history information further comprises: receiving a transmission request for the idle mode user equipment history information from the accessed base station; and transmitting the idle mode user equipment history information to the base station according to the reception of the transmission request.

**[0052]** The method according to the first aspect, further comprising transmitting the idle mode user equipment history information to a neighbor base station or to a core network entity.

**[0053]** The aspect of an apparatus for managing user equipment history information in a wireless communication network, the apparatus comprising: a user equip-

ment history information generator configured to determine if a recording event occurs when the user equipment enters into an idle mode, and to record information related to the recording event in idle mode user equipment history information when the recording event occurs; a storage unit configured to store the recorded idle mode user equipment history information; and a user equipment history information transmitting controller configured to transmit the recorded idle mode user equipment history information to a base station when the user equipment accesses the base station.

**[0054]** The apparatus according to the sixth aspect, wherein the recording event comprises at least one of an idle mode conversion event, a cell change event, a service non-available event, and a cell re-selection event.

**[0055]** The apparatus according to the sixth aspect, wherein the idle mode user equipment history information comprises at least one of an occurrence event, an ID of a cell selected by the user equipment and related information, Public Land Mobile Network (PLMN) information selected by the user equipment, a time influenced by each event, a time camped in a corresponding cell, and measuring information.

**[0056]** The apparatus according to the sixth aspect, wherein the user equipment history information transmitting controller controls transmission of the idle mode user equipment history information to the base station, when a transmission request for the idle mode user equipment history information is received from the base station.

**[0057]** The apparatus according to the sixth aspect, wherein the idle mode user equipment history information is shared with a neighbor base station or with a core network entity.

**[0058]** In addition, the present disclosure discloses the following further fourteen aspects.

1. An aspect of a method by a terminal, the method comprising: generating mobility history information upon entering a first radio access technology, RAT, from a second RAT or an out-of-service state, the mobility history information including information on a time duration for which the terminal stayed in the second RAT or information on a time duration for which the terminal stayed in the out-of-service state; receiving, from a base station, a request for the mobility history information; and transmitting the mobility history information to the base station, in response to the request.

2. An aspect of the method of aspect 1, wherein the mobility history information is generated upon entering in a radio resource, RRC, connected mode of the first RAT or an RRC idle mode of the first RAT.

3. An aspect of the method of aspect 1, wherein the request for the mobility history information is received in an RRC connected mode of the first RAT.

4. An aspect of the terminal of aspect 1, wherein the first RAT includes a long-term evolution, LTE.

5. An aspect of the method of aspect 1, wherein gen-

erating the mobility history information comprises generating the mobility history information based on a generating event occurring.

6. An aspect of the method of aspect 5, wherein the generating event includes time related information.

7. An aspect of the method of aspect 1, wherein the mobility history information includes at least one of a cell identifier, ID, or a cell signal strength.

8. An aspect of a terminal, the terminal comprising: a transceiver; and a controller configured to: generate mobility history information upon entering a first radio access technology, RAT from a second RAT or an out-of-service state, the mobility history information including information on a time duration for which the terminal stayed in the second RAT or information on a time duration for which the terminal stayed in the out-of-service state, receive, via the transceiver, from a base station, a request for the mobility history information, and transmit, via the transceiver, the mobility history information to the base station in response to the request.

9. An aspect of the terminal of aspect 8, wherein the mobility history information is generated upon entering in a radio resource, RRC, connected mode of the first RAT or an RRC idle mode of the first RAT.

10. An aspect of the terminal of aspect 8, wherein the request for the mobility history information is received in an RRC connected mode of the first RAT.

11. An aspect of the terminal of aspect 8, wherein the first RAT includes a long-term evolution, LTE.

12. An aspect of the terminal of aspect 8, wherein the controller is further configured to transmit, via the transceiver, the mobility history information based on a generating event occurring.

13. An aspect of the terminal of aspect 12, wherein the generating event includes time related information.

14. An aspect of the terminal of aspect 8, wherein the mobility history information includes at least one of a cell identifier, ID, or a cell signal strength.

## Claims

1. A method performed by a terminal in a communication system, the method comprising:

obtaining mobility history information upon change of a first cell in a radio resource control, RRC, idle state to a second cell, wherein at least one of the first cell and the second cell is an evolved universal mobile telecommunications system radio access network, E-UTRAN, cell and the mobility history information includes an identifier of the first cell and information on a time duration for which the terminal stayed in the first cell;

receiving, from a base station, a request for the mobility history information; and transmitting, to the base station, the mobility history information as a response to the request.

2. The method of claim 1, wherein the mobility history information is obtained upon entering in a radio resource control, RRC, connected mode or an RRC idle mode.

3. The method of claim 1, wherein the request for the mobility history information is received in an RRC connected mode.

4. The method of claim 1, wherein the E-UTRAN cell includes a long term evolution, LTE, cell.

5. The method of claim 1, wherein obtaining the mobility history information comprises obtaining the mobility history information based on an event occurring.

6. The method of claim 5, wherein the event includes time related information.

7. The method of claim 1, wherein the mobility history information includes a cell signal strength.

8. A terminal comprising:

a transceiver; and  
a controller coupled with the transceiver and configured to:

obtain mobility history information upon change of a first cell in a radio resource control, RRC, idle state to a second cell, wherein at least one of the first cell and the second cell is an evolved universal mobile telecommunications system radio access network, E-UTRAN, cell and the mobility history information includes an identifier of the first cell and information on a time duration for which the terminal stayed in the first cell; receive, from a base station, a request for the mobility history information; and transmit, to the base station, the mobility history information as a response to the request.

9. The terminal of claim 8, wherein the mobility history information is obtained upon entering in a radio resource control, RRC, connected mode or an RRC idle mode.

10. The terminal of claim 8, wherein the request for the mobility history information is received in an RRC connected mode.

11. The terminal of claim 8, wherein the E-UTRAN cell includes a long term evolution, LTE, cell.
12. The terminal of claim 8, wherein the controller is further configured to transmit the mobility history information based on an event occurring. 5
13. The terminal of claim 12, wherein the event includes time related information. 10
14. The terminal of claim 8, wherein the mobility history information a cell signal strength.

15

20

25

30

35

40


45

50


55



[Fig. 1]




[Fig. 2]




[Fig. 3]

INDEX	EVENT	CAMPING CELL ID	CELL INFORMATION	REGISTERED PLMN	DURATION
1	ENTER IN IDLE MODE	CELL01	PCI01 , MACRO,...	PLMN1	10 MINUTES AND 30 SECONDS
2	CELL RE-SELECTION	CELL02	PCI02 , MACRO,...	PLMN1	5 MINUTES AND 3 SECONDS
3	SERVICE NON-AVAILABLE	-	-	-	20 SECONDS
4	SELECT PLMN/CELL	CELL03	PCI01 , MACRO,...	PLMN2	12 MINUTES AND 30 SECONDS
5	CELL RE-SELECTION	CELL04	PCI11 , MACRO,...	PLMN2	30 MINUTES AND 23 SECONDS


[Fig. 4]




[Fig. 5]



[Fig. 6]



[Fig. 7]





## EUROPEAN SEARCH REPORT

Application Number  
EP 21 16 1562

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	NOKIA SIEMENS NETWORKS ET AL: "UE History Information for Inter-RAT", 3GPP DRAFT; R3-083202, 3RD GENERATION PARTNERSHIP PROJECT (3GPP), MOBILE COMPETENCE CENTRE ; 650, ROUTE DES LUCIOLES ; F-06921 SOPHIA-ANTIPOLIS CEDEX ; FRANCE, no. Prague, Czech Republic; 20081106, 6 November 2008 (2008-11-06), XP050324426, * 2. Discussion *	1-14	INV. H04W8/22 H04W36/00 H04W76/27  ADD. H04W48/20
A	WO 2008/040962 A1 (VODAFONE PLC [GB]; FOX DAVID [GB]; PUDNEY CHRISTOPHER DAVID [GB]; FROS) 10 April 2008 (2008-04-10) * page 2, lines 24-31 * * page 4, lines 16-31 * * page 21, line 14 - page 24, line 21 * * abstract; claims 23,24; figure 2 *	1-14	
A	WO 2008/133566 A1 (ERICSSON TELEFON AB L M [SE]; MILDH GUNNAR [SE]; WAHLQVIST MATTIAS [ES]) 6 November 2008 (2008-11-06) * page 2, lines 6-17 * * page 4, line 34 - page 5, line 15 * * page 7, lines 4-36 * * abstract; figure 2 *	1-14	TECHNICAL FIELDS SEARCHED (IPC)  H04W
The present search report has been drawn up for all claims			
Place of search <b>The Hague</b>		Date of completion of the search <b>26 August 2021</b>	Examiner <b>Coppieters, Stefaan</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

 1  
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 21 16 1562

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

26-08-2021

	Patent document cited in search report	Publication date	Patent family member(s)	Publication date
10	WO 2008040962 A1	10-04-2008	AT 537678 T	15-12-2011
			CN 101595752 A	02-12-2009
			EP 2070363 A1	17-06-2009
15			ES 2383979 T3	28-06-2012
			US 2011026484 A1	03-02-2011
			WO 2008040962 A1	10-04-2008
-----				
20	WO 2008133566 A1	06-11-2008	CN 101669381 A	10-03-2010
			CN 103327624 A	25-09-2013
			DK 2138003 T3	09-01-2017
			EP 2138003 A1	30-12-2009
			EP 3128799 A1	08-02-2017
			ES 2609513 T3	20-04-2017
25			JP 5296053 B2	25-09-2013
			JP 5621016 B2	05-11-2014
			JP 2010525735 A	22-07-2010
			JP 2013240076 A	28-11-2013
			NZ 579200 A	27-07-2012
			PL 2138003 T3	31-07-2017
30			PT 2138003 T	26-12-2016
			RU 2009143673 A	10-06-2011
			TW 200845629 A	16-11-2008
			US 2010142486 A1	10-06-2010
			US 2012238261 A1	20-09-2012
35			US 2013231116 A1	05-09-2013
			WO 2008133566 A1	06-11-2008
-----				
40				
45				
50				
55				

ORM P0459