

## **Dimension Reduction of Telcom Customer Churn Data**

Mike Mattinson

Western Governors University

D212: Data Mining II

Task 2: Dimension Reduction

Dr. Kesselly Kamara

May 16, 2022

Revision 6

### Abstract

Telecom customer data will be analyzed for feature selection using principal component analysis (PCA). The dataset consists of 50 features associated with 10,000 customer records. The analysis looked at the 50 features and select 13 continuous features to be used by the PCA. PCA results indicate that 11 principal components are needed to explained approx.. 95% of the total variance. 10 principal components are needed to explain approx.. 85% of total variance. The first principal component (PC1) has high correlation to the original features of Tenure and Bandwidth\_GB\_Year. The second principal component (PC2) has high correlation to population and location.

*Keywords:* Telecom. Churn. Data Mining. Dimension Reduction. PCA. Principal Components. Scree Plot. Load Factors.

### Scenario 1

One of the most critical factors in customer relationship management that directly affects a company's long-term profitability is understanding its customers. When a company can better understand its customer characteristics, it is better able to target products and marketing campaigns for customers, resulting in better profits for the company in the long term.

You are an analyst for a telecommunications company that wants to better understand the characteristics of its customers. You have been asked to use principal component analysis (PCA) to analyze customer data to identify the principal variables of your customers, ultimately allowing better business and strategic decision-making.

### List of Tables

Table 1 <i>First 5 rows of the original dataset</i> .....	9
Table 2 <i>First 5 rows of the scaled data</i> .....	11
Table 3 <i>Total variance by principal component by feature</i> .....	15

### List of Figures

Figure 1 <i>Define continuous features</i> .....	8
Figure 2 <i>Correlation matrix of all 13 principal components with loadings to original features</i> .	13
Figure 3 <i>Scree plot to identify explained variance for each principal component</i> .....	14
Figure 4 <i>Bar plot/line plot of variance and cumulative variance for all PCs</i> .....	16

### **Part I: Research Question**

A. Describe the purpose of this data mining report by doing the following:

**A1. Propose one question relevant to a real-world organizational situation that you will answer using principal component analysis (PCA)**

What are the best metrics when conducting dimension reduction using principal component analysis (PCA)?

**A2. Define one goal of the data analysis. Ensure that your goal is reasonable within the scope of the scenario and is represented in the available data.**

Reduce high dimension dataset (over 10 ) to a simpler, lower dimension dataset (less than 10 ) using principal component analysis (PCA).

## Part II: Method Justification

B. Explain the reasons for using PCA by doing the following:

**B1. Explain how the PCA analyzes the selected the selected dataset. Include expected outcomes.**

According to Vadapalli (2020), “Principal component analysis (PCA) is a statistical method used to transform a large number of possibly correlated variables into a much smaller number of uncorrelated variables referred to as principal components. PCA can be used as a data reduction technique as it allows us to find the most important variables that are needed to describe a dataset. PCA can also be used to reduce the dimensionality of the data space in order to get insight on the inner structure of the data. This is helpful when dealing with large datasets.”

The expected outcome of the reduction analysis is the appropriate number of principal components and total variance for each component.

The cost or limitation of the PCA is model accuracy, you are giving up accuracy for simplicity. The PCA will determine a lower dimension dataset and the order of significance of the identified principal components so that the results can be visualized and understood by less technical team members. Often, it can be very easy to visualize a 2-dimension plot using just the first two principal components.

The PCA key metrics are “explained variance” and “factor loading”. According to Schmalen, (Schmalen, 2020) “explained variance measures how much a model can reflect the variance of the whole data. Principle components try to capture as much of the variance as possible and this measure shows to what extent they can do that. It helps to see Components are sorted by explained variance, with the first one scoring highest and with a total sum of up to 1 across all components.” He continues, “factor loading indicates how much a variable correlates

with a component.” Using these two metrics and some scree plots and bar plots, the results can be verified as to how effectively the PCA accomplished the dimension reduction.

**B2. Summarize one assumption of PCA.**

PCA is dependent on having numeric, scaled data. If any one feature is not scaled and has large values, the PCA will give more weight to those higher values. In order to place equal weight of all features, all of the data should be scaled such that the mean of the feature is 0 and the standard deviation is 1.

### Part III: Data Preparation

C. Perform data preparation for the chosen dataset by doing the following:

**C1. Identify the continuous dataset variables that you will need in order to answer the PCA question proposed in part A1.**

The list of continuous features that will be used for the PCA is shown in Figure 1 and Figure 2. They are:

- Children
- Population
- Age
- Income
- Tenure
- Email
- Contacts
- Outage\_sec\_perweek
- MonthlyCharge
- Bandwidth\_GB\_Year
- Lat
- Lng

All remaining data is either categorical or discrete and will not be used for the PCA.

**Figure 1***Define continuous features*

```
In [6]: # define continuous features
# start with numerical data
# then remove non-continuous data
features = churn.select_dtypes(include=['number']).columns.tolist()
features.remove('CaseOrder') # id type field, non-continuous
features.remove('Zip') # non-continuous
features.remove('Item1') # non-continuous
features.remove('Item2') # non-continuous
features.remove('Item3') # non-continuous
features.remove('Item4') # non-continuous
features.remove('Item5') # non-continuous
features.remove('Item6') # non-continuous
features.remove('Item7') # non-continuous
features.remove('Item8') # non-continuous
features

Out[6]: ['Lat',
        'Lng',
        'Population',
        'Children',
        'Age',
        'Income',
        'Outage_sec_perweek',
        'Email',
        'Contacts',
        'Yearly_equip_failure',
        'Tenure',
        'MonthlyCharge',
        'Bandwidth_GB_Year']
```

Notes.



**Table 1***First 5 rows of the original dataset*

Lat	56.251	44.329	45.356	32.967	29.380
Lng	-133.376	-84.241	-123.247	-117.248	-95.807
Population	38.000	10446.000	3735.000	13863.000	11352.000
Children	0.000	1.000	4.000	1.000	0.000
Age	68.000	27.000	50.000	48.000	83.000
Income	28561.990	21704.770	9609.570	18925.230	40074.190
Outage_sec_perweek	7.978	11.699	10.753	14.914	8.147
Email	10.000	12.000	9.000	15.000	16.000
Contacts	0.000	0.000	0.000	2.000	2.000
Yearly_equip_failure	1.000	1.000	1.000	0.000	1.000
Tenure	6.796	1.157	15.754	17.087	1.671
MonthlyCharge	172.456	242.633	159.948	119.957	149.948
Bandwidth_GB_Year	904.536	800.983	2054.707	2164.579	271.493

&lt;class 'pandas.core.frame.DataFrame'&gt;

RangeIndex: 10000 entries, 0 to 9999

Data columns (total 13 columns):

#	Column	Non-Null Count	Dtype
0	Lat	10000 non-null	float64
1	Lng	10000 non-null	float64
2	Population	10000 non-null	int64
3	Children	10000 non-null	int64
4	Age	10000 non-null	int64
5	Income	10000 non-null	float64
6	Outage_sec_perweek	10000 non-null	float64
7	Email	10000 non-null	int64
8	Contacts	10000 non-null	int64
9	Yearly_equip_failure	10000 non-null	int64
10	Tenure	10000 non-null	float64
11	MonthlyCharge	10000 non-null	float64
12	Bandwidth_GB_Year	10000 non-null	float64

dtypes: float64(7), int64(6)

memory usage: 1015.8 KB

None

(10000, 13)

Notes. Using the original dataset, it can be seen that there are 13 numerical features that comprise the dataset for the company's 10,000 customer records. This will be the basis of the PCA.

**C2. Standardize the continuous dataset variables identified in part C1. Include a copy of the cleaned dataset.**

Scaled data is critical to the PCA. If not scaled properly, larger values will tend to dominate the PCA. Table 2 shows the first five rows of the scaled data. The StandardScaler was used to fit and transform the raw data.

**Table 2***First 5 rows of the scaled data*

	0	1	2	3	4
Lat	3.217	1.025	1.214	-1.065	-1.725
Lng	-2.810	0.432	-2.142	-1.746	-0.332
Population	-0.673	0.048	-0.417	0.285	0.111
Children	-0.972	-0.507	0.891	-0.507	-0.972
Age	0.721	-1.260	-0.149	-0.245	1.446
Income	-0.399	-0.642	-1.071	-0.741	0.009
Outage_sec_perweek	-0.680	0.570	0.252	1.651	-0.623
Email	-0.666	-0.005	-0.997	0.986	1.317
Contacts	-1.006	-1.006	-1.006	1.018	1.018
Yearly_equip_failure	0.947	0.947	0.947	-0.626	0.947
Tenure	-1.049	-1.262	-0.710	-0.660	-1.243
MonthlyCharge	-0.004	1.630	-0.295	-1.227	-0.528
Bandwidth_GB_Year	-1.138	-1.186	-0.612	-0.562	-1.428

`<class 'pandas.core.frame.DataFrame'>`

RangeIndex: 10000 entries, 0 to 9999

Data columns (total 13 columns):

#	Column	Non-Null Count	Dtype
0	Lat	10000 non-null	float64
1	Lng	10000 non-null	float64
2	Population	10000 non-null	float64
3	Children	10000 non-null	float64
4	Age	10000 non-null	float64
5	Income	10000 non-null	float64
6	Outage_sec_perweek	10000 non-null	float64
7	Email	10000 non-null	float64
8	Contacts	10000 non-null	float64
9	Yearly_equip_failure	10000 non-null	float64
10	Tenure	10000 non-null	float64
11	MonthlyCharge	10000 non-null	float64
12	Bandwidth_GB_Year	10000 non-null	float64

dtypes: float64(13)

memory usage: 1015.8 KB

None

(10000, 13)

Notes. The data is available as an attached file located at tables\scaled\_df.csv. This is the final scaled dataset, it can be seen that we have the same 13 features from the original data, but now scaled and ready to be used in PCA.

## Part IV: Analysis

D. Perform the data analysis and report on the results by doing the following:

**D1. Determine the matrix of all the principal components.**

Figure 2 shows the complete set of principal components and the factor loadings to the original features. It is called a correlation matrix with load factors and it shows how much each feature contributes towards each principal component.

**D2. Identify the total number of principal components using the elbow rule or the Kaiser criterion. Include a screenshot of the scree plot.**

Figure 3 shows the scree plot for all principal components showing the cumulative sum of total explained variance for each of the principal components. The plot also has lines to indicate 85%, 90% and 95% of total explained variance. The scree plot can be effectively used to select the desired number of principal components to use in the final PCA model.

**D3. Identify the variance of each of the principal components identified in part D2.**

Table 3 shows the total variance for each of the principal components.


**D4. Identify the total variance captured by the principal components identified in part D2.**

Figure 4 shows a bar plot of total variance for each principal component as well as a line plot showing the cumulative total variance for all of the PCs up to that point.

T

**Figure 2**


*Correlation matrix of all 13 principal components with loadings to original features*



Notes. The correlation matrix for the initial PCA using all 13 PCs. Load factors or +/- .7 indicate a high load factor for that component.

**Figure 3**

*Scree plot to identify explained variance for each principal component*



Notes. The scaled dataset used for the initial PCA is using all of the original 13 features, so the scree plot should have 13 principal components, PC1 through PC13. It looks like it will take about 10 or 11 PCs to account for a 90% total variance.

Each PC: [15.344 9.493 8.105 8.035 7.871 7.774 7.686 7.635 7.573  
7.398  
7.388 5.656 0.042]

Cumulative Sum: [ 15.344 24.836 32.942 40.977 48.847 56.622 64.308  
71.943 79.516  
86.914 94.302 99.958 100. ]

**Table 3***Total variance by principal component by feature*

	Lat	Lng	Population	Children	Age	Income	Outage_sec_perweek	\
PC1	-0.02	0.01	-0.00	0.01	0.00	0.00	0.01	
PC2	-0.71	0.18	0.65	-0.01	0.05	-0.05	0.01	
PC3	-0.03	-0.29	0.15	0.45	-0.44	0.20	-0.25	
PC4	0.11	-0.74	0.32	-0.46	0.23	-0.04	-0.13	
PC5	-0.09	0.34	-0.12	-0.11	0.44	0.31	-0.46	
PC6	-0.03	-0.09	0.10	0.13	-0.10	0.10	0.60	
PC7	-0.01	-0.05	0.05	0.03	-0.19	0.77	0.05	
PC8	-0.02	-0.09	0.08	-0.07	0.09	0.34	-0.18	
PC9	0.09	-0.17	-0.03	0.19	0.34	0.25	0.06	
PC10	0.02	-0.15	0.06	0.44	-0.08	-0.28	-0.52	
PC11	0.05	-0.11	0.10	0.57	0.61	-0.03	0.22	
PC12	0.67	0.38	0.63	-0.01	-0.04	0.01	-0.03	
PC13	0.00	0.00	-0.00	-0.02	0.02	-0.00	0.00	

	Email	Contacts	Yearly equip_failure	Tenure	MonthlyCharge	\
PC1	-0.02	0.00		0.02	0.71	0.04
PC2	0.15	0.03		-0.01	-0.01	-0.00
PC3	-0.09	-0.45		0.15	0.01	-0.40
PC4	-0.14	0.11		0.06	0.03	-0.14
PC5	-0.35	0.01		0.42	0.01	-0.22
PC6	-0.40	0.08		0.59	-0.04	0.26
PC7	0.00	0.52		-0.29	-0.00	-0.04
PC8	-0.13	-0.51		-0.19	-0.04	0.71
PC9	0.76	-0.05		0.40	0.00	0.06
PC10	-0.05	0.49		0.14	-0.04	0.41
PC11	-0.25	-0.03		-0.38	0.01	-0.14
PC12	0.03	-0.01		0.04	0.01	-0.01
PC13	0.00	-0.00		-0.00	-0.71	-0.05


  

	Bandwidth_GB_Year
PC1	0.71
PC2	-0.01
PC3	0.01
PC4	-0.00
PC5	-0.02
PC6	-0.01
PC7	0.00
PC8	0.00
PC9	0.00
PC10	0.01
PC11	-0.01
PC12	0.01
PC13	0.71

Notes.

**Figure 4**

*Bar plot/line plot of variance and cumulative variance for all PCs*



Notes. PC13 has a explained variance of 0042, very small.

Variance explained by the first principal component = 15.343888168137699

Variance explained by the first 2 principal components = 24.83641162467388

Variance explained by all 13 principal components = 100.0

Code adapted from Kumar (Kumar, 2020)



**D5. Summarize the results of your data analysis.**

The first observation is that 12 PCs are required to achieve a total explained variance of 99.9%. That would be a dimension reduction but not quite what was hoped for.

The first 2 principal components have a total explained variance of 24.8%. A much simpler dimensional dataset, but at the extreme expense of all accuracy.

The first 3 principal components have a total explained variance of 32.9%. Not much better.

The first principal component (PC1) is highly correlated to tenure and bandwidth. Either experienced customers who prefer more bandwidth or possibly new customers with only limited bandwidth. But, the correlation for tenure and bandwidth are both above a impact threshold of 0.70.

The second principal component (PC2) is correlated to location and population count in the region nearest to each customer. There is a positive correlation to population and a negative correlation to the location.

### **Part V: Attachments**

E. Record the web sources used to acquire data or segments of third-party code to support the analysis. Ensure the web sources are reliable. (see References below)

F. Acknowledge sources, using in-text citations and references, for content that is quoted, paraphrased, or summarized. (see References below)

G. Demonstrate professional communication in the content and presentation of your submission.

## References

- Albon, C. (2017). Drop Highly Correlated Features. Retrieved from [https://chrisalbon.com/code/machine\\_learning/feature\\_selection/drop\\_highly\\_correlated\\_features/](https://chrisalbon.com/code/machine_learning/feature_selection/drop_highly_correlated_features/)
- Alkhayrat, M., Aljnidi, M., & Aljoumaa, K. (2020). A comparative dimensionality reduction study in telecom customer segmentation using deep learning and PCA. Retrieved from <https://journalofbigdata.springeropen.com/articles/10.1186/s40537-020-0286-0>
- Arvai, K. (2022). K-Means Clustering in Python: A Practical Guide. Retrieved from <https://realpython.com/k-means-clustering-python/#:~:text=The SSE is defined as,try to minimize this value.&text=The purpose of this figure,centroids is an important step.>
- Bex, T. (2021, April 13). *How to Use Pairwise Correlation For Robust Feature Selection*. Retrieved May 8, 2022, from How to Use Pairwise Correlation For Robust Feature Selection: <https://towardsdatascience.com/how-to-use-pairwise-correlation-for-robust-feature-selection-20a60ef7d10>
- Boyle, T. (2019, March 25). *Feature Selection and Dimensionality Reduction*. Retrieved May 8, 2022, from Feature Selection and Dimensionality Reduction: <https://towardsdatascience.com/feature-selection-and-dimensionality-reduction-f488d1a035de>
- Brownlee, J. (2019). How to Calculate Principal Component Analysis (PCA) from Scratch in Python. Retrieved from <https://machinelearningmastery.com/calculate-principal-component-analysis-scratch-python/>
- Bruce, P. C., Gedeck, P., Shmueli, G., & Patel, N. R. (2019). *Data Mining for Business Analytics Concepts, Techniques and Applications in Python*. Wiley & Sons, Incorporated, John.

- Bruce, P., Bruce, A., & Gedeck, P. (2020). *Practical Statistics for Data Scientists 50+ Essential Concepts Using R and Python*. O'Reilly Media, Incorporated.
- Fenner, M. (2018). *Machine Learning with Python for Everyone*. Addison Wesley.
- Galarnyk, M. (2017). PCA using Python (scikit-learn). Retrieved from <https://towardsdatascience.com/pca-using-python-scikit-learn-e653f8989e60>
- Géron, A. (2019). *Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow Concepts, Tools, and Techniques to Build Intelligent Systems*. O'Reilly Media.
- h1ros. (2019). Drop Highly Correlated Features. Retrieved from <https://h1ros.github.io/posts/drop-highly-correlated-features/>
- Kaloyanova, E. (2020, March 10). *How to Combine PCA and K-means Clustering in Python?* Retrieved May 8, 2022, from How to Combine PCA and K-means Clustering in Python?: <https://365datascience.com/tutorials/python-tutorials/pca-k-means/>
- Kumar, A. (2020, August). PCA Explained Variance Concepts with Python Example. *PCA Explained Variance Concepts with Python Example*. Retrieved May 16, 2022, from <https://vitalflux.com/pca-explained-variance-concept-python-example/>
- Larose, C. D., & Larose, D. T. (2019). *Data Science*. Wiley.
- Parveez, S., & Iriondo, R. (2018). Principal Component Analysis (PCA) with Python Examples — Tutorial. Retrieved from <https://pub.towardsai.net/principal-component-analysis-pca-with-python-examples-tutorial-67a917bae9aa>
- ProjectPro. (2022). How to drop out highly correlated features in Python? Retrieved from <https://www.projectpro.io/recipes/drop-out-highly-correlated-features-in-python>
- Sawhani, D. (2017). Customer Churn Prediction Model. Retrieved from [https://rstudio-pubs-static.s3.amazonaws.com/344958\\_a3c32d38a83043c8ae8fc13cd6abbda4.html](https://rstudio-pubs-static.s3.amazonaws.com/344958_a3c32d38a83043c8ae8fc13cd6abbda4.html)

- Schmalen, P. (2020, August 16). *Understand your data with principal component analysis (PCA) and discover underlying patterns*. Retrieved May 15, 2022, from Understand your data with principal component analysis (PCA) and discover underlying patterns:  
<https://towardsdatascience.com/understand-your-data-with-principle-component-analysis-pca-and-discover-underlying-patterns-d6cadb020939>
- Sharma, A. (2021). PCA or Principal Component Analysis on Customer Churn Data. Retrieved from <https://medium.com/data-science-on-customer-churn-data/pca-or-principal-component-analysis-on-customer-churn-data-d18ca60397ed>
- Srinivas. (2022). Reducing Telecom Churn with PCA and Modeling. Retrieved from <https://www.kaggle.com/code/manoharsrinivas/reducing-telecom-churn-with-pca-and-modeling/notebook>
- VanderPlas, J. (2016). *In Depth: Principal Component Analysis*. O'Reilly. Retrieved from <https://jakevdp.github.io/PythonDataScienceHandbook/05.09-principal-component-analysis.html>