



Open in app

Get started



Published in Towards AI

This is your **last** free member-only story this month. [Sign up for Medium and get an extra one](#)



Michelangiolo Mazzeschi

Follow

Jun 30, 2020 · 5 min read ★ · [Listen](#)



Save



APRIORI, ASSOCIATION ANALYSIS, MACHINE LEARNING

Performing a Market Basket Analysis with Machine Learning

Improve Marketing with AI. Full code [available at my Github repo](#)

Unsupervised Learning has 3 main subsections: Clustering, Dimensionality Reduction, and Association. Although I have done some editing and simplifications, you can find the original code [at this source](#).





Open in app

Get started



Photo by [gemma](#) on [Unsplash](#)

The goal of Association Analysis, in general, is to find the following relationships:

antecedent



People who buy

consequent




will also buy



[Open in app](#)[Get started](#)

Market Basket Analysis. If I got this correctly, Association Analysis (also known as Association Rules Generation, Affinity Analysis, Association Rules Mining... just to make things easier) refers to a category of problems.



Market Basket Analysis

Within this category, Market Basket Analysis represents one of its subsections, and it is applied when there are **many lists of goods bought per consumer**. The same methodology applies to **watched movies**, for example. Different Association problems will require the use of different Association subsections that won't be classified under the Market Basket Analysis.

In order to perform the Market Basket Analysis, I will be using the notorious apriori algorithm.

Steps

The steps in building this algorithm are, fortunately, straightforward:

1. Installing Modules
2. Importing Libraries
3. Preparing the Dataset



[Open in app](#)[Get started](#)

6. EXTRACT RULES

7. Define Threshold and extract the final associations

1. Installing Modules

I will be importing the modules using pip.

```
! pip install mlxtend
! pip install xlrd
```

2. Importing Libraries

Scikit-Learn does not support the apriori algorithm. I will use an extension of the python library called mlxtend.

```
import pandas as pd
from mlxtend.preprocessing import TransactionEncoder
from mlxtend.frequent_patterns import apriori
from mlxtend.frequent_patterns import association_rules
```

3. Preparing the Dataset

Because I wanted to outline a simplified version of this problem, I found that the only compatible datasets on the internet have hundred of thousand of information. I will create a dataset myself, so you can better understand how it works.

```
#Onion, Sausages, Cheese, Water, Butter, Sugar, Eggs
df = [['Onion', 'Sausages', 'Cheese', 'Butter'],
      ['Onion', 'Sausages', 'Water', 'Sugar'],
      ['Onion', 'Water', 'Sausages'],
      ['Butter', 'Sugar', 'Eggs'],
      ['Butter', 'Sugar', 'Eggs', 'Cheese'],
      ['Water', 'Cheese', 'Eggs'],
      ['Water', 'Butter'],
      ['Onion', 'Butter', 'Sugar']]
```



[Open in app](#)[Get started](#)

	Butter	Cheese	Eggs	Onion	Sausages	Sugar	Water
0	True	True	False	True	True	False	False
1	False	False	False	True	True	True	True
2	False	False	False	True	True	False	True
3	True	False	True	False	False	True	False
4	True	True	True	False	False	True	False
5	False	True	True	False	False	False	True
6	True	False	False	False	False	False	True
7	True	False	False	True	False	True	False
8	True	True	False	True	False	False	False
9	True	False	False	True	False	False	True

This is the format of our dataset: ingredients as Features, customers in rows

Converting DataFrame to a compatible list

In reality, the dataset would have been ready before transforming it into a DataFrame. However, the point of this article is to illustrate to you what are the building blocks of Market Basket Analysis. Because you will likely start with information stored into a pandas DataFrame, this will prove useful in the future (you can skip, if not interested).

```
#1. conversione in list: il problema che ha None values
df = dataset.values.tolist()
df
[['Onion', 'Sausages', 'Cheese', 'Butter'],
 ['Onion', 'Sausages', 'Water', 'Sugar'],
 ['Onion', 'Water', 'Sausages', None],
 ['Butter', 'Sugar', 'Eggs', None],
 ['Butter', 'Sugar', 'Eggs', 'Cheese'],
 ['Water', 'Cheese', 'Eggs', None],
 ['Water', 'Butter', None, None],
 ['Onion', 'Butter', 'Sugar', None],
 ['Onion', 'Butter', 'Cheese', None],
```



[Open in app](#)[Get started](#)

```
#Removing None values in list, 2 dimensions
df_ = list()
for _ in df:
    #using list comprehension
    _ = [x for x in _ if x is not None]
    df_.append(_)
df = df_
df
[['Onion', 'Sausages', 'Cheese', 'Butter'],
 ['Onion', 'Sausages', 'Water', 'Sugar'],
 ['Onion', 'Water', 'Sausages'],
 ['Butter', 'Sugar', 'Eggs'],
 ['Butter', 'Sugar', 'Eggs', 'Cheese'],
 ['Water', 'Cheese', 'Eggs'],
 ['Water', 'Butter'],
 ['Onion', 'Butter', 'Sugar'],
 ['Onion', 'Butter', 'Cheese'],
 ['Onion', 'Butter', 'Water']]
```

I have recreated the list using **df_**, but dropping the None values. Because the DataFrame was structured using nested lists in 2 dimensions, this algorithm does not apply in case you want to drop None in multidimensional lists.

```
#one_hot encoding (boolean output)
te = TransactionEncoder()
te_ary = te.fit(df).transform(df)
df = pd.DataFrame(te_ary, columns=te.columns_)
df
```

Scikit-Learn does not support the apriori algorithm, I have installed **mlxtend** for the occasion. It will transform the bidimensional list into one_hot encoded DataFrame.

As mentioned above, this should be the final result:



[Open in app](#)[Get started](#)

For every customer, buying one ingredient will be equivalent to True, not buying to False. As you can notice, the apriori algorithm does not take into account the quantities, but only if a product has been bought or not.

4. Extract Frequent Itemsets

```
frequent_itemsets = apriori(df, min_support=0.4, use_colnames=True)
frequent_itemsets
```

	support	itemsets
0	0.7	(Butter)
1	0.4	(Cheese)
2	0.6	(Onion)
3	0.4	(Sugar)
4	0.5	(Water)
5	0.4	(Onion, Butter)

5. Extract Association Rules

Among all items, I will select the ones that have a minimum confidence of .4:

```
association_rules(frequent_itemsets, metric="confidence",
min_threshold=0.4)
```



[Open in app](#)[Get started](#)

6. Extract Rules

With this step, I will impose a minimum threshold on the lift of .7:

```
rules = association_rules(frequent_itemsets, metric="lift",
min_threshold=.7)
```

	antecedents	consequents	antecedent support	consequent support	support	confidence	lift	leverage	conviction
0	(Onion)	(Butter)	0.6	0.7	0.4	0.666667	0.952381	-0.02	0.900000
1	(Butter)	(Onion)	0.7	0.6	0.4	0.571429	0.952381	-0.02	0.933333

7. Define Threshold and extract the final associations

```
rules["antecedent_len"] = rules["antecedents"].apply(lambda x: len(x))
```

	antecedents	consequents	antecedent support	consequent support	support	confidence	lift	leverage	conviction	antecedent_len
0	(Onion)	(Butter)	0.6	0.7	0.4	0.666667	0.952381	-0.02	0.900000	1
1	(Butter)	(Onion)	0.7	0.6	0.4	0.571429	0.952381	-0.02	0.933333	1

As we can see, people who buy Onion  151  butter, and the rule is applicable vice-versa as well.

Make a selection based on specifics

In case you want to select association rules based on a threshold, you will find this algorithm useful.

Sign up for Towards AI Newsletter

By Towards AI

Join thousands of data leaders on the AI newsletter. It's free, we don't spam, and we never share your





[Open in app](#)

Get started



Get this newsletter

By signing up, you will create a Medium account if you don't already have one. Review our [Privacy Policy](#) for more information about our privacy practices.

[About](#) [Help](#) [Terms](#) [Privacy](#)

Get the Medium app

