

This document was generated on 12/07/2020

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: <u>1050170001</u>

Status: Active

Overview: USB Products and Solutions

Description: Micro-USB B Receptacle, Bottom Mount, Surface Mount, with Solder Tabs, Lead-Free

Documents:

<u>3D Model</u> <u>Product Specification PS-105017-001-001 (PDF)</u>
<u>Drawing (PDF)</u> <u>Packaging Specification PK-105017-001-001 (PDF)</u>

3D Model (PDF) RoHS Certificate of Compliance (PDF)

Agency Certification

UL E107635

General

Product Family I/O Connectors
Series 105017
Application Wire-to-Board

Comments Signal contacts 1.0A, Power contacts 1.8A

Component Type Receptacle

Overview <u>USB Products and Solutions</u>

 Product Name
 USB 2.0

 Type
 Micro-B

 UPC
 822350969109

Physical

Boot Color N/A Circuits (Loaded) 5 Circuits (maximum) 5 Color - Resin Black Durability (mating cycles max) 10000 Flammability 94V-0 Gender Female Keying to Mating Part Yes Lock to Mating Part No

Material - Metal Copper Alloy

Material - Plating Mating Gold Material - Plating Termination Gold

Material - Resin High Temperature Thermoplastic

Net Weight0.233/gNumber of Rows1OrientationRight Angle

PCB Retention None

Packaging Type Embossed Tape on Reel


Panel Mount No
Pitch - Mating Interface 0.65mm
Pitch - Termination Interface 0.65mm
Polarized to Mating Part Yes
Ports 1
Surface Mount Compatible (SMC) Yes

Temperature Range - Operating -30° to +85°C
Termination Interface: Style Surface Mount

Waterproof / Dustproof No

Electrical

Current - Maximum per Contact
Grounding to Panel
Shield Type
1.8A, 1.0A
Yes
Full Shield



EU ELV Compliant

EU RoHS China RoHS

Compliant
REACH SVHC
Not Contained Per D(2020)4578-DC (25

June 2020)
Halogen-Free
Status
Low-Halogen

For more information, please visit Contact US

China ROHS Green Image
ELV Compliant
RoHS Phthalates Not Contained

Search Parts in this Series

105017 Series

Shielded Yes

Voltage - Maximum 30V AC (RMS)

Solder Process Data

Duration at Max. Process Temperature (seconds)

Lead-freeProcess Capability

Max. Cycles at Max. Process Temperature

O01

Process Temperature max. C

260

Material Info

Engineering Number NT501-6734

Reference - Drawing Numbers

Packaging Specification PK-105017-001-001
Product Specification PS-105017-001-001

This document was generated on 12/07/2020

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION