

Hintikka’s World: scalable higher-order knowledge

Tristan Charrier^{1*}, Sébastien Gamblin², Alexandre Niveau^{2,3} and François Schwarzenruber⁴

¹First Affiliation

²Second Affiliation

³Third Affiliation

⁴Fourth Affiliation

{first, second}@example.com, third@other.example.com, fourth@example.com

Abstract

Hintikka’s World is a tool that shows how artificial agents can reason about higher-order knowledge (agent *a* knows that agent *b* knows that...). In this demonstration paper, we present symbolic models that enables to implement in *Hintikka’s World* large examples such as real card games.


1 Introduction

The current trend is to construct programs that play games with imperfect information, for instance Hanabi [Bard *et al.*, 2019], but also video games such as Starcraft 2 [Hu *et al.*, 2018]. An important ingredient is to reason about higher-order knowledge (an agent knows that another agents knows that...). In these systems, epistemic logic and its dynamic extension, Dynamic epistemic logic ([Baltag *et al.*, 1998], [van Ditmarsch *et al.*, 2008]) may offer formal tools for providing explanations in such AI programs. needs to be understood is relevant in AI, especially in strategic reasoning [Aumann, 1999].

The only pedagogical tool we are aware of that explains such models is *Hintikka’s world* and was presented at ECAI-IJCAI 2018 [Schwarzenruber, 2018]. *Hintikka’s world* is a proof of concept of a graphical user interface that represent Kripke models by comic strips, as shown in Figure 1. It enables to explore mental states of agents. The tool is available at the following address: <http://hintikkasworld.irisa.fr/>.

Kripke models are graphs, represented explicitly in memory in the first version of the tool. Explicit models are useful to learn how dynamic epistemic logic works by means of toy examples: muddy children, Sally and Anne [Wimmer and Perner, 1983], etc. However, in real card games, such as Hanabi, there are an exponential number of possible configurations of cards. For instance Hanabi has 50 cards total and each player has 4 cards and the order of the cards is important. Therefore with 4 players, the initial Kripke model features $50 \times 49 \times 48 \times \dots \times 38$ configurations, that is 2.2×10^{21} . Thus, it is impossible to represent explicitly the full graph in memory: the first version of *Hintikka’s world* does not *scale*.

That is why, in this demonstration, we propose to represent Kripke models symbolically by using the approach



TODO ajouter le modèle de Kripke

Figure 1: Graphical user interface of *Hintikka’s world*.

in [Charrier and Schwarzenruber, 2017] and [Charrier and Schwarzenruber, 2018]. The implementation relies on Binary Decision Diagrams (BDDs) [] as it was done in the tool DEMO¹ [van Benthem *et al.*, 2015].

2 Symbolic models

Symbolic Kripke models aim at representing succinctly so-called pointed Kripke models. A pointed Kripke model is a graph whose nodes are *possible worlds*, edges are labeled by agents and an edge $w \rightarrow^a u$ means that agent *a* considers world *u* as possible in world *w*. Each world *w* is equipped with a valuation telling which atomic propositions is true in *w*. A special world is called the pointed world and represents the true situation, while the other possible worlds are worlds imagined by the agents. The tool shows that graph in the right-part of the screen (in the example of Figure 1, the Kripke model has two possible worlds).

A symbolic model consists in a description of the model in a more succinct language. Such representations already exist for other formalisms, such as boolean circuits for searching for Hamiltonian paths in graphs [Papadimitriou, 2003], or BDDs for temporal logics [Burch *et al.*, 1990].

In the demonstration we use the symbolic description of [Charrier and Schwarzenruber, 2018] for dynamic epistemic

*Contact Author

¹The current implementation does not rely on DEMO since their work is not well-suited for a web application.

logic², and use the reduction to first-order logic of [Charrier et al., 2017] to implement this approach with BDDs.

Take for instance any card game. The initial model is described by BDDs for the following boolean formulas: formula χ_W whose valuations are the possible configurations and formula χ_R to describe which configurations agents do not distinguish. The formula χ_W actually describes legal configurations according to the rules of the game, and χ_W reflect the fact that agents do not see the hand of other agents, so they may imagine as possible any possible dealing.

Dynamic epistemic logic also provides so-called *event models* for describing actions (public announcements, public actions, private announcements/actions, etc.). The reader may refer to the textbook on DEL [van Ditmarsch et al., 2008] and to [Charrier and Schwarzenruber, 2017] for symbolic event models, that we do not detail here.

3 Demonstration Outline

In the demonstration we show a play of the game Hanabi. In this game, each agent has cards with a color and a number, but cannot see his own hand. In each turn, an agent can either give the information to some other agent about a number or a color, or play a card. The goal is to play the cards in increasing order for each color.

TODO expliquer la démo. Je me suis peut être trompé sur le nombre de cartes ici et si on gère les jetons pour les infos il faut le mettre dans le paragraphe.

4 System Description

TODO Expliquer comment c’est FAIT

4.1 Class Architecture

Figure 2 shows the main part of the architecture of *Hintikka’s world*. The interesting part is the fact that the graphical user interface (GUI) is independent from the current example that is running (muddy children, Sally and Anne, etc.). In particular, adding a new example only requires to add a new class that inherits from `World` and to implement the method for drawing the scene from data (valuations, numbers, etc.) that are members of the class.

4.2 Model Checking

The tool highly rely on model checking. Indeed, for instance, performing the public announcement of ϕ requires to compute the subset of worlds in which ϕ holds and to prune the current Kripke model. We chose to write the model checking procedure in Javascript. Since model checking is in PTIME – thus is an easy task – and is used intensively, it suitable to run it on the client-side for performance reasons.

4.3 Satisfiability Problem

5 Future Work

TODO implémenter d’autres exemples etc.

TODO d’autres façons de “scaler”




Figure 2: Architecture for the symbolic approach in *Hintikka’s world*

References

- [Aumann, 1999] Robert J. Aumann. Interactive epistemology I: knowledge. *Int. J. Game Theory*, 28(3):263–300, 1999.
- [Baltag et al., 1998] Alexandru Baltag, Lawrence S Moss, and Slawomir Solecki. The logic of public announcements, common knowledge, and private suspicions. In *Proceedings of the 7th conference on Theoretical aspects of rationality and knowledge*, pages 43–56. Morgan Kaufmann Publishers Inc., 1998.
- [Bard et al., 2019] Nolan Bard, Jakob N. Foerster, Sarath Chandar, Neil Burch, Marc Lanctot, Francis Song, Emilio Parisotto, Vincent Dumoulin, Subhodeep Moitra, Edward Hughes, Iain Dunning, Shihl Mourad, Hugo Larochelle, Marc G. Bellemare, and Michael Bowling. The hanabi challenge: A new frontier for AI research. *CoRR*, abs/1902.00506, 2019.
- [Burch et al., 1990] Jerry R. Burch, Edmund M. Clarke, Kenneth L. McMillan, David L. Dill, and L. J. Hwang. Symbolic model checking: 10²⁰ states and beyond. In *Proceedings of the Fifth Annual Symposium on Logic in Computer Science (LICS ’90), Philadelphia, Pennsylvania, USA, June 4-7, 1990*, pages 428–439, 1990.
- [Charrier and Schwarzenruber, 2017] Tristan Charrier and François Schwarzenruber. A succinct language for dynamic epistemic logic. In *Proceedings of the 16th Conference on Autonomous Agents and MultiAgent Systems, AAMAS 2017, São Paulo, Brazil, May 8-12, 2017*, pages 123–131, 2017.
- [Charrier and Schwarzenruber, 2018] Tristan Charrier and François Schwarzenruber. Complexity of dynamic epistemic logic with common knowledge. In *Advances in Modal Logic 12, proceedings of the 12th conference on “Advances in Modal Logic,” held in Bern, Switzerland, August 27-31, 2018*, pages 103–122, 2018.
- [Charrier et al., 2017] Tristan Charrier, Sophie Pinchinat, and François Schwarzenruber. Model checking against arbitrary public announcement logic: A first-order-logic prover approach for the existential fragment. In *Dynamic Logic. New Trends and Applications - First International Workshop, DALI 2017, Brasilia, Brazil, September 23-24, 2017, Proceedings*, pages 133–152, 2017.

²Which is actually a rewriting of the description of [Charrier and Schwarzenruber, 2017]

- [Hu *et al.*, 2018] Yue Hu, Juntao Li, Xi Li, Gang Pan, and Mingliang Xu. Knowledge-guided agent-tactic-aware learning for starcraft micromanagement. In *Proceedings of the Twenty-Seventh International Joint Conference on Artificial Intelligence, IJCAI 2018, July 13-19, 2018, Stockholm, Sweden.*, pages 1471–1477, 2018.
- [Papadimitriou, 2003] Christos H Papadimitriou. *Computational complexity*. John Wiley and Sons Ltd., 2003.
- [Schwarzentruher, 2018] François Schwarzentruher. Hintikka’s world: Agents with higher-order knowledge. In *Proceedings of the Twenty-Seventh International Joint Conference on Artificial Intelligence, IJCAI 2018, July 13-19, 2018, Stockholm, Sweden.*, pages 5859–5861, 2018.
- [van Benthem *et al.*, 2015] Johan van Benthem, Jan van Eijck, Malvin Gattinger, and Kaile Su. Symbolic model checking for dynamic epistemic logic. In *Logic, Rationality, and Interaction - 5th International Workshop, LORI 2015 Taipei, Taiwan*, pages 366–378, 2015.
- [van Ditmarsch *et al.*, 2008] Hans van Ditmarsch, Wiebe van der Hoek, and Barteld Kooi. *Dynamic Epistemic Logic*. Springer, Dordrecht, 2008.
- [Wimmer and Perner, 1983] Heinz Wimmer and Josef Perner. Beliefs about beliefs: Representation and constraining function of wrong beliefs in young children’s understanding of deception. *Cognition*, 13(1):103–128, 1983.