

Mountain Search UAV System Technical Guide

This guide describes setup, system behavior and test materials. See paper alignment and Android validation for implementation and validation summaries; the corresponding paper-alignment JSON and Android JSON contain result counts and source snapshot identifiers.

1 Archive Contents and Version

Mountain Search UAV System | Technical Guide | 30 September 2026
Implementation baseline: UAV-SEARCH-20260928

This archive contains the mobile application, ground station and UAV source code, together with MATLAB simulations of the three search modes, software verification records and outdoor footage. All paths in this guide are relative to the archive root.

File locations

Directory	Contents
code/	Three software components, integration tests and configuration checks
simulation/	MATLAB scripts, elevation data, trajectories, figures and animation
experiments/phone_relay_20260928/	Inputs and results from the local phone-record relay test
experiments/outdoor/	Original outdoor footage, ground-station footage and images
records/	Verification logs, source provenance and file checksums
docs/	This guide in Word, PDF and Markdown formats
LICENSES/	Source licenses and third-party copyright notices

Component directory abbreviations

M, G and U refer to the mobile, ground-station and UAV directories, respectively:

code/mobile_application
code/ground_station
code/search_uav

Current behavior

Mode 1 estimates the trip end time from the planned route and a fixed walking speed. Mode 2 checks whether the latest valid GPS sample exceeds the configured update timeout. Mode 3 places an SOS request in the verification queue. In all three modes, the operator verifies the situation and confirms a search before creating an event, reviewing its route and dispatching the mission.

Application and protocol version numbers are retained. The implementation baseline is recorded in code/source_revision.json; Git history identifies later changes. The software retains its English and Chinese interface options. Section 9 maps the manuscript's functions to implementation and evidence.

2 Local Setup and Verification

Use Python 3.12 with Tk support, Node.js 24 and a C++14 compiler for local verification. MATLAB R2025b was used for the archived simulation; MATLAB is not required to check the saved numeric outputs. Run the following commands from the archive root.

Create the Python environment

```
python3.12 -m venv .venv
source .venv/bin/activate
python -m pip install -r requirements-verification.txt
python scripts/prepare_local.py
```

Install mobile dependencies

```
cd code/mobile_application
npm ci
cd ../..
```

Run the complete verification sequence

```
python scripts/verify.py --output local-results/verification-01
```

Use a new output directory for each run. The sequence checks output preservation, lint rules, TypeScript types, version alignment, mobile tests, Python syntax, ground-station and UAV tests, C++ target-state handling and cross-component protocols. It then checks the saved MATLAB trajectories and figure axes. Results and logs, including `simulation_checks.json`, are written inside the selected directory. An `all_passed` value of `true` in `summary.json` means that all listed checks passed. Archived results are preserved.

`prepare_local.py` creates `M/services/db/firebaseConfig.ts` from the example only when the local file is absent. Its placeholder values configure the mocked cloud connections used by the test runner. A direct call to `python simulation/verify_outputs.py` prints its findings without writing a report. Add `--output` followed by a new JSON path to save a report; an existing report is rejected.

Repeat the local relay test

Install Mosquitto and make the `mosquitto` executable available on the command path. The test starts a temporary broker that listens only on the local loopback address and stops it when the test finishes.

```
python code/integration_tests/run_phone_uav_gs_bench.py \
--output local-results/phone-relay-01
```

The test sends a synthetic phone record through a local HTTP interface and uses a running Mosquitto broker for relay and acknowledgement. Its output includes nine key records, the broker log and file checksums.

On Windows, activate Python with `.venv\Scripts\Activate.ps1` in PowerShell. The complete shell-based verification entry point requires Git Bash or a compatible shell. Configure ROS programs on Ubuntu as described in Section 5.

3 Mobile Records and Trip-Time Estimation

Mode 1 Event Booking

The user enters a trip name, departure date and departure time, then selects successive locations along the planned route on the map. The interface displays the estimated end date and time automatically. Editing the route, departure date or departure time recalculates the estimate.

The application uses the Haversine formula between consecutive coordinates and sums these distances. It uses a fixed walking speed of 4 km/h and rounds the estimated duration up to a whole minute. The end timestamp is the departure timestamp plus that duration. Dates spanning midnight, a year boundary or a leap day retain the complete end timestamp.

```
duration_minutes = ceil(route_distance_m / 4000 * 60)
end_time = departure_time + duration_minutes * 60 seconds
```

The 4 km/h value follows the general walking-time reference in Ordnance Survey's Map Reading guide. This estimate uses horizontal route distance; selected points should represent the planned route turns. Gradient,

ground conditions and stops affect actual duration, so an overdue record still requires operator contact and verification.

Stored field	Meaning
waypoints	Planned route positions in the order selected by the user
expectedEndAtMs	Estimated end timestamp in Unix milliseconds
endDate / endTime	End date and time displayed by the interface
routeDistanceM	Total route distance in metres
estimatedDurationMinutes	Estimated duration, rounded up to whole minutes
walkingSpeedKmh	Fixed value: 4
estimationMethod	route_distance_fixed_speed_v1

Mode 2 Quick Start and Mode 3 SOS

Mode 2 uploads GPS positions and sample timestamps during the hike. The ground station checks the latest valid sample for a timeout and uses the uploaded position history when preparing a flight. Mode 3 stores the location and request information recorded when the user activates SOS, for operator verification and square-spiral route generation.

Mode 2 uses sampling time, not upload or receipt time. A stationary position with fresh samples does not trigger the current update-timeout rule. SOS uploads go to this system's Firebase database and ground station. The separate Call 999 Now button opens the phone dialer. The manuscript retains an earlier interface screenshot; the current English and Chinese SOS instructions explicitly describe ground-station operator verification.

Implementation: `M/services/eventBookingRecord.ts`. Booking interface: `M/pages/EventBookingPage.tsx`.

Tests: `M/__tests__/eventBookingRecord.test.ts`.

Reference: Ordnance Survey, Map Reading, "Timing", printed page 23. The complete source link is in `docs/Sources.txt`.

Mobile deployment configuration

The current mobile source supports Android only. For device operation, fill `M/services/db/firebaseConfig.ts` with the project's client configuration and use the same Realtime Database URL as the ground station. Configure the Android toolchain, native Firebase files and map credentials separately. From M, `npm start` starts Metro; `npm run android` invokes the Android build. The Android compile-only helper uses synthetic configuration. Build and verification results are listed in Android validation.

4 Ground-Station Verification and Dispatch

Common verification procedure

Overdue bookings, GPS update timeouts and new SOS requests enter the verification queue. The operator reads the user and emergency-contact details, contacts them and records the outcome. A confirmed safe status closes the alert. If safety cannot be confirmed, the operator contacts the available emergency contacts. After completing these records, the operator explicitly confirms a search before the platform creates a search event.

An SOS request no longer creates a dispatchable event directly. Repeated scans or confirmations do not create duplicates. A cancelled SOS cannot be confirmed through a stale alert. An unverified SOS event from the earlier implementation must complete contact verification before route preparation, provided it has not already entered execution.

Select an event, review its route and dispatch

After the operator selects an event, the ground station reads the associated user records and generates a route. Mode 1 uses the planned route; Mode 2 uses GPS history ordered by sample time; Mode 3 generates a square spiral around the SOS location. The operator reviews the route and settings before dispatch. Changes to the relevant records or operation state require the mission to be prepared again.

All three modes have the same initial event priority and the same waiting-time rule. SOS mode alone does not assign the highest priority. The operator selects and dispatches the mission.

Runtime configuration

Setting	Purpose
GS_FIREBASE_DATABASE_URL	Database URL shared with the mobile application
GS_FIREBASE_CREDENTIALS	Local service-account file path
GS_T_LOCATION_UPDATE_SECONDS	Positive Mode 2 update timeout, in seconds
GS_T_WAIT_SECONDS	Positive queue waiting-time threshold, in seconds
GS_EVENT_TIMEZONE	Time zone for legacy bookings; template: Asia/Hong_Kong
GS_STATE_DIR	Local directory for dispatch journal files
Communication endpoint	Shared service address and port; see G/runtime.env.example

Use G/runtime.env.example as the template. Supply and export the actual values, then run python ground_station.py from G. Both threshold fields are blank in the template. The 1-second GPS threshold in the tests checks time-boundary behavior.

Copy the template to G/runtime.env and fill it locally before running the following commands from the archive root. The application reads exported environment variables; it does not automatically load runtime.env.

```
set -a
./code/ground_station/runtime.env
set +a
python code/deployment_preflight.py
cd code/ground_station
python ground_station.py
```

The preflight command checks local configuration consistency without contacting Firebase or validating an installed phone application. Both the ground station and UAV must reach the configured broker over the deployment network; localhost is only suitable when that process shares the broker's host.

Verification logic: G/rescue_event_manager.py. Persistence and mission preparation: G/rescue_repository.py, G/active_event_queue.py and G/ground_station.py.

5 UAV Software and External Flight Stack

Mission reception and execution status

The ground station and UAV exchange missions and status over Wi-Fi. A mission contains event and execution identifiers, a waypoint sequence, flight altitude, hover duration and return settings. The bridge validates the mission, passes it to the flight program and reports waypoint arrivals and mission stages to the ground station.

The phone-record receiver saves uploads received through its HTTP interface. After a matching mission reports completion of all waypoints and requests landing, the receiver forwards stored records to the ground station. The ground station saves each record and returns an acknowledgement matching its identifier and content hash. The UAV then marks that transfer as complete. The recording program saves downward-facing video on the onboard computer.

Location within U	Purpose
catkin_ws/src/rescue_bridge/src/	Mission communication and execution programs
catkin_ws/src/rescue_bridge/src/ mission_commander.cpp	Waypoint and return-stage execution
drone_system/receiver/ phone_sos_receiver.py	Phone-record reception, storage and forwarding
drone_system/launcher/ cam_recorder.py	Onboard video recording
drone_system/launcher/ drone_console.py	Onboard program status and settings interface

Pinned external dependency

The flight stack uses Fast-Drone-250 from the original Drone repository at the commit below. Its 979 regular files were compared with the original local copy and matched. The external dependency retains its own licenses and documentation.

b3ac1591b63d15270c9856e7b664da0cf9d3ea48

Download and placement commands are in Flight environment setup. Place the Fast-Drone-250 workspace, rescue_bridge catkin workspace and drone_system directory in the configured onboard workspace. Set directory paths, camera indices, serial ports and sensor calibration for that installation.

The ROS environment uses Noetic and catkin. Build the external flight workspace before the rescue_bridge workspace. The default flight altitude in rescue_bridge.launch is the original project setting of 5 m. The 80 m above-ground setting in Section 6 belongs to the separate MATLAB simulation.

Phone-receiver settings are in U/drone_system/config/rescue_receiver.env.example. Set UAV_RESCUE_TOKEN when exposing the interface on the local network. Keep database credentials, runtime tokens and actual user records in their respective deployment environments.

6 Three-Mode MATLAB Terrain Simulation

The simulation uses terrain near Pak Tam Chung, Sai Kung. The three modes share a launch location and a target in the hills, using a planned route, pre-dispatch GPS history and a square spiral around the target, respectively. Each mission includes takeoff, cruise, target-area activity, return and landing.

Setting	Value
Random seed	20260926
Launch location	22.402° N, 114.322° E
Target location	22.40782761° N, 114.35687745° E
Target ground elevation	Approximately 177.44 m
Cruise altitude above ground	80 m, following the terrain
Speed limits	Horizontal: 15 m/s; vertical: 3 m/s
Waypoint hover duration	5 s
Mode 3 spiral	Initial side length: 30 m; increase by 30 m every two segments; stop at the first endpoint at least 200 m from the centre

Run commands

Set the MATLAB current folder to simulation and select the required entry point:

```
run_all('paper')
run_all('simulate', fullfile(pwd, '..', 'local-results', 'simulation-01'))
run_all('video', fullfile(pwd, '..', 'local-results', 'video-01'))
```

paper redraws the figure from saved trajectories into a new directory under simulation/regenerated. simulate recomputes all modes into the selected output directory. video renders the saved trajectories into its selected directory and requires ffmpeg. Each output directory must be new; simulation/output remains the saved input and result archive. The renderers use Event Booking, Quick Start and SOS.

Mode	Input waypoints	Target arrival / s	Landing complete / s
Mode 1	3	360.66	715.65
Mode 2	15	409.08	764.07
Mode 3	19	344.99	1008.53

Elevation comes from the Mapzen / Tilezen Skadi N22E114.hgt tile, with a 3601 × 3601 grid at 1 arc-second spacing and EGM96 elevations. Bilinear interpolation gives a 25 m plotting grid without increasing source resolution. Routes and GPS history are synthetic inputs generated with the fixed seed. Times start at simulated takeoff. Parameters, inputs and executed trajectories are in simulation/output/scenario_and_settings.json, the per-mode waypoint CSV files and the execution_trace.csv files.

Mode 2 timestamps use 1 m/s to construct the synthetic walking history; this is separate from the mobile booking estimate of 4 km/h. All 15 samples exist before dispatch. Mode 3 visits the centre plus 18 spiral endpoints, completes the entire route and then returns; reaching the target does not terminate the search early.

The archived MATLAB computation passed 30 assertions. A separate Python verification contains 53 checks covering terrain interpolation, 80 m ground clearance, speed limits, waypoint order, return and landing, and the saved figure-axis audit. Rechecking these outputs or redrawing the figure is separate from recomputing the MATLAB scenario.

7 Software Verification and Relay Records

The Android validation summary lists the Android release checks. The software-test table below describes the saved run in records/.

Verification ran on 28 September 2026 using macOS arm64, Python 3.12.14 and Node.js 24.19.0. Detailed results are in records/software.log and records/verification_summary.json.

The 30 September rerun is recorded separately in records/verification_20260930/. Selected component results are listed below. The run also passed three verification-output regression tests and 53 saved-simulation checks. The original protocol fixture from 9 September is now included at G/fixtures/capture_record_v2.json, so its six ground-station tests no longer depend on a file outside this repository. The archived software logs contain selected output for retained components and keep the original run dates.

Test group	Tests passed
Mobile application: Jest	229
Ground station	233
UAV phone-record receiver	44
UAV mission bridge	44
Video recorder and recording state	12
Cross-component protocols and state transitions	61

TypeScript type checking, ESLint, Python syntax, dependency-version checks, and compilation and execution of the C++ target-state tests also passed. New cases cover trip-time estimation, midnight rollover, recalculation after route edits, SOS contact steps, cancellation, stale requests, repeated scans and rejection of unverified events at dispatch preparation.

Local phone-record reception and forwarding

The relay bench sends a synthetic phone record containing an SOS location and GPS data through local HTTP to the UAV receiver. After the receiver saves it, the execution manager completes every waypoint and continuous hold, then persists the normal landing request before forwarding. The ground station validates and saves the received data, then sends an acknowledgement. The UAV uses that acknowledgement to complete the transfer.

Record numbers	Saved contents
01–03	Phone request, HTTP receipt and record saved by the UAV
04–05	Completed execution authorizing forwarding and outgoing record envelope
06–07	Phone record and envelope saved by the ground station
08–09	Ground-station acknowledgement and final UAV delivery state

The request_id, mission_id, record-content hash and envelope hash link these records for comparison. run_summary.json lists the result and test conditions. SHA256SUMS.txt contains the output-file checksums.

The software tests cover incorrect or missing acknowledgements, duplicate data and recovery after a restart. Source files and logs contain the test cases and results; Section 8 lists the demo videos and outdoor materials.

The 30 September relay records are in `experiments/phone_relay_20260930/`. The relay runs use synthetic uploads and a Mosquitto broker.

8 Demo Videos, Outdoor Materials, Sources and Integrity

Demo videos

Test component	Demo video
SOS search pattern and end-to-end pipeline	DEMO — SOS Search Pattern End to End Pipeline
Onboard console and failsafe interface	DEMO — Drone Console On Board Failsafe GUI
Real-world test footage	DEMO — Real-World Test Footage

See Demo videos and test materials for the video and material index.

Outdoor evidence

File in experiments/outdoor/	Contents
<code>outdoor_flight.mp4</code>	Original complete outdoor-test video
<code>ground_station.mp4</code>	Original ground-station operation video
<code>airframe.jpg</code>	UAV hardware photograph
<code>launch_area.png</code>	Original frame showing the launch area
<code>search_area.png</code>	Original frame showing the search area

The video files and images show the UAV, ground-station operation, launch site and search area. Numerical simulation trajectories and timestamps are stored in `simulation/output`.

Source provenance

The mobile application, ground station and UAV software originate from the FYP projects and subsequent local revisions. Upstream repository links, remote commit identifiers, local input files and checksums are recorded in `records/source_provenance.json`. The current implementation is recorded in `code/source_revision.json`. Remote commits and local revisions are identified separately.

The local input revision is WCNC-GPS-FRESHNESS-20260916. The current revision adds route-based trip-time estimation, operator verification before SOS event creation, and equal initial event priority across all three modes. Simulation source and data checksums are also recorded in `simulation/verification/source_manifest.json`.

Check archive integrity

```
python scripts/check_archive.py
```

This command reads `records/file_manifest.json` and checks each listed file's SHA-256 checksum and size. If source code, parameters or results are changed, save a new verification record. Preserve the original timestamps and identifiers of existing test outputs.

References

Ordnance Survey's Map Reading guide provides the walking-time reference. Mapzen / Tilezen Skadi provides the elevation tile. The three original FYP GitHub repositories identify the upstream projects. Complete links are in docs/Sources.txt.

9 Implementation and Evidence Index

This index follows the 30 September anonymous manuscript. M, G and U use the component abbreviations in Section 1. Paths identify source files, tests and saved results.

User records and event creation

Event Booking is implemented in M/services/eventBookingRecord.ts and M/pages/EventBookingPage.tsx.

M/__tests__/eventBookingRecord.test.ts checks the 4 km/h estimate, complete end timestamps and route edits.

G/rescue_event_manager.py detects overdue records and manages the contact steps;

G/test_rescue_event_manager.py checks the transitions.

Quick Start uses M/pages/AndroidQuickStartPage.tsx and M/services/persistentTracking.ts. The native TrackingService, TrackingStore and TrackingCore in M/android/app/src/main/java/com/fypproject/tracking/ collect and persist samples. G/quick_start_freshness.py uses the latest valid sample time.

code/integration_tests/test_quick_start_freshness_contract.py compiles the production Kotlin gate and exercises the mobile and ground-station contract, including 0.999 s, 1.000 s and 1.001 s boundary cases.

Configure GS_T_LOCATION_UPDATE_SECONDS for deployment.

SOS upload and dialing are implemented in M/pages/SosPage.tsx and checked by M/__tests__/SosPage.test.tsx.

G/rescue_event_manager.py enforces contact verification and explicit search confirmation.

G/test_sos_verification.py checks premature confirmation, cancellation, duplicate handling and unverified legacy events. The SOS instruction change is recorded in records/sos_operator_verification_20260929.json.

Route preparation and dispatch

G/ground_station.py and G/active_event_queue.py implement event selection, preparation, review and confirmed dispatch. G/sos_pattern.py generates the square spiral. G/test_ground_station_rescue_flow.py, G/test_active_event_queue.py and G/test_sos_pattern.py cover these behaviors.

code/integration_tests/test_flight_execution_contract.py checks the mission contract across components.

GS_T_WAIT_SECONDS controls the common waiting-time rule.

Mission execution and phone records

U/catkin_ws/src/rescue_bridge/src/ contains the mission communication program and mission_commander.cpp, which advances navigation goals. The test_*.py files there and U/catkin_ws/src/rescue_bridge/test/test_target_lifecycle.cpp test local logic. A ROS build requires the environment in docs/Flight_Environment_Setup.txt.

U/drone_system/receiver/phone_sos_receiver.py and G/rescue_record_protocol.py receive, persist, forward and acknowledge records. Their adjacent test files and

code/integration_tests/test_phone_uav_groundstation.py check integrity, retries and mission association.

experiments/phone_relay_20260928/ and experiments/phone_relay_20260930/ preserve concrete broker-test inputs and outputs.

Simulation and outdoor evidence

simulation/run_three_mode_simulation.m constructs the fixed-seed scenario and full trajectories.

simulation/output/ holds inputs, events, execution traces, mission_summary.csv and three_mode_study.mat.

simulation/verify_outputs.py checks numeric results against the terrain tile and spiral algorithm.

simulation/render_paper_terrain.m renders the manuscript's Figure 4 from saved data.

records/figure4_mode_names_20260929.json records the title update without changing trajectories.

U/drone_system/launcher/cam_recorder.py saves onboard video; adjacent recording tests cover storage and failure handling. experiments/outdoor/ contains the original videos, hardware photograph and site frames supporting the manuscript's outdoor observations. Images support operator inspection and post-flight review. Figure 3 in the current manuscript is the hardware image and Figure 5 contains the outdoor observations.