

Fault Page (Sample)

Fault	Fault or Indicator	Name/Description	Corrective Action
oC (flashing) Over Current	Over Current Indicator. Indicates excessive motor current.	1. Check motor for locked rotor or binding.	
LC dn LC Done	Load Chute Door Indicator. Indicates door open state.	1. Close the door.	
CPF18 and CPF19	Capacitor Fault. Excessive capacitor voltage ripple.	1. Reduce input line ripple. 2. Replace capacitor if fault persists.	
CPF20 and CPF21	Control Power Fault. Inadequate control supply.	1. Check voltage at H01.01.	
oPE02 Uv1	Output Phase Error. Phase loss on output. DC Bus Undervolt Fault. Bus voltage too low.	1. Check motor connections at U01.10. 1. Verify input AC voltage.	
bb	Base Block Indicator.	1. Reset system.	

Negative Test Page (Symptom Table)

Symptom	Corrective Action
Motor runs in reverse	Check phase wiring at output terminals.

Monitor Table

Monitor	Name	Function	Units
U02.01	Bus Voltage	Real-time monitor	V

Parameter Listing

Parameter	Parameter Name	Default	Range	Units	Page
H01.01	Bus Voltage Setup	0.00*	0.00–150.00	V	45
B01.18	Baud Rate	9600	0000–0001	bps	67
L02.05	Logic Type 00: Logic AND 01: Logic OR 0F: Not Used	—	00–1F	-	78
U01.10	Undervolt Threshold Setup	200.0	100.0–400.0	V	89
T05.12	Temperature Offset	0.0*	–200.0–0.0	°C	102

Negative Test Page (Prose)

To configure the system, set H01.01 to 5 and verify U01.10.

Then check the following parameters: B01.18, L02.05, T05.12.

These are just parameter references in running text.

Fault Page (Variable Action Column)

Fault	Fault or Indicator	Name/Description	Corrective Action
WL1	Wide Overtravel Limit One Indicator.	The wide overtravel limit one condition is active.	1. May not require corrective action.
SH2	Short fault.	1. Reset.	