CardPOS Europe

Ethernet Mifare Reader
ER750 / ER755

The ER750 series are Ethernet Mifare readers with built-in relay control & weather resistant ABS housing.

The RFID reader can also be assigned a reader ID number for multi-unit communication.

Internal LED and buzzer are also configurable.

Interface: Ethernat (Via CAT-5 / CAT-6)
DC Power: 7.5V -24V /125mA@12V
(regulated power is recommended)
Card Type: MIFARE® Classic (1K / 4K / 8K)
Frequency: 13.56MHz
Max. Read Distance:
Mifare (4Byte): Up to 7cm (MFA01A)
Mifare (7Byte): Up to 4cm
Audio/Visual: Internal LED and Buzzer
Relay: Built-in Relay
(5A 120VAC or 5A 24 VDC)
Temperature Range:
Operating Temp: -0°c ~ +60°c
Humidity: 10%~ 90% Non-condensing
Dimensions: 112.3(L) x 96(W) x 22(D) mm

Ordering information:
ER750: MIFARE UID Only
ER755: MIFARE Sector Data or MAD

Ethernet with PoE option

Built-in Relay Control

Weather Resistant

Configurable LED and Buzzer

Compact Size

ER750 series readers are compliant to ISO 1443A and have a read range of upto 7cm.

ER750 is Mifare UID Only,
ER755 is Mifare Sector Data or MAD

Applications:

Access Control

Time & Attendance

ID Authentication