

Week 4 – React Library

Dr Kiki Adhinugraha

Java Script Libraries/Frameworks

- Prototype Framework
- Dojo
- The Yahoo! UI Library
- jQuery
- Angular
- **React**
 - This is the JavaScript library we will be using in this subject
- Etc.

Why use a library?


- Why invent code when someone has already written it?
- Take inspiration from other coders.
- A well-written library can take away some of the headaches of writing cross-browser JavaScript

Prototype Framework

- Prototype extends JavaScript with a number of features.
- These features include
 - Defining classes and inheritance
 - Added custom methods to DOM element nodes
 - Simplifies the most common kinds of Ajax requests
 - Support for JSON encoding and decoding
 - Event delegation
- Due to time constraints we will not be able to go into these features.
However, you are welcome to look at the following web site to learn more.
 - <http://prototypejs.org/learn/>

React



- This is the JavaScript library that we will be using, hence we will go into this in more detail.
- This is a recent library developed by Facebook.
- It has rapidly become very popular.
- Many of the examples and slides for React come from the this excellent talk:
 - https://www.youtube.com/watch?v=m2fuO2wl_3c
- The examples have been updated to the latest version of React.



REACT

A JavaScript Library For
Building User Interfaces


Example of Interactive Frontend



React is declarative programming


- Traditional JavaScript libraries/frameworks take the imperative programming approach
 - Describe computation in terms of statements that change a program state.
- React takes a declarative programming approach
 - Express the logic of a computation without describing control flow.

Why is traditional imperative programming approach bad?




- In the above example suppose
 - Element $D = A + B + C$
 - Element $E = A - B - C$
- When using imperative programming approach you need **to manually specify how each element (D and E) is updated** when the user updates textboxes A, B C.
 - In this example the user need to write 6 separate event handlers.
 - Update D due to A change
 - Update D due to B change
 - Update D due to C change
 - Update E due to A change
 - Update E due to B change
 - Update E due to C change
 - Each event handler is a function which specifies exactly how the target element is updated given the updated input elements.

Why is traditional imperative programming approach bad?



- There can be much more complex scenarios than this.
- The programmer can easily forget to write an event handler or make a mistake when writing an event handler.
 - This will leave the web page in an inconsistent state.

React (declarative programming)



- In react you effectively just specify the formulas for computing elements D, E and F.
 - Element $D = A + B + C$
 - Element $E = A - B - C$
- When either A, B and C gets updated. The system will automatically re-render the entire web page! Which means elements D and E will automatically use the updated values in the A, B and C textboxes.

What are you kidding??

- Re-render the entire web page (DOM) on every single small update!
- That must be so so so slow!!!
- Actually not really.


Just update what has changed



- In this example the DOM (tree representing the web page) goes from state 1 to state 2 after the update.

Just update what has changed


- React figures out what has been updated and only renders the updated parts.
 - The way it does this is it constructs an updated virtual DOM
 - (state 2) and computes the difference between the updated virtual DOM (state 2) with the un-updated DOM (state 1).



React is very fast

- React is very fast because it just renders the updated parts.
- Two Big Ideas in React
 - Everything is a component: Component Hierarchy
 - JSX: Write code that resembles HTML

Component Hierarchy



Table

Row

Cell

Cell



Row

Cell

Cell

- Everything in React is a component.
- There is one root component
- There are other children components.
- One really powerful feature of react is that components can be reused for other applications.

Component Hierarchy (another example)



Why components are good?

- Composable
 - We can use components within each other.
- Reusable
 - Components can be reused for different applications.
- Maintainable
 - Easy to maintain since all the logic for the component are self contained
- Testable
 - We can test the correctness of each component individually.

JSX

- React allows you to program in a really cool and intuitive programming language.
- The code has HTML-like syntax.
- JSX is optional.
- You can program in raw JavaScript if you want.

JSX versus Javascript

- For example the following JSX

```
<div>Hello {this.props.name}</div>
```

- Looks like the following in JavaScript

```
React.createElement('div', null,  
  'Hello ', this.props.name)
```

Another JSX Example

```
class Square extends React.Component {  
  render() {  
    return (  
      <button className="square">  
        {this.props.value}  
      </button>  
    );  
  }  
}
```

Another JSX Example

(Notice the use of JavaScript functions)

```
class CartListComponent extends React.Component {  
  render() {  
    return (  
      <ul className="cartlist">  
        {this.props.list.map(item => (  
          <li>  
            <CartItemComponent key={item.id} item={item} />  
          </li>  
        ))}  
      </ul>  
    );  
  }  
}
```

Passing and Storing Data

- In react data can be pass from component to component using props



- You can think of props like parameters in a function
 - Calling function: `displayName(25, "Peter")`
 - Function prototype: `displayName(int age, string name)`

- Components can store data in itself using state

Component 1

state: counter

- You can think of state like local variables in a function
 - ```
Func() {
 int counter;

}
```

# React Properties

```
class ParentComponent extends React.Component {
 ...
 render() {
 return (
 <div>
 <ChildComponent firstname="Zhen" />
 </div>
);
 }
}
```

Parent Component



Child Component

Data is passed from parent to child via props

```
class ChildComponent extends React.Component {
 ...
 render() {
 return (<h1>Hello {this.props.firstname}</h1>);
 }
}
```



# Props are immutable

- The following is not allowed:

```
class ChildComponent extends
React.Component {
 ...
 doStuff
 () {
 this.props.firstname = "Peter";
 }
}
```

- The child component can not change the prop.

# Pass down properties via Spread Attributes

- Take the following example:
- `<Comp1 foo={x} bar={y} choo={z} />`
- In the above example we are passing down 3 properties to the Comp1 component. Another way to do this is via the spread attribute
- `var myProps = {};`  
`myProps.foo = x;`  
`myProps.bar = y;`  
`myProps.choo = z;`
- `<Comp1 {...myProps}>`
- **We can override property** (note order is important, later properties override earlier ones)
- `<Comp1 {...myProps} foo={h}/>`
- **We can also add an additional property like the following:**
- `<Comp1 {...myProps} doo={a}/>`


# State is Mutable

```
class ChildComponent extends React.Component {
 // Initializes the active state variable to false
 constructor(props) {
 super(props);
 this.state = {active: false};
 }
 // Sets the active state variable to true
 makeActive() {
 this.setState({active : true});
 }
 // Renders the component
 render() {
 // Uses the active state variable
 return (<input type="checkbox" checked={this.state.active} />);
 }
}
```

- Each component can have a state object. The state object can be mutated by the component.

# State can become props

```
class ParentComponent extends React.Component {
 ...
 render() {
 return (
 <div>
 <ChildComponent active={this.state.active} />
 </div>
);
 }
}
```



```
class ChildComponent extends React.Component {
 ...
 render() {
 // Uses the active state variable
 return (<input type="checkbox" checked={this.props.active} />);
 }
}
```

- The state object of a parent can be passed as a prop to a child.

# Pure React Components

| Standard React component                                                                                                                                                                             | Pure React component                                                                                                                                                                                                                                                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <pre>class Foo extends React.Component { render() {   return (     &lt;div&gt;       &lt;p&gt;{this.props.prop1}&lt;/p&gt;       &lt;p&gt;{this.props.prop2}&lt;/p&gt;     &lt;/div&gt;   ); }</pre> | <pre>// Version I: "Plain" JavaScript const Foo = function(props) { return (   &lt;div&gt;     &lt;p&gt;{props.prop1}&lt;/p&gt;     &lt;p&gt;{props.prop2}&lt;/p&gt;   &lt;/div&gt; ); };  // Version II: Using ES6 features const Foo = ({prop1, prop2}) =&gt; (   &lt;div&gt;     &lt;p&gt;{prop1}&lt;/p&gt;     &lt;p&gt;{prop2}&lt;/p&gt;   &lt;/div&gt; );</pre> |

- Pure react components is a convenience feature for writing simple components that only have a render function.
  - In the pure react component we do not need to explicitly specify the render function.
  - **In the pure react component everything is in the render function.**
- **The arguments of the function are the just of a list of props passed in from the parent component.**

# Examples

- We will show sequence of examples starting from the basic hello world and then adding more and more features on.

# Example 1 Basic Hello World

# The HTML file

```
<meta name="robots" content="noindex">
<html>
<head>
 <meta charset="utf-8">

 <script src="https://unpkg.com/react@latest/dist/react.js"></script>
 <script src="https://unpkg.com/react-dom@latest/dist/react-dom.js"></script>
 <script src="https://unpkg.com/babel-standalone@6.15.0/babel.min.js"></script>
</head>
<body>
 <div id="example"></div>
 <script src = labelapp.js type="text/babel">
</body>
</html>
```




# labelapp.js File

- The code below prints out Hello World! in the web page.

```
class LabelApp extends React.Component {
 render() {
 return (<h1> Hello World! </h1>);
 }
}
```

```
// This function renders the LabelApp component at the location of
// the element that has id example (see previous slide).
ReactDOM.render(
 <LabelApp />,
 document.getElementById('example')
);
```

# Output for Example 1




**Hello World!**

# Example 2 Using Properties

# Using properties


```
class LabelApp extends React.Component {
 render() {
 return (<h1> {this.props.message}</h1>);
 }
}
```

```
ReactDOM.render(
 <LabelApp message = "Hello Zhen!" />,
 document.getElementById('example')
);
```



- This example shows how to pass data from the root component to the LabelApp child component via the property **message**.

# Output for Example 2



**Hello Zhen!**

# Example 3 Using State

# Using State

```
class LabelApp extends React.Component {
 static defaultProps = {
 message: "Hello World!"
 }
 constructor(props) {
 super(props)
 this.state = {message: props.message, message2 : "Everyone"};
 }
 render() {
 return (<h1> {this.state.message} {this.state.message2} </h1>);
 }
}
```

Component LabelApp

state: message  
state: message2

```
ReactDOM.render(
 <LabelApp />,
 document.getElementById('example')
);
```

- In this example there are two state variables: **message** and **message2**
  - The **constructor** function initializes the two state variables.
- There is also a property called message (**this.props.message**)
  - The defaultProps assignment sets a default value for the message property. <#>
- The render function uses both of the state variables.

# Output for Example 3




**Hello World! Everyone**



# Example 4 Events

# Events Example

```
class LabelApp extends React.Component {
 static defaultProps = {
 message: "Hello World!"
 }
 constructor(props) {
 super(props)
 this.state = {message: props.message};
 }
 → onClick = () => {
 this.setState({message: "Hello Zhen!"});
 }
 render() {
 return (<h1 onClick ={this.onClick} > {this.state.message} </h1>);
 }
}
```




Event triggers function call

```
ReactDOM.render(
 <LabelApp />,
 document.getElementById('example')
);
```

- In the above example when the **Hello World** heading is clicked the message is replaced with **Hello Zhen!**
  - This is done by generating the **onClick** event which in turn calls the **onClick** function inside the LabelApp Component.


# Output for Example 4

- Before clicking on Hello World!



**Hello World!**


- After clicking on Hello World!



**Hello Zhen!**


# How Does Data Flow?

# Data flows from Parent to Child via Props




# Events Flow Up

- When an event occurs the event is passed to a high level component.
- Example events are:
  - Someone enters text into a textbox
  - Someone clicks a button



# Where to store state?

- State needs to be stored as high up as needed to be passed down to affected children.
- In the example below the price of every product and quantity
- placed in the cart need to be stored in the parent CartComponent because all of this information is needed to compute the total shown inside the CartComponent.



# The Table Example (Hierarchy of Components)





Table		
Row	Cell	Cell
Row	Cell	Cell



# The Table Example

- In this example, you can store the state within each cell component since the different components do not need to know each other's state.



# The Table Example


- In this example we need to generate a total for each row of the data.
- The row component is higher up the hierarchy and hence can not
- access the state of the cells.
- Hence the state for all the cells in this example need to be stored in the rows.

Table					
Row	Cell	Cell	Cell	Cell	Total
Row	Cell	Cell	Cell	Cell	Total
Row	Cell	Cell	Cell	Cell	Total

state is on rows

# The Table Example

- In the following example we need to store state in the root Table component since we need to sum across both rows and columns.



state is  
on table

# The Table Example (Table Component)

```
class Table extends React.Component {
 constructor(props) {
 super(props)
 const data = [];
 for (let r = 0; r < props.rows; r++) {
 data[r] = [];
 for (let c = 0; c < props.columns; c++) {
 data[r][c] = 0;
 }
 }
 this.state = {data: data};
 }
}
```

- In the above example we store the state in the 2D array inside the Table Component.
  - We will then pass all the state information to the children components via properties.
- We initialize all the array values to 0.

# The Table Example

## (Table Component Render Function)

```
render() {
 const rowArray = [];
 const columnTotals = [];
 for (let c = 0; c < this.props.columns; c++) {
 columnTotals[c] = 0;
 }
 for (let r = 0; r < this.props.rows; r++) {

 let total = 0;
 const childrenArray = [];
 for (var c = 0; c < this.props.columns; c++) {
 childrenArray.push(<Cell row={r} column={c}
 value={this.state.data[r][c]}
 onChange={this.onCellChange} />);
 total += this.state.data[r][c];
 columnTotals[c] += this.state.data[r][c];
 }
 childrenArray.push(<Total value={total} />);
 rowArray.push(<Row children = {childrenArray} />);
 }
}
```

... (continued on next page) ...

- We first create an array of rows and an array storing the totals for each column.
- **For each row** we first create all the cells that go inside the row.
  - We use properties to pass the row number, column number and value.
  - We also compute the row totals and column totals.
- We put the row total into the children array
- Next we create a row component and place the array of cells inside it.

# The Table Example (Table Component Continued)

```
render: function() {
 ... (continued from previous page) ...

 const totalsArrayComponent = []
 let finalTotal = 0;
 // Compute the column totals and put them into the final row which stores all the column
 // totals.
 for (let c = 0; c < this.props.columns; c++) {
 totalsArrayComponent[c] = <Total value={columnTotals[c]} />
 finalTotal += columnTotals[c];
 }
 totalsArrayComponent.push(<Total value= {finalTotal}/>);
 rowArray.push(totalsArrayComponent);
 // Finally return the array of rows enclosed inside the <table> HTML tag.
 return (<table> {rowArray} </table>)}

// Render Table component and pass in the properties columns and rows.
ReactDOM.render(
 <Table columns={4} rows = {5}/>,
 document.getElementById('example'));
)
```

# The Table Example (Row and Total Components)

```
class Row extends React.Component {
 render() {
 return (<tr>{this.props.children}</tr>);
 }
};
```

```
class Total extends React.Component {
 render() {
 return (<th>{this.props.value}</th>);
 }
};
```

# Table Example (Events)

```
class Cell extends React.Component {
 onChange = (e) => {
 this.props.onChange(
 this.props.row, this.props.column, parseInt(e.target.value)
);
 }
 render() {
 return (<td> <input type="number" value={this.props.value}
 onChange={this.onChange} /> </td>);
 }
};
class Table extends React.Component {

 onCellChange = (row, column, value) => {
 this.state.data[row][column] = value;
 this.setState({data: this.state.data});
 }
 Render() {

 childrenArray.push(<Cell row={r} column={c} value={this.state.data[r][c]}
 onChange={this.onCellChange} />);
 ...
 }
}
```

the new changed value passed in from the textbox via event e

Here is where you detect the change.  
The code then calls the onChange function


Here the onCellChange function changes the state of the 2D array to include the updated value.

Calls onCellChange function in child component via onChange prop




Lets Try it out!

# React Lifecycle (Initial Render)




- This shows the order by which functions are called in the React Lifecycle.
- **Mount** means initial render.
- The **constructor** function is usually used to initialize state variables to a specified value. You don't need to have a constructor.
- The **componentWillMount** function allows you to insert code that is run before the initial render (mount).
- The **componentDidMount** function allows you to insert code that is run after the initial render.

# React Lifecycle (change of state)



- The **shouldComponentUpdate** function allows you to insert code that decides whether the page needs to be rerendered as a result of a state change. So if you know no rerender is needed then you can use this function.
- The **componentWillUpdate** function allows you to insert code that is run just before the page gets rerendered as a result of state change.
- The **componentDidUpdate** function allows you to insert code that is run just after the page gets rerendered as a result of state change.

# React Lifecycle (property changes)



- The `componentWillReceiveProps` function is executed when the component will be receiving props. This function is executed on the first prop change but never on the first render.

# Conclusion

- There are many different JavaScript Libraries/Frameworks.
- The react library is particularly useful for complex web pages which many different event handlers.
- The declarative programming style of the react library simplifying the development complex web pages.