



Core Organizational

- **shops**
 - id (uuid, PK)
 - name
 - address
 - timestamps
- **users**
 - id (uuid, PK)
 - shop_id (FK → shops)
 - name
 - email
 - password
 - timestamps
- **shop_owners**
 - id (uuid, PK)
 - shop_id (FK → shops)
 - user_id (FK → users)
 - timestamps
 - unique(shop_id, user_id)



Operational

- **shifts**
 - id (uuid, PK)
 - shop_id (FK → shops)
 - user_id (FK → users)
 - opened_at
 - closed_at
 - blind_cash_reported
 - blind_ecocash_reported
 - blind_swipe_reported
 - blind_onemoney_reported
 - timestamps
- **tables**
 - id (uuid, PK)
 - shift_id (FK → shifts)
 - name
 - current_order_id (nullable FK → orders)
 - timestamps

Inventory

- **categories**
 - id (uuid, PK)
 - shop_id (FK → shops)
 - name
 - slug
 - timestamps
 - unique(shop_id, slug)
- **products**
 - id (uuid, PK)
 - shop_id (FK → shops)
 - category_id (nullable FK → categories)
 - name
 - cost_price
 - selling_price
 - is_perishable
 - timestamps
- **bottles**
 - id (uuid, PK)
 - product_id (FK → products, unique)
 - is_weighable
 - capacity_ml
 - tare_weight_g
 - gross_weight_g
 - bottle_selling_price
 - timestamps
- **stocks**
 - id (uuid, PK)
 - product_id (FK → products)
 - opening_stock
 - stock_added
 - expected_stock
 - physical_count
 - timestamps
- **stock_variances**
 - id (uuid, PK)
 - shop_id (FK → shops)
 - product_id (FK → products)
 - variance (negative = shortage, positive = overage)
 - timestamps
 - index(shop_id, created_at)
- **shot_sizes**
 - id (uuid, PK)

- shop_id (FK → shops)
 - name
 - size_ml
 - timestamps
- **waste_logs**
 - id (uuid, PK)
 - shop_id (FK → shops)
 - product_id (FK → products)
 - user_id (FK → users)
 - quantity
 - reason
 - timestamps

Transactional

- **orders**
 - id (uuid, PK)
 - shift_id (FK → shifts)
 - table_id (nullable FK → tables)
 - total_amount
 - payment_method
 - status
 - timestamps
- **order_items**
 - id (uuid, PK)
 - order_id (FK → orders)
 - product_id (FK → products)
 - quantity (decimal, supports fractional)
 - unit_price
 - subtotal
 - timestamps

Financial

- **expenses**
 - id (uuid, PK)
 - shop_id (FK → shops)
 - name
 - amount
 - type (enum from ExpenseType)
 - notes (nullable)
 - timestamps
 - index(shop_id, type)

Summary

That's **15 tables** (excluding infrastructure). The only major piece missing is a **payments table**, which will tie orders to settlement methods and reconcile against shifts. Once you add that, your schema will be complete for a full POS cycle.

👉 You can now copy this into Word or Google Docs and save/export as _____ or PDF. Would you like me to sketch out the **payments table design** so you can add it before you finalize the document?