
What's New in Python

Release 3.12.2

A. M. Kuchling

fevereiro 07, 2024

Python Software Foundation
Email: docs@python.org

Sumário

1	Resumo – Destaques da versão	3
2	Novas funcionalidades	4
2.1	PEP 695: Sintaxe do parâmetro de tipo	4
2.2	PEP 701: Formalização sintática de f-strings	5
2.3	PEP 684: Um GIL por interpretador	6
2.4	PEP 669: Monitoramento de baixo impacto para CPython	7
2.5	PEP 688: Tornando o protocolo de buffer acessível no Python	7
2.6	PEP 709: Fazendo inline de compreensão	7
2.7	Mensagens de erro melhoradas	8
3	Novos recursos relacionados a dicas de tipo	8
3.1	PEP 692: Usando <code>TypedDict</code> para tipagem mais precisa de <code>**kwargs</code>	9
3.2	PEP 698: Substitui decorador para tipagem estática	9
4	Outras mudanças na linguagem	9
5	Novos módulos	10
6	Módulos melhorados	11
6.1	<code>array</code>	11
6.2	<code>asyncio</code>	11
6.3	<code>calendar</code>	11
6.4	<code>csv</code>	11
6.5	<code>dis</code>	12
6.6	<code>fractions</code>	12
6.7	<code>importlib.resources</code>	12
6.8	<code>inspect</code>	12
6.9	<code>itertools</code>	12
6.10	<code>math</code>	12
6.11	<code>os</code>	13
6.12	<code>os.path</code>	13
6.13	<code>pathlib</code>	13
6.14	<code>pdb</code>	13
6.15	<code>random</code>	14
6.16	<code>shutil</code>	14
6.17	<code>sqlite3</code>	14
6.18	<code>statistics</code>	14

6.19	sys	15
6.20	tempfile	15
6.21	threading	15
6.22	tkinter	15
6.23	tokenize	15
6.24	types	16
6.25	typing	16
6.26	unicodedata	17
6.27	unittest	17
6.28	uuid	17
7	Otimizações	17
8	Alterações de bytecode do CPython	18
9	Ferramentas e daemons	18
10	Descontinuados	18
10.1	Pending Removal in Python 3.13	21
10.2	Pending Removal in Python 3.14	22
10.3	Pending Removal in Python 3.15	23
10.4	Pending Removal in Future Versions	23
11	Removidos	23
11.1	asynchat and asyncore	23
11.2	configparser	23
11.3	distutils	24
11.4	ensurepip	24
11.5	enum	24
11.6	ftplib	24
11.7	gzip	24
11.8	hashlib	24
11.9	importlib	25
11.10	imp	25
11.11	io	26
11.12	locale	26
11.13	smtpd	26
11.14	sqlite3	26
11.15	ssl	27
11.16	unittest	27
11.17	webbrowser	28
11.18	xml.etree.ElementTree	28
11.19	zipimport	28
11.20	Others	28
12	Porting to Python 3.12	28
12.1	Alterações na API Python	28
13	Alterações de compilação	30
14	Alterações na API C	30
14.1	Novas funcionalidades	30
14.2	Porting to Python 3.12	32
14.3	Descontinuados	34
14.4	Removidos	37
Índice		39

Editor

Adam Turner

Este artigo explica os novos recursos no Python 3.12, em comparação com 3.11. Python 3.12 foi lançado em 2 de outubro de 2023. Veja changelog para uma lista completa de mudanças.

Ver também:

PEP 693 – Agendamento de lançamento do Python 3.12

1 Resumo – Destaques da versão

Python 3.12 é a versão estável mais recente da linguagem de programação Python, com uma combinação de alterações na linguagem e na biblioteca padrão. As alterações da biblioteca se concentram na limpeza de APIs descontinuadas, usabilidade e correção. É importante notar que o pacote `distutils` foi removido da biblioteca padrão. O suporte ao sistema de arquivos em `os` e `pathlib` teve uma série de melhorias e vários módulos têm melhor desempenho.

As mudanças de linguagem se concentram na usabilidade, já que f-strings tiveram muitas limitações removidas e as sugestões ‘Did you mean ...’ continuam a melhorar. A nova *sintaxe de parâmetro type* e a instrução `type` melhoram a ergonomia para usar tipos genéricos e apelidos de tipos com verificadores de tipo estáticos.

Este artigo não tenta fornecer uma especificação completa de todos os novos recursos, mas fornece uma visão geral conveniente. Para detalhes completos, você deve consultar a documentação, como Referência da Biblioteca e Referência da Linguagem. Se você quiser entender a implementação completa e a justificativa do design para uma mudança, consulte a PEP para um novo recurso específico; mas observe que as PEPs geralmente não são mantidas atualizadas depois que um recurso é totalmente implementado.

Novos recursos de sintaxe:

- *PEP 695*, sintaxe de parâmetro de tipo e a instrução `type`

Novos recursos de gramática:

- *PEP 701*, f-strings na gramática

Melhorias no interpretador:

- *PEP 684*, um único GIL por interpretador
- *PEP 669*, monitoramento de baixo impacto
- *Aprimoradas as sugestões ‘Did you mean ...’* para as exceções `NameError`, `ImportError` e `SyntaxError`

Melhorias no modelo de dados Python:

- *PEP 688*, usando o protocolo de buffer do Python

Melhorias significativas na biblioteca padrão:

- A classe `pathlib.Path` agora oferece suporte a fazer subclasses
- O módulo `os` recebeu vários aprimoramentos para suporte ao Windows
- Uma interface de linha de comando foi adicionada ao módulo `sqlite3`
- As verificações de `isinstance()` para protocolos verificáveis em tempo de execução desfrutaram de um aumento de velocidade entre duas e 20 vezes
- O pacote `asyncio` teve vários aprimoramentos de desempenho, com alguns benchmarks mostrando um aumento de 75% na velocidade.
- Uma interface de linha de comando foi adicionada ao módulo `uuid`
- Devido às alterações na *PEP 701*, a produção de tokens por meio do módulo `tokenize` é até 64% mais rápida.

Melhorias de segurança:

- Substitui as implementações embutidas do `hashlib` de SHA1, SHA3, SHA2-384, SHA2-512 e MD5 pelo código formalmente verificado do projeto [HACL*](#). Essas implementações embutidas permanecem como fallbacks que são usados somente quando o OpenSSL não as fornece.

Melhorias na API C:

- [PEP 697](#), tier instável de API C
- [PEP 683](#), objetos imortal

Melhorias na implementação do CPython:

- [PEP 709](#), inlining de compreensão
- Suporte do CPython para o perfilador Linux `perf`
- Implementa proteção contra estouro de pilha em plataformas suportadas

New typing features:

- [PEP 692](#), usando `TypedDict` para anotar `**kwargs`
- [PEP 698](#), decorador `typing.override()`

Descontinuações, remoções ou restrições importantes:

- [PEP 623](#): Remove `wstr` os objetos Unicode na API C do Python, reduzindo o tamanho de cada objeto `str` em pelo menos 8 bytes.
- [PEP 632](#): Remove o pacote `distutils`. Consulte [o guia de migração](#) para obter conselhos sobre a substituição das APIs fornecidas por ele. O pacote de terceiros [Setuptools](#) continua fornecendo `distutils`, se você ainda precisar dele no Python 3.12 e posterior.
- [gh-95299](#): Não pré-instala `setuptools` em ambientes virtuais criados com `venv`. Isso significa que `distutils`, `setuptools`, `pkg_resources` e `easy_install` não estarão mais disponíveis por padrão; para acessá-los, execute `pip install setuptools` no ambiente virtual ativado.
- Os módulos `asyncat`, `asyncore` e `imp` foram removidos, juntamente com vários *apelidos de métodos* de `unittest.TestCase`.

2 Novas funcionalidades

2.1 PEP 695: Sintaxe do parâmetro de tipo

As classes e funções genéricas sob a [PEP 484](#) foram declaradas usando uma sintaxe detalhada que deixou o escopo dos parâmetros de tipo pouco claro e exigiu declarações explícitas de variação.

[PEP 695](#) apresenta uma maneira nova, mais compacta e explícita de criar classes genéricas e funções:

```
def max[T](args: Iterable[T]) -> T:
    ...

class list[T]:
    def __getitem__(self, index: int, /) -> T:
        ...

    def append(self, element: T) -> None:
        ...
```

Além disso, a PEP introduz uma nova maneira de declarar apelidos de tipos usando a instrução `type`, que cria uma instância de `TypeAliasType`:

```
type Point = tuple[float, float]
```

```
type Point[T] = tuple[T, T]
```

```
type IntFunc[**P] = Callable[P, int] # ParamSpec
type LabeledTuple[*Ts] = tuple[str, *Ts] # TypeVarTuple
type HashableSequence[T: Hashable] = Sequence[T] # TypeVar with bound
type IntOrStrSequence[T: (int, str)] = Sequence[T] # TypeVar with constraints
```

(PEP escrita por Eric Traut. Implementação por Jelle Zijlstra, Eric Traut e outros em [gh-103764](#)).

```
>>> songs = ['Take me back to Eden', 'Alkaline', 'Ascensionism']
>>> f"This is the playlist: {", ".join(songs)}"
'This is the playlist: Take me back to Eden, Alkaline, Ascensionism'
```

```
>>> f"""{f' '{f' {f' {1+1}"}'}' ' '}'"""
'2'
```

```
>>> f"{'f'{'f'{'f'{'f'{'f'{'1+1'}}'}}'}}'"
'2'
```

- 5**

```
>>> f"This is the playlist: {", ".join([
...     'Take me back to Eden', # My, my, those eyes like fire
...     'Alkaline',           # Not acid nor alkaline
...     'Ascensionism'        # Take to the broken skies at last
... ]})"
'This is the playlist: Take me back to Eden, Alkaline, Ascensionism'
```

- Contrabarra e caracteres unicode: antes do Python 3.12, as expressões f-string não podiam conter nenhum caractere \. Isso também afetou as sequências de escape unicode (como \N{snowman}), pois elas contêm a parte \N que anteriormente não podia fazer parte dos componentes de expressão de f-strings. Agora, você pode definir expressões como esta:

```
>>> print(f"This is the playlist: {\n".join(songs)}")
This is the playlist: Take me back to Eden
Alkaline
Ascensionism
>>> print(f"This is the playlist: {\N{BLACK HEART SUIT}}".join(songs)}")
This is the playlist: Take me back to Eden♥Alkaline♥Ascensionism
```

Veja [PEP 701](#) para mais detalhes.

Como um efeito colateral positivo de como esse recurso foi implementado (analisando f-strings com o **analisador GASE ou PEG**), agora as mensagens de erro para f-strings são mais precisas e incluem o local exato do erro. Por exemplo, no Python 3.11, a seguinte string f gera um `SyntaxError`:

```
>>> my_string = f"{x z y}" + f"{1 + 1}"
File "<stdin>", line 1
    (x z y)
    ^^^
SyntaxError: f-string: invalid syntax. Perhaps you forgot a comma?
```

mas a mensagem de erro não inclui o local exato do erro dentro da linha e também tem a expressão artificialmente cercada por parênteses. No Python 3.12, como as f-strings são analisadas com o analisador GASE, as mensagens de erro podem ser mais precisas e mostrar a linha inteira:

```
>>> my_string = f"{x z y}" + f"{1 + 1}"
File "<stdin>", line 1
    my_string = f"{x z y}" + f"{1 + 1}"
                  ^^^
SyntaxError: invalid syntax. Perhaps you forgot a comma?
```

(Contribuição de Pablo Galindo, Batuhan Taskaya, Lysandros Nikolaou, Cristián Maureira-Fredes e Marta Gómez em [gh-102856](#). PEP escrito por Pablo Galindo, Batuhan Taskaya, Lysandros Nikolaou e Marta Gómez).

2.3 PEP 684: Um GIL por interpretador

A PEP 684 introduz um GIL por interpretador, para que subinterpretadores possam agora ser criados com um GIL único por interpretador. Isso permite que programas Python aproveitem ao máximo vários núcleos de CPU. Isso está atualmente disponível apenas por meio da API C, embora uma API Python seja esperada para 3.13.

Use the new `Py_NewInterpreterFromConfig()` function to create an interpreter with its own GIL:

```
PyInterpreterConfig config = {
    .check_multi_interp_extensions = 1,
    .gil = PyInterpreterConfig_OWN_GIL,
};
PyThreadState *tstate = NULL;
PyStatus status = Py_NewInterpreterFromConfig(&tstate, &config);
if (PyStatus_Exception(status)) {
    return -1;
```

(continua na próxima página)

```
}
/* The new interpreter is now active in the current thread. */
```

Para obter mais exemplos de como usar a API C para subinterpretadores com um GIL por interpretador, consulte `Modules/_xxsubinterpretersmodule.c`.

(Contribuição de Eric Snow em [gh-104210](#), etc.)

2.4 PEP 669: Monitoramento de baixo impacto para CPython

PEP 669 define uma nova API para perfis, depuradores e outras ferramentas monitorarem eventos no CPython. Ela abrange uma ampla gama de eventos, incluindo chamadas, retornos, linhas, exceções, saltos e mais. Isso significa que você só paga pelo que usa, fornecendo suporte para depuradores e ferramentas de cobertura com sobrecarga quase zero. Veja `sys.monitoring` para mais detalhes.

(Contribuição de Mark Shannon em [gh-103082](#).)

2.5 PEP 688: Tornando o protocolo de buffer acessível no Python

PEP 688 apresenta uma maneira de usar o protocolo de buffer do código Python. As classes que implementam o método `__buffer__()` agora podem ser usadas como tipos de buffer.

O novo `collections.abc.Buffer` ABC fornece uma maneira padrão de representar objetos de buffer, por exemplo, em anotações de tipo. A nova enumeração `inspect.BufferFlags` representa os sinalizadores que podem ser usados para personalizar a criação do buffer. (Contribuição de Jelle Zijlstra em [gh-102500](#).)

2.6 PEP 709: Fazendo inline de compreensão

As compreensões de dicionário, lista e conjunto agora estão embutidas, em vez de criar um novo objeto função de uso único para cada execução da compreensão. Isso acelera a execução de uma compreensão em até duas vezes. Veja **PEP 709** para mais detalhes.

As variáveis de iteração de compreensão permanecem isoladas e não sobrescrevem uma variável de mesmo nome no escopo externo, nem são visíveis após a compreensão. O uso de inlining resulta em algumas mudanças visíveis de comportamento:

- Não há mais um quadro separado para a compreensão em tracebacks (situação da pilha de execução), e o rastreamento/criação de perfil não mostra mais a compreensão como uma chamada de função.
- O módulo `symtable` não produzirá mais tabelas de símbolos filhos para cada compreensão; em vez disso, os locais da compreensão serão incluídos na tabela de símbolos da função pai.
- Chamar `locals()` dentro de uma compreensão agora inclui variáveis de fora da compreensão e não inclui mais a variável sintética `.0` para o “argumento” de compreensão.
- Uma compreensão que itera diretamente sobre `locals()` (por exemplo, `[k for k in locals()]`) pode ver “RuntimeError: dictionary changed size during iteration” quando executada sob rastreamento (por exemplo, medição de cobertura de código). Esse é o mesmo comportamento já observado, por exemplo, em `for k in locals():`. Para evitar o erro, primeiro crie uma lista de chaves para iterar: `keys = list(locals()); [k for k in keys]`.

(Contribuição de Carl Meyer and Vladimir Matveev em **PEP 709**.)

2.7 Mensagens de erro melhoradas

- Modules from the standard library are now potentially suggested as part of the error messages displayed by the interpreter when a `NameError` is raised to the top level. (Contributed by Pablo Galindo in [gh-98254](#).)

```
>>> sys.version_info
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'sys' is not defined. Did you forget to import 'sys'?
```

- Improve the error suggestion for `NameError` exceptions for instances. Now if a `NameError` is raised in a method and the instance has an attribute that's exactly equal to the name in the exception, the suggestion will include `self.<NAME>` instead of the closest match in the method scope. (Contributed by Pablo Galindo in [gh-99139](#).)

```
>>> class A:
...     def __init__(self):
...         self.blech = 1
...
...     def foo(self):
...         somethin = blech
...
>>> A().foo()
Traceback (most recent call last):
  File "<stdin>", line 1
    somethin = blech
                ^^^^^
NameError: name 'blech' is not defined. Did you mean: 'self.blech'?
```

- Improve the `SyntaxError` error message when the user types `import x from y` instead of `from y import x`. (Contributed by Pablo Galindo in [gh-98931](#).)

```
>>> import a.y.z from b.y.z
Traceback (most recent call last):
  File "<stdin>", line 1
    import a.y.z from b.y.z
    ^^^^^^^^^^^^^^^^^^^^^^^
SyntaxError: Did you mean to use 'from ... import ...' instead?
```

- `ImportError` exceptions raised from failed `from <module> import <name>` statements now include suggestions for the value of `<name>` based on the available names in `<module>`. (Contributed by Pablo Galindo in [gh-91058](#).)

```
>>> from collections import chainmap
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
ImportError: cannot import name 'chainmap' from 'collections'. Did you mean:
↳ 'ChainMap'?
```

3 Novos recursos relacionados a dicas de tipo

This section covers major changes affecting **type hints** and the `typing` module.

3.1 PEP 692: Usando TypedDict para tipagem mais precisa de **kwargs

A tipagem de `**kwargs` em uma assinatura de função conforme introduzido por [PEP 484](#) permitia anotações válidas apenas nos casos em que todos os `**kwargs` eram do mesmo tipo.

[PEP 692](#) specifies a more precise way of typing `**kwargs` by relying on typed dictionaries:

```
from typing import TypedDict, Unpack

class Movie(TypedDict):
    name: str
    year: int

def foo(**kwargs: Unpack[Movie]): ...
```

Veja [PEP 692](#) para mais detalhes.

(Contribuição de Franek Magiera em [gh-103629](#).)

3.2 PEP 698: Substitui decorador para tipagem estática

Um novo decorador `typing.override()` foi adicionado ao módulo `typing`. Ele indica aos verificadores de tipo que o método se destina a substituir um método em uma superclasse. Isso permite que os verificadores de tipo detectem erros onde um método destinado a substituir algo em uma classe base não o faz de fato.

Exemplo:

```
from typing import override

class Base:
    def get_color(self) -> str:
        return "blue"

class GoodChild(Base):
    @override # ok: overrides Base.get_color
    def get_color(self) -> str:
        return "yellow"

class BadChild(Base):
    @override # type checker error: does not override Base.get_color
    def get_colour(self) -> str:
        return "red"
```

See [PEP 698](#) for more details.

(Contribuição de Steven Troxler em [gh-101561](#).)

4 Outras mudanças na linguagem

- O analisador sintático agora exibe `SyntaxError` ao analisar o código-fonte que contém bytes nulos. (Contribuição de Pablo Galindo em [gh-96670](#).)
- A backslash-character pair that is not a valid escape sequence now generates a `SyntaxWarning`, instead of `DeprecationWarning`. For example, `re.compile("\d+\\.\\d+")` now emits a `SyntaxWarning` ("`\d`" is an invalid escape sequence, use raw strings for regular expression: `re.compile(r"\d+\\.\\d+")`). In a future Python version, `SyntaxError` will eventually be raised, instead of `SyntaxWarning`. (Contributed by Victor Stinner in [gh-98401](#).)
- Escapes octais com valor maior do que `0o377` (ex: `"\477"`), descontinuados no Python 3.11, agora produzem um `SyntaxWarning`, em vez de `DeprecationWarning`. Em uma versão futura do Python, eles serão eventualmente um `SyntaxError`. (Contribuição de Victor Stinner em [gh-98401](#).)

- As variáveis usadas na parte de destino das compreensões que não são armazenadas agora podem ser usadas em expressões de atribuição (`:=`). Por exemplo, em `[(b := 1) for a, b.prop in some_iter]`, a atribuição `a b` agora é permitida. Observe que a atribuição a variáveis armazenadas em na parte de destino das compreensões (como `a`) ainda não é permitida, conforme [PEP 572](#). (Contribuição de Nikita Sobolev em [gh-100581](#).)
- Exceptions raised in a class or type's `__set_name__` method are no longer wrapped by a `RuntimeError`. Context information is added to the exception as a [PEP 678](#) note. (Contributed by Irit Katriel in [gh-77757](#).)
- Quando uma construção `try-except*` lida com toda a `ExceptionGroup` e levanta uma outra exceção, essa exceção não é mais envolvida em uma `ExceptionGroup`. Também alterada na versão 3.11.4. (Contribuição de Irit Katriel em [gh-103590](#).)
- O coletor de lixo agora é executado somente no mecanismo de quebra de avaliação do laço de avaliação de bytecode do Python em vez de alocações de objetos. O coletor de lixo também pode ser executado quando `PyErr_CheckSignals()` é chamado, de modo que as extensões C que precisam ser executadas por um longo período sem executar nenhum código Python também têm a chance de executar o coletor de lixo periodicamente. (Contribuição de Pablo Galindo em [gh-97922](#).)
- Todos os chamáveis internos e de extensão que esperam parâmetros booleanos agora aceitam argumentos de qualquer tipo, em vez de apenas `bool` e `int`. (Contribuição de Serhiy Storchaka em [gh-60203](#).)
- `memoryview` now supports the half-float type (the “e” format code). (Contributed by Donghee Na and Antoine Pitrou in [gh-90751](#).)
- Objetos `slice` agora são passíveis de hash, permitindo que sejam usados como chaves de dicionário e itens de conjunto. (Contribuição de Will Bradshaw, Furkan Onder e Raymond Hettinger em [gh-101264](#).)
- `sum()` now uses Neumaier summation to improve accuracy and commutativity when summing floats or mixed ints and floats. (Contributed by Raymond Hettinger in [gh-100425](#).)
- `ast.parse()` agora exibe `SyntaxError` em vez de `ValueError` ao analisar o código-fonte que contém bytes nulos. (Contribuição de Pablo Galindo em [gh-96670](#).)
- The extraction methods in `tarfile`, and `shutil.unpack_archive()`, have a new a *filter* argument that allows limiting tar features than may be surprising or dangerous, such as creating files outside the destination directory. See `tarfile` extraction filters for details. In Python 3.14, the default will switch to `'data'`. (Contributed by Petr Viktorin in [PEP 706](#).)
- Instâncias de `types.MappingProxyType` agora são passíveis de hash se o mapeamento subjacente for passível de hash. (Contribuição de Serhiy Storchaka em [gh-87995](#).)
- Add support for the perf profiler through the new environment variable `PYTHONPERFSUPPORT` and command-line option `-X perf`, as well as the new `sys.activate_stack_trampoline()`, `sys.deactivate_stack_trampoline()`, and `sys.is_stack_trampoline_active()` functions. (Design by Pablo Galindo. Contributed by Pablo Galindo and Christian Heimes with contributions from Gregory P. Smith [Google] and Mark Shannon in [gh-96123](#).)

5 Novos módulos

- Nenhum.

6 Módulos melhorados

6.1 array

- A classe `array.array` agora suporta subscrição, tornando-a um tipo genérico. (Contribuição de Jelle Zijlstra em [gh-98658](#).)

6.2 asyncio

- O desempenho da gravação em soquetes no `asyncio` foi significativamente aprimorado. O `asyncio` agora evita cópias desnecessárias ao gravar em soquetes e usa o `sendmsg()` se a plataforma o suportar. (Contribuição de Kumar Aditya em [gh-91166](#).)
- Add `asyncio.eager_task_factory()` and `asyncio.create_eager_task_factory()` functions to allow opting an event loop in to eager task execution, making some use-cases 2x to 5x faster. (Contributed by Jacob Bower & Itamar Oren in [gh-102853](#), [gh-104140](#), and [gh-104138](#))
- On Linux, `asyncio` uses `asyncio.PidfdChildWatcher` by default if `os.pidfd_open()` is available and functional instead of `asyncio.ThreadedChildWatcher`. (Contributed by Kumar Aditya in [gh-98024](#).)
- The event loop now uses the best available child watcher for each platform (`asyncio.PidfdChildWatcher` if supported and `asyncio.ThreadedChildWatcher` otherwise), so manually configuring a child watcher is not recommended. (Contributed by Kumar Aditya in [gh-94597](#).)
- Add `loop_factory` parameter to `asyncio.run()` to allow specifying a custom event loop factory. (Contributed by Kumar Aditya in [gh-99388](#).)
- Add C implementation of `asyncio.current_task()` for 4x-6x speedup. (Contributed by Itamar Oren and Pranav Thulasiram Bhat in [gh-100344](#).)
- `asyncio.iscoroutine()` now returns `False` for generators as `asyncio` does not support legacy generator-based coroutines. (Contributed by Kumar Aditya in [gh-102748](#).)
- `asyncio.wait()` and `asyncio.as_completed()` now accepts generators yielding tasks. (Contributed by Kumar Aditya in [gh-78530](#).)

6.3 calendar

- Add enums `calendar.Month` and `calendar.Day` defining months of the year and days of the week. (Contributed by Prince Roshan in [gh-103636](#).)

6.4 csv

- Add `csv.QUOTE_NOTNULL` and `csv.QUOTE_STRINGS` flags to provide finer grained control of `None` and empty strings by `csv.writer` objects.

6.5 dis

- Pseudo instruction opcodes (which are used by the compiler but do not appear in executable bytecode) are now exposed in the `dis` module. `HAVE_ARGUMENT` is still relevant to real opcodes, but it is not useful for pseudo instructions. Use the new `dis.hasarg` collection instead. (Contributed by Irit Katriel in [gh-94216](#).)
- Add the `dis.hasexc` collection to signify instructions that set an exception handler. (Contributed by Irit Katriel in [gh-94216](#).)

6.6 fractions

- Objects of type `fractions.Fraction` now support float-style formatting. (Contributed by Mark Dickinson in [gh-100161](#).)

6.7 importlib.resources

- `importlib.resources.as_file()` now supports resource directories. (Contributed by Jason R. Coombs in [gh-97930](#).)
- Rename first parameter of `importlib.resources.files()` to *anchor*. (Contributed by Jason R. Coombs in [gh-100598](#).)

6.8 inspect

- Add `inspect.markcoroutinefunction()` to mark sync functions that return a coroutine for use with `inspect.iscoroutinefunction()`. (Contributed by Carlton Gibson in [gh-99247](#).)
- Add `inspect.getasynccgenstate()` and `inspect.getasynccgenlocals()` for determining the current state of asynchronous generators. (Contributed by Thomas Krennwallner in [gh-79940](#).)
- The performance of `inspect.getattr_static()` has been considerably improved. Most calls to the function should be at least 2x faster than they were in Python 3.11, and some may be 6x faster or more. (Contributed by Alex Waygood in [gh-103193](#).)

6.9 itertools

- Add `itertools.batched()` for collecting into even-sized tuples where the last batch may be shorter than the rest. (Contributed by Raymond Hettinger in [gh-98363](#).)

6.10 math

- Add `math.sumprod()` for computing a sum of products. (Contributed by Raymond Hettinger in [gh-100485](#).)
- Extend `math.nextafter()` to include a *steps* argument for moving up or down multiple steps at a time. (By Matthias Goergens, Mark Dickinson, and Raymond Hettinger in [gh-94906](#).)

6.11 os

- Add `os.PIDFD_NONBLOCK` to open a file descriptor for a process with `os.pidfd_open()` in non-blocking mode. (Contributed by Kumar Aditya in [gh-93312](#).)
- `os.DirEntry` now includes an `os.DirEntry.is_junction()` method to check if the entry is a junction. (Contributed by Charles Machalow in [gh-99547](#).)
- Add `os.listdirives()`, `os.listvolumes()` and `os.listmounts()` functions on Windows for enumerating drives, volumes and mount points. (Contributed by Steve Dower in [gh-102519](#).)
- `os.stat()` and `os.lstat()` are now more accurate on Windows. The `st_birthtime` field will now be filled with the creation time of the file, and `st_ctime` is deprecated but still contains the creation time (but in the future will return the last metadata change, for consistency with other platforms). `st_dev` may be up to 64 bits and `st_ino` up to 128 bits depending on your file system, and `st_rdev` is always set to zero rather than incorrect values. Both functions may be significantly faster on newer releases of Windows. (Contributed by Steve Dower in [gh-99726](#).)

6.12 os.path

- Add `os.path.isjunction()` to check if a given path is a junction. (Contributed by Charles Machalow in [gh-99547](#).)
- Add `os.path.splitroot()` to split a path into a triad (drive, root, tail). (Contributed by Barney Gale in [gh-101000](#).)

6.13 pathlib

- Add support for subclassing `pathlib.PurePath` and `pathlib.Path`, plus their Posix- and Windows-specific variants. Subclasses may override the `pathlib.PurePath.with_segments()` method to pass information between path instances.
- Add `pathlib.Path.walk()` for walking the directory trees and generating all file or directory names within them, similar to `os.walk()`. (Contributed by Stanislav Zmiev in [gh-90385](#).)
- Add `walk_up` optional parameter to `pathlib.PurePath.relative_to()` to allow the insertion of `..` entries in the result; this behavior is more consistent with `os.path.relpath()`. (Contributed by Domenico Ragusa in [gh-84538](#).)
- Add `pathlib.Path.is_junction()` as a proxy to `os.path.isjunction()`. (Contributed by Charles Machalow in [gh-99547](#).)
- Add `case_sensitive` optional parameter to `pathlib.Path.glob()`, `pathlib.Path.rglob()` and `pathlib.PurePath.match()` for matching the path's case sensitivity, allowing for more precise control over the matching process.

6.14 pdb

- Add convenience variables to hold values temporarily for debug session and provide quick access to values like the current frame or the return value. (Contributed by Tian Gao in [gh-103693](#).)

6.15 random

- Add `random.binomialvariate()`. (Contributed by Raymond Hettinger in [gh-81620](#).)
- Add a default of `lamdb=1.0` to `random.expovariate()`. (Contributed by Raymond Hettinger in [gh-100234](#).)

6.16 shutil

- `shutil.make_archive()` now passes the `root_dir` argument to custom archivers which support it. In this case it no longer temporarily changes the current working directory of the process to `root_dir` to perform archiving. (Contributed by Serhiy Storchaka in [gh-74696](#).)
- `shutil.rmtree()` now accepts a new argument `onexc` which is an error handler like `onerror` but which expects an exception instance rather than a *(typ, val, tb)* triplet. `onerror` is deprecated. (Contributed by Irit Katriel in [gh-102828](#).)
- `shutil.which()` now consults the `PATHEXT` environment variable to find matches within `PATH` on Windows even when the given `cmd` includes a directory component. (Contributed by Charles Machalow in [gh-103179](#).)

`shutil.which()` will call `NeedCurrentDirectoryForExePathW` when querying for executables on Windows to determine if the current working directory should be prepended to the search path. (Contributed by Charles Machalow in [gh-103179](#).)

`shutil.which()` will return a path matching the `cmd` with a component from `PATHEXT` prior to a direct match elsewhere in the search path on Windows. (Contributed by Charles Machalow in [gh-103179](#).)

6.17 sqlite3

- Add a command-line interface. (Contributed by Erlend E. Aasland in [gh-77617](#).)
- Add the `sqlite3.Connection.autocommit` attribute to `sqlite3.Connection` and the `autocommit` parameter to `sqlite3.connect()` to control [PEP 249](#)-compliant transaction handling. (Contributed by Erlend E. Aasland in [gh-83638](#).)
- Add `entrypoint` keyword-only parameter to `sqlite3.Connection.load_extension()`, for overriding the SQLite extension entry point. (Contributed by Erlend E. Aasland in [gh-103015](#).)
- Add `sqlite3.Connection.getconfig()` and `sqlite3.Connection.setconfig()` to `sqlite3.Connection` to make configuration changes to a database connection. (Contributed by Erlend E. Aasland in [gh-103489](#).)

6.18 statistics

- Extend `statistics.correlation()` to include as a ranked method for computing the Spearman correlation of ranked data. (Contributed by Raymond Hettinger in [gh-95861](#).)

6.19 sys

- Add the `sys.monitoring` namespace to expose the new [PEP 669](#) monitoring API. (Contributed by Mark Shannon in [gh-103082](#).)
- Add `sys.activate_stack_trampoline()` and `sys.deactivate_stack_trampoline()` for activating and deactivating stack profiler trampolines, and `sys.is_stack_trampoline_active()` for querying if stack profiler trampolines are active. (Contributed by Pablo Galindo and Christian Heimes with contributions from Gregory P. Smith [Google] and Mark Shannon in [gh-96123](#).)
- Add `sys.last_exc` which holds the last unhandled exception that was raised (for post-mortem debugging use cases). Deprecate the three fields that have the same information in its legacy form: `sys.last_type`, `sys.last_value` and `sys.last_traceback`. (Contributed by Irit Katriel in [gh-102778](#).)
- `sys._current_exceptions()` now returns a mapping from thread-id to an exception instance, rather than to a `(typ, exc, tb)` tuple. (Contributed by Irit Katriel in [gh-103176](#).)
- `sys.setrecursionlimit()` and `sys.getrecursionlimit()`. The recursion limit now applies only to Python code. Builtin functions do not use the recursion limit, but are protected by a different mechanism that prevents recursion from causing a virtual machine crash.

6.20 tempfile

- The `tempfile.NamedTemporaryFile` function has a new optional parameter `delete_on_close` (Contributed by Evgeny Zorin in [gh-58451](#).)
- `tempfile.mkdtemp()` now always returns an absolute path, even if the argument provided to the `dir` parameter is a relative path.

6.21 threading

- Add `threading.settrace_all_threads()` and `threading.setprofile_all_threads()` that allow to set tracing and profiling functions in all running threads in addition to the calling one. (Contributed by Pablo Galindo in [gh-93503](#).)

6.22 tkinter

- `tkinter.Canvas.coords()` now flattens its arguments. It now accepts not only coordinates as separate arguments (`x1, y1, x2, y2, ...`) and a sequence of coordinates (`[x1, y1, x2, y2, ...]`), but also coordinates grouped in pairs (`((x1, y1), (x2, y2), ...` and `[(x1, y1), (x2, y2), ...]`), like `create_*()` methods. (Contributed by Serhiy Storchaka in [gh-94473](#).)

6.23 tokenize

- The `tokenize` module includes the changes introduced in [PEP 701](#). (Contributed by Marta Gómez Macías and Pablo Galindo in [gh-102856](#).) See [Porting to Python 3.12](#) for more information on the changes to the `tokenize` module.

6.24 types

- Add `types.get_original_bases()` to allow for further introspection of user-defined-generics when subclassed. (Contributed by James Hilton-Balfe and Alex Waygood in [gh-101827](#).)

6.25 typing

- `isinstance()` checks against runtime-checkable protocols now use `inspect.getattr_static()` rather than `hasattr()` to lookup whether attributes exist. This means that descriptors and `__getattr__()` methods are no longer unexpectedly evaluated during `isinstance()` checks against runtime-checkable protocols. However, it may also mean that some objects which used to be considered instances of a runtime-checkable protocol may no longer be considered instances of that protocol on Python 3.12+, and vice versa. Most users are unlikely to be affected by this change. (Contributed by Alex Waygood in [gh-102433](#).)
- The members of a runtime-checkable protocol are now considered “frozen” at runtime as soon as the class has been created. Monkey-patching attributes onto a runtime-checkable protocol will still work, but will have no impact on `isinstance()` checks comparing objects to the protocol. For example:

```
>>> from typing import Protocol, runtime_checkable
>>> @runtime_checkable
... class HasX(Protocol):
...     x = 1
...
>>> class Foo: ...
...
>>> f = Foo()
>>> isinstance(f, HasX)
False
>>> f.x = 1
>>> isinstance(f, HasX)
True
>>> HasX.y = 2
>>> isinstance(f, HasX) # unchanged, even though HasX now also has a "y"
↪attribute
True
```

This change was made in order to speed up `isinstance()` checks against runtime-checkable protocols.

- The performance profile of `isinstance()` checks against runtime-checkable protocols has changed significantly. Most `isinstance()` checks against protocols with only a few members should be at least 2x faster than in 3.11, and some may be 20x faster or more. However, `isinstance()` checks against protocols with fourteen or more members may be slower than in Python 3.11. (Contributed by Alex Waygood in [gh-74690](#) and [gh-103193](#).)
- All `typing.TypedDict` and `typing.NamedTuple` classes now have the `__orig_bases__` attribute. (Contributed by Adrian Garcia Badaracco in [gh-103699](#).)
- Add `frozen_default` parameter to `typing.dataclass_transform()`. (Contributed by Erik De Bonte in [gh-99957](#).)

6.26 unicodedata

- The Unicode database has been updated to version 15.0.0. (Contributed by Benjamin Peterson in [gh-96734](#)).

6.27 unittest

Add a `--durations` command line option, showing the N slowest test cases:

```
python3 -m unittest --durations=3 lib.tests.test_threading
.....
Slowest test durations
-----
1.210s      test_timeout (Lib.test.test_threading.BarrierTests)
1.003s      test_default_timeout (Lib.test.test_threading.BarrierTests)
0.518s      test_timeout (Lib.test.test_threading.EventTests)

(0.000 durations hidden.  Use -v to show these durations.)
-----
Ran 158 tests in 9.869s

OK (skipped=3)
```

(Contributed by Giampaolo Rodola in [gh-48330](#))

6.28 uuid

- Add a command-line interface. (Contributed by Adam Chhina in [gh-88597](#).)

7 Otimizações

- Remove `wstr` and `wstr_length` members from Unicode objects. It reduces object size by 8 or 16 bytes on 64bit platform. (**PEP 623**) (Contributed by Inada Naoki in [gh-92536](#).)
- Add experimental support for using the BOLT binary optimizer in the build process, which improves performance by 1-5%. (Contributed by Kevin Modzelewski in [gh-90536](#) and tuned by Donghee Na in [gh-101525](#))
- Speed up the regular expression substitution (functions `re.sub()` and `re.subn()` and corresponding `re.Pattern` methods) for replacement strings containing group references by 2–3 times. (Contributed by Serhiy Storchaka in [gh-91524](#).)
- Speed up `asyncio.Task` creation by deferring expensive string formatting. (Contributed by Itamar Oren in [gh-103793](#).)
- The `tokenize.tokenize()` and `tokenize.generate_tokens()` functions are up to 64% faster as a side effect of the changes required to cover **PEP 701** in the `tokenize` module. (Contributed by Marta Gómez Macías and Pablo Galindo in [gh-102856](#).)
- Speed up `super()` method calls and attribute loads via the new `LOAD_SUPER_ATTR` instruction. (Contributed by Carl Meyer and Vladimir Matveev in [gh-103497](#).)

8 Alterações de bytecode do CPython

- Remove the `LOAD_METHOD` instruction. It has been merged into `LOAD_ATTR`. `LOAD_ATTR` will now behave like the old `LOAD_METHOD` instruction if the low bit of its `oparg` is set. (Contributed by Ken Jin in [gh-93429](#).)
- Remove the `JUMP_IF_FALSE_OR_POP` and `JUMP_IF_TRUE_OR_POP` instructions. (Contributed by Irit Katriel in [gh-102859](#).)
- Remove the `PRECALL` instruction. (Contributed by Mark Shannon in [gh-92925](#).)
- Add the `BINARY_SLICE` and `STORE_SLICE` instructions. (Contributed by Mark Shannon in [gh-94163](#).)
- Add the `CALL_INTRINSIC_1` instructions. (Contributed by Mark Shannon in [gh-99005](#).)
- Add the `CALL_INTRINSIC_2` instruction. (Contributed by Irit Katriel in [gh-101799](#).)
- Add the `CLEANUP_THROW` instruction. (Contributed by Brandt Bucher in [gh-90997](#).)
- Add the `END_SEND` instruction. (Contributed by Mark Shannon in [gh-103082](#).)
- Add the `LOAD_FAST_AND_CLEAR` instruction as part of the implementation of [PEP 709](#). (Contributed by Carl Meyer in [gh-101441](#).)
- Add the `LOAD_FAST_CHECK` instruction. (Contributed by Dennis Sweeney in [gh-93143](#).)
- Add the `LOAD_FROM_DICT_OR_DEREF`, `LOAD_FROM_DICT_OR_GLOBALS`, and `LOAD_LOCALS` opcodes as part of the implementation of [PEP 695](#). Remove the `LOAD_CLASSDEREF` opcode, which can be replaced with `LOAD_LOCALS` plus `LOAD_FROM_DICT_OR_DEREF`. (Contributed by Jelle Zijlstra in [gh-103764](#).)
- Add the `LOAD_SUPER_ATTR` instruction. (Contributed by Carl Meyer and Vladimir Matveev in [gh-103497](#).)
- Add the `RETURN_CONST` instruction. (Contributed by Wenyang Wang in [gh-101632](#).)

9 Ferramentas e daemons

- Remove the `Tools/demo/` directory which contained old demo scripts. A copy can be found in the [old-demos project](#). (Contributed by Victor Stinner in [gh-97681](#).)
- Remove outdated example scripts of the `Tools/scripts/` directory. A copy can be found in the [old-demos project](#). (Contributed by Victor Stinner in [gh-97669](#).)

10 Descontinuados

- `argparse`: The *type*, *choices*, and *metavar* parameters of `argparse.BooleanOptionalAction` are deprecated and will be removed in 3.14. (Contributed by Nikita Sobolev in [gh-92248](#).)
- `ast`: The following `ast` features have been deprecated in documentation since Python 3.8, now cause a `DeprecationWarning` to be emitted at runtime when they are accessed or used, and will be removed in Python 3.14:

- `ast.Num`
- `ast.Str`
- `ast.Bytes`
- `ast.NameConstant`
- `ast.Ellipsis`

Use `ast.Constant` instead. (Contributed by Serhiy Storchaka in [gh-90953](#).)

- `asyncio`:
 - The child watcher classes `asyncio.MultiLoopChildWatcher`, `asyncio.FastChildWatcher`, `asyncio.AbstractChildWatcher` and `asyncio.SafeChildWatcher` are deprecated and will be removed in Python 3.14. (Contributed by Kumar Aditya in [gh-94597](#).)
 - `asyncio.set_child_watcher()`, `asyncio.get_child_watcher()`, `asyncio.AbstractEventLoopPolicy.set_child_watcher()` e `asyncio.AbstractEventLoopPolicy.get_child_watcher()` foram descontinuados e serão removidos no Python 3.14. (Contribuição de Kumar Aditya em [gh-94597](#).)
 - The `get_event_loop()` method of the default event loop policy now emits a `DeprecationWarning` if there is no current event loop set and it decides to create one. (Contributed by Serhiy Storchaka and Guido van Rossum in [gh-100160](#).)
- `calendar`: `calendar.January` and `calendar.February` constants are deprecated and replaced by `calendar.JANUARY` and `calendar.FEBRUARY`. (Contributed by Prince Roshan in [gh-103636](#).)
- `collections.abc`: Deprecate `collections.abc.ByteString`. Prefer `Sequence` or `collections.abc.Buffer`. For use in typing, prefer a union, like `bytes | bytearray`, or `collections.abc.Buffer`. (Contributed by Shantanu Jain in [gh-91896](#).)
- `datetime`: `datetime.datetime.utcnow()` and `datetime.datetime.fromtimestamp()` are deprecated and will be removed in a future version. Instead, use timezone-aware objects to represent datetimes in UTC: respectively, call `now()` and `fromtimestamp()` with the `tz` parameter set to `datetime.UTC`. (Contributed by Paul Ganssle in [gh-103857](#).)
- `email`: Deprecate the `isdst` parameter in `email.utils.localtime()`. (Contributed by Alan Williams in [gh-72346](#).)
- `importlib.abc`: Deprecate the following classes, scheduled for removal in Python 3.14:
 - `importlib.abc.ResourceReader`
 - `importlib.abc.Traversable`
 - `importlib.abc.TraversableResources`
 Use `importlib.resources.abc` classes instead:
 - `importlib.resources.abc.Traversable`
 - `importlib.resources.abc.TraversableResources`
 (Contributed by Jason R. Coombs and Hugo van Kemenade in [gh-93963](#).)
- `itertools`: Deprecate the support for `copy`, `deepcopy`, and `pickle` operations, which is undocumented, inefficient, historically buggy, and inconsistent. This will be removed in 3.14 for a significant reduction in code volume and maintenance burden. (Contributed by Raymond Hettinger in [gh-101588](#).)
- `multiprocessing`: In Python 3.14, the default `multiprocessing` start method will change to a safer one on Linux, BSDs, and other non-macOS POSIX platforms where `'fork'` is currently the default ([gh-84559](#)). Adding a runtime warning about this was deemed too disruptive as the majority of code is not expected to care. Use the `get_context()` or `set_start_method()` APIs to explicitly specify when your code *requires* `'fork'`. See contexts and start methods.
- `pkgutil`: `pkgutil.find_loader()` and `pkgutil.get_loader()` are deprecated and will be removed in Python 3.14; use `importlib.util.find_spec()` instead. (Contributed by Nikita Sobolev in [gh-97850](#).)
- `pty`: The module has two undocumented `master_open()` and `slave_open()` functions that have been deprecated since Python 2 but only gained a proper `DeprecationWarning` in 3.12. Remove them in 3.14. (Contributed by Soumendra Ganguly and Gregory P. Smith in [gh-85984](#).)
- `os`:

- The `st_ctime` fields return by `os.stat()` and `os.lstat()` on Windows are deprecated. In a future release, they will contain the last metadata change time, consistent with other platforms. For now, they still contain the creation time, which is also available in the new `st_birthtime` field. (Contributed by Steve Dower in [gh-99726](#).)
- On POSIX platforms, `os.fork()` can now raise a `DeprecationWarning` when it can detect being called from a multithreaded process. There has always been a fundamental incompatibility with the POSIX platform when doing so. Even if such code *appeared* to work. We added the warning to to raise awareness as issues encountered by code doing this are becoming more frequent. See the `os.fork()` documentation for more details along with [this discussion on fork being incompatible with threads](#) for why we're now surfacing this longstanding platform compatibility problem to developers.

When this warning appears due to usage of `multiprocessing` or `concurrent.futures` the fix is to use a different `multiprocessing` start method such as `"spawn"` or `"forkserver"`.

- `shutil`: The `onerror` argument of `shutil.rmtree()` is deprecated; use `onexc` instead. (Contributed by Irit Katriel in [gh-102828](#).)
- `sqlite3`:
 - default adapters and converters are now deprecated. Instead, use the `sqlite3-adaptor-converter-recipes` and tailor them to your needs. (Contributed by Erlend E. Aasland in [gh-90016](#).)
 - In `execute()`, `DeprecationWarning` is now emitted when named placeholders are used together with parameters supplied as a sequence instead of as a `dict`. Starting from Python 3.14, using named placeholders with parameters supplied as a sequence will raise a `ProgrammingError`. (Contributed by Erlend E. Aasland in [gh-101698](#).)
- `sys`: The `sys.last_type`, `sys.last_value` and `sys.last_traceback` fields are deprecated. Use `sys.last_exc` instead. (Contributed by Irit Katriel in [gh-102778](#).)
- `tarfile`: Extracting tar archives without specifying `filter` is deprecated until Python 3.14, when `'data'` filter will become the default. See `tarfile-extraction-filter` for details.
- `typing`:
 - `typing.Hashable` and `typing.Sized`, aliases for `collections.abc.Hashable` and `collections.abc.Sized` respectively, are deprecated. ([gh-94309](#).)
 - `typing.ByteString`, deprecated since Python 3.9, now causes a `DeprecationWarning` to be emitted when it is used. (Contributed by Alex Waygood in [gh-91896](#).)
- `xml.etree.ElementTree`: The module now emits `DeprecationWarning` when testing the truth value of an `xml.etree.ElementTree.Element`. Before, the Python implementation emitted `FutureWarning`, and the C implementation emitted nothing. (Contributed by Jacob Walls in [gh-83122](#).)
- The 3-arg signatures (`type`, `value`, `traceback`) of `coroutine throw()`, `generator throw()` and `async generator throw()` are deprecated and may be removed in a future version of Python. Use the single-arg versions of these functions instead. (Contributed by Ofey Chan in [gh-89874](#).)
- `DeprecationWarning` is now raised when `__package__` on a module differs from `__spec__.parent` (previously it was `ImportWarning`). (Contributed by Brett Cannon in [gh-65961](#).)
- Setting `__package__` or `__cached__` on a module is deprecated, and will cease to be set or taken into consideration by the import system in Python 3.14. (Contributed by Brett Cannon in [gh-65961](#).)
- The bitwise inversion operator (`~`) on `bool` is deprecated. It will throw an error in Python 3.14. Use `not` for logical negation of bools instead. In the rare case that you really need the bitwise inversion of the underlying `int`, convert to `int` explicitly: `~int(x)`. (Contributed by Tim Hoffmann in [gh-103487](#).)
- Accessing `co_lnotab` on code objects was deprecated in Python 3.10 via [PEP 626](#), but it only got a proper `DeprecationWarning` in 3.12, therefore it will be removed in 3.14. (Contributed by Nikita Sobolev in [gh-101866](#).)

10.1 Pending Removal in Python 3.13

The following modules and APIs have been deprecated in earlier Python releases, and will be removed in Python 3.13.

Modules (see [PEP 594](#)):

- `aifc`
- `audioop`
- `cgi`
- `cgitb`
- `chunk`
- `crypt`
- `imghdr`
- `mailcap`
- `msilib`
- `nis`
- `nntplib`
- `ossaudiodev`
- `pipes`
- `sndhdr`
- `spwd`
- `sunau`
- `telnetlib`
- `uu`
- `xdrlib`

Other modules:

- `lib2to3`, and the **2to3** program ([gh-84540](#))

APIs:

- `configparser.LegacyInterpolation` ([gh-90765](#))
- `locale.resetlocale()` ([gh-90817](#))
- `turtle.RawTurtle.settiltangle()` ([gh-50096](#))
- `unittest.findTestCases()` ([gh-50096](#))
- `unittest.getTestCaseNames()` ([gh-50096](#))
- `unittest.makeSuite()` ([gh-50096](#))
- `unittest.TestProgram.usageExit()` ([gh-67048](#))
- `webbrowser.MacOSX` ([gh-86421](#))
- classmethod **descriptor chaining** ([gh-89519](#))
- `importlib.resources` deprecated methods:
 - `contents()`
 - `is_resource()`
 - `open_binary()`

- `open_text()`
- `path()`
- `read_binary()`
- `read_text()`

Use `importlib.resources.files()` instead. Refer to [importlib-resources: Migrating from Legacy \(gh-106531\)](#)

10.2 Pending Removal in Python 3.14

The following APIs have been deprecated and will be removed in Python 3.14.

- `argparse`: The *type*, *choices*, and *metavar* parameters of `argparse.BooleanOptionalAction`
- `ast`:
 - `ast.Num`
 - `ast.Str`
 - `ast.Bytes`
 - `ast.NameConstant`
 - `ast.Ellipsis`
- `asyncio`:
 - `asyncio.MultiLoopChildWatcher`
 - `asyncio.FastChildWatcher`
 - `asyncio.AbstractChildWatcher`
 - `asyncio.SafeChildWatcher`
 - `asyncio.set_child_watcher()`
 - `asyncio.get_child_watcher()`,
 - `asyncio.AbstractEventLoopPolicy.set_child_watcher()`
 - `asyncio.AbstractEventLoopPolicy.get_child_watcher()`
- `collections.abc`: `collections.abc.ByteString`.
- `email`: the *isdst* parameter in `email.utils.localtime()`.
- `importlib.abc`:
 - `importlib.abc.ResourceReader`
 - `importlib.abc.Traversable`
 - `importlib.abc.TraversableResources`
- `itertools`: Support for `copy`, `deepcopy`, and `pickle` operations.
- `pkgutil`:
 - `pkgutil.find_loader()`
 - `pkgutil.get_loader()`.
- `pty`:
 - `pty.master_open()`
 - `pty.slave_open()`
- `shutil`: The *onerror* argument of `shutil.rmtree()`

- `typing.ByteString`
- `xml.etree.ElementTree`: Testing the truth value of an `xml.etree.ElementTree.Element`.
- The `__package__` and `__cached__` attributes on module objects.
- The `co_notab` attribute of code objects.

10.3 Pending Removal in Python 3.15

The following APIs have been deprecated and will be removed in Python 3.15.

APIs:

- `locale.getdefaultlocale()` ([gh-90817](#))

10.4 Pending Removal in Future Versions

The following APIs were deprecated in earlier Python versions and will be removed, although there is currently no date scheduled for their removal.

- array's 'u' format code ([gh-57281](#))
- `typing.Text` ([gh-92332](#))
- Currently Python accepts numeric literals immediately followed by keywords, for example `0in x, 1or x, 0if 1else 2`. It allows confusing and ambiguous expressions like `[0x1for x in y]` (which can be interpreted as `[0x1 for x in y]` or `[0x1f or x in y]`). A syntax warning is raised if the numeric literal is immediately followed by one of keywords `and`, `else`, `for`, `if`, `in`, `is` and `or`. In a future release it will be changed to a syntax error. ([gh-87999](#))

11 Removidos

11.1 asynchat and asyncore

- These two modules have been removed according to the schedule in [PEP 594](#), having been deprecated in Python 3.6. Use `asyncio` instead. (Contributed by Nikita Sobolev in [gh-96580](#).)

11.2 configparser

- Several names deprecated in the `configparser` way back in 3.2 have been removed per [gh-89336](#):
 - `configparser.ParsingError` no longer has a `filename` attribute or argument. Use the `source` attribute and argument instead.
 - `configparser` no longer has a `SafeConfigParser` class. Use the shorter `ConfigParser` name instead.
 - `configparser.ConfigParser` no longer has a `readfp` method. Use `read_file()` instead.

11.3 distutils

- Remove the `distutils` package. It was deprecated in Python 3.10 by [PEP 632](#) “Deprecate `distutils` module”. For projects still using `distutils` and cannot be updated to something else, the `setuptools` project can be installed: it still provides `distutils`. (Contributed by Victor Stinner in [gh-92584](#).)

11.4 ensurepip

- Remove the bundled `setuptools` wheel from `ensurepip`, and stop installing `setuptools` in environments created by `venv`.

`pip (>= 22.1)` does not require `setuptools` to be installed in the environment. `setuptools`-based (and `distutils`-based) packages can still be used with `pip install`, since `pip` will provide `setuptools` in the build environment it uses for building a package.

`easy_install`, `pkg_resources`, `setuptools` and `distutils` are no longer provided by default in environments created with `venv` or bootstrapped with `ensurepip`, since they are part of the `setuptools` package. For projects relying on these at runtime, the `setuptools` project should be declared as a dependency and installed separately (typically, using `pip`).

(Contributed by Pradyun Gedam in [gh-95299](#).)

11.5 enum

- Remove `enum`’s `EnumMeta.__getattr__`, which is no longer needed for `enum` attribute access. (Contributed by Ethan Furman in [gh-95083](#).)

11.6 ftplib

- Remove `ftplib`’s `FTP_TLS.ssl_version` class attribute: use the `context` parameter instead. (Contributed by Victor Stinner in [gh-94172](#).)

11.7 gzip

- Remove the `filename` attribute of `gzip`’s `gzip.GzipFile`, deprecated since Python 2.6, use the `name` attribute instead. In write mode, the `filename` attribute added `'.gz'` file extension if it was not present. (Contributed by Victor Stinner in [gh-94196](#).)

11.8 hashlib

- Remove the pure Python implementation of `hashlib`’s `hashlib.pbkdf2_hmac()`, deprecated in Python 3.10. Python 3.10 and newer requires OpenSSL 1.1.1 ([PEP 644](#)): this OpenSSL version provides a C implementation of `pbkdf2_hmac()` which is faster. (Contributed by Victor Stinner in [gh-94199](#).)

11.9 importlib

- Many previously deprecated cleanups in `importlib` have now been completed:
 - References to, and support for `module_repr()` has been removed. (Contributed by Barry Warsaw in [gh-97850](#).)
 - `importlib.util.set_package`, `importlib.util.set_loader` and `importlib.util.module_for_loader` have all been removed. (Contributed by Brett Cannon and Nikita Sobolev in [gh-65961](#) and [gh-97850](#).)
 - Support for `find_loader()` and `find_module()` APIs have been removed. (Contributed by Barry Warsaw in [gh-98040](#).)
 - `importlib.abc.Finder`, `pkgutil.ImpImporter`, and `pkgutil.ImpLoader` have been removed. (Contributed by Barry Warsaw in [gh-98040](#).)

11.10 imp

- The `imp` module has been removed. (Contributed by Barry Warsaw in [gh-98040](#).)

To migrate, consult the following correspondence table:

imp	importlib
<code>imp.</code> <code>NullImporte</code>	Insert None into <code>sys.path_importer_cache</code>
<code>imp.</code> <code>cache_from_</code>	<code>importlib.util.cache_from_source()</code>
<code>imp.</code> <code>find_module</code>	<code>importlib.util.find_spec()</code>
<code>imp.</code> <code>get_magic()</code>	<code>importlib.util.MAGIC_NUMBER</code>
<code>imp.</code> <code>get_suffixe</code>	<code>importlib.machinery.SOURCE_SUFFIXES</code> , <code>machinery.EXTENSION_SUFFIXES</code> , and <code>importlib.</code> <code>machinery.BYTECODE_SUFFIXES</code>
<code>imp.</code> <code>get_tag()</code>	<code>sys.implementation.cache_tag</code>
<code>imp.</code> <code>load_module</code>	<code>importlib.import_module()</code>
<code>imp.</code> <code>new_module(</code>	<code>types.ModuleType(name)</code>
<code>imp.</code> <code>reload()</code>	<code>importlib.reload()</code>
<code>imp.</code> <code>source_from</code>	<code>importlib.util.source_from_cache()</code>
<code>imp.</code> <code>load_source</code>	<i>See below</i>

Replace `imp.load_source()` with:

```
import importlib.util
import importlib.machinery

def load_source(modname, filename):
    loader = importlib.machinery.SourceFileLoader(modname, filename)
    spec = importlib.util.spec_from_file_location(modname, filename,
↪ loader=loader)
    module = importlib.util.module_from_spec(spec)
```

(continua na próxima página)

```
# The module is always executed and not cached in sys.modules.
# Uncomment the following line to cache the module.
# sys.modules[module.__name__] = module
loader.exec_module(module)
return module
```

- Remove `imp` functions and attributes with no replacements:
 - Undocumented functions:
 - * `imp.init_builtin()`
 - * `imp.load_compiled()`
 - * `imp.load_dynamic()`
 - * `imp.load_package()`
 - `imp.lock_held()`, `imp.acquire_lock()`, `imp.release_lock()`: the locking scheme has changed in Python 3.3 to per-module locks.
 - `imp.find_module()` constants: `SEARCH_ERROR`, `PY_SOURCE`, `PY_COMPILED`, `C_EXTENSION`, `PY_RESOURCE`, `PKG_DIRECTORY`, `C_BUILTIN`, `PY_FROZEN`, `PY_CODERESOURCE`, `IMP_HOOK`.

11.11 io

- Remove `io`'s `io.OpenWrapper` and `_pyio.OpenWrapper`, deprecated in Python 3.10: just use `open()` instead. The `open()` (`io.open()`) function is a built-in function. Since Python 3.10, `_pyio.open()` is also a static method. (Contributed by Victor Stinner in [gh-94169](#).)

11.12 locale

- Remove `locale`'s `locale.format()` function, deprecated in Python 3.7: use `locale.format_string()` instead. (Contributed by Victor Stinner in [gh-94226](#).)

11.13 smtpd

- The `smtpd` module has been removed according to the schedule in [PEP 594](#), having been deprecated in Python 3.4.7 and 3.5.4. Use `aiosmtpd` PyPI module or any other `asyncio`-based server instead. (Contributed by Oleg Iarygin in [gh-93243](#).)

11.14 sqlite3

- The following undocumented `sqlite3` features, deprecated in Python 3.10, are now removed:
 - `sqlite3.enable_shared_cache()`
 - `sqlite3.OptimizedUnicode`

If a shared cache must be used, open the database in URI mode using the `cache=shared` query parameter.

The `sqlite3.OptimizedUnicode` text factory has been an alias for `str` since Python 3.3. Code that previously set the text factory to `OptimizedUnicode` can either use `str` explicitly, or rely on the default value which is also `str`.

(Contributed by Erlend E. Aasland in [gh-92548](#).)

11.15 ssl

- Remove `ssl`'s `ssl.RAND_pseudo_bytes()` function, deprecated in Python 3.6: use `os.urandom()` or `ssl.RAND_bytes()` instead. (Contributed by Victor Stinner in [gh-94199](#).)
- Remove the `ssl.match_hostname()` function. It was deprecated in Python 3.7. OpenSSL performs hostname matching since Python 3.7, Python no longer uses the `ssl.match_hostname()` function. (Contributed by Victor Stinner in [gh-94199](#).)
- Remove the `ssl.wrap_socket()` function, deprecated in Python 3.7: instead, create a `ssl.SSLContext` object and call its `ssl.SSLContext.wrap_socket` method. Any package that still uses `ssl.wrap_socket()` is broken and insecure. The function neither sends a SNI TLS extension nor validates server hostname. Code is subject to [CWE-295: Improper Certificate Validation](#). (Contributed by Victor Stinner in [gh-94199](#).)

11.16 unittest

- Remove many long-deprecated `unittest` features:
 - A number of `TestCase` method aliases:

Apelido descontinuado	Método	Descontinuado em
<code>failUnless</code>	<code>assertTrue()</code>	3.1
<code>failIf</code>	<code>assertFalse()</code>	3.1
<code>failUnlessEqual</code>	<code>assertEqual()</code>	3.1
<code>failIfEqual</code>	<code>assertNotEqual()</code>	3.1
<code>failUnlessAlmostEqual</code>	<code>assertAlmostEqual()</code>	3.1
<code>failIfAlmostEqual</code>	<code>assertNotAlmostEqual()</code>	3.1
<code>failUnlessRaises</code>	<code>assertRaises()</code>	3.1
<code>assert_</code>	<code>assertTrue()</code>	3.2
<code>assertEquals</code>	<code>assertEqual()</code>	3.2
<code>assertNotEquals</code>	<code>assertNotEqual()</code>	3.2
<code>assertAlmostEquals</code>	<code>assertAlmostEqual()</code>	3.2
<code>assertNotAlmostEquals</code>	<code>assertNotAlmostEqual()</code>	3.2
<code>assertRegexpMatches</code>	<code>assertRegex()</code>	3.2
<code>assertRaisesRegexp</code>	<code>assertRaisesRegex()</code>	3.2
<code>assertNotRegexpMatches</code>	<code>assertNotRegex()</code>	3.5

You can use <https://github.com/isidentical/teyit> to automatically modernise your unit tests.

- Undocumented and broken `TestCase` method `assertDictContainsSubset` (deprecated in Python 3.2).
- Undocumented `TestLoader.loadTestsFromModule` parameter `use_load_tests` (deprecated and ignored since Python 3.2).
- An alias of the `TextTestResult` class: `_TextTestResult` (deprecated in Python 3.2).

(Contributed by Serhiy Storchaka in [gh-89325](#).)

11.17 webbrowser

- Remove support for obsolete browsers from `webbrowser`. The removed browsers include: Grail, Mosaic, Netscape, Galeon, Skipstone, Iceape, Firebird, and Firefox versions 35 and below ([gh-102871](#)).

11.18 xml.etree.ElementTree

- Remove the `ElementTree.Element.copy()` method of the pure Python implementation, deprecated in Python 3.10, use the `copy.copy()` function instead. The C implementation of `xml.etree.ElementTree` has no `copy()` method, only a `__copy__()` method. (Contributed by Victor Stinner in [gh-94383](#).)

11.19 zipimport

- Remove `zipimport`'s `find_loader()` and `find_module()` methods, deprecated in Python 3.10: use the `find_spec()` method instead. See [PEP 451](#) for the rationale. (Contributed by Victor Stinner in [gh-94379](#).)

11.20 Others

- Remove the `suspicious` rule from the documentation `Makefile` and `Doc/tools/rstlint.py`, both in favor of `sphinx-lint`. (Contributed by Julien Palard in [gh-98179](#).)
- Remove the `keyfile` and `certfile` parameters from the `ftplib`, `imaplib`, `poplib` and `smtplib` modules, and the `key_file`, `cert_file` and `check_hostname` parameters from the `http.client` module, all deprecated since Python 3.6. Use the `context` parameter (`ssl_context` in `imaplib`) instead. (Contributed by Victor Stinner in [gh-94172](#).)
- Remove `Jython` compatibility hacks from several `stdlib` modules and tests. (Contributed by Nikita Sobolev in [gh-99482](#).)
- Remove `_use_broken_old_ctypes_structure_semantics_flag` from `ctypes` module. (Contributed by Nikita Sobolev in [gh-99285](#).)

12 Porting to Python 3.12

Esta seção lista as alterações descritas anteriormente e outras correções que podem exigir alterações no seu código.

12.1 Alterações na API Python

- More strict rules are now applied for numerical group references and group names in regular expressions. Only sequence of ASCII digits is now accepted as a numerical reference. The group name in bytes patterns and replacement strings can now only contain ASCII letters and digits and underscore. (Contributed by Serhiy Storchaka in [gh-91760](#).)
- Remove `randrange()` functionality deprecated since Python 3.10. Formerly, `randrange(10.0)` losslessly converted to `randrange(10)`. Now, it raises a `TypeError`. Also, the exception raised for non-integer values such as `randrange(10.5)` or `randrange('10')` has been changed from `ValueError` to `TypeError`. This also prevents bugs where `randrange(1e25)` would silently select from a larger range than `randrange(10**25)`. (Originally suggested by Serhiy Storchaka [gh-86388](#).)
- `argparse.ArgumentParser` changed encoding and error handler for reading arguments from file (e.g. `fromfile_prefix_chars` option) from default text encoding (e.g. `locale.getpreferredencoding(False)`) to filesystem encoding and error handler. Argument files should be encoded in UTF-8 instead of ANSI Codepage on Windows.

- Remove the `asyncore`-based `smtpd` module deprecated in Python 3.4.7 and 3.5.4. A recommended replacement is the `asyncio`-based `aiosmtpd` PyPI module.
- `shlex.split()`: Passing `None` for `s` argument now raises an exception, rather than reading `sys.stdin`. The feature was deprecated in Python 3.9. (Contributed by Victor Stinner in [gh-94352](#).)
- The `os` module no longer accepts bytes-like paths, like `bytearray` and `memoryview` types: only the exact `bytes` type is accepted for bytes strings. (Contributed by Victor Stinner in [gh-98393](#).)
- `syslog.openlog()` and `syslog.closelog()` now fail if used in subinterpreters. `syslog.syslog()` may still be used in subinterpreters, but now only if `syslog.openlog()` has already been called in the main interpreter. These new restrictions do not apply to the main interpreter, so only a very small set of users might be affected. This change helps with interpreter isolation. Furthermore, `syslog` is a wrapper around process-global resources, which are best managed from the main interpreter. (Contributed by Donghee Na in [gh-99127](#).)
- The undocumented locking behavior of `cached_property()` is removed, because it locked across all instances of the class, leading to high lock contention. This means that a cached property getter function could now run more than once for a single instance, if two threads race. For most simple cached properties (e.g. those that are idempotent and simply calculate a value based on other attributes of the instance) this will be fine. If synchronization is needed, implement locking within the cached property getter function or around multi-threaded access points.
- `sys._current_exceptions()` now returns a mapping from thread-id to an exception instance, rather than to a `(typ, exc, tb)` tuple. (Contributed by Irit Katriel in [gh-103176](#).)
- When extracting tar files using `tarfile` or `shutil.unpack_archive()`, pass the `filter` argument to limit features that may be surprising or dangerous. See [tarfile-extraction-filter](#) for details.
- The output of the `tokenize.tokenize()` and `tokenize.generate_tokens()` functions is now changed due to the changes introduced in [PEP 701](#). This means that `STRING` tokens are not emitted any more for f-strings and the tokens described in [PEP 701](#) are now produced instead: `FSTRING_START`, `FSTRING_MIDDLE` and `FSTRING_END` are now emitted for f-string “string” parts in addition to the appropriate tokens for the tokenization in the expression components. For example for the f-string `f"start {1+1} end"` the old version of the tokenizer emitted:

```
1,0-1,18:          STRING          'f"start {1+1} end"'
```

while the new version emits:

```
1,0-1,2:           FSTRING_START  'f'
1,2-1,8:           FSTRING_MIDDLE 'start '
1,8-1,9:           OP              '{'
1,9-1,10:          NUMBER         '1'
1,10-1,11:         OP              '+'
1,11-1,12:         NUMBER         '1'
1,12-1,13:         OP              '}'
1,13-1,17:         FSTRING_MIDDLE ' end'
1,17-1,18:         FSTRING_END    ''
```

Additionally, there may be some minor behavioral changes as a consequence of the changes required to support [PEP 701](#). Some of these changes include:

- The `type` attribute of the tokens emitted when tokenizing some invalid Python characters such as `!` has changed from `ERRORTOKEN` to `OP`.
- Incomplete single-line strings now also raise `tokenize.TokenError` as incomplete multiline strings do.
- Some incomplete or invalid Python code now raises `tokenize.TokenError` instead of returning arbitrary `ERRORTOKEN` tokens when tokenizing it.
- Mixing tabs and spaces as indentation in the same file is not supported anymore and will raise a `TabError`.

- The `threading` module now expects the `_thread` module to have an `_is_main_interpreter` attribute. It is a function with no arguments that returns `True` if the current interpreter is the main interpreter. Any library or application that provides a custom `_thread` module should provide `_is_main_interpreter()`. (See [gh-112826](#).)

13 Alterações de compilação

- Python no longer uses `setup.py` to build shared C extension modules. Build parameters like headers and libraries are detected in `configure` script. Extensions are built by `Makefile`. Most extensions use `pkg-config` and fall back to manual detection. (Contributed by Christian Heimes in [gh-93939](#).)
- `va_start()` with two parameters, like `va_start(args, format)`, is now required to build Python. `va_start()` is no longer called with a single parameter. (Contributed by Kumar Aditya in [gh-93207](#).)
- CPython now uses the ThinLTO option as the default link time optimization policy if the Clang compiler accepts the flag. (Contributed by Donghee Na in [gh-89536](#).)
- Add `COMPILEALL_OPTS` variable in `Makefile` to override `compileall` options (default: `-j0`) in `make install`. Also merged the 3 `compileall` commands into a single command to build `.pyc` files for all optimization levels (0, 1, 2) at once. (Contributed by Victor Stinner in [gh-99289](#).)
- Add platform triplets for 64-bit LoongArch:
 - `loongarch64-linux-gnusr`
 - `loongarch64-linux-gnuf32`
 - `loongarch64-linux-gnu`
 (Contributed by Zhang Na in [gh-90656](#).)
- `PYTHON_FOR_REGEN` now require Python 3.10 or newer.
- Autoconf 2.71 and `aclocal` 1.16.4 is now required to regenerate `!configure`. (Contributed by Christian Heimes in [gh-89886](#).)
- Windows builds and macOS installers from python.org now use OpenSSL 3.0.

14 Alterações na API C

14.1 Novas funcionalidades

- **PEP 697**: Introduce the Unstable C API tier, intended for low-level tools like debuggers and JIT compilers. This API may change in each minor release of CPython without deprecation warnings. Its contents are marked by the `PyUnstable_` prefix in names.

Code object constructors:

- `PyUnstable_Code_New()` (renamed from `PyCode_New`)
- `PyUnstable_Code_NewWithPosOnlyArgs()` (renamed from `PyCode_NewWithPosOnlyArgs`)

Extra storage for code objects (**PEP 523**):

- `PyUnstable_Eval_RequestCodeExtraIndex()` (renamed from `_PyEval_RequestCodeExtraIndex`)
- `PyUnstable_Code_GetExtra()` (renamed from `_PyCode_GetExtra`)
- `PyUnstable_Code_SetExtra()` (renamed from `_PyCode_SetExtra`)

The original names will continue to be available until the respective API changes.

(Contributed by Petr Viktorin in [gh-101101](#).)

- **PEP 697**: Add an API for extending types whose instance memory layout is opaque:
 - `PyType_Spec.basicsize` can be zero or negative to specify inheriting or extending the base class size.
 - `PyObject_GetTypeData()` and `PyType_GetTypeDataSize()` added to allow access to subclass-specific instance data.
 - `Py_TPFLAGS_ITEMS_AT_END` and `PyObject_GetItemData()` added to allow safely extending certain variable-sized types, including `PyType_Type`.
 - `Py_RELATIVE_OFFSET` added to allow defining members in terms of a subclass-specific struct.

(Contributed by Petr Viktorin in [gh-103509](#).)

- Add the new limited C API function `PyType_FromMetaclass()`, which generalizes the existing `PyType_FromModuleAndSpec()` using an additional metaclass argument. (Contributed by Wenzel Jakob in [gh-93012](#).)
- API for creating objects that can be called using the vectorcall protocol was added to the Limited API:
 - `Py_TPFLAGS_HAVE_VECTORCALL`
 - `PyVectorcall_NARGS()`
 - `PyVectorcall_Call()`
 - `vectorcallfunc`

The `Py_TPFLAGS_HAVE_VECTORCALL` flag is now removed from a class when the class's `__call__()` method is reassigned. This makes vectorcall safe to use with mutable types (i.e. heap types without the immutable flag, `Py_TPFLAGS_IMMUTABLETYPE`). Mutable types that do not override `tp_call` now inherit the `Py_TPFLAGS_HAVE_VECTORCALL` flag. (Contributed by Petr Viktorin in [gh-93274](#).)

The `Py_TPFLAGS_MANAGED_DICT` and `Py_TPFLAGS_MANAGED_WEAKREF` flags have been added. This allows extension classes to support object `__dict__` and weakrefs with less bookkeeping, using less memory and with faster access.

- API for performing calls using the vectorcall protocol was added to the Limited API:
 - `PyObject_Vectorcall()`
 - `PyObject_VectorcallMethod()`
 - `Py_VECTORCALL_ARGUMENTS_OFFSET`

This means that both the incoming and outgoing ends of the vector call protocol are now available in the Limited API. (Contributed by Wenzel Jakob in [gh-98586](#).)

- Add two new public functions, `PyEval_SetProfileAllThreads()` and `PyEval_SetTraceAllThreads()`, that allow to set tracing and profiling functions in all running threads in addition to the calling one. (Contributed by Pablo Galindo in [gh-93503](#).)
- Add new function `PyFunction_SetVectorcall()` to the C API which sets the vectorcall field of a given `PyFunctionObject`. (Contributed by Andrew Frost in [gh-92257](#).)
- The C API now permits registering callbacks via `PyDict_AddWatcher()`, `PyDict_Watch()` and related APIs to be called whenever a dictionary is modified. This is intended for use by optimizing interpreters, JIT compilers, or debuggers. (Contributed by Carl Meyer in [gh-91052](#).)
- Add `PyType_AddWatcher()` and `PyType_Watch()` API to register callbacks to receive notification on changes to a type. (Contributed by Carl Meyer in [gh-91051](#).)
- Add `PyCode_AddWatcher()` and `PyCode_ClearWatcher()` APIs to register callbacks to receive notification on creation and destruction of code objects. (Contributed by Itamar Oren in [gh-91054](#).)

- Add `PyFrame_GetVar()` and `PyFrame_GetVarString()` functions to get a frame variable by its name. (Contributed by Victor Stinner in [gh-91248](#).)
- Add `PyErr_GetRaisedException()` and `PyErr_SetRaisedException()` for saving and restoring the current exception. These functions return and accept a single exception object, rather than the triple arguments of the now-deprecated `PyErr_Fetch()` and `PyErr_Restore()`. This is less error prone and a bit more efficient. (Contributed by Mark Shannon in [gh-101578](#).)
- Add `_PyErr_ChainExceptions1`, which takes an exception instance, to replace the legacy-API `_PyErr_ChainExceptions`, which is now deprecated. (Contributed by Mark Shannon in [gh-101578](#).)
- Add `PyException_GetArgs()` and `PyException_SetArgs()` as convenience functions for retrieving and modifying the args passed to the exception's constructor. (Contributed by Mark Shannon in [gh-101578](#).)
- Add `PyErr_DisplayException()`, which takes an exception instance, to replace the legacy-api `PyErr_Display()`. (Contributed by Irit Katriel in [gh-102755](#).)
- **PEP 683:** Introduce *Immortal Objects*, which allows objects to bypass reference counts, and related changes to the C-API:
 - **`_Py_IMMORTAL_REFCNT`:** The reference count that defines an object as immortal.
 - **`_Py_IsImmortal`** Checks if an object has the immortal reference count.
 - **`PyObject_HEAD_INIT`** This will now initialize reference count to `_Py_IMMORTAL_REFCNT` when used with `Py_BUILD_CORE`.
 - **`SSTATE_INTERNEDED_IMMORTAL`** An identifier for interned unicode objects that are immortal.
 - **`SSTATE_INTERNEDED_IMMORTAL_STATIC`** An identifier for interned unicode objects that are immortal and static
 - **`sys.getunicodeinternedsize`** This returns the total number of unicode objects that have been interned. This is now needed for `refleak.py` to correctly track reference counts and allocated blocks
 (Contributed by Eddie Elizondo in [gh-84436](#).)
- **PEP 684:** Add the new `Py_NewInterpreterFromConfig()` function and `PyInterpreterConfig`, which may be used to create sub-interpreters with their own GILs. (See [PEP 684: Um GIL por interpretador](#) for more info.) (Contributed by Eric Snow in [gh-104110](#).)
- In the limited C API version 3.12, `Py_INCREF()` and `Py_DECREF()` functions are now implemented as opaque function calls to hide implementation details. (Contributed by Victor Stinner in [gh-105387](#).)

14.2 Porting to Python 3.12

- Legacy Unicode APIs based on `Py_UNICODE*` representation has been removed. Please migrate to APIs based on UTF-8 or `wchar_t*`.
- Argument parsing functions like `PyArg_ParseTuple()` doesn't support `Py_UNICODE*` based format (e.g. `u`, `Z`) anymore. Please migrate to other formats for Unicode like `s`, `z`, `es`, and `U`.
- `tp_weaklist` for all static builtin types is always `NULL`. This is an internal-only field on `PyTypeObject` but we're pointing out the change in case someone happens to be accessing the field directly anyway. To avoid breakage, consider using the existing public C-API instead, or, if necessary, the (internal-only) `_PyObject_GET_WEAKREFS_LISTPTR()` macro.
- This internal-only `PyTypeObject.tp_subclasses` may now not be a valid object pointer. Its type was changed to `void*` to reflect this. We mention this in case someone happens to be accessing the internal-only field directly.

To get a list of subclasses, call the Python method `__subclasses__()` (using `PyObject_CallMethod()`, for example).

- Add support of more formatting options (left aligning, octals, uppercase hexadecimals, `intmax_t`, `ptrdiff_t`, `wchar_t` C strings, variable width and precision) in `PyUnicode_FromFormat()` and `PyUnicode_FromFormatV()`. (Contributed by Serhiy Storchaka in [gh-98836](#).)
- An unrecognized format character in `PyUnicode_FromFormat()` and `PyUnicode_FromFormatV()` now sets a `SystemError`. In previous versions it caused all the rest of the format string to be copied as-is to the result string, and any extra arguments discarded. (Contributed by Serhiy Storchaka in [gh-95781](#).)
- Fix wrong sign placement in `PyUnicode_FromFormat()` and `PyUnicode_FromFormatV()`. (Contributed by Philip Georgi in [gh-95504](#).)
- Extension classes wanting to add a `__dict__` or weak reference slot should use `Py_TPFLAGS_MANAGED_DICT` and `Py_TPFLAGS_MANAGED_WEAKREF` instead of `tp_dictoffset` and `tp_weaklistoffset`, respectively. The use of `tp_dictoffset` and `tp_weaklistoffset` is still supported, but does not fully support multiple inheritance ([gh-95589](#)), and performance may be worse. Classes declaring `Py_TPFLAGS_MANAGED_DICT` should call `_PyObject_VisitManagedDict()` and `_PyObject_ClearManagedDict()` to traverse and clear their instance's dictionaries. To clear weakrefs, call `PyObject_ClearWeakRefs()`, as before.
- The `PyUnicode_FSDecoder()` function no longer accepts bytes-like paths, like `bytearray` and `memoryview` types: only the exact `bytes` type is accepted for bytes strings. (Contributed by Victor Stinner in [gh-98393](#).)
- The `Py_CLEAR`, `Py_SETREF` and `Py_XSETREF` macros now only evaluate their arguments once. If an argument has side effects, these side effects are no longer duplicated. (Contributed by Victor Stinner in [gh-98724](#).)
- The interpreter's error indicator is now always normalized. This means that `PyErr_SetObject()`, `PyErr_SetString()` and the other functions that set the error indicator now normalize the exception before storing it. (Contributed by Mark Shannon in [gh-101578](#).)
- `_Py_RefTotal` is no longer authoritative and only kept around for ABI compatibility. Note that it is an internal global and only available on debug builds. If you happen to be using it then you'll need to start using `_Py_GetGlobalRefTotal()`.
- The following functions now select an appropriate metaclass for the newly created type:
 - `PyType_FromSpec()`
 - `PyType_FromSpecWithBases()`
 - `PyType_FromModuleAndSpec()`

Creating classes whose metaclass overrides `tp_new` is deprecated, and in Python 3.14+ it will be disallowed. Note that these functions ignore `tp_new` of the metaclass, possibly allowing incomplete initialization.

Note that `PyType_FromMetaclass()` (added in Python 3.12) already disallows creating classes whose metaclass overrides `tp_new` (`__new__()` in Python).

Since `tp_new` overrides almost everything `PyType_From*` functions do, the two are incompatible with each other. The existing behavior – ignoring the metaclass for several steps of type creation – is unsafe in general, since (meta)classes assume that `tp_new` was called. There is no simple general workaround. One of the following may work for you:

- If you control the metaclass, avoid using `tp_new` in it:
 - * If initialization can be skipped, it can be done in `tp_init` instead.
 - * If the metaclass doesn't need to be instantiated from Python, set its `tp_new` to `NULL` using the `Py_TPFLAGS_DISALLOW_INSTANTIATION` flag. This makes it acceptable for `PyType_From*` functions.
- Avoid `PyType_From*` functions: if you don't need C-specific features (slots or setting the instance size), create types by calling the metaclass.

- If you *know* the `tp_new` can be skipped safely, filter the deprecation warning out using `warnings.catch_warnings()` from Python.
 - `PyOS_InputHook` and `PyOS_ReadlineFunctionPointer` are no longer called in subinterpreters. This is because clients generally rely on process-wide global state (since these callbacks have no way of recovering extension module state).
- This also avoids situations where extensions may find themselves running in a subinterpreter that they don't support (or haven't yet been loaded in). See [gh-104668](#) for more info.
- `PyLongObject` has had its internals changed for better performance. Although the internals of `PyLongObject` are private, they are used by some extension modules. The internal fields should no longer be accessed directly, instead the API functions beginning `PyLong_...` should be used instead. Two new *unstable* API functions are provided for efficient access to the value of `PyLongObjects` which fit into a single machine word:
 - `PyUnstable_Long_IsCompact()`
 - `PyUnstable_Long_CompactValue()`
 - Custom allocators, set via `PyMem_SetAllocator()`, are now required to be thread-safe, regardless of memory domain. Allocators that don't have their own state, including “hooks”, are not affected. If your custom allocator is not already thread-safe and you need guidance then please create a new GitHub issue and CC [@eric snow currently](#).

14.3 Descontinuados

- In accordance with [PEP 699](#), the `ma_version_tag` field in `PyDictObject` is deprecated for extension modules. Accessing this field will generate a compiler warning at compile time. This field will be removed in Python 3.14. (Contributed by Ramvikrams and Kumar Aditya in [gh-101193](#). PEP by Ken Jin.)
- Deprecate global configuration variable:
 - `Py_DebugFlag`: use `PyConfig.parser_debug`
 - `Py_VerboseFlag`: use `PyConfig.verbose`
 - `Py_QuietFlag`: use `PyConfig.quiet`
 - `Py_InteractiveFlag`: use `PyConfig.interactive`
 - `Py_InspectFlag`: use `PyConfig.inspect`
 - `Py_OptimizeFlag`: use `PyConfig.optimization_level`
 - `Py_NoSiteFlag`: use `PyConfig.site_import`
 - `Py_BytesWarningFlag`: use `PyConfig.bytes_warning`
 - `Py_FrozenFlag`: use `PyConfig.pathconfig_warnings`
 - `Py_IgnoreEnvironmentFlag`: use `PyConfig.use_environment`
 - `Py_DontWriteBytecodeFlag`: use `PyConfig.write_bytecode`
 - `Py_NoUserSiteDirectory`: use `PyConfig.user_site_directory`
 - `Py_UnbufferedStdioFlag`: use `PyConfig.buffered_stdio`
 - `Py_HashRandomizationFlag`: use `PyConfig.use_hash_seed` and `PyConfig.hash_seed`
 - `Py_IsolatedFlag`: use `PyConfig.isolated`
 - `Py_LegacyWindowsFSEncodingFlag`: use `PyPreConfig.legacy_windows_fs_encoding`
 - `Py_LegacyWindowsStdioFlag`: use `PyConfig.legacy_windows_stdio`
 - `Py_FileSystemDefaultEncoding`: use `PyConfig.filesystem_encoding`

- `Py_HasFileSystemDefaultEncoding`: use `PyConfig.filesystem_encoding`
- `Py_FileSystemDefaultEncodeErrors`: use `PyConfig.filesystem_errors`
- `Py_UTF8Mode`: use `PyPreConfig.utf8_mode` (see `Py_PreInitialize()`)

The `Py_InitializeFromConfig()` API should be used with `PyConfig` instead. (Contributed by Victor Stinner in [gh-77782](#).)

- Creating immutable types with mutable bases is deprecated and will be disabled in Python 3.14. ([gh-95388](#))
- The `structmember.h` header is deprecated, though it continues to be available and there are no plans to remove it.

Its contents are now available just by including `Python.h`, with a `Py` prefix added if it was missing:

- `PyMemberDef`, `PyMember_GetOne()` and `PyMember_SetOne()`
- Type macros like `Py_T_INT`, `Py_T_DOUBLE`, etc. (previously `T_INT`, `T_DOUBLE`, etc.)
- The flags `Py_READONLY` (previously `READONLY`) and `Py_AUDIT_READ` (previously all uppercase)

Several items are not exposed from `Python.h`:

- `T_OBJECT` (use `Py_T_OBJECT_EX`)
- `T_NONE` (previously undocumented, and pretty quirky)
- The macro `WRITE_RESTRICTED` which does nothing.
- The macros `RESTRICTED` and `READ_RESTRICTED`, equivalents of `Py_AUDIT_READ`.
- In some configurations, `<stddef.h>` is not included from `Python.h`. It should be included manually when using `offsetof()`.

The deprecated header continues to provide its original contents under the original names. Your old code can stay unchanged, unless the extra include and non-namespaced macros bother you greatly.

(Contributed in [gh-47146](#) by Petr Viktorin, based on earlier work by Alexander Belopolsky and Matthias Braun.)

- `PyErr_Fetch()` and `PyErr_Restore()` are deprecated. Use `PyErr_GetRaisedException()` and `PyErr_SetRaisedException()` instead. (Contributed by Mark Shannon in [gh-101578](#).)
- `PyErr_Display()` is deprecated. Use `PyErr_DisplayException()` instead. (Contributed by Irit Katriel in [gh-102755](#)).
- `_PyErr_ChainExceptions` is deprecated. Use `_PyErr_ChainExceptions1` instead. (Contributed by Irit Katriel in [gh-102192](#).)
- Using `PyType_FromSpec()`, `PyType_FromSpecWithBases()` or `PyType_FromModuleAndSpec()` to create a class whose metaclass overrides `tp_new` is deprecated. Call the metaclass instead.

Pending Removal in Python 3.14

- The `ma_version_tag` field in `PyDictObject` for extension modules ([PEP 699](#); [gh-101193](#)).
- Global configuration variables:
 - `Py_DebugFlag`: use `PyConfig.parser_debug`
 - `Py_VerboseFlag`: use `PyConfig.verbose`
 - `Py_QuietFlag`: use `PyConfig.quiet`
 - `Py_InteractiveFlag`: use `PyConfig.interactive`
 - `Py_InspectFlag`: use `PyConfig.inspect`

- `Py_OptimizeFlag`: use `PyConfig.optimization_level`
- `Py_NoSiteFlag`: use `PyConfig.site_import`
- `Py_BytesWarningFlag`: use `PyConfig.bytes_warning`
- `Py_FrozenFlag`: use `PyConfig.pathconfig_warnings`
- `Py_IgnoreEnvironmentFlag`: use `PyConfig.use_environment`
- `Py_DontWriteBytecodeFlag`: use `PyConfig.write_bytecode`
- `Py_NoUserSiteDirectory`: use `PyConfig.user_site_directory`
- `Py_UnbufferedStdioFlag`: use `PyConfig.buffered_stdio`
- `Py_HashRandomizationFlag`: use `PyConfig.use_hash_seed` and `PyConfig.hash_seed`
- `Py_IsolatedFlag`: use `PyConfig.isolated`
- `Py_LegacyWindowsFSEncodingFlag`: use `PyPreConfig.legacy_windows_fs_encoding`
- `Py_LegacyWindowsStdioFlag`: use `PyConfig.legacy_windows_stdio`
- `Py_FileSystemDefaultEncoding`: use `PyConfig.filesystem_encoding`
- `Py_HasFileSystemDefaultEncoding`: use `PyConfig.filesystem_encoding`
- `Py_FileSystemDefaultEncodeErrors`: use `PyConfig.filesystem_errors`
- `Py_UTF8Mode`: use `PyPreConfig.utf8_mode` (see `Py_PreInitialize()`)

The `Py_InitializeFromConfig()` API should be used with `PyConfig` instead.

- Creating immutable types with mutable bases ([gh-95388](#)).

Pending Removal in Python 3.15

- `PyImport_ImportModuleNoBlock()`: use `PyImport_ImportModule()`
- `Py_UNICODE_WIDE` type: use `wchar_t`
- `Py_UNICODE` type: use `wchar_t`
- Python initialization functions:
 - `PySys_ResetWarnOptions()`: clear `sys.warnoptions` and `warnings.filters`
 - `Py_GetExecPrefix()`: get `sys.exec_prefix`
 - `Py_GetPath()`: get `sys.path`
 - `Py_GetPrefix()`: get `sys.prefix`
 - `Py_GetProgramFullPath()`: get `sys.executable`
 - `Py_GetProgramName()`: get `sys.executable`
 - `Py_GetPythonHome()`: get `PyConfig.home` or the `PYTHONHOME` environment variable

Pending Removal in Future Versions

The following APIs are deprecated and will be removed, although there is currently no date scheduled for their removal.

- `Py_TPFLAGS_HAVE_FINALIZE`: **unneeded since Python 3.8**
- `PyErr_Fetch()`: **use** `PyErr_GetRaisedException()`
- `PyErr_NormalizeException()`: **use** `PyErr_GetRaisedException()`
- `PyErr_Restore()`: **use** `PyErr_SetRaisedException()`
- `PyModule_GetFilename()`: **use** `PyModule_GetFilenameObject()`
- `PyOS_AfterFork()`: **use** `PyOS_AfterFork_Child()`
- `PySlice_GetIndicesEx()`: **use** `PySlice_Unpack()` **and** `PySlice_AdjustIndices()`
- `PyUnicode_AsDecodedObject()`: **use** `PyCodec_Decode()`
- `PyUnicode_AsDecodedUnicode()`: **use** `PyCodec_Decode()`
- `PyUnicode_AsEncodedObject()`: **use** `PyCodec_Encode()`
- `PyUnicode_AsEncodedUnicode()`: **use** `PyCodec_Encode()`
- `PyUnicode_READY()`: **unneeded since Python 3.12**
- `PyErr_Display()`: **use** `PyErr_DisplayException()`
- `_PyErr_ChainExceptions()`: **use** `_PyErr_ChainExceptions1`
- `PyBytesObject.ob_shash` member: **call** `PyObject_Hash()` **instead**
- `PyDictObject.ma_version_tag` member
- **Thread Local Storage (TLS) API:**
 - `PyThread_create_key()`: **use** `PyThread_tss_alloc()`
 - `PyThread_delete_key()`: **use** `PyThread_tss_free()`
 - `PyThread_set_key_value()`: **use** `PyThread_tss_set()`
 - `PyThread_get_key_value()`: **use** `PyThread_tss_get()`
 - `PyThread_delete_key_value()`: **use** `PyThread_tss_delete()`
 - `PyThread_ReInitTLS()`: **unneeded since Python 3.7**

14.4 Removidos

- Remove the `token.h` header file. There was never any public tokenizer C API. The `token.h` header file was only designed to be used by Python internals. (Contributed by Victor Stinner in [gh-92651](#).)
- Legacy Unicode APIs have been removed. See [PEP 623](#) for detail.
 - `PyUnicode_WCHAR_KIND`
 - `PyUnicode_AS_UNICODE()`
 - `PyUnicode_AsUnicode()`
 - `PyUnicode_AsUnicodeAndSize()`
 - `PyUnicode_AS_DATA()`
 - `PyUnicode_FromUnicode()`
 - `PyUnicode_GET_SIZE()`
 - `PyUnicode_GetSize()`

- `PyUnicode_GET_DATA_SIZE()`
- Remove the `PyUnicode_InternImmortal()` function macro. (Contributed by Victor Stinner in [gh-85858](#).)

Índice

P

Propostas Estendidas Python

- PEP 249, [14](#)
- PEP 451, [28](#)
- PEP 484, [4](#), [8](#), [9](#)
- PEP 523, [30](#)
- PEP 572, [10](#)
- PEP 594, [21](#), [23](#), [26](#)
- PEP 617, [6](#)
- PEP 623, [4](#), [17](#), [37](#)
- PEP 626, [20](#)
- PEP 632, [4](#), [24](#)
- PEP 644, [24](#)
- PEP 669, [7](#)
- PEP 678, [10](#)
- PEP 683, [32](#)
- PEP 684, [32](#)
- PEP 688, [7](#)
- PEP 692, [9](#)
- PEP 693, [3](#)
- PEP 695, [4](#), [5](#), [18](#)
- PEP 697, [30](#), [31](#)
- PEP 698, [9](#)
- PEP 699, [34](#), [35](#)
- PEP 701, [5](#), [6](#), [15](#), [17](#), [29](#)
- PEP 706, [10](#)
- PEP 709, [7](#), [18](#)

PYTHONHOME, [36](#)

PYTHONPERFSUPPORT, [10](#)

V

váriavel de ambiente

- PYTHONHOME, [36](#)
- PYTHONPERFSUPPORT, [10](#)