Отчёт по практической работе №5

1. Настроить SSH на каждом сетевом устройстве таким образом, чтобы с устройства SSH-Client можно было подключиться по SSH к любому устройству в рамках всех лабораторных работ.

Подключение по TELNET с SSH-Client’а к коммутатору Switch-3:

```
root@localhost:~# telnet 10.210.70.3
Trying 10.210.70.3...
Connected to 10.210.70.3.
Escape character is '^]'.


User Access Verification

Username: admin
Password:

DMikheeva-Switch-3>
```

Подключение по SSH с SSH-Client’а к роутеру Main-Router:

```
root@localhost:~# ssh admin@10.122.0.2
The authenticity of host '10.122.0.2 (10.122.0.2)' can't be established.
RSA key fingerprint is SHA256:4RmRQgcibkCpdusnx5zPQBN3OHameYO8xJHyR0Ykp5k.
This host key is known by the following other names/addresses:
    ~/.ssh/known_hosts:1: [hashed name]
    ~/.ssh/known_hosts:2: [hashed name]
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '10.122.0.2' (RSA) to the list of known hosts.
(admin@10.122.0.2) Password:

DMikheeva-Main-Router>_
```

Подключение по SSH с SSH-Client’а к роутеру C-RIP-10:

```
root@localhost:~# ssh admin@186.208.48.2
The authenticity of host '186.208.48.2 (186.208.48.2)' can't be established.
RSA key fingerprint is SHA256:S4kV7FDbmvar+8mW3hlmf16Lza9WLW4PW5Wge8gj+2I.
This host key is known by the following other names/addresses:
    ~/.ssh/known_hosts:5: [hashed name]
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '186.208.48.2' (RSA) to the list of known hosts.
(admin@186.208.48.2) Password:

DMikheeva-C-RIP-10>
```

Подключение по SSH с SSH-Client’а к роутеру C-OSPF-5:

```
root@localhost:~# ssh admin@12.208.16.2
The authenticity of host '12.208.16.2 (12.208.16.2)' can't be established.
RSA key fingerprint is SHA256:dCr6JhZR5rapYtkvWlwByAHE6xGwQkET6mI8CbKvj00.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '12.208.16.2' (RSA) to the list of known hosts.
(admin@12.208.16.2) Password:

DMikheeva-C-OSPF-5>
```

Подключение по SSH с SSH-Client’а к роутеру M-iBGP-101:

```
root@localhost:~# ssh admin@13.231.9.101
The authenticity of host '13.231.9.101 (13.231.9.101)' can't be established.
RSA key fingerprint is SHA256:/FIf0t+PwGxRreLTcL++juZYX4+J8ArA3rVjOQj+oLk.
This host key is known by the following other names/addresses:
    ~/.ssh/known_hosts:3: [hashed name]
    ~/.ssh/known_hosts:10: [hashed name]
    ~/.ssh/known_hosts:11: [hashed name]
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '13.231.9.101' (RSA) to the list of known hosts.
admin@13.231.9.101's password:





  MMM      MMM       KKK                          TTTTTTTTTTT      KKK
  MMMM    MMMM       KKK                          TTTTTTTTTTT      KKK
  MMM MMMM MMM  III  KKK  KKK  RRRRRR     OOOOOO      TTT     III  KKK  KKK
  MMM  MM  MMM  III  KKKKK     RRR  RRR  OOO  OOO     TTT     III  KKKKK
  MMM      MMM  III  KKK KKK   RRRRRR    OOO  OOO     TTT     III  KKK KKK
  MMM      MMM  III  KKK  KKK  RRR  RRR   OOOOOO      TTT     III  KKK  KKK

  MikroTik RouterOS 6.49.18 (c) 1999-2025       http://www.mikrotik.com/

[?]             Gives the list of available commands
command [?]     Gives help on the command and list of arguments

[Tab]           Completes the command/word. If the input is ambiguous,
                a second [Tab] gives possible options

/               Move up to base level
..              Move up one level
/command        Use command at the base level
dec/19/2025 08:02:28 system,error,critical router was rebooted without proper shutdown
dec/21/2025 15:49:12 system,error,critical router was rebooted without proper shutdown

[admin@DMikheeva-M-iBGP-101] >
```

2. Настроить технологию NAT на роутерах C-RIP-10 и C-OSPF-5.

Пинг 8.8.8.8 с коммутатора Switch-1:

```
DMikheeva-Switch-1#ping 8.8.8.8
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 8.8.8.8, timeout is 2 seconds:
!!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 24/33/42 ms
```

Пинг 8.8.8.8 с роутера C-R-2-2:

```
DMikheeva-C-R-2-2#ping 8.8.8.8
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 8.8.8.8, timeout is 2 seconds:
!!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 26/34/47 ms
```

Пинг 8.8.8.8 с роутера C-RIP-2:

```
DMikheeva-C-RIP-2#ping 8.8.8.8
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 8.8.8.8, timeout is 2 seconds:
!!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 24/28/33 ms
```

Пинг 8.8.8.8 с роутера M-OSPF-2:

```
[admin@DMikheeva-M-OSPF-2] > ping 8.8.8.8
  SEQ HOST                                     SIZE TTL TIME  STATUS
    0 8.8.8.8                                    56 126 51ms
    1 8.8.8.8                                    56 126 41ms
    2 8.8.8.8                                    56 126 32ms
    3 8.8.8.8                                    56 126 35ms
    4 8.8.8.8                                    56 126 31ms
    5 8.8.8.8                                    56 126 31ms
    6 8.8.8.8                                    56 126 33ms
    7 8.8.8.8                                    56 126 31ms
    8 8.8.8.8                                    56 126 27ms
    sent=9 received=9 packet-loss=0% min-rtt=27ms avg-rtt=34ms max-rtt=51ms
```

Пинг 8.8.8.8 с роутера C-iBGP-33:

```
DMikheeva-C-iBGP-33#ping 8.8.8.8
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 8.8.8.8, timeout is 2 seconds:
!!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 29/33/39 ms
```