



1. Create 3 EC2 instances i.e master, worker1, and worker2.



2. Change network setting.



3. Set up Docker

Install Docker

Kubernetes requires an existing Docker installation. If you already have Docker installed, skip ahead to Step 4.

If you do not have Kubernetes, install it by following these steps:

Update the package list with the command:

```
on-master&slave$ sudo apt-get update
```

```
Welcome to Ubuntu 22.04 LTS (GNU/Linux 5.15.0-1011-aws x86_64)

* Documentation:  https://help.ubuntu.com
* Management:    https://landscape.canonical.com
* Support:        https://ubuntu.com/advantage

System information as of Fri Sep  2 05:28:16 UTC 2022

System load:  0.32568359375      Processes:            103
Usage of /:   19.2% of 7.58GB    Users logged in:     0
Memory usage: 21%               IPv4 address for eth0: 172.31.85.215
Swap usage:   0%

0 updates can be applied immediately.

The list of available updates is more than a week old.
To check for new updates run: sudo apt update

Last login: Fri Sep  2 05:26:49 2022 from 18.206.107.27
To run a command as administrator (user "root"), use "sudo <command>".
See "man sudo_root" for details.

ubuntu@ip-172-31-85-215:~$ sudo apt-get update
Hit:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu jammy InRelease
Get:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu-jammy-updates InRelease [114 kB]
```

Next, install Docker with the command:

```
on-master&slave$sudo apt-get install docker.io
```

Repeat the process on each server that will act as a node.

Check the installation (and version) by entering the following:

```
on-master&slave$docker --version
```

```
No VM guests are running outdated hypervisor (qemu) binaries on this host.
ubuntu@ip-172-31-85-215:~$ docker -version
docker: '-version' is not a docker command.
See 'docker --help'
ubuntu@ip-172-31-85-215:~$ docker --version
Docker version 20.10.12, build 20.10.12-0ubuntu4
ubuntu@ip-172-31-85-215:~$
```

i-05e94c28b2d8cbec6 (master)

PublicIPs: 34.227.173.250 PrivateIPs: 172.31.85.215

4. Start and Enable Docker

Set Docker to launch at boot by entering the following:

on-master&slave\$ sudo systemctl enable docker

```
No user sessions are running outdated binaries.

No VM guests are running outdated hypervisor (qemu) binaries on this host.
ubuntu@ip-172-31-85-215:~$ docker -version
docker: '-version' is not a docker command.
See 'docker --help'
ubuntu@ip-172-31-85-215:~$ docker --version
Docker version 20.10.12, build 20.10.12-0ubuntu4
ubuntu@ip-172-31-85-215:~$ sudo systemctl enable docker
ubuntu@ip-172-31-85-215:~$
```


i-05e94c28b2d8cbec6 (master)

PublicIPs: 34.227.173.250 PrivateIPs: 172.31.85.215

Verify Docker is running:

on-master&slave\$ sudo systemctl status docker To start Docker if it's not running:

on-master&slave\$ sudo systemctl start docker



```
Scanning linux images...
Running kernel seems to be up-to-date.
No services need to be restarted.
No containers need to be restarted.
No user sessions are running outdated binaries.

No VM guests are running outdated hypervisor (qemu) binaries on this host.
ubuntu@ip-172-31-85-215:~$ docker -version
docker: '-version' is not a docker command.
See 'docker --help'
ubuntu@ip-172-31-85-215:~$ docker --version
Docker version 20.10.12, build 20.10.12-0ubuntu4
ubuntu@ip-172-31-85-215:~$ sudo systemctl status docker
* docker.service - Docker Application Container Engine
   Loaded: loaded (/lib/systemd/system/docker.service; enabled; vendor preset: enabled)
   Active: active (running) since Fri 2022-09-02 05:29:46 UTC; 3min 46s ago
     TriggeredBy: ● docker.socket
       Docs: https://docs.docker.com
    Main PID: 2937 (dockerd)
      Tasks: 7
     Memory: 37.4M
        CPU: 259ms
    CGroup: /system.slice/docker.service
            └─2937 /usr/bin/dockerd -H fd:// --containerd=/run/containerd/containerd.sock

Sep 02 05:29:45 ip-172-31-85-215 dockerd[2937]: time="2022-09-02T05:29:45.579556777Z" level=info msg="scheme \"unix\" not registered, fallback to default scheme" module=grpc
Sep 02 05:29:45 ip-172-31-85-215 dockerd[2937]: time="2022-09-02T05:29:45.579754719Z" level=info msg="ccResolverWrapper: sending update to cc: {[{unix:///run/containerd/containerd.sock <nil> 0 <nil>}] <nil> <nil>}"
Sep 02 05:29:45 ip-172-31-85-215 dockerd[2937]: time="2022-09-02T05:29:45.579938436Z" level=info msg="ClientConn switching balancer to \"pick_first\"" module=grpc
Sep 02 05:29:45 ip-172-31-85-215 dockerd[2937]: time="2022-09-02T05:29:45.660192618Z" level=info msg="Loading containers: start."
Sep 02 05:29:45 ip-172-31-85-215 dockerd[2937]: time="2022-09-02T05:29:45.900388773Z" level=info msg="Default bridge (docker0) is assigned with an IP address 172.17.0.0/16. Daemon option --bip can be used to set a bridge IP address"
Sep 02 05:29:46 ip-172-31-85-215 dockerd[2937]: time="2022-09-02T05:29:46.002573565Z" level=info msg="Loading containers: done."
Sep 02 05:29:46 ip-172-31-85-215 dockerd[2937]: time="2022-09-02T05:29:46.080811492Z" level=info msg="Docker daemon" commit=20.10.12-0ubuntu4 graphdriver(s)=overlay2 version=20.10.12
Sep 02 05:29:46 ip-172-31-85-215 dockerd[2937]: time="2022-09-02T05:29:46.081218831Z" level=info msg="Daemon has completed initialization"
Sep 02 05:29:46 ip-172-31-85-215 systemd[1]: Started Docker Application Container Engine.
Sep 02 05:29:46 ip-172-31-85-215 dockerd[2937]: time="2022-09-02T05:29:46.121820482Z" level=info msg="API listen on /run/docker.sock"

lines 1-22/22 (END)
```

Repeat on all the other nodes.

Install Kubernetes

5. Add Kubernetes Signing Key

Since you are downloading Kubernetes from a non-standard repository, it is essential to ensure that the software is authentic. This is done by adding a signing key.

Enter the following to add a signing key:

on-master&slave\$curl -s https://packages.cloud.google.com/apt/doc/apt-key.gpg | sudo apt-key add

```
ubuntu@ip-172-31-85-215:~$ curl -s https://packages.cloud.google.com/apt/doc/apt-key.gpg | sudo apt-key add
Warning: apt-key is deprecated. Manage keyring files in trusted.gpg.d instead (see apt-key(8)).
gpg: no valid OpenPGP data found.
ubuntu@ip-172-31-85-215:~$ curl -s https://packages.cloud.google.com/apt/doc/apt-key.gpg | sudo apt-key add
Warning: apt-key is deprecated. Manage keyring files in trusted.gpg.d instead (see apt-key(8)).
OK
ubuntu@ip-172-31-85-215:~$
```

If you get an error that curl is not installed, install it with:

on-master&slave\$sudo apt-get install curl

Then repeat the previous command to install the signing keys. Repeat for each server node.

6. Add Software Repositories

Kubernetes is not included in the default repositories. To add them, enter the following:

on-master&slave\$sudo apt-add-repository "deb http://apt.kubernetes.io/ kubernetes-xenial main"

```
ubuntu@ip-172-31-19-150:~$ sudo apt-add-repository "deb http://apt.kubernetes.io/ kubernetes-xenial main"
Repository: 'deb http://apt.kubernetes.io/ kubernetes-xenial main'
Description:
Archive for codename: kubernetes-xenial components: main
More info: http://apt.kubernetes.io/
Adding repository.
Press [ENTER] to continue or Ctrl-c to cancel.
Adding deb entry to /etc/apt/sources.list.d/archive_uri-http_apt_kubernetes_io_-jammy.list
Adding disabled deb-src entry to /etc/apt/sources.list.d/archive_uri-http_apt_kubernetes_io_-jammy.list
Hit:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu jammy InRelease
Hit:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu jammy-updates InRelease
Hit:3 http://us-east-1.ec2.archive.ubuntu.com/ubuntu jammy-backports InRelease
Hit:4 http://security.ubuntu.com/ubuntu jammy-security InRelease
Get:5 https://packages.cloud.google.com/apt kubernetes-xenial InRelease [9383 B]
Get:6 https://packages.cloud.google.com/apt kubernetes-xenial/main amd64 Packages [58.4 kB]
Fetched 67.8 kB in 0s (138 kB/s)
Reading package lists... Done
W: http://apt.kubernetes.io/dists/kubernetes-xenial/InRelease: Key is stored in legacy trusted.gpg keyring
ubuntu@ip-172-31-19-150:~$
```

Repeat on each server node.

7. Kubernetes Installation Tools

Kubeadm (Kubernetes Admin) is a tool that helps initialize a cluster. It fast-tracks setup by using community-sourced best practices. Kubelet is the work package, which runs on every node and starts containers. The tool gives you command-line access to clusters.

Install Kubernetes tools with the command:

on-master&slave\$ sudo apt-get install kubeadm kubelet kubect1 -y

```
ubuntu@ip-172-31-85-215:~$ sudo apt-get install kubeadm kubelet kubect1 -y
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following additional packages will be installed:
  conntrack cri-tools ebtables kubernetes-cni socat
The following NEW packages will be installed:
  conntrack cri-tools ebtables kubeadm kubect1 kubelet kubernetes-cni socat
0 upgraded, 8 newly installed, 0 to remove and 76 not upgraded.
Need to get 75.9 MB of archives.
After this operation, 310 MB of additional disk space will be used.
Get:1 http://us-east-1.ec2.archive.ubuntu.com/ubuntu jammy/main amd64 conntrack amd64 1:1.4.6-2build2 [33.5 kB]
Get:2 http://us-east-1.ec2.archive.ubuntu.com/ubuntu jammy/main amd64 ebtables amd64 2.0.11-4build2 [84.9 kB]
Get:4 http://us-east-1.ec2.archive.ubuntu.com/ubuntu jammy/main amd64 socat amd64 1.7.4.1-3ubuntu4 [349 kB]
Get:3 https://packages.cloud.google.com/apt kubernetes-xenial/main amd64 cri-tools amd64 1.24.2-00 [12.3 MB]
Get:5 https://packages.cloud.google.com/apt kubernetes-xenial/main amd64 kubernetes-cni amd64 0.8.7-00 [25.0 MB]
Get:6 https://packages.cloud.google.com/apt kubernetes-xenial/main amd64 kubelet amd64 1.25.0-00 [19.5 MB]
Get:7 https://packages.cloud.google.com/apt kubernetes-xenial/main amd64 kubect1 amd64 1.25.0-00 [9500 kB]
Get:8 https://packages.cloud.google.com/apt kubernetes-xenial/main amd64 kubeadm amd64 1.25.0-00 [9213 kB]
Fetched 75.9 MB in 2s (50.0 MB/s)
Selecting previously unselected package conntrack.
(Reading database ... 63966 files and directories currently installed.)
Preparing to unpack .../0-conntrack_1:1.4.6-2build2_amd64.deb ...
Unpacking conntrack (1:1.4.6-2build2) ...
Selecting previously unselected package cri-tools.
Preparing to unpack .../1-cri-tools_1.24.2-00_amd64.deb ...
Unpacking cri-tools (1.24.2-00) ...
Selecting previously unselected package ebtables.
Preparing to unpack .../2-ebtables_2.0.11-4build2_amd64.deb ...
Unpacking ebtables (2.0.11-4build2) ...
Selecting previously unselected package kubernetes-cni.
Preparing to unpack .../3-kubernetes-cni_0.8.7-00_amd64.deb ...
Unpacking kubernetes-cni (0.8.7-00) ...
Selecting previously unselected package socat.
Preparing to unpack .../4-socat_1.7.4.1-3ubuntu4_amd64.deb ...
Unpacking socat (1.7.4.1-3ubuntu4) ...
Selecting previously unselected package kubelet.
Preparing to unpack .../5-kubelet_1.25.0-00_amd64.deb ...
Unpacking kubelet (1.25.0-00) ...
Selecting previously unselected package kubect1.
Preparing to unpack .../6-kubect1_1.25.0-00_amd64.deb ...
```

on-master&slave\$ sudo apt-mark hold kubeadm kubelet kubect1

```
No user sessions are running outdated binaries.
No VM guests are running outdated hypervisor (qemu) binaries on this host.
ubuntu@ip-172-31-85-215:~$ sudo apt-mark hold kubeadm kubelet kubect1
kubeadm set on hold.
kubelet set on hold.
kubect1 set on hold.
ubuntu@ip-172-31-85-215:~$
```

Allow the process to complete.

Verify the installation with:

on-master&slave\$ kubeadm version

```
kubelet set on hold.
kubect1 set on hold.
ubuntu@ip-172-31-85-215:~$ kubeadm version
kubeadm version: &version.Info{Major:"1", Minor:"25", GitVersion:"v1.25.0", GitCommit:"a866cbe2e5bbaa01cfd5e969aa3e033f3282a8a2", GitTreeStat
ler:"gc", Platform:"linux/amd64"}
ubuntu@ip-172-31-85-215:~$
```

Repeat for each server node.

Note: Make sure you install the same version of each package on each machine. Different versions can create instability. Also, this process prevents apt from automatically updating Kubernetes. For update instructions, please see the developers' instructions.

Kubernetes Deployment

8. Begin Kubernetes Deployment

Start by disabling the swap memory on each server:

on-master&slave\$ sudo swapoff --a

```
kubectrl set on hold.
ubuntu@ip-172-31-85-215:~$ kubectl version
kubectl version: &version.Info{Major:"1", Minor:"25",
ler:"gc", Platform:"linux/amd64"}
ubuntu@ip-172-31-85-215:~$ sudo swapoff --a
ubuntu@ip-172-31-85-215:~$
```

9. Assign Unique Hostname for Each Server Node

Decide which server to set as the master node. Then enter the command:

on-master\$ sudo hostnamectl set-hostname master-node

```
ubuntu@ip-172-31-85-215:~$ kubectl version
kubectl version: &version.Info{Major:"1", Minor:"25", GitVersion:"v1.2
ler:"gc", Platform:"linux/amd64"}
ubuntu@ip-172-31-85-215:~$ sudo swapoff --a
ubuntu@ip-172-31-85-215:~$ sudo hostnamectl set-hostname master-node
ubuntu@ip-172-31-85-215:~$
```

Next, set a worker node hostname by entering the following on the worker server:

on-slave\$ sudo hostnamectl set-hostname worker01\

```
kubectl version: &version.Info{Major:"1", Minor:"25", GitVersion:"v
ler:"gc", Platform:"linux/amd64"}
ubuntu@ip-172-31-22-222:~$ sudo swapoff --a
ubuntu@ip-172-31-22-222:~$ sudo hostnamectl set-hostname worker01
ubuntu@ip-172-31-22-222:~$
```

```
ubuntu@ip-172-31-19-150:~$ kubectl version
kubectl version: &version.Info{Major:"1", Minor:"25", GitVersion:"v
ler:"gc", Platform:"linux/amd64"}
ubuntu@ip-172-31-19-150:~$ sudo swapoff --a
ubuntu@ip-172-31-19-150:~$ sudo hostnamectl set-hostname worker02
ubuntu@ip-172-31-19-150:~$
```

If you have additional worker nodes, use this process to set a unique hostname on each.

10. Initialize Kubernetes on Master Node

Switch to the master server node, and enter the following:

on-master\$ sudo kubeadm init --pod-network-cidr=10.244.0.0/16

If you are trying to run this on EC2 you'll get an error message saying less cpu and memory to override the error run the above command with `--ignore-preflight-errors=all`

For eg: `on-master$ sudo kubeadm init --pod-network-cidr=10.244.0.0/16
--ignore-preflight-errors=all`

Once this command finishes, it will display a kubeadm join message at the end. Make a note of the whole entry. This will be used to join the worker nodes to the cluster.


```
kubeadm join 172.31.38.116:6443 --token lhu178.98f4hafj9qdn4pve \  
--discovery-token-ca-cert-hash  
sha256:8f55371cd3d53a5d72faa368e93e0a99d2953016706de871fdb27c83e5b995c
```

Next, enter the following to create a directory for the cluster:

```
kubernetes-master:~$ mkdir -p $HOME/.kube  
kubernetes-master:~$ sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config  
kubernetes-master:~$ sudo chown $(id -u):$(id -g) $HOME/.kube/config
```

```
[addons] Applied essential addon: kube-proxy  
  
Your Kubernetes control-plane has initialized successfully!  
  
To start using your cluster, you need to run the following as a regular user:  
  
  mkdir -p $HOME/.kube  
  sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config  
  sudo chown $(id -u):$(id -g) $HOME/.kube/config  
  
Alternatively, if you are the root user, you can run:  
  
  export KUBECONFIG=/etc/kubernetes/admin.conf  
  
You should now deploy a pod network to the cluster.  
Run "kubectl apply -f [podnetwork].yaml" with one of the options listed at:  
  https://kubernetes.io/docs/concepts/cluster-administration/addons/  
  
Then you can join any number of worker nodes by running the following on each as root:  
  
kubeadm join 172.31.85.215:6443 --token 02ital.99zaej30du0i6taf \  
--discovery-token-ca-cert-hash sha256:446d54ed5bc3337ebfaa4af0d3163510f84e82e3faf4e49  
ubuntu@ip-172-31-85-215:~$ mkdir -p $HOME/.kube  
ubuntu@ip-172-31-85-215:~$ sudo cp -i /etc/kubernetes/admin.conf  
cp: missing destination file operand after '/etc/kubernetes/admin.conf'  
Try 'cp --help' for more information.  
ubuntu@ip-172-31-85-215:~$ sudo cp -i /etc/kubernetes/admin.conf $HOME/.kube/config  
ubuntu@ip-172-31-85-215:~$
```

11. Install Docker Desktop.
12. Enable Kubernetes in settings.



13. Run this commands

```
kubectl create deployment httpenv --image=bretfisher/httpenv  
kubectl scale deployment/httpenv --replicas=3  
kubectl expose deployment/httpenv --port 8888  
kubectl get service  
kubectl run tmp-shell --rm -it --image bretfisher/netshoot -- bash
```

14. To delete pods run `kubectl delete pod <pod-name>`