

Exercise 2: Apriori, Confidence, Itemsets and Association Rules

Exercise 2-1: Combinatoric explosion

- (a) A database contains transactions over the following items: “apples”, “bananas”, and “cherries”. How many different combinations of these items can exist (i.e., how many different transactions could possibly occur in the database)?
(We do not distinguish whether a transaction contains a fruit once or several times, e.g., if someone bought one apple or several apples would just result in the transaction containing “apples”.)
- (b) The database now also contains the items “dates”, “eggplants”, “figs”, and “guavas”. How many possible transactions do we have now?
- (c) How many combinations (possible different transactions) do we have with n items?
- (d) How many transactions with exactly two items (i.e., 2-itemsets) can we have when the database contains 3 items? When it contains 5 items? How many k -itemsets do we have when the database contains n items?

Exercise 2-2: Itemsets and Association Rules

Given a set of transactions T according to the following table:

Set of transactions T	
Transaction ID	items in basket
1	{Milk, Beer, Diapers}
2	{Bread, Butter, Milk}
3	{Milk, Diapers, Cookies }
4	{Bread, Butter, Cookies}
5	{Beer, Cookies, Diapers}
6	{Milk, Diapers, Bread, Butter}
7	{Bread, Butter, Diapers}
8	{Beer, Diapers}
9	{Milk, Diapers, Bread, Butter}
10	{Beer, Cookies}

- (a) What are the support and the confidence of $\{\text{Milk}\} \Rightarrow \{\text{Diapers}\}$?
- (b) What are the support and the confidence of $\{\text{Diapers}\} \Rightarrow \{\text{Milk}\}$?
- (c) What is the maximum number of size-3 itemsets that can be derived from this data set?
- (d) What is the maximum number of association rules that can be extracted from this dataset (including rules, that have zero support)?
- (e) What is the maximum size of frequent itemsets that can be extracted (assuming $\sigma > 0$)?
- (f) Find an itemset (of size 2 or larger) that has the largest support.
- (g) Find a pair of items, a and b , such that the rules $\{a\} \Rightarrow \{b\}$ and $\{b\} \Rightarrow \{a\}$ have the same confidence.

Exercise 2-3: Apriori candidate generation

Given the frequent 3-itemsets:

$$\{1, 2, 3\}, \{1, 2, 4\}, \{1, 2, 5\}, \{1, 3, 5\}, \{2, 3, 4\}, \{2, 3, 5\}, \{2, 3, 6\}, \{2, 5, 6\}, \{3, 4, 5\}, \{3, 5, 6\}$$

List all candidate 4-itemsets following the Apriori joining and pruning procedure.

Exercise 2-4: The monotonicity of confidence

Theorem 2.1 in the Lecture states:

Given:

- itemset X
- $Y \subset X, Y \neq \emptyset$

If $\text{conf}(Y \Rightarrow (X \setminus Y)) < c$, then $\forall Y' \subset Y$:

$$\text{conf}(Y' \Rightarrow (X \setminus Y')) < c.$$

- (a) Prove the theorem.
- (b) Sketch an algorithm (pseudo code) that generates all association rules with support σ or above and a minimum confidence of c , provided the set F of all frequent itemsets (w.r.t. σ) with their support, efficiently using the pruning power of the given theorem.

Exercise 2-5: Tools

- (a) Install python packages: `scikit-learn`, `numpy`, `matplotlib`, `metrics`, and `linear-model` from `scikit-learn`, then load `diabetes` dataset from `sklearn`.
- (b) Reserve a randomly chosen 80% of the data for training and the remaining for test using `sklearn.model_selection.train_test_split`, then assign data as `x` and target as `y` and investigate the shapes of the data.
- (c) Normalize data using `StandardScaler` from `sklearn.preprocessing`.
- (d) Fit a linear regression model to the training set and make prediction.
- (e) Evaluate mean squared error (MSE) of the fitted model on the test set.
- (f) Plot the fitted model as a line and print its intercept and slope.
- (g) Comment on the outcome. Could the model fit to data accurately enough?