


Support Vector Machine (SVM) Algorithm

Last Updated : 13 Nov, 2025

Support Vector Machine (SVM) is a supervised machine learning algorithm used for classification and regression tasks. It tries to find the best boundary known as hyperplane that separates different classes in the data. It is useful when you want to do binary classification like spam vs. not spam or cat vs. dog.


- Support Vector Machine is used for classification and regression.
- It works by finding decision planes that separate data into different classes.




The decision Plane

Support Vectors & Hyperplane

- Support Vectors are the closest data points to the hyperplane that define the class boundary.
- A hyperplane is a plane that separates different classes.






The main goal of SVM is to maximize the margin between the two classes. The larger the margin the better the model performs on new and unseen data.

Key Concepts of Support Vector Machine

- **Hyperplane:** A decision boundary separating different classes in feature space and is represented by the equation $wx + b = 0$ in linear classification.
- **Support Vectors:** The closest data points to the hyperplane, crucial for determining the hyperplane and margin in SVM.
- **Margin:** The distance between the hyperplane and the support vectors. SVM aims to maximize this margin for better classification performance.
- **Kernel:** A function that maps data to a higher-dimensional space enabling SVM to handle non-linearly separable data.
- **Hard Margin:** A maximum-margin hyperplane that perfectly separates the data without misclassifications.
- **Soft Margin:** Allows some misclassifications by introducing slack variables, balancing margin maximization and misclassification penalties when data is not perfectly separable.
- **C:** A regularization term balancing margin maximization and misclassification penalties. A higher C value forces stricter penalty for misclassifications.
- **Hinge Loss:** A loss function penalizing misclassified points or margin violations and is combined with regularization in SVM.
- **Dual Problem:** Involves solving for Lagrange multipliers associated with support vectors, facilitating the kernel trick and efficient computation.


How does Support Vector Machine Algorithm Work?

The key idea behind the SVM algorithm is to find the hyperplane that best separates two classes by maximizing the margin between them. This margin is the distance from the hyperplane to the nearest data points (support vectors) on each side.



Multiple hyperplanes separate the data from two classes

The best hyperplane also known as the "**hard margin**" is the one that maximizes the distance between the hyperplane and the nearest data points from both classes. This ensures a clear separation between the classes. So from the above figure, we choose L2 as hard margin. Let's consider a scenario like shown below:




Selecting hyperplane for data with outlier

Here, we have one blue ball in the boundary of the red ball.

How does SVM classify the data?

The blue ball in the boundary of red ones is an outlier of blue balls. The SVM algorithm has the characteristics to ignore the outlier and finds the best hyperplane that maximizes the margin. SVM is robust to outliers.



Hyperplane which is the most optimized one

A soft margin allows for some misclassifications or violations of the margin to improve generalization. The SVM optimizes the following equation to balance margin maximization and penalty minimization:

$$\text{Objective Function} = \left(\frac{1}{\text{margin}}\right) + \lambda \sum \text{penalty}$$


The penalty used for violations is often [hinge loss](#) which has the following behavior:

- If a data point is correctly classified and within the margin there is no penalty (loss = 0).
- If a point is incorrectly classified or violates the margin the hinge loss increases proportionally to the distance of the violation.

Till now we were talking about linearly separable data that separates group of blue balls and red balls by a straight line/linear line.

What if data is not linearly separable?

When data is not linearly separable i.e it can't be divided by a straight line, SVM uses a technique called [kernels](#) to map the data into a higher-dimensional space where it becomes separable. This transformation helps SVM find a decision boundary even for non-linear data.




Original 1D dataset for classification

A kernel is a function that maps data points into a higher-dimensional space without explicitly computing the coordinates in that space. This allows SVM to work efficiently with non-linear data by implicitly performing the mapping. For example consider data points that are not linearly separable. By

applying a kernel function SVM transforms the data points into a higher-dimensional space where they become linearly separable.

- **Linear Kernel:** For linear separability.
- **Polynomial Kernel:** Maps data into a polynomial space.
- **Radial Basis Function (RBF) Kernel:** Transforms data into a space based on distances between data points.



Mapping 1D data to 2D to become able to separate the two classes

In this case the new variable y is created as a function of distance from the origin.

Mathematical Computation of SVM

Consider a binary classification problem with two classes, labeled as $+1$ and -1 . We have a training dataset consisting of input feature vectors X and their corresponding class labels Y . The equation for the linear hyperplane can be written as:

$$w^T x + b = 0$$

Where:

- w is the normal vector to the hyperplane (the direction perpendicular to it).
- b is the offset or bias term representing the distance of the hyperplane from the origin along the normal vector w .

Distance from a Data Point to the Hyperplane

The distance between a data point x_i and the decision boundary can be calculated as:

$$d_i = \frac{w^T x_i + b}{\|w\|}$$

where $\|w\|$ represents the Euclidean norm of the weight vector w .

Linear SVM Classifier

Distance from a Data Point to the Hyperplane:

$$\hat{y} = \begin{cases} 1 & : w^T x + b \geq 0 \\ -1 & : w^T x + b < 0 \end{cases}$$

Where \hat{y} is the predicted label of a data point.

Optimization Problem for SVM

For a linearly separable dataset the goal is to find the hyperplane that maximizes the margin between the two classes while ensuring that all data points are correctly classified. This leads to the following optimization problem:

$$\underset{w,b}{\text{minimize}} \frac{1}{2} \|w\|^2$$

Subject to the constraint:

$$y_i(w^T x_i + b) \geq 1 \text{ for } i = 1, 2, 3, \dots, m$$

Where:

- y_i is the class label (+1 or -1) for each training instance.
- x_i is the feature vector for the i -th training instance.
- m is the total number of training instances.

The condition $y_i(w^T x_i + b) \geq 1$ ensures that each data point is correctly classified and lies outside the margin.

Soft Margin in Linear SVM Classifier

In the presence of outliers or non-separable data the SVM allows some misclassification by introducing slack variables ζ_i . The optimization problem is modified as:

$$\underset{w,b}{\text{minimize}} \frac{1}{2} \|w\|^2 + C \sum_{i=1}^m \zeta_i$$

Subject to the constraints:

$$y_i(w^T x_i + b) \geq 1 - \zeta_i \quad \text{and} \quad \zeta_i \geq 0 \quad \text{for } i = 1, 2, \dots, m$$

Where:

- C is a regularization parameter that controls the trade-off between margin maximization and penalty for misclassifications.
- ζ_i are slack variables that represent the degree of violation of the margin by each data point.

Dual Problem for SVM

The dual problem involves maximizing the Lagrange multipliers associated with the support vectors. This transformation allows solving the SVM optimization using kernel functions for non-linear classification.

The dual objective function is given by:

$$\underset{\alpha}{\text{maximize}} \frac{1}{2} \sum_{i=1}^m \sum_{j=1}^m \alpha_i \alpha_j t_i t_j K(x_i, x_j) - \sum_{i=1}^m \alpha_i$$

Where:

- α_i are the Lagrange multipliers associated with the i^{th} training sample.
- t_i is the class label for the i^{th} -th training sample.

- $K(x_i, x_j)$ is the kernel function that computes the similarity between data points x_i and x_j . The kernel allows SVM to handle non-linear classification problems by mapping data into a higher-dimensional space.

The dual formulation optimizes the Lagrange multipliers α_i and the support vectors are those training samples where $\alpha_i > 0$.

SVM Decision Boundary

Once the dual problem is solved, the decision boundary is given by:

$$w = \sum_{i=1}^m \alpha_i t_i K(x_i, x) + b$$

Where w is the weight vector, x is the test data point and b is the bias term. Finally the bias term b is determined by the support vectors, which satisfy:

$$t_i (w^T x_i - b) = 1 \quad \Rightarrow \quad b = w^T x_i - t_i$$

Where x_i is any support vector.

This completes the mathematical framework of the Support Vector Machine algorithm which allows for both linear and non-linear classification using the dual problem and kernel trick.

Types of Support Vector Machine

Based on the nature of the decision boundary, Support Vector Machines (SVM) can be divided into two main parts:

- **Linear SVM:** Linear SVMs use a linear decision boundary to separate the data points of different classes. When the data can be precisely linearly separated, linear SVMs are very suitable. This means that a single straight line (in 2D) or a hyperplane (in higher dimensions) can entirely divide the data points into their respective classes. A hyperplane that maximizes the margin between the classes is the decision boundary.
- **Non-Linear SVM:** [Non-Linear SVM](#) can be used to classify data when it cannot be separated into two classes by a straight line (in the case of 2D). By using kernel functions, nonlinear SVMs can handle nonlinearly separable data. The original input data is transformed by these kernel functions into a higher-dimensional feature space where the data points can be linearly separated. A linear SVM is used to locate a nonlinear decision boundary in this modified space.

Implementing SVM Algorithm Using Scikit-Learn

We will predict whether cancer is Benign or Malignant using historical data about patients diagnosed with cancer. This data includes independent attributes such as tumor size, texture, and others. To perform this classification, we will use an SVM (Support Vector Machine) classifier to differentiate between benign and malignant cases effectively.

- **load_breast_cancer():** Loads the breast cancer dataset (features and target labels).
- **SVC(kernel="linear", C=1):** Creates a Support Vector Classifier with a linear kernel and regularization parameter $C=1$.
- **svm.fit(X, y):** Trains the SVM model on the feature matrix X and target labels y .
- **DecisionBoundaryDisplay.from_estimator():** Visualizes the decision boundary of the trained model with a specified color map.

- **plt.scatter():** Creates a scatter plot of the data points, colored by their labels.
- **plt.show():** Displays the plot to the screen.

```
from sklearn.datasets import load_breast_cancer
import matplotlib.pyplot as plt
from sklearn.inspection import DecisionBoundaryDisplay
from sklearn.svm import SVC


cancer = load_breast_cancer()
X = cancer.data[:, :2]
y = cancer.target

svm = SVC(kernel="linear", C=1)
svm.fit(X, y)

DecisionBoundaryDisplay.from_estimator(
    svm,
    X,
    response_method="predict",
    alpha=0.8,
    cmap="Pastel1",
    xlabel=cancer.feature_names[0],
    ylabel=cancer.feature_names[1],
)

plt.scatter(X[:, 0], X[:, 1],
            c=y,
            s=20, edgecolors="k")
plt.show()
```

Output:



Advantages of Support Vector Machine (SVM)

1. **High-Dimensional Performance:** SVM excels in high-dimensional spaces, making it suitable for image classification and gene expression analysis.
2. **Nonlinear Capability:** Utilizing kernel functions like RBF and polynomial SVM effectively handles nonlinear relationships.
3. **Outlier Resilience:** The soft margin feature allows SVM to ignore outliers, enhancing robustness in spam detection and anomaly detection.
4. **Binary and Multiclass Support:** SVM is effective for both binary classification and multiclass classification suitable for applications in text classification.
5. **Memory Efficiency:** It focuses on support vectors making it memory efficient compared to other algorithms.

Disadvantages of Support Vector Machine (SVM)

1. **Slow Training:** SVM can be slow for large datasets, affecting performance in SVM in data mining tasks.
2. **Parameter Tuning Difficulty:** Selecting the right kernel and adjusting parameters like C requires careful tuning, impacting SVM algorithms.
3. **Noise Sensitivity:** SVM struggles with noisy datasets and overlapping classes, limiting effectiveness in real-world scenarios.
4. **Limited Interpretability:** The complexity of the hyperplane in higher dimensions makes SVM less interpretable than other models.
5. **Feature Scaling Sensitivity:** Proper feature scaling is essential, otherwise SVM models may perform poorly.

Suggested Quiz

🔄 10 Questions

What is the primary objective of a Support Vector Machine (SVM) in classification tasks?

- ☐ (A) To minimize the number of support vectors
- ☐ (B) To maximize the separation margin between classes
- ☐ (C) To minimize the dimensionality of the feature space

- ☐ (D) To maximize the number of misclassifications



Corporate & Communications Address:

A-143, 7th Floor, Sovereign Corporate Tower, Sector- 136, Noida, Uttar Pradesh (201305)

Registered Address:

K 061, Tower K, Gulshan Vivante Apartment, Sector 137, Noida, Gautam Buddh Nagar, Uttar Pradesh, 201305

Company

About Us
Legal
Privacy
Policy
Contact Us
Advertise with us
GFG
Corporate
Solution

Explore

POTD
Job-A-Thon
Blogs
Nation
Skill Up

Tutorials

Programming
Languages
DSA
Web
Technology
AI, ML &
Data Science
DevOps
CS Core
Subjects
Interview
Preparation
Software and
Tools

Courses

ML and Data
Science
DSA and
Placements
Web
Development
Programming
Languages
DevOps &
Cloud
GATE
Trending
Technologies

Videos

DSA
Python
Java
C++
Web
Development
Data Science
CS Subjects

Preparation Corner

Interview
Corner
Aptitude
Puzzles
GfG 160
System Design



@GeeksforGeeks, Sanchhaya Education Private Limited, All rights reserved

Python for Machine Learning

Feature Engineering

Supervised Learning

Unsupervised Learning

Model Evaluation and Tuning

Advanced Techniques

Machine Learning Practice