

## ▼ Frame 191: 540 bytes on wire (4320 bits), 540 bytes captured (4320 bits) on interface 0

## ▼ Interface id: 0 (en0)

Interface name: en0

Interface description: Wi-Fi

Encapsulation type: Ethernet (1)

Arrival Time: May 16, 2019 18:12:41.442309000 EEST

[Time shift for this packet: 0.000000000 seconds]

Epoch Time: 1558019561.442309000 seconds

[Time delta from previous captured frame: 0.000265000 seconds]

[Time delta from previous displayed frame: 0.000000000 seconds]

[Time since reference or first frame: 3.692519000 seconds]

Frame Number: 191

Frame Length: 540 bytes (4320 bits)

Capture Length: 540 bytes (4320 bits)

[Frame is marked: False]

[Frame is ignored: False]

[Protocols in frame: eth:ethertype:ip:tcp:http]

[Coloring Rule Name: HTTP]

[Coloring Rule String: http || tcp.port == 80 || http2]

- ▶ Ethernet II, Src: Apple\_59:3b:05 (88:e9:fe:59:3b:05), Dst: AsustekC\_67:19:61 (00:18:f3:67:19:61)
- ▶ Internet Protocol Version 4, Src: 192.168.124.204, Dst: 128.119.245.12
- ▶ Transmission Control Protocol, Src Port: 55979, Dst Port: 80, Seq: 1, Ack: 1, Len: 474
- ▶ Hypertext Transfer Protocol

0000	00 18 f3 67 19 61 88 e9	fe 59 3b 05 08 00 45 02	...g.a... ·Y;...E·
0010	02 0e 00 00 00 00 40 06	c5 ef c0 a8 7c cc 80 77	.....@· ..... ·w
0020	f5 0c da ab 00 50 cf 3f	9e 1d 5e 2e 34 0a 80 18	.....P·? ..^·4...
0030	08 0a ff e4 00 00 01 01	08 0a 45 1e a6 bb fa 24	..... ·E....\$