



Claude Code Reminder

Claude Code - Crucial Commands

<code>/help</code>	List available commands and get usage help.
<code>/model</code>	Choose the active model for the current session.
<code>/clear</code>	Clear session context window (i.e., start a new session, effectively).
<code>/compact</code>	Compact (summarize) current session context history and clear it thereafter.
<code>/config</code>	Open interactive settings menu.
<code>/context</code>	View statistics about current context window & context usage.
<code>/usage</code>	View current usage for your active plan (i.e., how much usage remains until the next reset). For more details about plans and usage, see the official help pages .
<code>/init</code>	Analyze project and create initial CLAUDE.MD file (covered later).
<code>/mcp</code>	View and manage installed MCP servers.
<code>/permissions</code>	View and update / change permissions.
<code>/rewind</code>	Rewind (undo) to earlier point in conversation, same as ESC + ESC.
<code>/statusline</code>	Configure the Claude Code status line.
<code>/teleport</code>	Resume a remote Claude Code session



Claude Code - CLI Commands & Flags (for all available commands and flags, see the [official docs](#))

<code>claude / claude "my prompt"</code>	Start a new Claude Code session, optionally with an initial prompt.
<code>claude -p "my prompt"</code>	Query Claude Code with "my prompt" and quit session once it's done (no ongoing session).
<code>claude -c</code>	Continue most recent session.
<code>claude --agent DocsExplorer</code>	Start a new session with a custom agent (instead of the default one).
<code>claude --allowedTools "Read" "Write"</code>	Skip permission confirmation dialog for specified permissions.
<code>claude --disallowedTools "Write"</code>	Disallow certain tools (specified tools are removed from Claude Code's context => it doesn't know about them).
<code>claude --dangerously-skip-permissions</code>	Skip ALL permissions confirmation dialogs. Use with great caution!
<code>claude --append-system-prompt "Always check if redundant code can be deleted"</code>	Append an instruction to the default system prompt. Can be used as session-specific alternative to instructions placed in <code>CLAUDE.MD</code> (<code>CLAUDE.MD</code> will be covered later).
<code>claude --model opus</code>	Sets the default model for the current session. Can be changed in the session via <code>/model</code> , or generally via settings (see below). For valid options, see the official list .
<code>claude --permission-mode plan</code>	Start in plan mode (default is "default" mode where Claude Code asks for permissions). For available options, see the official list .
<code>claude --remote "Add dark mode"</code>	Start a remote (web) session



<code>claude --system-prompt "You are a Angular expert"</code>	Replace the entire default system prompt with a custom one.
--	---

Claude Code - Claude Code Interaction (for all available shortcuts and commands, see the [official docs](#).)

SHIFT + ENTER / OPTION + ENTER / CTRL + J	Enter new line. Exact command depends on platform and terminal software used.
SHIFT + TAB	Switch through different modes ("default", "write permissions", "plan").
CTRL + C	Cancel current input or generation.
ESC	Cancel current generation (can be used to inject a new prompt into an ongoing task).
ESC + ESC	Restore the code prior to the last action performed by Claude Code.
OPTION + P / ALT + P	Switch model. Alternative to /model which can be useful if you already entered a prompt.
ARROW keys (left / right / top / down)	Cycle through options or questions (left / right) or past message (up / down).
CTRL + O	Toggle verbose output (more / less details).



Claude Code – Settings (for all available settings, see the [official docs](#))

<code>{ "permissions": {...} }</code>	Manage permissions for all sessions. See official permissions settings docs .
<code>{ "model": "opus" }</code>	Manage default AI model used for new sessions.
<code>{ "alwaysThinkingEnabled": true }</code>	Whether to enabled "advanced thinking" mode or not. Is on by default. Turning it off will likely yield worse results
<code>{ "hooks": { } }</code>	Manage hooks
<code>{ "env": { "IS_DEMO": 1 } }</code>	Environment variables that will be applied to every session.